

## [Synchronization + Constrained coding (inner code)]

 $\Sigma = \{0, 1, 2, 3\}$  (A,T,G,C)

 $\ell$  : constraint length

 $\mathcal{Q} \subset \Sigma^\ell$  : valid state set

 (ex)  $\mathcal{Q}_{\ell,k}^R$  : maximum run-length  $k$ 
 $\mathcal{Q}_{\ell,\varepsilon}^B$  : local  $\varepsilon$ -balanced

 $\mathcal{Q}_\ell^M$  : motif (?)

 $\mathcal{Q}_\ell^S$  : synchronization (?)

 $\mathcal{Q} = \mathcal{Q}_{\ell,k}^R \cap \mathcal{Q}_{\ell,\varepsilon}^B \cap \mathcal{Q}_\ell^M \cap \mathcal{Q}_\ell^S \cap \dots$ 

 state:  $\mathbf{q} = q_0 q_1 \dots q_{\ell-2} q_{\ell-1} \in \mathcal{Q}$ 

 left-shift:  $\overleftarrow{\mathbf{q}} a = q_1 q_2 \dots q_{\ell-1} a \in \Sigma^\ell$ 

 state transition:  $t(\mathbf{q}, a) = \{\mathbf{q}' = \overleftarrow{\mathbf{q}} a \mid \mathbf{q}' \in \mathcal{Q}\}$   
 $|t(\mathbf{q}, a)| \in \{0, 1\}$ 

 edge label set:  $\mathcal{L}(\mathbf{q}) = \{a \mid t(\mathbf{q}, a) \neq \phi\}$ 




 encoding:  $f_e : \mathcal{Q} \times \mathbb{B}^2 \rightarrow \Sigma$ 

$\mathcal{L}(\mathbf{q})$	00	01	10	11
$\{0, 1, 2, 3\}$	0	1	2	3
$\{0, 1, 2\}$	0	1	2	2
$\{0, 1, 3\}$	0	1	3	3
$\{0, 2, 3\}$	0	0	2	3
$\{1, 2, 3\}$	1	1	2	3
$\{q_0, q_1\}$	$q_0$	$q_0$	$q_1$	$q_1$
$\{q\}$	$q$	$q$	$q$	$q$
$\phi$	(invalidate $\mathbf{q}$ )			

outer code:

 $\mathcal{C}_0$  : left-bit

 $\mathcal{C}_1$  : right-bit

 (rate)  $R(\mathcal{C}_0) > R(\mathcal{C}_1)$ 

 FBA:  $s_i = (\mathbf{q}_i, d_i)$   
 $x_i = (x_i^0, x_i^1) \in \mathbb{B}^2$ 


## [Synchronization + Constrained coding (inner code)]

$$\Sigma = \{0, 1, 2, 3\} \quad (\text{A,T,G,C})$$

$k$  : maximum run-length


$$\delta : \text{balance margin} \quad |w_{01}(x_0^{i-1}) - w_{23}(x_0^{i-1})| \leq \delta \rightarrow \text{local balance: } b = (2\delta + \ell')/\ell$$

$$|2w_{01}(x_0^{i-1}) - i| \leq \delta \quad (\forall i \in [n])$$

$$\ell' = \begin{cases} (\ell - 2\delta)/2 & (\ell : \text{even}) \\ (\ell - 2\delta - 1)/2 & (\ell : \text{odd}) \end{cases}$$

$$b = \begin{cases} \frac{1}{2} + \frac{\delta}{\ell} & (\ell : \text{even}) \\ \frac{1}{2} + \frac{\delta}{\ell} - \frac{1}{2\ell} & (\ell : \text{odd}) \end{cases}$$

$$\varepsilon = \begin{cases} \frac{\delta}{\ell} & (\ell : \text{even}) \\ \frac{\delta}{\ell} - \frac{1}{2\ell} & (\ell : \text{odd}) \end{cases}$$



## [IDS channel]

$p_i$  : insertion

$p_d$  : deletion

$p_s(y|x)$  : asymmetric error


$d_{\min} < 0$  : drift min

$d_{\max} > 0$  : drift max


$$\mathcal{D} = \{d \in \mathbb{Z} | d_{\min} \leq d \leq d_{\max}\}$$

## [state transition]

$$\text{run-length: } t_R(p, a) : \mathcal{P} \times \Sigma \rightarrow \mathcal{P} \cup \{\perp\}$$




$$\text{balance: } t_B(q, a) : \mathcal{Q} \times \Sigma \rightarrow \mathcal{Q} \cup \{\perp\}$$



$$\text{run-length + balance:}$$

$$t(p, q, a) : \mathcal{P} \times \mathcal{Q} \times \Sigma \rightarrow (\mathcal{P} \times \mathcal{Q}) \cup \{\perp\}$$



number of states:  
 $4k(2\delta+1)+1$

$$t(p, q, a) =$$

$$\begin{cases} (p', q') & (t_R(p, a) = p', t_B(q, a) = q') \\ \perp & (\text{otherwise}) \end{cases}$$

## [information mapping]

$$\mathcal{L}(p, q) = \{a | t(p, q, a) \neq \perp\}$$

$$f_e : \mathcal{P} \times \mathcal{Q} \times \mathbb{B}^2 \rightarrow \Sigma$$

$\mathcal{L}(p, q)$	00	01	10	11
$\{0, 1, 2, 3\}$	0	1	2	3
$\{0, 1, 2\}$	0	1	2	2
$\{0, 1, 3\}$	0	1	3	3
$\{0, 2, 3\}$	0	0	2	3
$\{1, 2, 3\}$	1	1	2	3
$\{q_0, q_1\}$	$q_0$	$q_0$	$q_1$	$q_1$
$\{q\}$	$q$	$q$	$q$	$q$
$\phi$	(delete $(p, q)$ )			

erasures:  
corrected by outer code

## [FBA]

$$s_i = (p_i, q_i, d_i) \in \mathcal{P} \times \mathcal{Q} \times \mathcal{D}$$


$$x_i = (x_i^0, x_i^1) \in \mathbb{B}^2$$

$$p(y, x, p, q, d)$$

$$= p(y|x, p, q, d)p(x, p, q, d)$$

$$= p(x, p, q, d) \prod_{i=0}^{n-1} p(y_{i+d_i+1}^{i+d_i+1} | x_i, p_i, p_{i+1}, q_i, q_{i+1}, d_i, d_{i+1})$$

$$= p(p_0)p(q_0)p(d_0) \prod_{i=0}^{n-1} p(y_{i+d_i}^{i+d_i+1} | x_i, p_i, p_{i+1}, q_i, q_{i+1}, d_i, d_{i+1})p(x_i | p_i, q_i)p(p_{i+1} | p_i)p(q_{i+1} | q_i)p(d_{i+1} | d_i)$$



## [evaluation]

\* code rate


- capacity of constrained channel

- encoding rate (erasure prob.)


\* mutual information: I(channel input, FBA output)

- comparison to marker, watermark ?


[run-length]




[balance]



[run-length + balance]



number of states:  
 $4k(2\varepsilon + 1) + 1$



info mapping: rate-1

