

# Solving $\ell_1$ Regularized Least Squares via Proximal Gradient Descent

# Objectives

- apply proximal gradient approach to solve  $\ell_1$ -regularized least squares
- derive solution to regularization phase
- explore alternating gradient and soft thresholding steps

The  $\ell_1$ -regularized least-squares problem <sup>2</sup>  
can be solved via proximal gradient descent

features/labels  $(\underline{x}_i, d_i)$  model  $\underline{x}_i^T \underline{w} \approx d_i$

$$\min_{\underline{w}} \|\underline{A}\underline{w} - \underline{d}\|_2^2 + \lambda \|\underline{w}\|_1$$

encourages sparse solutions

no closed form solution

Proximal Gradient Descent Algorithm

a)  $\underline{z}^{(k)} = \underline{w}^{(k)} - \tau \underline{A}^T (\underline{A} \underline{w}^{(k)} - \underline{d})$  least squares gradient descent

b)  $\underline{w}^{(k+1)} = \arg \min_{\underline{w}} \|\underline{z}^{(k)} - \underline{w}\|_2^2 + \tau \lambda \|\underline{w}\|_1$

Regularization step involves scalar minimization<sup>3</sup>

$$\min_{\underline{w}} \|\underline{z}^{(k)} - \underline{w}\|_2^2 + \tau \lambda \|\underline{w}\|_1 \Rightarrow \min_{w_i, i=1, \dots, M} \sum_{i=1}^M (z_i^{(k)} - w_i)^2 + \lambda \tau |w_i|$$

Consider  $\min_{w_i} (z_i^{(k)} - w_i)^2 + \lambda \tau |w_i|, \lambda, \tau > 0$

case 1:  $w_i \geq 0$

$$\min_{w_i} (z_i - w_i)^2 + \lambda \tau w_i, \quad w_i \geq 0 \quad \text{if } z_i > \frac{\lambda \tau}{2},$$
$$\frac{d}{dw_i} \{(z_i - w_i)^2 + \lambda \tau w_i\} = 0, \quad w_i \geq 0 \quad w_i = z_i - \frac{\lambda \tau}{2}$$

$$-2(z_i - w_i) + \lambda \tau = 0, \quad w_i \geq 0$$

$$\text{if } z_i < \frac{\lambda \tau}{2},$$
$$w_i = 0$$


$$w_i = z_i - \frac{\lambda \tau}{2}, \quad w_i \geq 0$$

$$w_i = \left(z_i - \frac{\lambda \tau}{2}\right)_+$$

Case 2:  $w_i \leq 0$

$$\min_{w_i} (z_i - w_i)^2 - \lambda \tau w_i \Rightarrow \frac{d}{dw_i} \{ (z_i - w_i)^2 - \lambda \tau w_i \} = 0$$

$$-2(z_i - w_i) - \lambda \tau = 0, w_i \leq 0 \quad w_i = \left( z_i + \frac{\lambda \tau}{2} \right)_-$$



case 2

case 1


"Soft threshold"

$$w_i = \begin{cases} 0, & -\frac{\lambda \tau}{2} < z_i < \frac{\lambda \tau}{2} \\ z_i - \frac{\lambda \tau}{2}, & z_i > \frac{\lambda \tau}{2} \\ z_i + \frac{\lambda \tau}{2}, & z_i < -\frac{\lambda \tau}{2} \end{cases}$$

shrinkage

$$w_i = \left( |z_i| - \frac{\lambda \tau}{2} \right)_+ \text{sign}(z_i)$$

# Algorithm alternates descent and shrinkage 5



**Copyright 2019**  
**Barry Van Veen**