


NLC

Label Clear Film

PRODUCT OVERVIEW

NLC is coextruded Transparent BOPP film, one side Corona Treated and both sides non-sealable. Film is used for Over wrap and wrap around Labeling.



KEY FEATURES

- Excellent gloss and surface appearance
- Very good machinability
- High mechanical properties
- High stiffness
- Excellent web flatness
- Suitable for high-quality printing

APPLICATIONS

- General-purpose packaging
- General-purpose packaging
- Lamination applications
- High-quality rotogravure printing
- Flexographic printing

TECHNICAL DATA — TYPICAL VALUES

Property		Unit	Typical values			Test Method
Thickness		μm	20	25	30	NODA PLAST Lab
Unit Weight		g/m ²	18.2	22.7	27.3	NODA PLAST Lab
Yield		m ² /kg	54.9	44	36.6	NODA PLAST Lab
Wetting Tension		mN/m	≥ 38			ASTM D2578
Opacity		%	1.8	2.2	2.5	DIN 53146
Haze		%	1.6	1.7	1.8	ASTM D1003
Gloss 45°		%	95	94	93	ASTM D2457
COF Dynamic F-F (U-U)		—	≤ 0.30			DIN EN ISO 8295
Tensile Strength	MD	MPa	160			ASTM D882
	TD		290			ASTM D882
Elongation at Break	MD	%	180			ASTM D882
	TD		60			ASTM D882
Tensile Modulus of Elasticity	MD	MPa	2000			ASTM D882
	TD		3800			ASTM D882
Thermal Shrinkage	MD	%	≤ 5			BMS TT 0.2
	TD		≤ 3			BMS TT 0.2

TECHNICAL NOTES

The numerical values reported in this data sheet are obtained from the average of the values recorded in our laboratory tests. Before final use, we recommend technical tests to ensure the film's suitability for the intended use. NODA PLAST Film is not responsible for inappropriate use of the product, and its liability is limited to the exclusive replacement of the product, excluding any compensation or damages of any kind.