CHROMIUM Chrome	**ICSC: 0029 (October 2004)**
CAS #: 7440-47-3 **EC Number: 231-157-5**	

	ACUTE HAZARDS	PREVENTION	FIRE FIGHTING
FIRE & EXPLOSION	Combustible under specific conditions.	If powder: NO open flames Closed system, dust explosion-proof electrical equipment and lighting. Prevent deposition of dust.	In case of fire in the surroundings, use appropriate extinguishing media.

PREVENT DISPERSION OF DUST!			
	SYMPTOMS	**PREVENTION**	**FIRST AID**
Inhalation	Cough.	Use local exhaust or breathing protection.	Fresh air, rest.
Skin		Protective gloves.	Remove contaminated clothes. Rinse skin with plenty of water or shower.
Eyes	Redness.	Wear safety goggles.	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.
Ingestion		Do not eat, drink, or smoke during work.	Rinse mouth.

SPILLAGE DISPOSAL	CLASSIFICATION & LABELLING
Personal protection: particulate filter respirator adapted to the airborne concentration of the substance. Sweep spilled substance into covered containers. If appropriate, moisten first to prevent dusting.	**According to UN GHS Criteria** **Transportation** **UN Classification**
STORAGE	
PACKAGING	

International Labour Organization World Health Organization

Prepared by an international group of experts on behalf of ILO and WHO, with the financial assistance of the European Commission.

European Commission

CHROMIUM **ICSC: 0029**

PHYSICAL & CHEMICAL INFORMATION

Physical State; Appearance
GREY POWDER.

Physical dangers
Dust explosion possible if in powder or granular form, mixed with air.

Chemical dangers
Chromium is a catalytic substance and may cause reaction in contact with many organic and inorganic substances, causing fire and explosion hazard.

Formula: Cr
Atomic mass: 52.0
Boiling point: 2642°C
Melting point: 1900°C
Density: 7.15 g/cm³
Solubility in water: none

EXPOSURE & HEALTH EFFECTS

Routes of exposure

Effects of short-term exposure
May cause mechanical irritation to the eyes and respiratory tract.

Inhalation risk
A harmful concentration of airborne particles can be reached quickly when dispersed.

Effects of long-term or repeated exposure

OCCUPATIONAL EXPOSURE LIMITS

TLV: (as Cr(0), inhalable fraction): 0.5 mg/m^3, as TWA

ENVIRONMENT

NOTES

The surface of the chromium particles is oxidized to chromium(III)oxide in air.
See ICSC 1531.

ADDITIONAL INFORMATION

EC Classification