

TITANIUM DIOXIDE**ICSC: 0338 (November 2019)**

Titanium (IV) oxide

Rutile

Anatase

CAS #: 13463-67-7; 1317-70-7; 1317-80-2**EC Number: 236-675-5**

	ACUTE HAZARDS	PREVENTION	FIRE FIGHTING
FIRE & EXPLOSION	Not combustible.		In case of fire in the surroundings: use appropriate extinguishing media.

PREVENT DISPERSION OF DUST!			
	SYMPTOMS	PREVENTION	FIRST AID
Inhalation		Avoid inhalation of dust.	
Skin		Protective gloves.	Rinse and then wash skin with water and soap.
Eyes	Redness.	Wear safety spectacles.	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.
Ingestion		Do not eat, drink, or smoke during work.	Rinse mouth.

SPILLAGE DISPOSAL	CLASSIFICATION & LABELLING
Personal protection: particulate filter respirator adapted to the airborne concentration of the substance. If appropriate, moisten first to prevent dusting. Sweep spilled substance into covered containers.	According to UN GHS Criteria DANGER Causes damage to respiratory system through prolonged or repeated exposure if inhaled Suspected of causing cancer Transportation UN Classification
STORAGE	
Store in covered containers.	
PACKAGING	
Do not transport with food and feedstuffs.	



World Health Organization

Prepared by an international group of experts on behalf of ILO and WHO, with the financial assistance of the European Commission.
© ILO and WHO 2021



European Commission

TITANIUM DIOXIDE

ICSC: 0338

PHYSICAL & CHEMICAL INFORMATION

Physical State; Appearance

COLOURLESS-TO-WHITE CRYSTALLINE POWDER.

Physical dangers**Chemical dangers**Formula: TiO₂

Molecular mass: 79.9

Boiling point: 2500-3000°C

Melting point: 1855°C

Density: 3.9-4.3 g/cm³

Solubility in water: none

EXPOSURE & HEALTH EFFECTS

Routes of exposure

The substance can be absorbed into the body by inhalation of dust.

Effects of short-term exposure**Inhalation risk**

A harmful concentration of airborne particles can be reached quickly when dispersed, especially if powdered.

Effects of long-term or repeated exposure

Lungs may be affected by repeated or prolonged exposure. This may result in chronic inflammation. This substance is possibly carcinogenic to humans if inhaled.

OCCUPATIONAL EXPOSURE LIMITS

TLV: 10 mg/m³, as TWA; A4 (not classifiable as a human carcinogen).MAK: 0.3 mg/m³; peak limitation category: II(8); carcinogen category: 4; pregnancy risk group: C

ENVIRONMENT

NOTES

The CAS numbers for different forms are: CAS 13463-67-7 (anatase/rutile); CAS 1317-70-7 (anatase); CAS 1317-80-2 (rutile). See ICSC 1782 for the nanoform of this substance.

ADDITIONAL INFORMATION

EC Classification

Note:

All rights reserved. The published material is being distributed without warranty of any kind, either expressed or implied. Neither ILO nor WHO nor the European Commission shall be responsible for the interpretation and use of the information contained in this material.