

ETHYL ACETATE**ICSC: 0367 (April 2014)**Acetic acid, ethyl ester
Acetic ether**CAS #: 141-78-6****UN #: 1173****EC Number: 205-500-4**

	ACUTE HAZARDS	PREVENTION	FIRE FIGHTING
FIRE & EXPLOSION	Highly flammable. Vapour/air mixtures are explosive. Heating will cause rise in pressure with risk of bursting.	NO open flames, NO sparks and NO smoking. Closed system, ventilation, explosion-proof electrical equipment and lighting. Use non-sparking handtools. Do NOT use compressed air for filling, discharging, or handling.	Use alcohol-resistant foam, foam, powder, carbon dioxide, fine water spray. In case of fire: keep drums, etc., cool by spraying with water.

PREVENT GENERATION OF MISTS!

	SYMPTOMS	PREVENTION	FIRST AID
Inhalation	Sore throat. Cough. Headache. Drowsiness.	Use ventilation, local exhaust or breathing protection.	Fresh air, rest. Refer for medical attention.
Skin	Redness. Dry skin.	Protective gloves.	Rinse contaminated clothes (fire hazard) with plenty of water. Remove contaminated clothes. Rinse skin with plenty of water or shower.
Eyes	Redness.	Wear safety spectacles or eye protection in combination with breathing protection.	Rinse with plenty of water for several minutes (remove contact lenses if easily possible).
Ingestion		Do not eat, drink, or smoke during work.	Rinse mouth. Seek medical attention if you feel unwell.

SPILLAGE DISPOSAL	CLASSIFICATION & LABELLING
Remove all ignition sources. Evacuate danger area! Consult an expert! Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance. Do NOT wash away into sewer. Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations.	According to UN GHS Criteria  DANGER Highly flammable liquid and vapour May cause drowsiness or dizziness Transportation UN Classification UN Hazard Class: 3; UN Pack Group: II
STORAGE	
Fireproof. Separated from strong oxidants, strong bases and strong acids.	
PACKAGING	

International
Labour
OrganizationWorld Health
OrganizationPrepared by an international group of experts on behalf of ILO and WHO, with the financial assistance of the European Commission.
© ILO and WHO 2021European
Commission

ETHYL ACETATE

ICSC: 0367

PHYSICAL & CHEMICAL INFORMATION

Physical State; Appearance

COLOURLESS LIQUID WITH CHARACTERISTIC ODOUR.

Physical dangers

The vapour is heavier than air and may travel along the ground; distant ignition possible.

Chemical dangers

Reacts with strong oxidants. This generates fire and explosion hazard.

Reacts violently with strong bases and strong acids. Attacks rubber and some forms of plastic.

Formula: $C_4H_8O_2$ / $CH_3COOC_2H_5$

Molecular mass: 88.1

Boiling point: 77°C

Melting point: -84°C

Relative density (water = 1): 0.9

Solubility in water, g/100ml at 20°C: 8.7 (poor)

Vapour pressure, kPa at 20°C: 10

Relative vapour density (air = 1): 3.0

Relative density of the vapour/air-mixture at 20°C (air = 1): 1.2

Flash point: -4°C c.c.

Auto-ignition temperature: 427°C

Explosive limits, vol% in air: 2.0-12.8

Octanol/water partition coefficient as log Pow: 0.73

EXPOSURE & HEALTH EFFECTS

Routes of exposure

The substance can be absorbed into the body by inhalation of its vapour.

Effects of short-term exposure

The substance is mildly irritating to the eyes and respiratory tract. The substance may cause effects on the central nervous system. Exposure far above the OEL could cause lowering of consciousness.

Inhalation risk

A harmful contamination of the air will be reached rather slowly on evaporation of this substance at 20°C.

Effects of long-term or repeated exposure

The substance defats the skin, which may cause dryness or cracking.

OCCUPATIONAL EXPOSURE LIMITS

TLV: 400 ppm as TWA.

MAK: 750 mg/m³, 200 ppm; peak limitation category: I(2); pregnancy risk group: C.EU-OEL: 734 mg/m³, 200 ppm as TWA; 1468 mg/m³, 400 ppm as STEL

ENVIRONMENT

NOTES

Do NOT take working clothes home.

ADDITIONAL INFORMATION

EC Classification

Symbol: F, Xi; R: 11-36-66-67; S: (2)-16-26-33

All rights reserved. The published material is being distributed without warranty of any kind, either expressed or implied. Neither ILO nor WHO nor the European Commission shall be responsible for the interpretation and use of the information contained in this material.