

BENZYL ALCOHOL**ICSC: 0833 (April 2000)**

Benzenemethanol
 Phenyl carbinol
 alpha-Hydroxytoluene
 Benzoyl alcohol
 Phenyl methanol

CAS #: 100-51-6**EC Number: 202-859-9**

	ACUTE HAZARDS	PREVENTION	FIRE FIGHTING
FIRE & EXPLOSION	Combustible.	NO open flames.	Use powder, AFFF, foam, carbon dioxide.

	SYMPTOMS	PREVENTION	FIRST AID
Inhalation	Cough. Dizziness. Headache.	Use ventilation.	Fresh air, rest. Refer for medical attention.
Skin	Redness.	Protective gloves.	Remove contaminated clothes. First rinse with plenty of water for at least 15 minutes, then remove contaminated clothes and rinse again.
Eyes	Redness.	Wear safety spectacles.	First rinse with plenty of water for several minutes (remove contact lenses if easily possible), then refer for medical attention.
Ingestion	Abdominal pain. Diarrhoea. Drowsiness. Nausea. Vomiting.	Do not eat, drink, or smoke during work.	Rinse mouth. Refer for medical attention .

SPILLAGE DISPOSAL	CLASSIFICATION & LABELLING
Collect leaking and spilled liquid in sealable containers as far as possible. Absorb remaining liquid in sand or inert absorbent. Then store and dispose of according to local regulations. Personal protection: filter respirator for organic gases and vapours adapted to the airborne concentration of the substance.	According to UN GHS Criteria Transportation UN Classification
STORAGE	
Separated from strong oxidants.	
PACKAGING	



International
Labour
Organization



World Health
Organization

Prepared by an international group of experts on behalf of ILO and WHO, with the financial assistance of the European Commission.
 © ILO and WHO 2021



European
Commission

BENZYL ALCOHOL**ICSC: 0833****PHYSICAL & CHEMICAL INFORMATION****Physical State; Appearance**

COLOURLESS LIQUID WITH CHARACTERISTIC ODOUR.

Physical dangers**Chemical dangers**

Reacts with strong oxidants. Attacks some forms of plastic. On combustion, forms toxic gases including carbon monoxide.

Formula: C_7H_8O / $C_6H_5CH_2OH$

Molecular mass: 108.1

Boiling point: 205°C

Melting point: -15°C

Relative density (water = 1): 1.04

Solubility in water, g/100ml: 4

Vapour pressure, Pa at 20°C: 13.2

Relative vapour density (air = 1): 3.7

Relative density of the vapour/air-mixture at 20°C (air = 1): 1.0

Flash point: 93°C c.c.

Auto-ignition temperature: 436°C

Explosive limits, vol% in air: 1.3-13

Octanol/water partition coefficient as log Pow: 1.1

EXPOSURE & HEALTH EFFECTS**Routes of exposure**

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

Effects of short-term exposure

The aerosol is irritating to the eyes and skin. The substance may cause effects on the nervous system.

Inhalation risk

No indication can be given about the rate at which a harmful concentration of this substance in the air is reached on evaporation at 20°C.

Effects of long-term or repeated exposure

Repeated or prolonged contact may cause skin sensitization.

OCCUPATIONAL EXPOSURE LIMITSMAK: 22 mg/m³, 5 ppm; peak limitation category: I(2); skin absorption (H); pregnancy risk group: C**ENVIRONMENT**

The substance is toxic to aquatic organisms.

NOTES**ADDITIONAL INFORMATION****EC Classification**

Symbol: Xn; R: 20/22; S: (2)-26

All rights reserved. The published material is being distributed without warranty of any kind, either expressed or implied. Neither ILO nor WHO nor the European Commission shall be responsible for the interpretation and use of the information contained in this material.