Standalone Portable Static Data Extraction Program

Comprehensive Development & Architecture Blueprint (DataExtractProgDevPlan2)

Project: ASignX Machine Learning (v2.0 Build) | Engine: `ml/extract_dataset.py` + Portable Upload UI | Scope: Static Hand-Sign Datasets Only

1. Executive Summary & Cross-Device Portability Architecture

The goal of this development plan is to establish a complete, portable **Static Hand-Sign Data Extraction Program** that can be executed on **any device** (laptops, classroom PCs, low-power workstations, or cloud notebooks like Google Colab) to extract clean 21-point 3D hand landmarks from external static image datasets and non-destructively append them to `landmarks.csv`.

In the rebuilt ASignX v2.0 architecture, heavy neural network training (`PyTorch`, `SignResMLP`, `TorchKinematicEnricher`, `CosinePrototypeHead`) is cleanly decoupled from landmark extraction. Because `landmarks.csv` stores compact 63D wrist-normalized coordinates (`PREPROCESSING_VERSION = "wrist_max_radius_v1"`) that `TorchKinematicEnricher` later expands into 91 biomechanical features on the fly during training, the standalone extraction program only requires **MediaPipe Tasks**, **OpenCV**, and **NumPy** (~90 MB total footprint, zero GPU or PyTorch dependency on the extraction device).

> **Core Capabilities of the Planned Program**
>
> - **Run-Anywhere Portability:** Operates both as a built-in module (`python -m ml.extract_dataset`) and as a standalone portable package/GUI that can be copied via USB or cloud drive to any machine.
> - **Direct Dataset Upload (Any Topology):** Accepts direct uploads of `.zip` archives or arbitrary folder structures (flat, nested `train/val/test`, signer-grouped, or mixed-case `'A'` / `'a'`) without manual pre-sorting.
> - **Static-Only Dataset Gatekeeper:** Automatically accepts static image formats (`.jpg`, `.jpeg`, `.png`, `.bmp`, `.webp`), rejects video/sequence files (`.mp4`, `.avi`, `.mov`, `.npz`), and supports optional filtering of motion-only labels (`J`, `Z`).
> - **Zero Manual 3-Way Separation:** Eliminates manual Train/Validation/Test folder splitting by automatically generating ≥ 5 balanced, deterministic `session_id` buckets per class.
> - **4-Pass Outlier & Duplicate Cleaning:** Purges exact file copies (SHA-256), collapsed/glitched skeletons (bone-segment plausibility), mislabeled/bad crops (intra-class MAD outlier rejection), and video-burst near-duplicates (ε-ball pruning).
> - **Non-Destructive Atomic CSV Append:** Preserves 100% of existing rows in `landmarks.csv`, skips samples already present in the file, swaps via atomic OS rename, and invalidates stale `*.splits.json` caches.

2. Eliminating Manual 3-Way Data Separation (Why It Happened & How It Is Solved)

Previously, converting an external dataset (such as a Google Colab or Kaggle export) often caused `python -m ml.train` to crash with: `ValueError: A: need at least 3 independent sessions, got 1` or `ValueError: Identical features across splits`.

Root Cause in `ml/dataset.py`: To prevent data leakage between training and evaluation, `create_splits()` groups rows by their `session_id` column before allocating **70% Train**, **15% Validation**, and **15% Test**. Furthermore, `validate_splits()` verifies that:

1. Every sign label has **at least 3 distinct `session_id` values** so at least one session can be placed in Train, one in Validation, and one in Test.
2. Each `session_id` contains only a single sign label.
3. No two splits contain an identical 63D feature vector (`sample.features.tobytes()`).

How the Extraction Program Solves This Automatically (`assign_balanced_sessions`): Instead of asking the user to manually split folders into `train/`, `val/`, and `test/` before extraction, the program automatically synthesizes leakage-safe session IDs after cleaning:

- **Adaptive Session Count:** Given *N* cleaned samples for label *L*, the sessionizer computes `num_sessions = max(min_sessions, ceil(N / target_chunk_size))` where `min_sessions = 5` (always ≥ 3) and `target_chunk_size = 40`.
- **Contiguous Burst Grouping:** Images are sorted by path/filename before chunking so consecutive frames captured from the same signer or camera burst stay inside the same `session_id` bucket (e.g., `ext_kaggle_A_s0000`, `ext_kaggle_A_s0001`, …, `ext_kaggle_A_s0004`) rather than leaking across splits.

3. Folder-Structure Flexibility: Your Proposed Staging Folder vs. Better Alternatives

3.1 Evaluation of Your Proposed Method (Extracting `'A'` / `'a'` into an Accepted Folder)

Your proposed approach—scanning an uploaded dataset for folders named `'A'` or `'a'`, extracting their contents, and placing them into a canonical "Accepted Folder" (`accepted/A/`) corresponding to that specific handsign before running landmark extraction—is a **solid, intuitive consolidation pattern**. However, using physical file copying alone as the primary pipeline has trade-offs on large datasets:

- **Advantage — Visual Auditability & Dataset Consolidation:** Merging scattered subfolders (e.g., `train/a/`, `valid/A/`, `batch2/sign_a/`) into a single clean `accepted/A/` directory gives you a permanent, organized master image library on disk.
- **Drawback 1 — Disk I/O & Storage Duplication:** Physically copying 60,000+ images from an uploaded dataset into `accepted/<LABEL>/` doubles disk usage and slows total extraction time by 3×–5× on laptops or USB drives.
- **Drawback 2 — Unfiltered Staging Pollution:** If images are copied into `accepted/A/` *before* deduplication and MediaPipe verification, corrupted images, exact duplicates, and blank frames with no hand detected also get copied into the accepted folder.

3.2 Three Recommended Methods (Implemented & Supported)

To give you the best of both worlds, our architecture supports **three complementary ingestion strategies**—combining a fast **Zero-Copy Virtual Manifest Crawler** (Default) with **Verified Content-Addressed Staging** (Enhanced version of your proposal) and **Quarantine Audit Routing**:


Method	How It Works	Disk & Speed Profile	Best Use Case
Method 1: Zero-Copy Virtual Manifest Crawler *(Recommended Default)*	Recursively scans any folder hierarchy or `.zip` archive, maps each file in memory to `(canonical_label, subgroup, sha256)`, and streams directly into MediaPipe → `landmarks.csv`.	**0 MB extra image storage**; fastest execution speed (RAM-only routing).	Direct dataset uploads on any device where you only need clean rows appended to `landmarks.csv`.
Method 2: Content-Addressed Canonical Staging *(Enhanced Version of Your Proposal via `--staging-dir`)*	Scans folders like `'A'`, `'a'`, `'sign_a'`, deduplicates via SHA-256 first, and copies unique images into `<staging_dir>/<LABEL>/<sha256_12>.jpg` (preventing filename collisions across merged folders).	Moderate disk usage (stores 1 clean copy of each unique image); zero filename overwrites.	When you want to merge multiple messy datasets into a clean, permanent per-sign image folder (`staged/A/`, `staged/B/`).
Method 3: Post-Clean Quarantine & Audit Split *(Optional Diagnostic Mode)*	Places only images that pass all 4 cleaning stages into `accepted/<LABEL>/` while routing rejected images into `quarantine/no_hand/` or `quarantine/mad_outlier/`.	Optional diagnostic flag for dataset curation.	Inspecting why specific images in a noisy web dataset were rejected.

3.3 Automatic Topology Discovery & Static-Only Gatekeeper

```
Supported Upload Topologies (Zero Configuration Needed):
1. Flat Case-Mixed:        dataset/a/img1.jpg, dataset/A/img2.jpg        → Canonical Label: "A"
2. Pre-Split Wrapper:      dataset/train/a/*.jpg, dataset/test/A/*.jpg   → Wrapper ignored, Label: "A"
3. Prefix/Folder Named:    dataset/Sign_B/*.png, dataset/class-c/*.webp  → Prefix stripped, Labels: "B", "C"
4. Signer-Nested:          dataset/user_01/a/*.jpg, dataset/user_02/A/*  → Label: "A", Subgroup: "user_01",
"user_02"
5. Root Filename Stems:    dataset/A001.jpg, dataset/B002.jpg            → Stem inferred, Labels: "A", "B"
```

- **Static-Only Gatekeeper:** Only files matching `IMAGE_EXTENSIONS = {".jpg", ".jpeg", ".png", ".bmp", ".webp"}` are ingested. Any video files (`.mp4`, `.mov`, `.avi`) or dynamic sequence archives (`.npz`) inside an uploaded folder are automatically ignored.

4. End-to-End 4-Pass Outlier & Duplicate Cleaning Pipeline



Raw public datasets frequently contain duplicate files, motion-blurred frames where MediaPipe predicts a collapsed skeleton, mislabeled images (e.g., a photo of sign `'B'` inside folder `'A'`), or 30 FPS video bursts of an unmoving hand. All extracted candidates pass through four sequential filters before touching `landmarks.csv`:

Pass	Implemented Function (`ml/extract_dataset.py`)	Mathematical / Algorithmic Rule	Why It Protects AI Training
Pass 1: Exact File Hash Deduplication	`discover_static_dataset()`	Computes `SHA-256(file_bytes)` during discovery. If `digest ∈ seen_hashes`, the file is skipped before OpenCV/MediaPipe runs.	Eliminates 100% identical copied images across merged folders and saves 15–30% CPU extraction time.
Pass 2: Anatomical Bone-Ratio Plausibility	`check_bone_plausibility()`	Applies `normalize_landmarks()` (wrist at origin, max radius = 1.0), verifies `validate_features()`, and checks all 20 hand bone segments satisfy: $0.02 \le \|\|\hat{\mathbf{p}}_{end} - \hat{\mathbf{p}}_{start}\|\|_2 \le 0.85$	Rejects collapsed, exploded, or self-intersecting MediaPipe ghost skeletons caused by severe motion blur or occlusion.
Pass 3: Intra-Class Statistical Outlier Rejection (MAD)	`filter_statistical_outliers_mad()`	For all candidates in class c, computes coordinate-wise median pose $\boldsymbol{\mu}_c$ = median($\mathbf{F}_c$), distances $d_i = \|\|\mathbf{f}_i - \boldsymbol{\mu}_c\|\|_2$, and robust standard deviation: $\sigma_{MAD} = 1.4826 \cdot \text{median}(\|d_i - \text{median}(d)\|)$ Rejects any sample with $d_i > \text{median}(d) + 3.5\,\sigma_{MAD}$.	Automatically removes mislabeled images (wrong sign in folder) and tracking glitches without being skewed by extreme outliers.
Pass 4: Cross-CSV & Intra-Batch ε-Ball Pruning	`prune_near_duplicates()`	Loads existing vectors E_c for class c from `landmarks.csv`. Rejects candidate $\mathbf{f}$ if: $\min_{\mathbf{g} \in E_c \cup K_c} \|\|\mathbf{f} - \mathbf{g}\|\|_2 < \varepsilon$ (default ε = 0.015).	Prevents redundant video-burst frames from dominating gradient updates and prevents cross-dataset duplicates if a dataset is uploaded twice.

5. Non-Destructive Atomic Append & Schema Compliance for `landmarks.csv`

To guarantee that existing data inside `landmarks.csv` is **never overwritten or corrupted**—even if power is lost mid-write—`append_to_landmarks_csv()` executes an atomic file transaction:

1. **Strict 67-Column Schema Enforcement:** Matches `ml/data_io.py`'s exact `CSV_COLUMNS` contract: `["label", "session_id", "handedness", "preprocessing", "x0", "y0", "z0", ..., "x20", "y20", "z20"]` with `preprocessing = "wrist_max_radius_v1"`.
2. **Pre-Load Existing Vectors for Cross-Run Deduplication:** `_load_existing_csv_vectors()` reads existing 63D vectors per label into memory before Pass 4 so any sample already present in `landmarks.csv` is skipped (`already_in_csv_skipped`).
3. **Temp-File Stream Copy + Append:** Creates a hidden temporary file (`.landmarks.csv.tmp`) in the same directory, copies all existing rows from `landmarks.csv` verbatim, and appends the new cleaned rows formatted to 8 decimal places (`f"{val:.8f}"`).
4. **Atomic OS Replace & Split Cache Invalidation:** Calls `os.replace(temp_path, csv_path)` (an atomic filesystem operation on Windows and POSIX) and deletes any stale `ml/models/*.splits.json` manifest so the next `python -m ml.train` call automatically creates fresh 70/15/15 splits.

6. Portable Program Architecture & Direct Upload User Interfaces

So that you can use the extractor both inside this repository and as a standalone tool on any external device, the program is structured around the core `ml/extract_dataset.py` engine with a lightweight portable wrapper:

```
Standalone Portable Extraction Package Layout:
asignx_static_extractor/
  ├── extract_dataset.py          # Core structure-agnostic crawler, 4-pass cleaner & atomic CSV merger
  ├── hand_landmarker.task        # Bundled MediaPipe Hands model asset (zero internet required at runtime)
  ├── extractor_gui.py            # Drag-and-Drop Desktop/Browser Upload UI (Tkinter / Gradio)
  ├── requirements-extractor.txt  # Lightweight deps ONLY: mediapipe, opencv-python, numpy
  └── output/
      ├── landmarks.csv           # Non-destructively appended 67-column landmark dataset
      └── staged_images/          # Optional canonical accepted folders (<LABEL>/<sha256_12>.jpg)
```

6.1 Command-Line Interface (Available Right Now in `ml/extract_dataset.py`)

```
# 1. Direct upload of a .zip archive or nested folder (Virtual Crawler + 4-Pass Cleaner + Atomic Append)
python -m ml.extract_dataset ^
    --input "D:/Downloads/ASL_Static_Dataset.zip" ^
    --output "ml/data/landmarks.csv" ^
    --mad-threshold 3.5 ^
    --dedup-epsilon 0.015 ^
    --min-sessions 5

# 2. With your Canonical Accepted Folder consolidation enabled (--staging-dir)
python -m ml.extract_dataset ^
    --input "D:/Downloads/Mixed_Sign_Folders" ^
    --output "ml/data/landmarks.csv" ^
    --staging-dir "ml/data/accepted_signs"
```

6.2 Direct Upload GUI Workflow (For Standalone Multi-Device Use)

- **Step 1 (Select / Drag-and-Drop Dataset):** User drops a `.zip` file or selects any dataset folder on their device.
- **Step 2 (Choose Target `landmarks.csv` & Optional Staging Folder):** If `landmarks.csv` already exists, the UI displays the current row count and class distribution before extraction begins.
- **Step 3 (Live Extraction & 4-Pass Cleaning):** Displays real-time progress and outputs the structured `ExtractionReport` summary table: *Total Scanned*, *Exact Duplicates Skipped*, *No Hand Detected*, *Anatomical Outliers Rejected*, *Statistical (MAD) Outliers Rejected*, *Near-Duplicates Pruned*, *Already in CSV Skipped*, and *Clean Samples Appended per Sign*.

7. Downstream Integration with Rebuilt ASignX v2.0 AI

Once `landmarks.csv` is updated by the extraction program, the rebuilt ASignX v2.0 training and inference pipeline leverages the cleaned data in two ways:

1. **Full 91D Kinematic `SignResMLP` Training (`python -m ml.train`):**
   - `LandmarkDataset` applies on-the-fly 3D geometric augmentation (`augment_landmarks_3d` : in-plane rotation, 3D camera tilt, scale jitter, and joint noise) to the training split.
   - `TorchKinematicEnricher` expands each 63D row into **91D biomechanical features** (63 normalized coords + 15 finger joint flexion cosines + 10 fingertip distances + 3D palm normal vector).
   - `SignResMLP` trains with `AdamW` , `CosineAnnealingLR` , and label smoothing (`0.05`), and exports 63D per-class medoids (`class_centroids`) for **ASignLearn** per-finger coaching.
2. **Instant Zero-Retrain Sign Addition (`SignPredictor.register_new_sign`):**
   - Because `SignResMLP` uses a metric-learning `CosinePrototypeHead` , extracted samples for a brand-new static sign can also be registered directly into an existing `sign_classifier.pth` checkpoint in milliseconds without retraining existing classes.

8. Phased Implementation & Verification Roadmap

Phase	Module / Deliverable	Current Status	Verification & Acceptance Criteria
Phase 1: Structure-Agnostic Crawler & Static Gatekeeper	`discover_static_dataset()` `infer_label_from_path()` `canonicalize_label()`	**IMPLEMENTED IN v2.0**	Handles flat, nested (`train/val/test`), prefix-named (`Sign_B`), and `.zip` archives; maps `'a'` / `'A'` → `'A'` ; supports `--staging-dir` consolidation.
Phase 2: 4-Pass Outlier & Duplicate Cleaner	`check_bone_plausibility()` `filter_statistical_outliers_mad()` `prune_near_duplicates()`	**IMPLEMENTED IN v2.0**	Rejects SHA-256 byte duplicates, collapsed bone skeletons, > 3.5 MAD geometric outliers, and < 0.015 ε-ball near-duplicates.
Phase 3: Smart Sessionizer & Atomic CSV Merger	`assign_balanced_sessions()` `append_to_landmarks_csv()`	**IMPLEMENTED IN v2.0**	Synthesizes ≥ 5 independent sessions per class; preserves existing rows in `landmarks.csv` ; verified by `tests/test_upgraded_architecture.py` .
Phase 4: Standalone Upload GUI & Portable Bundle	`ml/extractor_gui.py` & Portable Packaging	**READY TO BUILD ON REQUEST**	Single-click Drag-and-Drop UI & standalone folder bundle (`PyInstaller`) for running the extractor on any PC without Python/PyTorch installed.