

Cementitious HPL Finish Raised Floor FS800

## **Product Description:**

The panel is made of high quality cold-rolled steel sheet .The bottom sheet is used ST14 stretched steel, which are punched, spot-welded, coated with epoxy powder after being phosphorated and infilled the foamed cement. The finish can cover the HPL, PVC or others, the edges of panel are trimmed with 4 pieces black PVC. This panel is high capacity, easy installation, elegant appearance, fouling resistance, corrosion resistance, long using life, excellent waterproof and fireproof performance.

Туре		FS800	
Panel			
Panel Size		600*600*35mm	
Color		White	
Concentrated	N	3560	4
Load	KG	363	*
Impact Load/N		670	
Ultimate Load/N		10680	
Uniform Load/N		16000	ılı
Rolling	10 times	3560	] 4: []
Load/N	1000 times	2950	
Reaction to Fire		A1	
Weight Per Panel/KG		13	
Flat Pedestal			
Pedestal Top		80*80*3mm	
Pedestal Rod		Φ22mm	3
Pedestal Base		90*90*3mm	~ \s
Adjustment		±20mm	Panel
Color		White	Stringer
Stringer			
Size		21*32*572mm	Pedestal top
Thickness of Tube Wall		1mm	redesign top
Color		White	Pedestal tube
Weight Per Stringer/KG		0.4	Pedestal base
Screw			reuestal base
Size		6*43mm	6