


BLG252E - Object Oriented Programming

HOMEWORK #1

Due Date: 24.10.2013

The following diagram shows three C++ classes for a school.

Upper sections are class names, middle sections are attributes (member data), and lower sections are methods (functions).



Write a C++ program to do the followings:

- 1) Read the input text data files (CATALOG.TXT, SECTIONS.TXT, and STUDENTS.TXT) and initialize your objects. (For file reading, you may use either the C functions fscanf and fgets, or the C++ object ifstream).
- 2) Read the input transactions file (TRANSACTIONS.TXT) which contains several transaction directives (as uppercase strings) and parameter data, and perform the requested actions.

There are 5 possible transaction directives (i.e., operations) which are described below.

Transaction Directive	Transaction Parameters	Things to do
ENROLL	<CRN> <List of Student ID numbers>	Add the specified students to the given course section. (You should consider it as a sequence of several ADD actions.)
ADD	<CRN> <Student ID number>	Add the student to the given course section.
DROP	<CRN> <Student ID number>	Remove the student from the given course section.
PRINT_SECTION	<CRN>	Print list of students (ID, First name, Last name, students' MajorCode) that are enrolled to the given course section. Also total number of students enrolled should be displayed.
PRINT_STUDENT	< Student ID number >	Print list of course sections (CRN, Course Code, Course Title, Credits) that the student is enrolled. Also total credits of the student should be calculated and displayed.

SAMPLE INPUT DATA FILES (4 Files):

CATALOG.TXT

```
MAT101 Mathematics 4
MAT105 Calculus 4
ELE101 Electronics 3
FIZ101 Physics 2
.....
```

STUDENTS.TXT

```
10030066 Abdullah Akkaya MET
10050183 Adnan Erguven TEK
10070045 Ahmet Pekkoc ISL
10070090 Ahmet Avci ISL
10070046 Ahmet Ozdemir INS
10080049 Ahmet Ulas GMI
10080094 Asli Karacayli KIM
```

.....

.....

.....

SECTIONS.TXT

```
6001 MAT105 JEO MAD INS
6002 MAT105 JEO MAD INS
7001 MAT101 BIO GID GMI INS ISL JEO KIM KMM MAD MET TEK
7002 MAT101 BIO GID GMI INS ISL JEO KIM KMM MAD MET TEK
7003 MAT101 BIO GID GMI INS ISL JEO KIM KMM MAD MET TEK
8001 ELE101 GMI TEK
8002 ELE101 GMI TEK
9001 FIZ101 INS
```

.....

.....

TRANSACTIONS.TXT

```
ENROLL 6001 130100204 70080016 140080024
ENROLL 6002 130080015 60100119 60100419 90100335 60080179
ENROLL 7001 70100025 130100204 60100119 140100028 10030066 130100272 70080016
ENROLL 7002 70100074 70100069 90090270 70110128 10100136 10080125 10110065
ENROLL 8001 70080016 10080097 70100025 140090046 10050183 130120701
ENROLL 8002 70110050 60060124 60110810 10030066 70080016
ENROLL 9001 60100119 70080016 50080129 60080155 70100025 10100553 70080023
ADD 7001 60100119
ADD 7001 140080016
ADD 7002 70090072
DROP 7001 130100272
DROP 7002 90090270
PRINT_SECTION 6001
PRINT_SECTION 7001
PRINT_SECTION 7002
PRINT_SECTION 8002
PRINT_STUDENT 70100025
PRINT_STUDENT 70080016
```

.....

.....

OTHER REQUIREMENTS:

- When adding a student to a course section, your program should check the student's major code with the allowed major codes for that section. Display a warning message if the ADD operation fails.
- The TotalCredits of a student can not be more than 10 credits. Display a warning message if the ADD operation fails for that reason.
- Write appropriate class constructors and destructors in your code.
- Your program should be general, and should be independent of the sample data given in the input files.

In order to tokenize (i.e., splitting into separate words) a sentence of unknown size, you may use the function **tokenlara_ayir()** given below.

```
#include <iostream>
#include <string.h>
using namespace std;
#define N 20      // Maximum number of words
#define LEN 15    // Maximum length of a word

void tokenlara_ayir( char * cumle, char dizi[N][LEN])
// Input : cumle
// Output : dizi
{
    int i=0;
    char *tokenPtr; // Define word pointer

    tokenPtr = strtok( cumle, " " ); // Begin tokenizing sentence.

    // Continue tokenizing sentence until tokenPtr becomes NULL.
    while ( tokenPtr != NULL ) {
        strcpy(dizi[i] , tokenPtr );
        i++;
        tokenPtr = strtok( NULL, " " ); // Get next token
    }
}

int main() {
    char ornek_cumle[200] = "aaaa bbbbb cccc dddd";
    char kelimeler[N][LEN];
    int i;
    for (i=0; i< N; i++)
        strcpy(kelimeler[i] , "");

    tokenlara_ayir(ornek_cumle, kelimeler);
    for (i=0; i< N; i++)
        if (strcmp(kelimeler[i], "") != 0 )
            cout << i+1 << " = " << kelimeler[i]<< endl;
    return 0;
}
```