

**TD88 std. RAL 7035, singlepack - Wing nut**  
**120822**

**Our standard solutions meet most needs**

We know not two customers are alike, which is why you can choose from a range of standard solutions or customised dishes and packaging upon request.

As a leading satellite dish manufacturer, we offer “one-stop-shopping” with all accessories needed to get the installation right.

We have also made installation quick and easy, as many parts are pre-mounted on the dish meaning few tools are needed.

- Size (height) 88 cm
- Colour - RAL 7035
- Acc. bags - Wing nut with 1 or 2 mastclamps depending on dish size
- Packaging: Single pack

All TRIAX dishes are manufactured in galv. steel and are supplied with mounting kit and TRIAX logo on the reflector. All standard LNBs can be fitted and our range of wall brackets provide different options for your installation.

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702661208225

### CHARACTERISTICS

G/T LNB 0.7 19.2 dB/K  
 X-polarisation >27 dB  
 Offset angle 26 °  
 Elevation range 10-60 °

### FREQUENCY

Frequency range 10.7 - 12.75 GHz

### GAIN

Gain @ 11.7 GHz 38.8 dBi

### MECHANICAL

Material Galvanized Steel  
 Height (cm) 95 cm  
 Width (cm) 85 cm  
 LNB holder 23-40mm / Black  
 Mast bracket diameter <60 mm  
 Reflector type Offset  
 Beamwidth 2.0 °  
 Windload @ 42 m/s 902 N

20-10-2016

Triax - TD88 std. RAL 7035, singlepack - Wing nut

|                               |                       |
|-------------------------------|-----------------------|
| Dish colour                   | RAL 7035              |
| Back structure colour         | raw                   |
| Dimensions carton (H x D x W) | 937 x 942 x 150       |
| Finish                        | Polyester powder coat |
| Remarks                       | Singlepacked          |
| Packaging Volume              | 0,132 m3              |
| Net Weight                    | 5,800 kg              |
| Tara Weight                   | 1,200 kg              |
| Total Weight                  | 7,000 kg              |
| Packaging Height              | 0,150 m               |
| Packaging Width               | 0,942 m               |
| Packaging Depth               | 0,937 m               |