BUG BOUNTY
MISSION ANSWER KEY

CyberForge Games - Classified Document

Type the EXACT text from the 'Answer to Type' column. Game picks 2 missions randomly each run.

INITIATE LEVEL [90s timer]

ID	Lang	Code / Clue	Answer to Type
BB_IN_01	C	printf("Hello World") [;]	printf("Hello World") [;] **;**
BB_IN_02	Python	def greet(name) [:]	def greet(name) [:] **:**
BB_IN_03	HTML	Hello World [ ]	Hello World [ ] ** **
BB_IN_04	HTML	<img src=logo.png> ["]	<img src=logo.png> ["] **"**
BB_IN_05	Python	if True [:]	if True [:] **:**
BB_IN_06	C	if (a = 10) [==]	if (a = 10) [==] **==**
BB_IN_07	HTML	 [href]	 [href] **href**
BB_IN_08	HTML	<button type="submit" Click... [>]	<button type="submit" Click... [>] **>**
BB_IN_09	Python	items[3] [index]	items[3] [index] **index**
BB_IN_10	C	char name[5] = "Antigravity" [size]	char name[5] = "Antigravity" [size] **size**
BB_IN_11	HTML	Content [nesting]	Content [nesting] **nesting**
BB_IN_12	Python	print inside while; no indent [indent]	print inside while; no indent [indent] **indent**
BB_IN_13	HTML	1 2 [ ]	1 2 [ ] ** **
BB_IN_14	C	int x = 10 / 0 [zero]	int x = 10 / 0 [zero] **zero**

ID	Lang	Code / Clue	Answer to Type
BB_IN_15	HTML	<table <tr><td>Row... [>]	<table <tr><td>Row... [>] >
BB_IN_16	Python	x(int) + "5"(str) [type]	x(int) + "5"(str) [type] type
BB_IN_17	C	void swap(int a, int b) [pointer]	void swap(int a, int b) [pointer] pointer
BB_IN_18	HTML	<h1>Main Title</h3> [</h1>]	<h1>Main Title</h3> [</h1>] </h1>
BB_IN_19	HTML	<input type=text value=Name> ["]	<input type=text value=Name> ["] "
BB_IN_20	Python	for/if without proper indentation [indent]	for/if without proper indentation [indent] indent
BB_IN_21	C	void main() [int]	void main() [int] int
BB_IN_22	HTML	head inside body tag [order]	head inside body tag [order] order
BB_IN_23	HTML	<meta charset="UTF-8" > [none]	<meta charset="UTF-8" > [none] none
BB_IN_24	Python	print(unknown_var) [name]	print(unknown_var) [name] name
BB_IN_25	C	scanf("%d", x) [&]	scanf("%d", x) [&] &
BB_IN_26	HTML	<img src="logo.png" alt="Logo"> [none]	<img src="logo.png" alt="Logo"> [none] none
BB_IN_27	HTML	Item 1 [ ]	- Item 1 [ ]
BB_IN_28	HTML	Home []	Home []

OPERATIVE LEVEL [60s timer]

ID	Lang	Code / Clue	Answer to Type
BB_OP_01	C	malloc without free [free]	malloc without free [free] **free**
BB_OP_02	HTML	multiple ID attributes on element [duplicate]	multiple ID attributes on element [duplicate] **duplicate**
BB_OP_03	HTML	label missing 'for' attribute [for]	label missing 'for' attribute [for] **for**
BB_OP_04	Python	def func(a=[]) [mutable]	def func(a=[]) [mutable] **mutable**
BB_OP_05	C	while(1) { fork(); } [fork]	while(1) { fork(); } [fork] **fork**
BB_OP_06	HTML	form with multiple actions [action]	form with multiple actions [action] **action**
BB_OP_07	HTML	invalid overlapping tags [nesting]	invalid overlapping tags [nesting] **nesting**
BB_OP_08	Python	1 / 0.0000...1 [none]	1 / 0.0000...1 [none] **none**
BB_OP_09	C	ptr != NULL && *ptr == 0 [none]	ptr != NULL && *ptr == 0 [none] **none**
BB_OP_10	HTML	nested button elements [nested]	nested button elements [nested] **nested**
BB_OP_11	HTML	invalid child inside select [option]	invalid child inside select [option] **option**
BB_OP_12	Python	[[]] * 3 [copy]	[[]] * 3 [copy] **copy**
BB_OP_13	C	gets(buf) [bounds]	gets(buf) [bounds] **bounds**
BB_OP_14	HTML	img missing alt attribute [alt]	img missing alt attribute [alt] **alt**
BB_OP_15	HTML	iframe with 'path' instead of 'src' [src]	iframe with 'path' instead of 'src' [src] **src**
BB_OP_16	Python	isinstance(True, int) [none]	isinstance(True, int) [none] **none**
BB_OP_17	C	return &local_var [scope]	return &local_var [scope] **scope**
BB_OP_18	HTML	style tag using 'color' attribute [type]	style tag using 'color' attribute [type] **type**

ID	Lang	Code / Clue	Answer to Type
BB_OP_19	HTML	script with src and inline content [both]	script with src and inline content [both] **both**
BB_OP_20	Python	x=5 outer; def f(): x=10 local [global]	x=5 outer; def f(): x=10 local [global] **global**
BB_OP_21	C	alloca(10000000) [stack]	alloca(10000000) [stack] **stack**
BB_OP_22	HTML	video missing controls [controls]	video missing controls [controls] **controls**
BB_OP_23	HTML	form missing submission method [method]	form missing submission method [method] **method**
BB_OP_24	Python	round(2.5) vs round(3.5) [round]	round(2.5) vs round(3.5) [round] **round**
BB_OP_25	C	printf(user_input) [format]	printf(user_input) [format] **format**

OMEGA LEVEL [45s timer]

ID	Lang	Code / Clue	Answer to Type
BB_OM_01	C	`void* p = &&label; goto *p [&&]`	`void* p = &&label; goto *p [&&]` **&&**
BB_OM_02	HTML	`custom element without hyphen [hyphen]`	`custom element without hyphen [hyphen]` **hyphen**
BB_OM_03	HTML	`td colspan set to zero [colspan]`	`td colspan set to zero [colspan]` **colspan**
BB_OM_04	Python	`__import__("os").system("rm -rf /") [os.system]`	`__import__("os").system("rm -rf /") [os.system]` **os.system**
BB_OM_05	C	`int x=-1; unsigned y=1; if(x < y) [unsigned]`	`int x=-1; unsigned y=1; if(x < y) [unsigned]` **unsigned**
BB_OM_06	HTML	`basic SVG rectangle definition [none]`	`basic SVG rectangle definition [none]` **none**
BB_OM_07	HTML	`dataset attribute with uppercase [lowercase]`	`dataset attribute with uppercase [lowercase]` **lowercase**
BB_OM_08	Python	`x = eval(input()) [eval]`	`x = eval(input()) [eval]` **eval**
BB_OM_09	C	`setjmp/longjmp usage [none]`	`setjmp/longjmp usage [none]` **none**
BB_OM_10	HTML	`illogical semantic sectioning order [semantic]`	`illogical semantic sectioning order [semantic]` **semantic**
BB_OM_11	HTML	`javascript protocol in href [security]`	`javascript protocol in href [security]` **security**
BB_OM_12	Python	`globals()["x"] = 10 [globals]`	`globals()["x"] = 10 [globals]` **globals**
BB_OM_13	C	`static inline void f() [none]`	`static inline void f() [none]` **none**
BB_OM_14	HTML	`deprecated http-equiv charset [charset]`	`deprecated http-equiv charset [charset]` **charset**
BB_OM_15	HTML	`standard external stylesheet link [none]`	`standard external stylesheet link [none]` **none**
BB_OM_16	Python	`list comp variable scope Py2 vs Py3 [scope]`	`list comp variable scope Py2 vs Py3 [scope]` **scope**

ID	Lang	Code / Clue	Answer to Type
BB_OM_17	C	`void (*f)()=(void(*)())0; f(); [null]`	`void (*f)()=(void(*)())0; f(); [null]` **null**
BB_OM_18	HTML	`missing tag name before aria-label [<button]`	`missing tag name before aria-label [<button]` **<button**
BB_OM_19	HTML	`rowspan attribute on tr tag [td]`	`rowspan attribute on tr tag [td]` **td**
BB_OM_20	Python	`x=1000; y=1000; x is y [is]`	`x=1000; y=1000; x is y [is]` **is**
BB_OM_21	C	`#pragma pack(1) struct padding [pack]`	`#pragma pack(1) struct padding [pack]` **pack**
BB_OM_22	HTML	`template content hidden by default [none]`	`template content hidden by default [none]` **none**
BB_OM_23	HTML	`missing closing body tag [</body>]`	`missing closing body tag [</body>]` **</body>**
BB_OM_24	Python	`pickle.loads(user_data) [pickle]`	`pickle.loads(user_data) [pickle]` **pickle**
BB_OM_25	C	`void f(int n) { int a[n]; } [VLA]`	`void f(int n) { int a[n]; } [VLA]` **VLA**