Cache Design 2

CS/COE 1541 (Fall 2020)

Wonsun Ahn

Cache Design Parameter 5: Write-Through vs. Write-Back

Writes and Cache Consistency

- Assume **&x** is 111010_2, and x == 24 initially

```
lw   t0, &x
addi t0, t0, 1       # x++
sw   t0, &x
```

- How will the **lw** change the cache?
- How will the **sw** change the cache?
  - Uh oh, now the cache is **inconsistent**. (Memory still has the old value 24.)

	V	Tag	Data
000	0		
001	0		
010	1	111	25
011	0		
100	0		
101	0		
110	0		
111	0		

- How can we solve this? Two policies:
  - **Write-through**: Propagate write all the way through memory
  - **Write-back**: Write back cache block when it is evicted from cache

Policy 1: Write-through

- Write-through:
  - If write hit, update cache block in current cache
  - Propagate write to lower memory to update it as well
- What happens if we write **25** to address **111010_2**?
- What happens if we write **94** to address **000010_2**?
- Caches are kept consistent at all points of time!



L1 Cache

	V	Tag	Data
000	0		
001	0		
010	1	111	25
…		…	…

L2 Cache

	V	Tag	Data
000	0		
001	0		
010	1	000	94
…		…	…

Memory

Address	Data
…	…
000010	94
…	…
111010	25
…	…

University of Pittsburgh

Write-through: Reads

- What happens if we read from address $\mathbf{000010}_2$?
  - We can just discard the conflicting cache block $\mathbf{111010}_2$
  - It's just an extra copy of the same data
- Note how we allocate lines only on reads
  - We do not allocate lines on writes
  - This policy is called **no write allocate**



L1 Cache

	V	Tag	Data
000	0		
001	0		
010	1	000	94
…		…	…

L2 Cache

	V	Tag	Data
000	0		
001	0		
010	1	000	94
…		…	…

Memory

Address	Data
…	…
000010	94
…	…
111010	25
…	…

University of Pittsburgh

Write-through: Drawbacks

- Drawback: **Long write delays** regardless of hit or miss
  - Must propagate write all the way to DRAM memory regardless
- Solution: **Write buffer** maintaining pending writes
  - CPU gets on with work after moving pending write to write buffer
  - But does the write buffer solve all problems?



Write Buffer

V	Tag	Data

L1 Cache

	V	Tag	Data
000	0		
001	0		
010	1	111	25
…		…	…

L2 Cache

	V	Tag	Data
000	0		
001	0		
010	1	000	94
…		…	…

Memory

Address	Data
…	…
000010	94
…	…
111010	25
…	…

University of Pittsburgh

Write-through: Drawbacks

- The write buffer does not solve all problems.

1. Write buffer must be **very big** to store all pending writes
   - May take more than 100 cycles for write to propagate to memory
   - Write buffer is always checked before L1$ → adds to **hit time**

2. Write buffer does not solve **bandwidth** problems
   - If memory bandwidth < rate of writes in program, write buffer will fill up quickly, no matter how big it is

- Impractical to write-through all the way to memory
  - Typically only L1 caches are write-through, if any
- We need another strategy that is not so bandwidth-intensive

Policy 2: Write-back

- Write-back:
  - **Dirty** block: a block that is temporarily inconsistent with memory
  - Update cache block in current cache only, marking it dirty
  - Write back dirty block to memory when it is evicted from cache
- A **dirty bit** is added to the cache block metadata (marked "D")
  - Block **000001**$_2$ is clean → can be discarded on eviction
  - Block **111010**$_2$ is dirty → needs to be written back on eviction



Write-back: Write allocate

- Unlike write-through, write-back has a **write allocate** policy
  - On a write miss, cache block is always allocated in current cache
  - To update cache block in current cache, it must be there first ☺
- On allocation, the block is **read** in from **lower memory**
- Q: Why the wasted effort?
  - Aren't we going to overwrite the block anyway with new data?
  - Why read in data that is going be overwritten?

Write-back: Write allocate

- Because a block is multiple bytes, and you are updating just a few
  - Suppose a cache block is 8 bytes (2 words)
  - Suppose you are writing to only the **first word**

V	D	Tag	Data	
1	1		first word (written)	second word (not written)

  - After allocate, the entire cache block is marked **valid**
    - That means **second word** as well as **first word** must be valid
    - Means it must be fetched from lower memory
    - Otherwise if later **second word** is read, it will contain junk data
    - Unavoidable, unless you have a valid bit for each byte
      - That means spending 1 bit for every 8 bits of data
      - That's just too much metadata overhead

Policy 2: Write-back

- What happens if we write **25** to address **111010_2**?



Write Buffer

V	Tag	Data

L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	111	24
...			...	...

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93
...			...	...

Memory

Address	Data
...	...
000010	93
...	...
111010	24
...	...

Policy 2: Write-back

- What happens if we write **25** to address **111010_2**?
  - L1 Cache Hit! Update cache block and mark it dirty.



Write Buffer

V	Tag	Data

L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	1	111	25
…			…	…

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93
…			…	…

Memory

Address	Data
…	…
000010	93
…	…
111010	24
…	…

Policy 2: Write-back

- What happens if we write **25** to address **111010_2**?
  - L1 Cache **hit**! Update cache block and mark it dirty.
- What happens if we write **94** to address **000010_2**?
  - L1 Cache **miss**! First thing we will do is add store to **Write Buffer**. (So that the CPU can continue executing past the store)



Write Buffer

V	Tag	Data
1		94

L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	1	111	25
...			...	...

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93
...			...	...

Memory

Address	Data
...	...
000010	93
...	...
111010	24
...	...

Policy 2: Write-back

- What happens if we write **94** to address **000010_2**? (cont'd)
  - Next the L2 Cache is searched and it's a **hit**!
  - To bring in block to L1 Cache, we first need to evict block **25**.
  - It's a dirty block, so we can't just discard it. Need to **write** it **back**!
  - But if we write it back to L2, it will overwrite block **93**!
  - Where can we put this block?



Write Buffer

V	Tag	Data
1		94

L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	1	111	25
...			...	...

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93
...			...	...

Memory

Address	Data
...	...
000010	93
...	...
111010	24
...	...

Policy 2: Write-back

- What happens if we write **94** to address **000010_2**? (cont'd)
  - Add Write Buffers for the caches too!
  - Move block to L1 Write Buffer so L1 Cache can continue working
  - Pending block will get written back to L2 Cache eventually



L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	1	111	25

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93

Memory

Address	Data
...	...
000010	93
...	...
111010	24
...	...

Write Buffer

V	Tag	Data
1		94

Write Buffer

V	D	Tag	Data
0	0		
0	0		

Write Buffer

V	D	Tag	Data
0	0		
0	0		

Policy 2: Write-back

- What happens if we write **94** to address **000010_2**? (cont'd)
  - Now we can finally read in block **93** to the L1 Cache



L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	0	0		

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93

Memory

Address	Data
...	...
000010	93
...	...
111010	24
...	...

Write Buffer

V	Tag	Data
1		94

Write Buffer

V	D	Tag	Data
1	1	111	25
0	0		

Write Buffer

V	D	Tag	Data
0	0		
0	0		

Policy 2: Write-back

- What happens if we write **94** to address **000010_2**? (cont'd)
  - Now we can finally read in block **93** to the L1 Cache
  - And write **94** into the cache block, also marking it dirty
  - Store is finished, so now remove it from pipeline Write Buffer!



L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	1	000	94

Write Buffer

V	Tag	Data
1		94

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93

Write Buffer

V	D	Tag	Data
1	1	111	25
0	0		

Write Buffer

V	D	Tag	Data
0	0		
0	0		

Memory

Address	Data
…	…
000010	93
…	…
111010	24
…	…

Policy 2: Write-back

- What happens if we write **94** to address **000010_2**? (cont'd)
  - Eventually, the pending block in L1 Write Buffer will write back (Note that L2 Cache block **93** can be discarded since not dirty)
  - But this is off the critical path (won't add to store delay)



L1 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	1	000	94

L2 Cache

	V	D	Tag	Data
000	0	0		
001	0	0		
010	1	0	000	93

Write Buffer

V	Tag	Data

Write Buffer

V	D	Tag	Data
1	1	111	25
0	0		

Write Buffer

V	D	Tag	Data
0	0		
0	0		

Memory

Address	Data
…	…
000010	93
…	…
111010	24
…	…

Write-though vs. Write-back

- Advantages of write-through caches
  - Simpler to implement
    - Don't have to deal with block allocation on write misses
    - Don't have to deal with write-backs on block eviction
- Advantages of write-back caches
  - Lower bandwidth requirements
    - Lower memory accessed only on cache misses
      (Unlike write-though which propagates all writes to memory)
    - Cache misses are typically a small percentage of all accesses
- L1 caches are sometimes write-through for simplicity
  - Plenty of bandwidth within chip to support this
- Last-level caches are almost always write-back
  - Long latency and low bandwidth to DRAM prohibits write-through

Cache Design Parameter 6: Unified vs. Split

Problem with Split Caches

- If cache is split into two (i-cache and d-cache)
  - Space cannot be flexibly allocated between data and code

If our working set looks like this – say, in a small loop that's accessing a large array – then we run out of data space.



If our working set looks like this – say, in a large function that's only using stack variables – then we run out of code space.

Impact of Unifying Cache

- The answer to the problem is to simply **unify** the cache into one
- AMAT = hit time + (miss rate × miss penalty)
- Impact of unifying cache on miss rate:
  - **Smaller miss rate** due to more flexible use of space
- Impact of unifying cache on hit time:
  - Potentially **longer hit time** due to structural hazard
  - With split caches, i-cache and d-cache can be accessed simultaneously
  - With unified cache, access request must wait until port is available
- **L1** cache is almost always **split**
  - Frequent accesses directly from pipeline trigger structural hazard often
- **Lower level** caches are almost always **unified**
  - Accesses are infrequent (filtered by L1), so structural hazards are rare

Cache Design Parameter 7: Private vs. Shared

Private vs. Shared Cache

- On a multi-core system, there are two ways to organize the cache
- **Private** caches: each core (processor) uses its own cache



- **Shared** cache: all the cores share one big cache

Shared Cache can Use Space More Flexibly

- Suppose only 1st core is active and other cores are idle
  - How much cache space is available to 1st core? (Shown in **red**)
- **Private** caches: 1st core can only use its own private cache



- **Shared** cache: 1st core can use entire shared cache!

Banking: Solution to Structural Hazards

- Now what if all the cores are active at the same time?
  - Won't that cause structural hazards due to simultaneous access?

  - Could add more ports, but adding **banks** is more cost effective



Shared L1$

    - Each bank has its own read / write port
    - As long as two cores do not access same bank, no hazard!

Banking: Solution to Structural Hazards

- Cache blocks are **interleaved** between banks



  - Blocks 0, 4, 8 … → Bank 0
  - Blocks 1, 5, 9 … → Bank 1
  - Blocks 2, 6, 10 … → Bank 2
  - Blocks 3, 7, 11 … → Bank 3
  - That way, blocks are evenly distributed across banks
    - Causes cache accesses to also be distributed → less hazards

Shared Cache have Longer Access Times

- Again, suppose only 1st core is active and other cores are idle
  - The working set data is shown in **red**
- **Private** caches: entire working set data in nearby private cache



- **Shared** cache: data sometimes distributed to remote banks



Shared Cache have Longer Access Times

- Remember this picture?



Impact of Shared Cache

- AMAT = hit time + (miss rate × miss penalty)

- Impact of shared cache on miss rate:
  - **Smaller miss rate** due to more flexible use of space

- Impact of shared cache on hit time:
  - **Longer hit time** due to sometimes having to access remote banks

- **L1** caches are almost always **private**
  - Hit time is important for L1. Cannot afford access to remote banks.
- **L3** (**last level**) caches are almost always **shared**
  - Reducing miss rate is top priority to avoid DRAM access.

Cache Organization of Broadwell CPU

- This is the cache organization of Broadwell used in our Linux server



Cache Design Parameter 8: Prefetching

Prefetching

- **Prefetching**: fetching data that is expected to be needed soon
  - Allows you to hide the latency of fetching that data
  - E.g. Web browsers prefetch resources from not-yet-clicked links
    → when user later clicks on link, response is almost instantaneous
  - Caches also prefetch data that is expected to be used soon
    - Can be used to avoid even **cold misses**

- Two ways prefetching can happen:
  - Compiler-driven: compiler emits **prefetch instructions**
    - Can manually insert one in C program: __builtin_prefetch(addr)
    - Or rely on compiler to insert them using heuristics
  - Hardware-driven: CPU emits prefetches dynamically
    - Relies on CPU to detect a pattern in memory accesses

Hardware Prefetching

- What do you notice about both these snippets of code?
- They both access memory **sequentially.**
  - The first one data, the next instructions.

```
for(i = 0 .. 100000)
    A[i]++;
```

```
00 lw
04 lw
08 lw
0C addi
10 sub
14 mul
18 sw
1C sw
20 sw
```



Sequential



Reverse sequential



Strided sequential
(think "accessing one field from each item in an array of structs")

Hardware Prefetching Stride Detection

- What kinds of things would you need?
- A table of the last *n* memory accesses would be a good start.



- Some subtractors to calculate the stride
- Some comparators to see if strides are the same
- Some detection logic

Where Hardware Prefetching Doesn't Work

- Sequential accesses are where prefetcher works best
  - E.g. Iterating over elements of an **array**

- Some accesses don't have a pattern or is too complex to detect
  - At below is how a typical **linked-list** traversal looks like



(colors are different cache blocks)

  - Other pointer-chasing data structures (graphs, trees) look similar
  - Can only rely on spatial locality to avoid cold misses

Mystery Solved



- How come Array performed well for even an array 1.28 GB large?
  - No spatial locality since each node takes up two 64-byte cache blocks
  - No temporal locality since working set of 1.28 GB exceeds any cache

- The answer is: Array had the benefit of a strided **prefetcher**!
  - Access pattern of Linked List was too complex for prefetcher to detect

Impact of Prefetching

- Prefetcher runs **in parallel** with the rest of the cache hardware
  - Does not slow down any on-demand reads or writes

- What if prefetcher is wrong? It can be wrong in two ways:
  - It fetched a block that was never going to be used
  - It fetched a useful block but fetched it too soon or too late
    - Too soon: the block gets evicted before it can be used
    - Too late: the prefetch doesn't happen in time for the access

- A bad prefetch results in **cache pollution**
  - Unused data is fetched, potentially pushing out other useful data

- On the other hand, good prefetches can reduce misses drastically!