VERTEX ENGINEERING
DELIVERING EXCELLENCE IN ENGINEERING – GLOBALLY

Phone: +91 99095 51658
Web: vertexengineering.in.
Sales@vertexengineering.in

Date 13 May 2026

TECHNO-COMMERCIAL QUOTATION

Seller: Vertex Engineering
Buyer: **Blue Waves Technical Enterprises LLC**
Abu Dhabi, UAE
Quotation Ref: VE/BWTE/0526/017
Currency: USD
Incoterm: C & F Abu Dhabi
Validity: 15 Days

Product Details

Sr No	Description	QTY	**Unit Price (USD)**	Total Price (USD)
1	ABB Motor – M3BM 400 LA 4 B3, 308kW, 6600V, 50Hz, 1500 RPM, IP55 with Rex-VIVA VS Coupling	1	39,850.00	39,850.00
2	ABB Motor – M3BP 315SM C4 B3, 139kW, 380V, 50Hz, 1500 RPM, IP55 with Rex-VIVA VS Coupling	1	11,950.00	11,950.00
3	Siemens Motor – 1LG4317-4AA90-Z, 170kW, 380V, 50Hz, 1475 RPM, 305A	1	14,750.00	14,750.00

Total Quoted Value: USD 66,550.00

LEAD TIME

Sr No	Description	Lead Time
1	ABB Motor – 308kW, 6600V	12 – 14 Weeks
2	ABB Motor – 139kW, 380V	8 – 10 Weeks
3	Siemens Motor – 170kW	8 – 10 Weeks

WEIGHT & VOLUME DETAILS

Sr No	Description	Approx Weight	Approx Volume
1	ABB Motor – 308kW, 6600V	2450 Kg	4.80 CBM
2	ABB Motor – 139kW, 380V	980 Kg	2.20 CBM
3	Siemens Motor – 170kW	1120 Kg	2.50 CBM

TECHNICAL DATA SHEET

1. ABB Motor

Parameter	Details
Manufacturer	ABB
Motor IEC Code	400L
Power Output	308.00 kW
Frequency	50 Hz
Speed	1500 RPM
Voltage	6600 V
Enclosure Protection	IP55
Motor Type	M3BM 400 LA 4 B3
Mounting	B3
Cooling Method	IC411
Insulation Class	Class F
Duty	S1 Continuous
Coupling Type	Rex-VIVA VS
Application	Industrial Process / Heavy Duty Applications

---

2. ABB Motor

Parameter	Details
Manufacturer	ABB
Motor IEC Code	315M80
Power Output	139.00 kW
Frequency	50 Hz
Speed	1500 RPM
Voltage	380 V
Enclosure Protection	IP55
Motor Type	M3BP 315SM C4 B3
Mounting	B3
Cooling Method	IC411
Insulation Class	Class F
Duty	S1 Continuous
Coupling Type	Rex-VIVA VS
Application	Industrial Process / Heavy Duty Applications

---

3. Siemens Motor

Parameter	Details
Manufacturer	Siemens
Model	1LG4317-4AA90-Z
Output Power	170 kW
Poles	4
Frequency	50 Hz

Voltage	380 V
Current	305 A
Speed	1475 RPM
Protection Class	IP55
Mounting	B3
Cooling Method	IC411
Insulation Class	Class F
Duty	S1 Continuous
Application	Industrial Process / Heavy Duty Applications

TERMS & CONDITIONS

1. Prices are quoted in USD on C & F Abu Dhabi basis.
2. Packing suitable for export sea shipment is included.
3. Freight charges up to Abu Dhabi Port are included.
4. Insurance is excluded unless specifically requested.
5. Payment Terms: 50% Advance along with Purchase Order and balance 50% before dispatch.
6. Delivery schedule shall commence from the date of receipt of advance payment and technical confirmation.
7. Warranty: 12 Months from date of dispatch against manufacturing defects.
8. Any taxes, duties, VAT or customs charges at destination shall be in buyer's scope.
9. Offer validity: 15 Days from the date of quotation.
10. Force majeure conditions applicable.

VERTEX ENGINEERING
DELIVERING EXCELLENCE IN ENGINEERING - GLOBALLY

Phone: +91 99095 51658
Web: vertexengineering.in.
Sales@vertexengineering.in

Date 03 April 2026

TECHNO-COMMERCIAL QUOTATION

To: AL Marjie Trading Company LLC
From: Vertex Electrotechnical General Trading FZCO
Quotation No.: VCC/EL/0426/11

Subject: Supply of Electrical & Instrumentation Components

1. SOLID STATE RELAY (Motor Protection Unit)

- **Part No.:** SPE0130300003 / LTMCUF
- **Make:** Schneider Electric / L&T
- **Type:** Motor Protection Relay Control Unit
- **Mounting:** Flush
- **Protection:** IP20 / IP54
- **Standard:** IEC 61131-2
- **Temp Range:** -20°C to +60°C

Qty	Unit Price (USD)	Total (USD)
4	220	880

2. DISPLAY UNIT (TESYS T)

- **Part No.:** LTMCU
- **Type:** LCD Display Module
- **Size:** 117 × 50 × 70 mm
- **Voltage:** 7V DC
- **Mounting:** Panel
- **Protection:** IP54

Qty	Unit Price (USD)	Total (USD)
4	180	720

3. CONTROL RELAY

- **Part No.:** RXM2AB2BD
- **Type:** Plug-in Electromechanical Relay
- **Coil Voltage:** 220VAC
- **Contact:** 2CO (DPDT)
- **Rating:** 10A
- **Standard:** IEC 61810-1

Qty	Unit Price (USD)	Total (USD)
59	9.5	560.5

---

4. ELECTRIC PLUG (SCHUKO TYPE)

- **Part No.:** 123463
- **Type:** 1P+N+E Plug
- **Rating:** 16A, 250V
- **Protection:** IP44
- **Material:** PVC

Qty	Unit Price (USD)	Total (USD)
30	7.5	225

---

5. UNDER VOLTAGE RELEASE

- **Part No.:** 26963
- **Voltage:** 220–240VAC
- **Standard:** IEC 60947-5-1
- **Compatibility:** Multi 9 / C60 series

Qty	Unit Price (USD)	Total (USD)
1	95	95

---

6. TEMPERATURE TRANSMITTER (ATEX)

- **Part No.:** RTT80-T1GGA
- **Type:** RTD PT100 Transmitter
- **Output:** 4–20 mA + HART
- **Range:** 0–100°C
- **Protection:** IP66
- **Certification:** ATEX (Ex ia IIC T4–T6)

Qty	Unit Price (USD)	Total (USD)
6	310	1,860

---

7. SELECTOR SWITCH

- **Part No.:** XB5AD33
- **Type:** 3 Position Selector Switch
- **Contact:** 2NO
- **Mounting:** 22mm panel
- **Material:** Plastic

Qty	Unit Price (USD)	Total (USD)
1	28	28

---

8. CIRCUIT BREAKER (MV)

- **Part No.:** Q1/630
- **Type:** SF6 Circuit Breaker
- **Voltage:** 12kV

- **Current:** 630A
- **Breaking Capacity:** 25kA
- **Make:** Merlin Gerin

Qty	Unit Price (USD)	Total (USD)
1	4,800	4,800

✅ **GRAND TOTAL: USD 9,168.50**

COMMERCIAL TERMS

- Price Basis: C&F Abu Dhabi
- Delivery: 3–5 weeks
- Payment: 40% Advance, 60% Against Documents
- Packing: Export standard
- Warranty: 12 Months
- Validity: 7 Days
- Country of Origin: EU / India

VERTEX ENGINEERING
DELIVERING EXCELLENCE IN ENGINEERING - GLOBALLY

Phone: +91 99095 51658
Web: vertexengineering.in.
Sales@vertexengineering.in

Date 10 June 2026

TECHNO COMMERCIAL QUOTATION

Buyer: Target Industrial Equipment SPC
Seller: Vertex Engineering
Price Basis: CIF Sultanate of Oman
Payment Terms: 50% Advance Payment & 50% Against BL Copy
Delivery Time: 6–7 Weeks
Quotation Validity: 7 Days
Currency: USD

Product Details:

Sr. No.	Description	Qty	Unit Price (USD)	Total Price (USD)
1	Siemens FD63F250 Molded Case Circuit Breaker (MCCB), 3 Pole, 250A, Thermal Magnetic Trip, 600VAC, FD Frame	2 Nos	998.00	1996.00

Grand Total(CIF) : USD 1996.00

TECHNICAL DATASHEET

Siemens FD63F250 Molded Case Circuit Breaker (MCCB)

Parameter	Specification
Manufacturer	Siemens
Product Series	Sentron FD Series
Part Number	FD63F250
Product Type	Molded Case Circuit Breaker (MCCB)
Frame Size	FD Frame
Number of Poles	3 Pole
Rated Current (In)	250 A
Trip Unit Type	Thermal Magnetic
Application	Distribution and feeder circuit protection

Electrical Specifications

Parameter	Specification
Rated Operational Voltage (Ue)	Up to 600 VAC
Rated DC Voltage	Up to 500 VDC
Frequency	50/60 Hz
Interrupting Capacity @ 480 VAC	35 kA
Interrupting Capacity @ 600 VAC	22 kA
Current Limiting	Yes
Protection Functions	Overload & Short-Circuit Protection

Trip Characteristics

Parameter	Specification
Thermal Protection	Inverse Time Overload Protection
Magnetic Protection	Instantaneous Short-Circuit Protection
Trip Adjustment	Factory Set
Operating Mechanism	Toggle Type

Mechanical Specifications

Parameter	Specification
Mounting Type	Bolt-On
Enclosure Compatibility	Panelboard / Switchboard
Terminal Type	Line & Load Lug Connections
Operating Position	Vertical or Horizontal
Housing Material	High-Strength Thermoset Insulating Material

Environmental Conditions

Parameter	Specification
Ambient Operating Temperature	-25°C to +70°C
Storage Temperature	-40°C to +85°C
Humidity	Up to 95% Non-Condensing
Pollution Degree	3

Standards & Compliance

Parameter	Specification
Standard	UL 489
Certification	UL Listed
CSA Certification	Yes
RoHS Compliance	Yes (subject to manufacturing revision)

Key Features

- 250A continuous current rating.
- Thermal-magnetic trip protection.
- High interrupting capacity for industrial applications.
- Compact FD frame design.
- Suitable for feeder and branch circuit protection.
- Reliable bolt-on mounting configuration.
- UL and CSA certified.
- Designed for commercial, industrial, and OEM power distribution systems.

Typical Applications

- Industrial Power Distribution Panels
- Motor Control Centers (MCC)
- Switchboards
- Manufacturing Plants
- Oil & Gas Facilities
- Water Treatment Plants
- Commercial Buildings
- Utility Distribution Systems

Terms and Conditions:

- **Delivery:** CIF as per buyer requirement
- **Payment: :** 50% Advance Payment & 50% Against BL Copy
- **Warranty:** 12 months from date of commissioning
- **Shipping:** Standard export packing included
- **Validity:** Quotation valid for 07 days from the date of issue

VERTEX ENGINEERING
DELIVERING EXCELLENCE IN ENGINEERING – GLOBALLY

Phone: +91 99095 51658
Web: vertexengineering.in.
Sales@vertexengineering.in

Date 15 June 2026

TECHNO COMMERCIAL QUOTATION

Buyer: Inspire Measurement & Equip Fix LLC SP
Seller: Vertex Engineering
Price Basis: CIF Sharjah | UAE
Payment Terms: 50% Advance Payment & 50% against BL Copy
Delivery Time: 6–7 Weeks
Quotation Validity: 7 Days
Currency: USD

Product Details:

Sr. No.	Part Number	Description	Qty	Unit Price(USD)	Total (USD)
1	6ES7212-1AE40-0XB0	CPU 1212C DC/DC/DC	2	477.72	955.44
2	6ES7214-1AG40-0XB0	CPU 1214C DC/DC/DC	4	632.94	2,531.76
3	6ES7511-1CK01-0AB0	CPU 1511C-1 PN	1	2,435.31	2,435.31

- **Incoterm:** CIF Sharjah, UAE
- **Total Quantity:** 7 Nos.
- **Total Value: USD 5,922.51**

TECHNICAL DATASHEET

1. Siemens SIMATIC S7-1200 CPU 1212C DC/DC/DC

Part Number: 6ES7212-1AE40-0XB0

Technical Specifications

- Power Supply: 20.4–28.8 VDC
- Integrated Inputs: 8 × Digital Inputs (24 VDC)
- Integrated Outputs: 6 × Digital Outputs (24 VDC Transistor)
- Program Memory: 100 KB
- Data Memory: 4 MB
- High-Speed Counters: Up to 6
- High-Speed Outputs: Up to 2 × 100 kHz
- Communication Port: 1 × PROFINET Ethernet
- Expansion Capability: Signal Boards, Signal Modules, Communication Modules
- Programming Software: TIA Portal
- Protection Rating: IP20
- Operating Temperature: 0°C to +60°C

2. Siemens SIMATIC S7-1200 CPU 1214C DC/DC/DC

Part Number: 6ES7214-1AG40-0XB0

Technical Specifications

- Power Supply: 20.4–28.8 VDC
- Integrated Inputs: 14 × Digital Inputs (24 VDC)
- Integrated Outputs: 10 × Digital Outputs (24 VDC Transistor)
- Program Memory: 150 KB
- Data Memory: 4 MB
- High-Speed Counters: Up to 6
- High-Speed Outputs: Up to 4 × 100 kHz
- Communication Port: 1 × PROFINET Ethernet
- Expansion Capability: Up to 8 Signal Modules
- Programming Software: TIA Portal
- Protection Rating: IP20
- Operating Temperature: 0°C to +60°C

---

3. Siemens SIMATIC S7-1500 CPU 1511C-1 PN

Part Number: 6ES7511-1CK01-0AB0

Technical Specifications

- Power Supply: 24 VDC
- Integrated Inputs: 16 × Digital Inputs (24 VDC)
- Integrated Outputs: 16 × Digital Outputs (24 VDC Transistor)
- Analog Inputs: 5
- Analog Outputs: 2
- Work Memory: 300 KB
- Load Memory: SIMATIC Memory Card Required
- Bit Performance: 60 ns
- Communication Ports: 2 × PROFINET Interfaces
- Integrated Web Server: Yes
- Motion Control Functions: Supported
- Technology Objects: PID, Positioning, Counting
- Expansion Capability: S7-1500 I/O Modules
- Protection Rating: IP20
- Operating Temperature: 0°C to +60°C

Common Features

- Programming Environment: Siemens TIA Portal
- Ethernet-Based PROFINET Communication
- Integrated Diagnostics
- Industrial EMC Compliance
- DIN Rail Mounting
- CE, UL, cUL Approved

Terms and Conditions:

- **Delivery:** CIF as per buyer requirement
- **Payment: :** 50% Advance Payment & 50% Against BL Copy
- **Warranty:** 12 months from date of commissioning
- **Shipping:** Standard export packing included
- **Validity:** Quotation valid for 07 days from the date of issue