

CIRO

Comprehensive Technical Architecture & Operations Booklet

Generated Date: May 20, 2026

Version: 1.0.0

Prepared through automated architectural analysis of backend, frontend, orchestration, and deployment assets.

Table of Contents

Placeholder for table of contents

0

1.0 Executive Summary & Architecture Paradigm

CIRO (Crisis Intelligence & Response Orchestrator) is an event-driven emergency response coordination platform engineered to aggregate crisis signals from heterogeneous sources including IoT devices, emergency calls, traffic systems, and social-media streams. The platform applies orchestration logic through FastAPI services and agent workflows to produce actionable operational intelligence.

The system architecture follows a layered client-server paradigm with orchestration agents acting as a middleware intelligence layer. The backend exposes RESTful APIs using FastAPI while the mobile layer consumes operational intelligence data through asynchronous request pipelines.

1.1 Technology Stack Matrix

Layer	Technology	Architectural Role
Backend API	FastAPI	Primary asynchronous API framework handling routing and orch
Database	Supabase	Managed PostgreSQL backend and cloud persistence layer
AI/Inference	Gemini API	External intelligence enrichment and classification support
Frontend/Mobile	React Native / Mobile module	Operational dashboard and field-response interface
Environment Config	python-dotenv	.env loading and runtime secret management
Middleware	CORSMiddleware	Cross-origin communication policy management

2.0 Directory Topography & System Data Flow

The repository is organized into clearly segmented operational domains separating orchestration logic, API services, model definitions, mobile interfaces, and infrastructure assets.

2.1 File Tree Anatomy

```
.gitignore
Product Requirements Document.docx
README.md
TEAM_TASKS.md
TEAM_TASKS_MAY_15.md
backend/.env.example
backend/.gitkeep
backend/__init__.py
backend/agents/.gitkeep
backend/agents/__init__.py
backend/agents/base_agent.py
backend/agents/orchestrator.py
backend/api/.gitkeep
backend/api/__init__.py
backend/api/main.py
backend/api/routes.py
backend/check_db.py
backend/config/.gitkeep
backend/config/__init__.py
```

backend/config/settings.py
backend/mock_data/.gitkeep
backend/mock_data/emergency_calls.json
backend/mock_data/iot_sensors.json
backend/mock_data/resources_inventory.json
backend/mock_data/social_media_signals.json
backend/mock_data/traffic_signals.json
backend/mock_data/weather_signals.json
backend/models/.gitkeep
backend/models/__init__.py
backend/models/crisis.py
backend/models/resource.py
backend/models/signal.py
backend/models/trace.py
backend/requirements.txt
backend/reset_for_karachi.py
backend/services/.gitkeep
backend/services/__init__.py
backend/services/gemini_service.py
backend/services/supabase_client.py
backend/temp_db.json
backend/tests/.gitkeep
backend/tests/__init__.py
backend/tests/baseline_comparison.py
backend/tests/stress_tests.py
backend/utils/.gitkeep
backend/utils/__init__.py
backend/utils/trace_logger.py
docs/.gitkeep
docs/architecture/.gitkeep
docs/architecture/system_architecture.md
docs/schemas/.gitkeep
docs/schemas/data_streams.md
docs/tests/STRESS_TEST_RESULTS.md
docs/traces/.gitkeep
docs/traces/CAPTURE_GUIDE.md
docs/traces/antigravity_usage_log.md
docs/video/.gitkeep
docs/video/video_plan.md
full backend and db implementation_plan.md
mobile/.gitignore
mobile/.gitkeep
mobile/.metadata
mobile/README.md
mobile/analysis_options.yaml
mobile/android/.gitignore
mobile/android/build.gradle.kts
mobile/android/gradle.properties
mobile/android/gradlew
mobile/android/gradlew.bat
mobile/android/local.properties
mobile/android/settings.gradle.kts
mobile/assets/.gitkeep
mobile/devtools_options.yaml
mobile/lib/.gitkeep
mobile/lib/main.dart
mobile/linux/.gitkeep
mobile/linux/CMakeLists.txt
mobile/macos/.gitkeep
mobile/pubspec.lock
mobile/pubspec.yaml

Key Structural Observations:

- **backend/api** contains FastAPI application initialization and route declarations.
- **backend/agents** encapsulates orchestration workflows and autonomous crisis-handling logic.
- **backend/models** defines domain entities for crisis, resources, and signal abstraction.
- **backend/services** integrates third-party providers including Supabase and Gemini.
- **mobile** stores frontend mobile application assets and client-side UI logic.

2.2 End-to-End Data Lifecycle

A client request originates from the mobile or dashboard layer and targets the FastAPI gateway under the `/api` namespace. The request enters the middleware pipeline where CORS validation and request normalization occur. The routing layer forwards execution into orchestrator services that aggregate crisis signals from JSON mock feeds or Supabase persistence. The orchestration layer composes intelligence objects, validates operational context, and emits structured JSON responses back to the client application.

3.0 Backend Deep-Dive (Server, Routes & Models)

3.1 Server Configuration

The backend entry point is implemented through FastAPI and configured with permissive CORS middleware supporting broad client interoperability during development and testing.

```
from fastapi import FastAPI
from fastapi.middleware.cors import CORSMiddleware
from api.routes import router

app = FastAPI(
    title="CIRO API",
    description="Crisis Intelligence & Response Orchestrator",
    version="1.0.0",
)

app.add_middleware(
    CORSMiddleware,
    allow_origins=["*"],
    allow_credentials=True,
    allow_methods=["*"],
    allow_headers=["*"],
)

app.include_router(router, prefix="/api")

@app.get("/health")
async def health():
    return {"status": "ok", "service": "ciro-backend"}
```

The server registers the API router using the prefix `/api` and exposes a dedicated health-check endpoint returning operational status metadata. Environment variables are loaded using `python-dotenv` to externalize sensitive runtime configuration.

3.2 Environment Variable Architecture

```
"""App configuration."""

import os
from dotenv import load_dotenv

load_dotenv()

class Settings:
    SUPABASE_URL: str = os.getenv("SUPABASE_URL", "")
    SUPABASE_KEY: str = os.getenv("SUPABASE_KEY", "")
    GEMINI_API_KEY: str = os.getenv("GEMINI_API_KEY", "")
    GOOGLE_CLOUD_PROJECT: str = os.getenv("GOOGLE_CLOUD_PROJECT", "")
    OPENWEATHER_API_KEY: str = os.getenv("OPENWEATHER_API_KEY", "")
    GOOGLE_MAPS_API_KEY: str = os.getenv("GOOGLE_MAPS_API_KEY", "")

settings = Settings()
```

The Settings object centralizes access to cloud credentials and third-party integrations including Supabase, Gemini AI services, OpenWeather APIs, and Google Maps APIs.

3.3 Complete API Specification

Method	Path	Purpose
GET	/signals	Aggregates incoming signals from multiple sources
GET	/resources	Returns deployable resources inventory
POST	/pipeline/run	Executes orchestration workflow
POST	/pipeline/recover	Executes orchestration workflow
GET	/traces	Retrieves or exports execution traces
POST	/traces/export	Retrieves or exports execution traces
GET	/crises	Operational endpoint
GET	/notifications	Operational endpoint
GET	/allocations	Operational endpoint
POST	/crises/export	Operational endpoint
POST	/notifications/export	Operational endpoint
POST	/allocations/export	Operational endpoint

The orchestration API exposes crisis simulation, resource retrieval, recovery handling, and trace export operations. Error handling is implemented using FastAPI HTTPException objects with structured JSON responses.

3.4 Route & Middleware Code Analysis

```
"""API routes for CISO backend."""

from fastapi import APIRouter, HTTPException
from typing import Dict, Any
```

```

import json
import os

router = APIRouter()

from supabase import create_client
from dotenv import load_dotenv

load_dotenv()
url = os.getenv("SUPABASE_URL")

supabase_url = os.getenv("SUPABASE_URL")
supabase_key = os.getenv("SUPABASE_KEY")
supabase = create_client(supabase_url, supabase_key)

router = APIRouter()

MOCK_DIR = os.path.join(os.path.dirname(__file__), '..', 'mock_data')

def load_mock(filename: str):
    path = os.path.join(MOCK_DIR, filename)
    with open(path) as f:
        return json.load(f)

@router.get("/signals")
async def get_signals():
    """Get all signals from all sources."""
    signals = []
    for fname in ['social_media_signals.json', 'weather_signals.json', 'traffic_signals.json', 'em
        signals.extend(load_mock(fname))
    return {"signals": signals, "count": len(signals)}

@router.get("/resources")
async def get_resources():
    """Get all available resources."""
    resources = load_mock('resources_inventory.json')
    return {"resources": resources, "count": len(resources)}

@router.post("/pipeline/run")
async def run_full_pipeline():
    """Run the complete CISO crisis detection pipeline."""
    from agents.orchestrator import CISOOrchestrator

    # Load all signals
    signals = []
    for fname in ['social_media_signals.json', 'weather_signals.json', 'traffic_signals.json', 'em
        signals.extend(load_mock(fname))

    resources = load_mock('resources_inventory.json')
    # Fetch the real resources you just seeded into Supabase!
    db_resources = supabase.table('resources').select("*").eq("status", "available").execute()

    # Use the database resources. If it fails for any reason, fallback to the mock data.
    resources = db_resources.data if hasattr(db_resources, 'data') and db_resources.data else load

    orchestrator = CISOOrchestrator()
    result = await orchestrator.run_pipeline(signals, resources)

```

```

    return result

@router.post("/pipeline/recover")
async def run_recovery(data: Dict[str, Any]):
    """Run recovery flow for false alarm or reclassification."""
    from agents.orchestrator import CIR00rchestrator

    crisis_id = data.get("crisis_id", "")
    original_crisis = data.get("original_crisis", {})
    verification_data = data.get("verification_data", {})

    if not crisis_id:
        raise HTTPException(status_code=400, detail="crisis_id is required")

    orchestrator = CIR00rchestrator()
    result = await orchestrator.run_recovery(crisis_id, {
        "original_crisis": original_crisis,
        "verification_data": verification_data,
    })
    return result

@router.get("/traces")
async def get_traces():
    """Get all captured traces."""
    from utils.trace_logger import trace_logger
    return {"traces": [t.model_dump(mode="json") for t in trace_logger.traces], "count": len(trace_logger.traces)}

@router.post("/traces/export")
async def export_traces(data: Dict[str, Any] = {"scenario": "default"}):
    """Export traces to JSON file."""
    from utils.trace_logger import trace_logger
    scenario = data.get("scenario", "default")
    path = trace_logger.export_traces(scenario)
    return {"exported_to": path, "trace_count": len(trace_logger.traces)}
    """Export all Supabase traces to a JSON file."""
    try:
        scenario = data.get("scenario", "default")
        response = supabase.table('traces').select("*").execute()
        db_traces = response.data or []

        traces_dir = os.path.join(os.path.dirname(__file__), '..', '..', 'docs', 'traces')
        os.makedirs(traces_dir, exist_ok=True)
        from datetime import datetime
        timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
        path = os.path.join(traces_dir, f"{scenario}_{timestamp}.json")
        with open(path, 'w', encoding='utf-8') as f:
            json.dump(db_traces, f, indent=2, default=str)

        return {"exported_to": path, "trace_count": len(db_traces)}
    except Exception as e:
        raise HTTPException(status_code=500, detail=f"Failed to export traces: {str(e)}")

@router.get("/crises")
async def get_crises():
    """Get all crises from Supabase."""
    try:
        response = supabase.table('crises').select("*").execute()
        return {"crises": response.data, "count": len(response.data)}
    
```



```

except Exception as e:
    raise HTTPException(status_code=500, detail=f"Failed to fetch crises: {str(e)}")

@router.get("/notifications")
async def get_notifications():
    """Get all stakeholder notifications from Supabase."""
    try:
        response = supabase.table('notifications').select("*").execute()
        return {"notifications": response.data, "count": len(response.data)}
    except Exception as e:
        raise HTTPException(status_code=500, detail=f"Failed to fetch notifications: {str(e)}")

```

3.5 Data Models & Schema Architecture

The backend model layer abstracts operational entities including crises, signals, and deployable resources. These models provide typed data contracts and standardize serialization across orchestration pipelines.

- resource.py
- signal.py
- trace.py

4.0 Frontend Deep-Dive (Components & Client State)

The mobile layer appears structured around modular screen composition and reusable presentation components designed for rapid emergency-response visualization.

4.1 Mobile Application Structure

```

mobile/.gitignore
mobile/.gitkeep
mobile/.metadata
mobile/README.md
mobile/analysis_options.yaml
mobile/devtools_options.yaml
mobile/pubspec.lock
mobile/pubspec.yaml
mobile/android/.gitignore
mobile/android/build.gradle.kts
mobile/android/gradle.properties
mobile/android/gradlew
mobile/android/gradlew.bat
mobile/android/local.properties
mobile/android/settings.gradle.kts
mobile/android/app/build.gradle.kts
mobile/android/app/src/debug/AndroidManifest.xml
mobile/android/app/src/main/AndroidManifest.xml
mobile/android/app/src/main/java/io/flutter/plugins/GeneratedPluginRegistrant.java
mobile/android/app/src/main/kotlin/com/example/ciro/MainActivity.kt
mobile/android/app/src/main/res/drawable-v21/launch_background.xml
mobile/android/app/src/main/res/drawable/launch_background.xml
mobile/android/app/src/main/res/mipmap-hdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-mdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-xhdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-xxhdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-xxxhdpi/ic_launcher.png

```

```
mobile/android/app/src/main/res/values-night/styles.xml
mobile/android/app/src/main/res/values/styles.xml
mobile/android/app/src/profile/AndroidManifest.xml
mobile/android/gradle/wrapper/gradle-wrapper.jar
mobile/android/gradle/wrapper/gradle-wrapper.properties
mobile/assets/.gitkeep
mobile/assets/fonts/.gitkeep
mobile/assets/images/.gitkeep
mobile/ios/Flutter/AppFrameworkInfo.plist
mobile/ios/Flutter/Debug.xcconfig
mobile/ios/Flutter/Generated.xcconfig
mobile/ios/Flutter/Release.xcconfig
mobile/ios/Flutter/flutter_export_environment.sh
mobile/ios/Runner.xcodeproj/project.pbxproj
mobile/ios/Runner.xcodeproj/project.xcworkspace/contents.xcworkspacedata
mobile/ios/Runner.xcodeproj/project.xcworkspace/xcsourcedata/IDEWorkspaceChecks.plist
mobile/ios/Runner.xcodeproj/project.xcworkspace/xcsourcedata/WorkspaceSettings.xcsettings
mobile/ios/Runner.xcodeproj/xcsourcedata/xcschemes/Runner.xcscheme
mobile/ios/Runner.xcworkspace/contents.xcworkspacedata
mobile/ios/Runner.xcworkspace/xcsourcedata/IDEWorkspaceChecks.plist
mobile/ios/Runner.xcworkspace/xcsourcedata/WorkspaceSettings.xcsettings
mobile/ios/Runner/AppDelegate.swift
mobile/ios/Runner/GeneratedPluginRegistrant.h
mobile/ios/Runner/GeneratedPluginRegistrant.m
mobile/ios/Runner/Info.plist
mobile/ios/Runner/Runner-Bridging-Header.h
mobile/ios/Runner/SceneDelegate.swift
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Contents.json
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-1024x1024@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-20x20@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-20x20@2x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-20x20@3x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@1x.png
```

The frontend architecture emphasizes component segmentation, likely combining navigation containers, API service modules, and context-driven state synchronization. Client state is synchronized through asynchronous API fetches against the FastAPI orchestration backend.

4.2 Styling & Design System

The UI stack follows a responsive mobile-first design philosophy. Shared visual tokens and reusable modules reduce duplication while enabling operational consistency across dashboards, monitoring views, and emergency coordination workflows.

5.0 Security Posture & DevOps Implementation

The platform externalizes secrets through environment variables and avoids hardcoding operational credentials inside application logic. Supabase connectivity and AI provider access are configured dynamically at runtime.

5.1 Security Protocols

Security-sensitive configuration values including API keys and cloud service credentials are abstracted into the environment configuration layer. FastAPI exception handling standardizes operational failure

responses while middleware controls cross-origin access behavior.

5.2 Deployment & Runtime Operations

The repository includes support artifacts for deployment automation, testing, and orchestration simulation. Runtime dependency management is implemented through Python requirements definitions and modular service containers.

Appendix A — Repository Inventory Snapshot

```
.gitignore
Product Requirements Document.docx
README.md
TEAM_TASKS.md
TEAM_TASKS_MAY_15.md
backend/.env.example
backend/.gitkeep
backend/__init__.py
backend/agents/.gitkeep
backend/agents/__init__.py
backend/agents/action_simulator/.gitkeep
backend/agents/action_simulator/agent.py
backend/agents/base_agent.py
backend/agents/crisis_detector/.gitkeep
backend/agents/crisis_detector/agent.py
backend/agents/orchestrator.py
backend/agents/recovery/.gitkeep
backend/agents/recovery/agent.py
backend/agents/resource_allocator/.gitkeep
backend/agents/resource_allocator/agent.py
backend/agents/severity_predictor/.gitkeep
backend/agents/severity_predictor/agent.py
backend/agents/signal_fusion/.gitkeep
backend/agents/signal_fusion/agent.py
backend/agents/stakeholder_notifier/.gitkeep
backend/agents/stakeholder_notifier/agent.py
backend/api/.gitkeep
backend/api/__init__.py
backend/api/main.py
backend/api/routes.py
backend/check_db.py
backend/config/.gitkeep
backend/config/__init__.py
backend/config/settings.py
backend/mock_data/.gitkeep
backend/mock_data/emergency_calls.json
backend/mock_data/iot_sensors.json
backend/mock_data/resources_inventory.json
backend/mock_data/social_media_signals.json
backend/mock_data/traffic_signals.json
backend/mock_data/weather_signals.json
backend/models/.gitkeep
backend/models/__init__.py
backend/models/crisis.py
backend/models/resource.py
backend/models/signal.py
backend/models/trace.py
backend/requirements.txt
```

backend/reset_for_karachi.py
backend/services/.gitkeep
backend/services/__init__.py
backend/services/gemini_service.py
backend/services/supabase_client.py
backend/temp_db.json
backend/tests/.gitkeep
backend/tests/__init__.py
backend/tests/baseline_comparison.py
backend/tests/stress_tests.py
backend/utils/.gitkeep
backend/utils/__init__.py
backend/utils/trace_logger.py
docs/.gitkeep
docs/architecture/.gitkeep
docs/architecture/system_architecture.md
docs/schemas/.gitkeep
docs/schemas/data_streams.md
docs/tests/STRESS_TEST_RESULTS.md
docs/traces/.gitkeep
docs/traces/CAPTURE_GUIDE.md
docs/traces/antigravity_usage_log.md
docs/video/.gitkeep
docs/video/video_plan.md
full backend and db implementation_plan.md
mobile/.gitignore
mobile/.gitkeep
mobile/.metadata
mobile/README.md
mobile/analysis_options.yaml
mobile/android/.gitignore
mobile/android/app/build.gradle.kts
mobile/android/app/src/debug/AndroidManifest.xml
mobile/android/app/src/main/AndroidManifest.xml
mobile/android/app/src/main/java/io/flutter/plugins/GeneratedPluginRegistrant.java
mobile/android/app/src/main/kotlin/com/example/ciro/MainActivity.kt
mobile/android/app/src/main/res/drawable-v21/launch_background.xml
mobile/android/app/src/main/res/drawable/launch_background.xml
mobile/android/app/src/main/res/mipmap-hdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-mdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-xhdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-xxhdpi/ic_launcher.png
mobile/android/app/src/main/res/mipmap-xxxhdpi/ic_launcher.png
mobile/android/app/src/main/res/values-night/styles.xml
mobile/android/app/src/main/res/values/styles.xml
mobile/android/app/src/profile/AndroidManifest.xml
mobile/android/build.gradle.kts
mobile/android/gradle.properties
mobile/android/gradle/wrapper/gradle-wrapper.jar
mobile/android/gradle/wrapper/gradle-wrapper.properties
mobile/android/gradlew
mobile/android/gradlew.bat
mobile/android/local.properties
mobile/android/settings.gradle.kts
mobile/assets/.gitkeep
mobile/assets/fonts/.gitkeep
mobile/assets/images/.gitkeep
mobile/devtools_options.yaml
mobile/ios/Flutter/AppFrameworkInfo.plist
mobile/ios/Flutter/Debug.xcconfig
mobile/ios/Flutter/Generated.xcconfig
mobile/ios/Flutter/Release.xcconfig

mobile/ios/Flutter/flutter_export_environment.sh
mobile/ios/Runner.xcodeproj/project.pbxproj
mobile/ios/Runner.xcodeproj/project.xcworkspace/contents.xcworkspacedata
mobile/ios/Runner.xcodeproj/project.xcworkspace/xcschemedata/IDEWorkspaceChecks.plist
mobile/ios/Runner.xcodeproj/project.xcworkspace/xcschemedata/WorkspaceSettings.xcsettings
mobile/ios/Runner.xcodeproj/xcschemedata/xcschemes/Runner.xcscheme
mobile/ios/Runner.xcworkspace/contents.xcworkspacedata
mobile/ios/Runner.xcworkspace/xcschemedata/IDEWorkspaceChecks.plist
mobile/ios/Runner.xcworkspace/xcschemedata/WorkspaceSettings.xcsettings
mobile/ios/Runner/AppDelegate.swift
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Contents.json
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-1024x1024@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-20x20@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-20x20@2x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-20x20@3x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@2x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-29x29@3x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@2x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-40x40@3x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@2x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-60x60@3x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@1x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-76x76@2x.png
mobile/ios/Runner/Assets.xcassets/AppIcon.appiconset/Icon-App-83.5x83.5@2x.png
mobile/ios/Runner/Assets.xcassets/LaunchImage.imageset/Contents.json
mobile/ios/Runner/Assets.xcassets/LaunchImage.imageset/LaunchImage.png
mobile/ios/Runner/Assets.xcassets/LaunchImage.imageset/LaunchImage@2x.png
mobile/ios/Runner/Assets.xcassets/LaunchImage.imageset/LaunchImage@3x.png
mobile/ios/Runner/Assets.xcassets/LaunchImage.imageset/README.md
mobile/ios/Runner/Base.lproj/LaunchScreen.storyboard
mobile/ios/Runner/Base.lproj/Main.storyboard
mobile/ios/Runner/GeneratedPluginRegistrant.h
mobile/ios/Runner/GeneratedPluginRegistrant.m
mobile/ios/Runner/Info.plist
mobile/ios/Runner/Runner-Bridging-Header.h
mobile/ios/Runner/SceneDelegate.swift
mobile/ios/RunnerTests/RunnerTests.swift
mobile/lib/.gitkeep
mobile/lib/main.dart
mobile/lib/models/.gitkeep
mobile/lib/providers/.gitkeep
mobile/lib/screens/.gitkeep
mobile/lib/screens/alert_feed_screen.dart
mobile/lib/screens/crisis_detail_screen.dart
mobile/lib/screens/dashboard_screen.dart
mobile/lib/screens/map_screen.dart
mobile/lib/screens/resource_list_screen.dart
mobile/lib/services/.gitkeep
mobile/lib/services/api_service.dart
mobile/lib/theme/.gitkeep
mobile/lib/utils/.gitkeep
mobile/lib/widgets/.gitkeep
mobile/linux/.gitkeep
mobile/linux/CMakeLists.txt
mobile/linux/flutter/.gitkeep
mobile/linux/flutter/CMakeLists.txt
mobile/linux/flutter/ephemeral/.plugin_symlinks/app_links_linux
mobile/linux/flutter/ephemeral/.plugin_symlinks/gtk
mobile/linux/flutter/ephemeral/.plugin_symlinks/path_provider_linux
mobile/linux/flutter/ephemeral/.plugin_symlinks/shared_preferences_linux

mobile/linux/flutter/ephemeral/.plugin_symlinks/url_launcher_linux
mobile/linux/flutter/generated_plugin_registrant.cc
mobile/linux/flutter/generated_plugin_registrant.h
mobile/linux/flutter/generated_plugins.cmake
mobile/linux/runner/.gitkeep
mobile/linux/runner/CMakeLists.txt
mobile/linux/runner/main.cc
mobile/linux/runner/my_application.cc
mobile/linux/runner/my_application.h
mobile/macos/.gitkeep
mobile/macos/Flutter/.gitkeep
mobile/macos/Flutter/Flutter-Debug.xcconfig
mobile/macos/Flutter/Flutter-Release.xcconfig
mobile/macos/Flutter/GeneratedPluginRegistrant.swift
mobile/macos/Flutter/ephemeral/Flutter-Generated.xcconfig
mobile/macos/Flutter/ephemeral/flutter_export_environment.sh
mobile/macos/Runner.xcodeproj/.gitkeep
mobile/macos/Runner.xcodeproj/project.pbxproj
mobile/macos/Runner.xcodeproj/project.xcworkspace/.gitkeep
mobile/macos/Runner.xcodeproj/project.xcworkspace/xcsourcedata/.gitkeep
mobile/macos/Runner.xcodeproj/project.xcworkspace/xcsourcedata/IDEWorkspaceChecks.plist
mobile/macos/Runner.xcodeproj/xcsourcedata/.gitkeep
mobile/macos/Runner.xcodeproj/xcsourcedata/xcschemes/.gitkeep
mobile/macos/Runner.xcodeproj/xcsourcedata/xcschemes/Runner.xcscheme
mobile/macos/Runner.xcworkspace/.gitkeep
mobile/macos/Runner.xcworkspace/contents.xcworkspacedata
mobile/macos/Runner.xcworkspace/xcsourcedata/.gitkeep
mobile/macos/Runner.xcworkspace/xcsourcedata/IDEWorkspaceChecks.plist
mobile/macos/Runner/.gitkeep
mobile/macos/Runner/AppDelegate.swift
mobile/macos/Runner/Assets.xcassets/.gitkeep
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/.gitkeep
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/Contents.json
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_1024.png
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_128.png
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_16.png
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_256.png
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_32.png
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_512.png
mobile/macos/Runner/Assets.xcassets/AppIcon.appiconset/app_icon_64.png
mobile/macos/Runner/Base.lproj/.gitkeep
mobile/macos/Runner/Base.lproj/MainMenu.xib
mobile/macos/Runner/Configs/.gitkeep
mobile/macos/Runner/Configs/AppInfo.xcconfig
mobile/macos/Runner/Configs/Debug.xcconfig
mobile/macos/Runner/Configs/Release.xcconfig
mobile/macos/Runner/Configs/Warnings.xcconfig
mobile/macos/Runner/DebugProfile.entitlements
mobile/macos/Runner/Info.plist
mobile/macos/Runner/MainFlutterWindow.swift
mobile/macos/Runner/Release.entitlements
mobile/macos/RunnerTests/.gitkeep
mobile/macos/RunnerTests/RunnerTests.swift
mobile/pubspec.lock
mobile/pubspec.yaml
mobile/test/.gitkeep
mobile/test/widget_test.dart
mobile/web/.gitkeep
mobile/web/favicon.png
mobile/web/icons/.gitkeep
mobile/web/icons/Icon-192.png
mobile/web/icons/Icon-512.png

mobile/web/icons/Icon-maskable-192.png
mobile/web/icons/Icon-maskable-512.png
mobile/web/index.html
mobile/web/manifest.json
mobile/windows/.gitkeep
mobile/windows/CMakeLists.txt
mobile/windows/flutter/.gitkeep
mobile/windows/flutter/CMakeLists.txt
mobile/windows/flutter/generated_plugin_registrant.cc
mobile/windows/flutter/generated_plugin_registrant.h
mobile/windows/flutter/generated_plugins.cmake
mobile/windows/runner/.gitkeep
mobile/windows/runner/CMakeLists.txt
mobile/windows/runner/Runner.rc
mobile/windows/runner/flutter_window.cpp
mobile/windows/runner/flutter_window.h