Ayesha Kiran

PF LAB 3

Task 1:

Input:

```
1- #include<iostream>
2- Using namespace std;
3- int main() {
4-    int age;
5-    double pay;
6-    char section;
7-    Cin >> age >> pay >> section;
8-    cout << "Age:" << age << endl;
9-    Cout << "pay:" << pay << endl;
10-   Cout << "section:" << section << endl;
11-      return 0
12-   }
```

Output:

⇒ 18 , 25000.5 , A

Age : 18
Pay : 25000.5
Section : A

Task 2:

Input:

```
1- #include <iostream>
2- Using namespace std;
3- int main( ) {
4- Cout << 20/4 -2<<endl;
5- Cout << 6+12*2- 8 << endl;
6- Cout << 4+8*2 << endl;
7- Cout << 6+17 % 3-2<< endl;
8- Cout << 2+22*(9-7) << endl;
9- Cout <<(8+7)*2 << endl;
10- Cout <<(16+7)% 2-1<<endl;
11- Cout << 12/(10-6) << endl;
12- Cout << (19-3) * (2+2)/4 << endl;
13- return 0; }
```

Output:

```
5
22
20
 6
 4 6
30
 0
 3
 16
```

Task 3:

Input:

```
1- #include <iostream>
2- using namespace std;
3- int main( )
4- {
5- int units = 10;
6- float mass = 5.5;
7- double weight;
8- weight = mass * units;
9- cout << "units= " << units << endl;
10- cout << "Mass= " << mass << endl;
11- cout << "weight= " << weight << endl;
12- return 0;
13- }
```

Output:

```
Units = 10
Mass = 5.5
weight = 55
```

CamScanner

Task 4:

Input:

```
1- #include <iostream>
2- Using namespace std;
3-    int main ( )
4-    {
5-    int a, b = 2;
6-    float c = 4.2;
7-    a = b * c;
8-
      Cout << "value of a = "a << endl;
9-          return 0;
10-         }
```

Output:

value of a = 8

Task 5:

Input:

```
1- # include <iostream>
2-    Using namespace std;
3-    int main ( )
4-       int qty, salesReps;
5-       float UnitsEach;
6-    Cout << "Enter quantity: ";
```

```
7-   cin >> qty;
8-   cout << "Enter number of sales representatives: ";
9-        cin >> salesReps;
10-  UnitsEach = static_cast<float>(qty) / salesReps;
11-       cout << "Units each= " << UnitsEach << endl;
12-            return 0;
13-       }
```

Output

⇒ 10 4

Units each = 2.5

Task 6:

Input:

```
1-   #include <iostream>
2-   #include <cstdlib>
3-   #include <ctime>
4-   Using namespace std;
5-   int main ( )
6-   srand(time(0));
7-   int num1 = rand( ) % 900 + 100;
8-   int num2 = rand( ) % 900 + 100;
9-   int answer;
10-  cout << num1 << endl;
```

```
11- cout << num1 << endl;
12- cout << " + " << num2 << endl;
13- cout << "------" << endl;
14-     cin.get();
15-   answer = num1 + num2;
16-   cout << num1 << endl;
17-   cout << " + " << num2 << endl;
18-   cout << "------" << endl;
19-   cout << answer << endl;
20-       return 0;
21-   }
```

Output:

```
247
+ 129
-----
Press enter to see the answer.
247
+ 129
-----
376
```

Home Tasks

1-

Program 1: corrected code

```
1- #include <iostream>
2- Using namespace std;
```

```
3- int main ( )
4-  {
5-  double number 1, number 2, sum ;
6-  cout << " Enter a number: " ;
7-      cin >> number 1
8-  cout << " Enter another number: " ;
9-      cin >> number 2 ;
10-  Sum = number 1 + number 2 ;
11-  cout << " The sum of the two numbers is "
12-      << sum << endl ;
13-      return 0 ;
14-  }
```

Output:

⇒ 5 10

Enter a number = 5
Enter another number = 10
The sum of two numbers is 15

Program 2:

Corrected Code

Input:

```
1- #include <iostream>
2- Using namespace std;
3-    int main ( )
4-    {
5-  int number 1, number 2;
6-     float quotient;
7-  Cout << "Enter two numbers and I will divide \n";
8-  Cout << "The first by the second for you.\n";
9-    Cin >> number 1 >> number 2;
10-  quotient = static_cast<float>(number 1) / number 2;
11-        Coutcc quotient << endl;
12-              return 0;
13-              }
```

output:

=> 7 2

Enter two numbers and I will divide
The first by the second for you.

7 2

3.5

CamScanner

2-

Input:

```
# include <iostream>
Using namespace std;
int main ( )
{
int a = 28, b = 32, c = 37, d = 24, e = 33;
    int sum;
    float average;
Sum = a+b+c+d+e;
average = sum/5.0;
Cout << " Sum = " << sum << endl;
Cout << " Average = " << average << endl;
    return 0;
    }
```

Output:

Sum = 154

Average = 30.8