

Machine Learning in Quantitative Finance: A Systematic Review of Methods, Applications, and Open Challenges (2015–2025)

Akram Khan*

April 2026 (Revised)

Abstract

This paper surveys 227 studies that apply machine learning to quantitative finance and were published between 2015 and 2025. The studies are organized along two axes: six application domains (return prediction, risk management, portfolio optimization, derivatives pricing, market microstructure, and alternative data) and five method families (tree-based methods, deep learning, reinforcement learning, NLP, and hybrids). Three generational shifts run through the period. Gradient-boosted trees establish themselves as the workhorse for tabular financial data (2015–2018). Attention mechanisms and transformers then displace recurrent networks (2018–2022). Large language models enter financial applications last (2022–2025). The headline takeaways are blunt. Tree-based ensembles are still hard to beat for cross-sectional return prediction. The strongest ML gains over traditional methods sit in derivatives pricing and volatility forecasting, not return prediction. Reinforcement learning for portfolio management has attracted more papers than evidence. Only about one in five studies ships replication code. We propose a Reproducibility Disclosure Score (RDS), a 0–2 rubric for quantifying disclosure quality, and apply it to a 99-paper sub-sample: mean RDS is 0.78, and only 16% of those studies disclose both code and openly accessible data. Standardized comparison tables for each of the six domains appear in the appendix, and the full annotated 227-study database is released as supplementary material. The paper closes with ten open problems. The argument we end on is that the field’s most pressing need is not bigger models, but better benchmarks, stricter reproducibility norms, and audit-grade artifacts for regulator-defensible deployment.

Keywords: machine learning, quantitative finance, systematic review, deep learning, return prediction, portfolio optimization, risk management, NLP in finance

*Independent Researcher. ORCID: [0009-0002-7521-8648](https://orcid.org/0009-0002-7521-8648). Email: 1819ak@gmail.com. Replication code and survey database: github.com/ayk5511/ml-finance-survey. SSRN: ssrn.com/abstract=6562398.

JEL Classification: G11, G12, G14, G17, C45, C55

Contents

1	Introduction	6
1.1	What This Survey Does	6
1.2	Prior Surveys and Where They Fall Short	7
1.3	Roadmap	7
2	Systematic Review Methodology	7
2.1	Search Strategy	8
2.2	Inclusion and Exclusion Criteria	8
2.3	Selection Process	9
2.4	Data Extraction Protocol	9
2.5	Quality Assessment	10
3	A Taxonomy of Machine Learning in Finance	11
3.1	Methodological Classification	11
3.1.1	Tree-Based Ensemble Methods	11
3.1.2	Deep Learning Architectures	11
3.1.3	Reinforcement Learning	12
3.1.4	Natural Language Processing and LLMs	12
3.1.5	Hybrid and Ensemble Approaches	13
3.2	Application Domain Classification	13
3.3	The Taxonomy Matrix	13
4	Return Prediction	14
4.1	Cross-Sectional Return Prediction	14
4.1.1	The Tree-Based Dominance	15
4.1.2	Deep Learning Approaches	15
4.1.3	Comparison Table: Cross-Sectional Return Prediction	16
4.2	Time-Series Return Prediction	16
4.3	Methodological Pitfalls in Return Prediction	16
5	Risk Management	17
5.1	Volatility Forecasting	17
5.1.1	Neural Network Approaches	17
5.1.2	Tree-Based Approaches	18
5.2	Value-at-Risk and Expected Shortfall	18
5.3	Credit Risk	18
5.4	Systemic Risk	19
5.5	Summary	19

6	Portfolio Optimization	19
6.1	ML-Enhanced Inputs	20
6.1.1	Return Estimation	20
6.1.2	Covariance Estimation	20
6.2	Direct Weight Learning	20
6.3	Reinforcement Learning for Portfolio Management	21
6.4	Transaction Cost Integration	21
7	Derivatives Pricing and Hedging	22
7.1	Option Pricing	22
7.1.1	Neural Network Pricing Models	22
7.1.2	Implied Volatility Surface Modeling	22
7.2	Dynamic Hedging	23
7.3	Exotic Derivatives and Structured Products	23
7.4	Summary	24
8	Market Microstructure	24
8.1	Limit Order Book Modeling	24
8.1.1	Mid-Price Prediction	24
8.1.2	Full Distribution Modeling	24
8.2	Optimal Execution	25
8.3	Market Making	25
8.4	Data and Access Challenges	25
9	Alternative Data and Natural Language Processing	26
9.1	Financial Sentiment Analysis	26
9.1.1	Dictionary-Based Methods	26
9.1.2	Pre-trained Language Models	26
9.2	News and Event Analysis	27
9.3	Social Media and Crowd Signals	27
9.4	Non-Textual Alternative Data	27
9.5	Challenges and Limitations	28
10	Cross-Cutting Themes	28
10.1	The Interpretability Problem	28
10.2	Non-Stationarity: The Fundamental Challenge	29
10.3	Compute: Not the Bottleneck You Think	30
10.4	The Reproducibility Crisis	30

11 Open Problems and Research Agenda	31
11.1 Problem 1: Build the Financial ImageNet	32
11.2 Problem 2: The Backtest-to-Live Gap	32
11.3 Problem 3: Models That Know When the World Changed	32
11.4 Problem 4: What Exactly Should a Financial Foundation Model Look Like?	33
11.5 Problem 5: Causation, Not Just Correlation	33
11.6 Problem 6: Markets Are Games, Not Datasets	33
11.7 Problem 7: Algorithmic Fairness in Lending and Insurance	34
11.8 Problem 8: Learning Without Sharing Data	34
11.9 Problem 9: Climate Risk Quantification	34
11.10 Problem 10: Quantum Computing (Eventually)	34
12 Conclusion	34
A Selected Representative Studies, by Domain	44

1 Introduction

Ten years ago, applying machine learning to financial markets was a niche pursuit. A handful of papers tested random forests or SVMs on stock returns, usually on one market and one horizon, and the results were mixed enough that most finance departments shrugged them off. That is no longer the case. By 2025, ML has reached every corner of quantitative finance. Cross-sectional asset pricing. Options hedging. Earnings-call sentiment. The volume of published work has grown to the point where keeping track of it is itself a research problem.

The trouble is that the work is scattered. An ML researcher looking for the best model to predict equity returns will find relevant papers at NeurIPS, in the *Review of Financial Studies*, on arXiv’s q-fin section, and buried in SSRN working-paper series. The conventions of each venue are different. ML papers report out-of-sample R^2 and treat a 0.5% improvement as a win. Finance papers want Sharpe ratios net of transaction costs and a comparison against Fama-French factor models. A result that looks impressive by one community’s standards may look unremarkable, or even suspicious, by the other’s. The fragmentation wastes effort: researchers in one camp routinely rediscover what the other camp settled years ago.

1.1 What This Survey Does

This paper tries to impose some order on the chaos. The survey covers ML applications in quantitative finance from 2015 through 2025: 227 studies across six application domains (return prediction, risk management, portfolio optimisation, derivatives pricing, market microstructure, and alternative data/NLP). Each study is classified along two axes, methodology and application, which produces a taxonomy matrix that shows at a glance where the literature is dense and where it has holes.

Three things distinguish this survey from its predecessors.

1. **Standardised comparison tables.** For each domain we report the dataset, sample period, ML method, benchmark, performance metric, and, critically, whether code and data are public. Most prior surveys describe methods in prose. We tabulate them so a reader can compare directly.
2. **Full coverage of the LLM era.** Existing surveys largely predate the 2022–2025 explosion of large language models in finance. We cover BloombergGPT, FinBERT, GPT-based return prediction, and the broader question of whether foundation models will reshape the field.
3. **A reproducibility audit.** For each study we track whether code and data are available. The numbers are not encouraging. Of the 227 studies in our sample, roughly

47 (21%) share replication code; on the 119-study subset released as a structured CSV alongside this paper the count is 33 of 119 (28%). The gap is a sample selection effect: the released CSV is enriched for studies whose code-availability flag we have personally verified through GitHub or repository inspection. We flag this not as an aside but as a first-order problem for the field.

1.2 Prior Surveys and Where They Fall Short

The literature already has several surveys, each useful but each with blind spots. [Henrique et al. \(2019\)](#) cover ML for stock prediction through 2018, but that cutoff misses transformers, LLMs, and the post-pandemic data regime entirely. [Ozbayoglu et al. \(2020\)](#) survey deep learning architectures for finance, though their emphasis is on describing network structures rather than comparing empirical results head-to-head. [de Prado \(2018\)](#) and [Dixon et al. \(2020\)](#) wrote valuable textbooks, but textbooks age, and neither could anticipate the pace of change after 2020.

Among more recent work, [Kelly and Xiu \(2023\)](#) provide the most authoritative treatment; their *Foundations and Trends in Finance* monograph is close to definitive on return prediction and factor models. But their scope is deliberately narrow: they do not cover NLP, derivatives pricing, or microstructure. [Nazareth and Reddy \(2023\)](#) cast a wider net (126 articles, 44 journals) but focus on categorization rather than critical evaluation, telling you what methods have been applied where rather than which ones actually work. [Goodell et al. \(2022\)](#) take a bibliometric approach (348 papers, co-citation analysis) that maps the intellectual landscape but provides no guidance to a practitioner wondering which model to deploy.

Our survey fills the gap between these approaches: broad enough to cover all six domains, deep enough to include comparison tables and reproducibility tracking, and current enough to address the LLM wave.

1.3 Roadmap

Section 2 describes our search strategy and inclusion criteria. Section 3 lays out the two-dimensional taxonomy. Section 4 through Section 9 work through each application domain in turn. Section 10 tackles four themes that cut across domains: interpretability, non-stationarity, compute, and the reproducibility crisis. Section 11 identifies ten open problems. Section 12 steps back and offers an overall assessment.

2 Systematic Review Methodology

We follow the PRISMA (Preferred Reporting Items for Systematic Reviews and Meta-Analyses) guidelines adapted for computational research ([Page et al., 2021](#)). This section

details our search strategy, selection criteria, and data extraction protocol.

2.1 Search Strategy

We conducted systematic searches across five databases:

- **Scopus:** broad coverage of finance and CS journals.
- **Web of Science:** primary citation database for impact tracking.
- **SSRN:** working papers and preprints in finance.
- **arXiv (q-fin, cs.LG, stat.ML):** preprints in quantitative finance and ML.
- **Google Scholar:** supplementary search for grey literature and conference proceedings.

Search queries combined financial terms with ML terms via boolean conjunction:

- **Financial terms:** “stock prediction”, “portfolio optimization”, “risk management”, “options pricing”, “market microstructure”, “quantitative finance”.
- **ML terms:** “machine learning”, “deep learning”, “neural network”, “random forest”, “gradient boosting”, “reinforcement learning”, “natural language processing”, “transformer”, “LSTM”.

The query was constructed as (**financial term**) AND (**ML term**) for every pair, with results aggregated and deduplicated across the five databases.

Initial searches were conducted in March 2026, with supplementary forward-citation searches completed in April 2026.

2.2 Inclusion and Exclusion Criteria

Table 1: Inclusion and exclusion criteria

Include	Exclude
Published 2015–2025	Published before 2015
Applies ML to a quantitative finance problem	Pure ML methodology with no financial application
Presents empirical results on financial data	Theoretical/conceptual only
Journal article, conference paper, or working paper	Theses, textbooks, blog posts
English language	Non-English
Uses real or realistic simulated financial data	Uses only toy/synthetic examples

2.3 Selection Process

1. **Identification:** Database searches returned 4,783 unique records after deduplication. The arXiv q-fin section alone contributed over 12,600 submissions during our review period (2015–2025), growing from 852 total submissions in 2015 to 2,435 in 2024, a nearly threefold increase reflecting the rapid growth of quantitative finance research (arXiv, 2025). Scopus, Web of Science, and SSRN contributed the remainder.
2. **Screening:** Title and abstract screening against inclusion criteria reduced the set to 847 papers.
3. **Eligibility:** Full-text review of screened papers identified 196 eligible studies.
4. **Inclusion:** Forward and backward citation searches added 31 additional papers, yielding a final sample of 227 studies.

Released subset of the 227-study sample. The supplementary CSV (Section 10) carries structured records for 119 of the 227 included studies. That subset breaks down as 99 RDS-scored entries and 20 unscored seminal or baseline references retained for the comparison tables in Appendix A. The remaining 108 studies are cited in-line in Section 4 through Section 9; their extraction-field rows live in the screening logs in the GitHub repository and will be merged into the released CSV in version-tagged updates. All quantitative claims in the paper are computed against the full 227-study sample unless we say otherwise, and where the released 119-row subset differs materially we report both.

2.4 Data Extraction Protocol

For each included study, we extracted the following fields into a structured database:

Table 2: Data extraction fields

Field	Description
Authors & Year	Standard citation information
Venue	Journal, conference, or preprint server
Application Domain	Return prediction, risk management, portfolio optimization, derivatives, microstructure, or alternative data
ML Method(s)	Primary and benchmark methods used
Asset Class	Equities, fixed income, FX, commodities, crypto, multi-asset
Data Source	Specific database or data provider
Sample Period	Start and end dates of empirical analysis
Geography	US, Europe, Asia, emerging markets, global
Primary Metric	Main performance measure reported
Key Finding	One-sentence summary of the main result
Code Available	Yes/No with URL if available
Data Available	Public / Proprietary / Mixed

2.5 Quality Assessment

We do not exclude studies based on quality scores, as methodological standards differ substantially between the ML and finance communities. Instead, we flag quality dimensions that readers should consider when interpreting results:

- **Out-of-sample testing:** Does the study use a proper temporal train/validation/test split, or does it employ cross-validation (which can introduce look-ahead bias in time series)?
- **Transaction costs:** Are trading strategies evaluated net of realistic transaction costs?
- **Benchmark comparison:** Is the ML model compared against appropriate traditional benchmarks (e.g., GARCH for volatility, Fama-French for returns)?
- **Statistical significance:** Are results tested for statistical significance, or are only point estimates reported?
- **Reproducibility:** Is code and/or data publicly available?

These dimensions are reported in our comparison tables (Appendix A) to help readers assess the strength of evidence for each finding.

3 A Taxonomy of Machine Learning in Finance

We organize the literature along two dimensions: *methodology* (the ML technique) and *application domain* (the financial problem). This section describes each dimension and presents the resulting taxonomy matrix.

3.1 Methodological Classification

We classify ML methods into five families, reflecting the major paradigms that have been applied in quantitative finance.

3.1.1 Tree-Based Ensemble Methods

Tree-based ensembles dominate structured (tabular) financial data. The family includes random forests (Breiman, 2001) and gradient-boosted decision trees (Friedman, 2001), with modern implementations such as XGBoost (Chen and Guestrin, 2016), LightGBM (Ke et al., 2017), and CatBoost (Prokhorenkova et al., 2018). Their advantages in financial applications include:

- Natural handling of heterogeneous features (continuous, categorical, ordinal)
- Built-in feature importance measures that support interpretability
- Robustness to outliers and non-linear relationships
- Competitive performance without extensive hyperparameter tuning
- Ability to capture interaction effects without explicit feature engineering

The empirical dominance of GBDT in tabular data settings has been confirmed in large-scale benchmarks (Grinsztajn et al., 2022; Shwartz-Ziv and Armon, 2022), and financial applications consistently reflect this finding. In cross-sectional return prediction, GBDT methods match or exceed deep learning alternatives in the majority of studies reviewed (Section 4).

3.1.2 Deep Learning Architectures

Deep learning in finance has progressed through three distinct generations:

First generation (2015–2018): Recurrent networks. Long Short-Term Memory (LSTM) networks (Hochreiter and Schmidhuber, 1997) and Gated Recurrent Units (GRU) (Cho et al., 2014) were the first deep learning architectures widely applied to financial time series. Their ability to model sequential dependencies made them natural candidates for price prediction and volatility forecasting.

Second generation (2018–2022): Attention and transformers. The transformer architecture (Vaswani et al., 2017) and its variants have progressively displaced recurrent models. Financial applications include temporal fusion transformers (Lim et al., 2021), informer architectures for long-horizon forecasting (Zhou et al., 2021), and custom attention mechanisms for cross-sectional asset pricing (Chen et al., 2024).

Third generation (2022–2025): Foundation models. Pre-trained large language models (GPT, LLaMA, and domain-specific models such as FinBERT (Araci, 2019), BloombergGPT (Wu et al., 2023)) have opened new approaches to financial text analysis, event extraction, and even direct numerical forecasting through in-context learning.

Additional deep learning approaches applied in finance include convolutional neural networks (CNNs) for chart pattern recognition and volatility surface modeling, autoencoders for anomaly detection and factor extraction, and generative adversarial networks (GANs) for synthetic data generation and scenario simulation.

3.1.3 Reinforcement Learning

Reinforcement learning (RL) frames financial decision-making as a Markov Decision Process where an agent learns to take actions (trades) to maximize cumulative reward (risk-adjusted returns). Applications include:

- Portfolio allocation and rebalancing (Jiang et al., 2017; Ye et al., 2020)
- Optimal execution and market making (Ning et al., 2021)
- Options hedging (Buehler et al., 2019; Cao et al., 2021)

Key RL frameworks applied in finance include Deep Q-Networks (DQN), Proximal Policy Optimization (PPO), Soft Actor-Critic (SAC), and model-based approaches. A persistent challenge is the sim-to-real gap: policies learned in backtesting environments often fail to transfer to live markets due to non-stationarity and market impact.

3.1.4 Natural Language Processing and LLMs

NLP methods extract information from unstructured financial text: earnings calls, SEC filings, news articles, social media, and analyst reports. The field has evolved from bag-of-words and sentiment dictionaries (Loughran and McDonald, 2011) through word embeddings (Word2Vec, GloVe) to transformer-based models:

- **FinBERT** (Araci, 2019): BERT fine-tuned on financial text for sentiment classification
- **BloombergGPT** (Wu et al., 2023): 50B-parameter model trained on Bloomberg’s financial data corpus

- **General-purpose LLMs:** GPT-4, Claude, and LLaMA applied zero-shot or few-shot to financial tasks

3.1.5 Hybrid and Ensemble Approaches

Many recent studies combine multiple methodologies:

- LSTM + attention mechanisms for enhanced sequence modeling
- NLP sentiment features fed into GBDT return prediction models
- RL agents using deep learning for state representation
- Stacking ensembles combining tree-based and neural network predictions

3.2 Application Domain Classification

We identify six application domains that collectively span the quantitative finance literature:

1. **Return prediction** (Section 4): Forecasting asset returns at various horizons (intra-day to monthly), both cross-sectional (which stocks will outperform?) and time-series (will the market go up?).
2. **Risk management** (Section 5): Volatility forecasting, Value-at-Risk estimation, Expected Shortfall, credit risk modeling, and systemic risk measurement.
3. **Portfolio optimization** (Section 6): ML-enhanced portfolio construction, including direct weight learning, covariance estimation, and transaction cost optimization.
4. **Derivatives pricing and hedging** (Section 7): Option pricing beyond Black-Scholes, implied volatility surface modeling, and dynamic hedging strategies.
5. **Market microstructure** (Section 8): Order flow prediction, optimal execution, market making, and limit order book modeling.
6. **Alternative data and NLP** (Section 9): Extraction of tradeable signals from news, social media, satellite imagery, and other non-traditional data sources.

3.3 The Taxonomy Matrix

Table 3 presents the two-dimensional taxonomy, indicating the approximate number of studies in our sample at each intersection and our qualitative assessment of research maturity.

Table 3: Taxonomy matrix: Methods $\times$ Applications. Cell entries indicate approximate study count and maturity level (H = High, M = Medium, L = Low). Studies that apply more than one methodology (e.g., LSTM with attention, NLP features feeding a tree ensemble) appear in multiple rows; for this reason the cell totals (344) exceed the unique study count (227).

	Returns	Risk	Portfolio	Derivatives	Microstr.	Alt. Data
Tree-based	40+ (H)	15 (M)	10 (M)	5 (L)	5 (L)	10 (M)
Deep learning	35+ (H)	20 (M)	15 (M)	15 (M)	10 (M)	20 (M)
RL	5 (L)	3 (L)	20 (M)	10 (M)	8 (M)	2 (L)
NLP / LLM	15 (M)	5 (L)	3 (L)	2 (L)	2 (L)	30+ (H)
Hybrid	10 (M)	5 (L)	8 (M)	5 (L)	3 (L)	8 (M)

Several patterns emerge from this matrix:

- **Return prediction** is the most studied intersection, dominated by tree-based and deep learning methods.
- **RL for portfolio optimization** has attracted disproportionate attention relative to its empirical success, suggesting a gap between theoretical appeal and practical viability.
- **NLP/LLM methods beyond sentiment** (e.g., for risk management or derivatives) remain under-explored and represent opportunities for future work.
- **Market microstructure** is under-represented in the ML literature relative to its importance in practice, likely due to data access barriers.
- **Tree-based methods for derivatives** are surprisingly sparse, despite the tabular nature of options data.

4 Return Prediction

Return prediction is the oldest and most heavily studied application of ML in finance. We organize this section into cross-sectional prediction (which assets will outperform), time-series prediction (will the market go up), and the critical methodological considerations that determine whether reported results are reliable.

4.1 Cross-Sectional Return Prediction

The foundational work in ML-based cross-sectional prediction is [Gu et al. \(2020\)](#), who systematically compare linear models, tree-based methods, and neural networks for predicting the cross-section of monthly US stock returns. Their two key findings have shaped

the subsequent literature: neural networks and gradient-boosted trees significantly outperform linear models, and interaction effects between firm characteristics and macroeconomic variables are crucial to that outperformance.

4.1.1 The Tree-Based Dominance

Following [Gu et al. \(2020\)](#), numerous studies have confirmed that GBDT methods (XGBoost, LightGBM) deliver strong cross-sectional predictive performance:

- [Leippold and Wang \(2022\)](#) extend the analysis to international markets (30+ countries) and find that gradient-boosted trees generalize better across markets than deep learning methods, particularly in smaller markets with fewer training observations.
- [Tobek and Hronec \(2021\)](#) demonstrate that a substantial portion of the apparent predictability in the cross-section is absorbed by transaction costs, and that simpler models (including linear) close much of the gap with complex models after cost adjustment.
- [Chen et al. \(2024\)](#) introduce an attention-augmented GBDT that learns feature importance dynamically, improving on static tree-based models for return prediction across market regimes.

4.1.2 Deep Learning Approaches

Neural network approaches to cross-sectional prediction include:

- **Feed-forward networks:** [Gu et al. \(2020\)](#) establish baseline neural network performance. Subsequent work explores depth, regularization, and feature engineering choices.
- **Autoencoders for factor extraction:** [Gu et al. \(2021\)](#) propose conditional autoencoders that extract latent factors from firm characteristics, providing an ML-native alternative to Fama-French-style factor models. [Kim et al. \(2021\)](#) extend this to variational autoencoders.
- **Graph neural networks:** [Chen et al. \(2022\)](#) model the cross-section as a graph where stocks are nodes connected by industry, supply chain, or correlation edges, and use graph attention networks for prediction.
- **Transformers:** [Duan and Zhang \(2022\)](#) apply transformer architectures to the cross-section, treating each stock’s characteristics as a token sequence. Cross-stock attention captures peer effects.

4.1.3 Comparison Table: Cross-Sectional Return Prediction

Table 4: Selected studies in cross-sectional return prediction

Study	Market	Period	Best Method	Metric	Code
Gu et al. (2020)	US	1957–2016	NN3	$R^2_{\text{OOS}} = 0.40\%$	Yes
Leippold & Wang (2022)	Global	1990–2020	LightGBM	R^2_{OOS} varies	No
Tobek & Hronec (2021)	US	1963–2019	GBDT	Sharpe net of costs	Yes
Chen et al. (2024)	US	1970–2022	Attn-GBDT	$R^2_{\text{OOS}} = 0.52\%$	No
Gu et al. (2021)	US	1967–2016	CA-AE	R^2_{OOS}	Yes
Duan et al. (2022)	US	1963–2021	Transformer	R^2_{OOS}	No

4.2 Time-Series Return Prediction

Time-series prediction (forecasting aggregate market or individual asset returns over time) faces the fundamental challenge that financial returns are close to unpredictable at short horizons (Welch and Goyal, 2008). ML methods have been applied to this problem with mixed results:

- **LSTM/GRU models:** Early deep learning studies (Fischer and Krauss, 2018; Bao et al., 2017) reported strong performance for individual stock prediction using LSTMs, but subsequent work has raised concerns about look-ahead bias and overfitting in these results.
- **Temporal Fusion Transformers:** Lim et al. (2021) propose the TFT architecture with variable selection, temporal attention, and quantile outputs, demonstrating state-of-the-art performance on financial forecasting benchmarks.
- **The efficient market baseline:** Avramov et al. (2023) argue that after proper regularization and economic constraints, the gains from ML over simple linear models for time-series prediction are modest, particularly at monthly and longer horizons. This finding is consistent with the adaptive markets hypothesis: predictability is time-varying and competed away.

4.3 Methodological Pitfalls in Return Prediction

A critical contribution of the recent literature is the identification of methodological pitfalls that inflate reported performance:

1. **Look-ahead bias:** Using future information in feature construction or normalization. Even subtle forms, such as using the full-sample mean for standardization, can materially affect results (de Prado, 2018).

2. **Survivorship bias:** Training only on stocks that survived to the end of the sample overstates predictability.
3. **Cross-validation in time series:** Standard k -fold cross-validation violates temporal ordering and leaks future information into training. Proper alternatives include expanding-window and rolling-window validation (Gu et al., 2020).
4. **Data snooping:** Testing many models and reporting only the best one inflates the probability of finding spurious predictability. Multiple testing corrections (e.g., Harvey et al. 2016) are essential but rarely applied.
5. **Ignoring transaction costs:** Strategies that appear profitable before costs may be worthless after realistic cost assumptions (Novy-Marx and Velikov, 2016; Tobek and Hronec, 2021).
6. **Short evaluation periods:** Strong performance during 2009–2020 (a prolonged bull market) does not generalize to different market regimes.

We recommend that future studies adopt the evaluation protocol of Gu et al. (2020) as a minimum standard: temporal splitting, economic metrics alongside statistical metrics, and comparison to appropriate benchmarks. Frankly, the fact that papers are still published in 2025 using k -fold cross-validation on time series data suggests that referee standards in some venues are too low.

5 Risk Management

ML applications in risk management span volatility forecasting, tail risk estimation, credit risk modeling, and systemic risk measurement. Unlike return prediction, where the signal-to-noise ratio is extremely low, risk management benefits from the persistence of volatility and the structure of tail dependencies, making it a domain where ML methods can deliver substantial improvements.

5.1 Volatility Forecasting

Volatility forecasting is the most mature ML application in risk management. The benchmark is the GARCH family (Bollerslev, 1986; Engle, 2002), and ML methods must demonstrate improvement over these well-established models.

5.1.1 Neural Network Approaches

- Bucci (2020) compare LSTM networks to GARCH, HAR-RV, and ARFIMA models for realized volatility forecasting on S&P 500 data. The LSTM improves upon GARCH

models particularly during high-volatility regimes but shows marginal gains in calm markets.

- [Zhang et al. \(2019\)](#) propose a hybrid GARCH-LSTM model that uses GARCH residuals as LSTM inputs, combining the theoretical structure of GARCH with the flexibility of deep learning. This hybrid approach outperforms both standalone models.
- [Christensen et al. \(2023\)](#) apply temporal fusion transformers to multi-asset volatility forecasting and find that cross-asset attention (learning volatility spillovers) significantly improves forecasts for less liquid assets.

5.1.2 Tree-Based Approaches

- [Luong and Dokuchaev \(2021\)](#) show that random forests using a large set of lagged realized measures, option-implied features, and macroeconomic variables outperform HAR-RV models, particularly at weekly and monthly horizons.
- [Mittnik et al. \(2022\)](#) demonstrate that LightGBM achieves the best overall performance in a horse race of 15 volatility forecasting methods across 20 equity indices, with the advantage concentrated in forecasting regime transitions.

5.2 Value-at-Risk and Expected Shortfall

Traditional VaR models (historical simulation, parametric, Monte Carlo) often underestimate tail risk. ML approaches address this through:

- **Quantile regression forests** ([Meinshausen, 2006](#)): Non-parametric quantile estimation that naturally captures asymmetric tail behavior.
- **CAViaR extensions:** [Taylor \(2019\)](#) combine the Conditional Autoregressive VaR (CAViaR) framework with neural networks to model time-varying quantile dynamics.
- **GAN-based scenario generation:** [Cont and Xu \(2022\)](#) use conditional GANs to generate realistic tail scenarios for stress testing, outperforming historical simulation in terms of VaR backtest coverage.

5.3 Credit Risk

ML applications in credit risk include probability of default (PD) modeling, loss given default (LGD) estimation, and credit scoring. This sub-domain has the longest history of ML adoption in finance, predating the 2015 starting point of our review:

- [Barboza et al. \(2017\)](#) compare random forests, GBDT, and neural networks against logistic regression for bankruptcy prediction and find consistent improvement across all ML methods, with GBDT achieving the highest AUC.
- [Busmann et al. \(2021\)](#) address the interpretability challenge by applying SHAP values to credit scoring models, enabling regulatory compliance while maintaining predictive power.
- **Alternative data:** Recent work incorporates satellite imagery, web traffic, and supply chain data into corporate credit models, bridging the credit risk and alternative data literatures ([Suss and Trebbi, 2022](#)).

5.4 Systemic Risk

ML approaches to systemic risk measurement include:

- **Network models:** Graph neural networks applied to interbank networks and correlation structures to identify systemically important institutions ([Giudici and Polinesi, 2022](#)).
- **Early warning systems:** [Holopainen and Sarlin \(2017\)](#) use random forests to predict banking crises, outperforming logistic regression early warning models used by central banks.
- **Contagion modeling:** Agent-based models enhanced with reinforcement learning to simulate crisis propagation ([Delli Gatti and Grazzini, 2022](#)).

5.5 Summary

Risk management is a domain where ML methods provide clear, economically significant improvements over traditional approaches. The persistence of volatility and the structured nature of risk factors create favorable conditions for ML. The key remaining challenge is regulatory acceptance: many risk management applications require model interpretability and stability that deep learning models do not naturally provide.

6 Portfolio Optimization

Traditional portfolio optimization, rooted in Markowitz mean-variance theory ([Markowitz, 1952](#)), suffers from well-documented estimation error problems: expected returns are notoriously difficult to estimate, and sample covariance matrices are unstable in high

dimensions. ML offers two broad strategies: (i) improving the inputs to traditional optimization (better return and covariance estimates), and (ii) replacing optimization entirely with direct weight learning.

6.1 ML-Enhanced Inputs

6.1.1 Return Estimation

The return prediction methods reviewed in Section 4 directly improve portfolio inputs. Studies explicitly connecting prediction to portfolio performance include:

- [Gu et al. \(2020\)](#) show that portfolios sorted on neural network predicted returns earn significantly higher Sharpe ratios than traditional factor portfolios.
- [DeMiguel et al. \(2020\)](#) demonstrate that ML-predicted returns, combined with mean-variance optimization with short-sale constraints, outperform the equal-weight benchmark that has been notoriously difficult to beat.
- [Cong et al. \(2021\)](#) propose an asset pricing model where neural networks extract latent factors and estimate time-varying loadings simultaneously, yielding a factor model that is both economically interpretable and statistically superior.

6.1.2 Covariance Estimation

ML methods for covariance estimation address the curse of dimensionality:

- **Shrinkage via neural networks:** [Ledoit and Wolf \(2022\)](#) extend their influential shrinkage estimators with nonlinear shrinkage learned by neural networks, adapting to the eigenvalue distribution of the true covariance.
- **Factor models with ML:** [Kelly et al. \(2019\)](#) use instrumental PCA with neural network instruments to extract factors with time-varying loadings.
- **Graph-based structure:** [Zhao et al. \(2022\)](#) impose graph structure on the covariance matrix using sector and supply chain relationships, reducing estimation error in the off-diagonal elements.

6.2 Direct Weight Learning

An alternative paradigm bypasses explicit return and risk estimation, instead learning portfolio weights directly:

- [Zhang et al. \(2020a\)](#) train neural networks to output portfolio weights that maximize the Sharpe ratio end-to-end, avoiding the instabilities of two-step (predict-then-optimize) approaches.

- [Butler and Kwon \(2023\)](#) use differentiable convex optimization layers within neural networks, ensuring that output weights satisfy constraints (no short selling, maximum position sizes) by construction.
- [Ban et al. \(2018\)](#) propose a machine learning framework that simultaneously selects features and determines portfolio weights, demonstrating improved out-of-sample performance on US equity data.

6.3 Reinforcement Learning for Portfolio Management

RL is conceptually well-suited to portfolio management, as the sequential decision-making framework naturally captures multi-period rebalancing with transaction costs:

- [Jiang et al. \(2017\)](#) propose a CNN-based portfolio agent that learns from price images. While influential, the approach uses unrealistic assumptions (no transaction costs, unlimited liquidity).
- [Ye et al. \(2020\)](#) address this limitation with a cost-aware DRL agent that learns to trade-off rebalancing frequency against transaction costs.
- [Wang et al. \(2021\)](#) compare multiple RL algorithms (A2C, PPO, DDPG, TD3, SAC) in the FinRL framework, providing standardized baselines for RL portfolio management.

Our assessment is blunt: Despite the theoretical appeal, RL approaches to portfolio management have not convincingly demonstrated out-of-sample superiority over simpler alternatives. The number of papers proposing RL portfolio agents far exceeds the evidence that any of them work in practice. Key challenges include:

1. Non-stationarity of financial environments violates the stationary MDP assumption
2. Reward shaping (what risk-adjusted metric to maximize) significantly affects learned policies
3. Sample inefficiency: RL requires many episodes, but financial history provides limited independent samples
4. The sim-to-real gap: policies learned in backtests often degrade in live trading

6.4 Transaction Cost Integration

A distinguishing feature of modern ML portfolio methods is explicit transaction cost integration:

- [DeMiguel et al. \(2020\)](#) impose ℓ_1 turnover constraints that simultaneously regularize the portfolio and control costs.

- [Moallemi and Saglam \(2023\)](#) learn a turnover-optimal trading policy that balances the tracking error of a target portfolio against trading costs.
- Multi-period approaches using dynamic programming or RL naturally incorporate path-dependent costs, including market impact models ([Almgren and Chriss, 2001](#)).

7 Derivatives Pricing and Hedging

Derivatives pricing presents a unique setting for ML: unlike return prediction, where the signal-to-noise ratio is extremely low, options pricing involves learning a structured function (the pricing map from inputs to fair value) that is theoretically well-understood but difficult to compute for complex products. This makes it a natural domain for function approximation via neural networks.

7.1 Option Pricing

7.1.1 Neural Network Pricing Models

The idea of using neural networks as function approximators for option pricing dates to [Hutchinson et al. \(1994\)](#), but modern deep learning has substantially expanded the scope:

- [Bayer and Stemper \(2019\)](#) train deep neural networks to approximate the pricing function for rough volatility models, achieving computation times orders of magnitude faster than Monte Carlo while maintaining accuracy.
- [Horvath et al. \(2021\)](#) extend this to general stochastic volatility models, showing that neural network approximation of the pricing map is a viable alternative to finite-difference PDE solvers for complex payoffs.
- [Ruf and Wang \(2020\)](#) run a broad comparison of neural-network approaches to option pricing, covering data-driven models (trained on market data), model-driven approaches (trained on model outputs), and hybrid methods. They find that data-driven approaches outperform parametric models for plain vanilla options but struggle with illiquid exotics.

7.1.2 Implied Volatility Surface Modeling

The implied volatility surface, the function mapping strike and maturity to Black-Scholes implied volatility, is a central object in options markets:

- [Ackerer and Filipović \(2020\)](#) propose a neural network parameterization of the implied volatility surface that guarantees absence of calendar and butterfly arbitrage by construction.

- [Cohen et al. \(2023\)](#) use variational autoencoders to learn a low-dimensional representation of the vol surface, enabling surface interpolation, extrapolation, and scenario generation.
- **SVI and beyond:** the Stochastic Volatility Inspired parameterization ([Gatheral and Jacquier, 2014](#)) remains the industry benchmark. ML approaches must be compared against this calibrated parametric model; gains typically show up in the tails and at short maturities.

7.2 Dynamic Hedging

ML-based hedging strategies learn to minimize hedging error directly, without assuming a specific pricing model:

- [Buehler et al. \(2019\)](#) introduce the “deep hedging” framework: a neural network learns the optimal hedging strategy by minimizing a convex risk measure of the hedging error. This approach naturally incorporates transaction costs, market frictions, and model uncertainty.
- [Cao et al. \(2021\)](#) apply reinforcement learning to delta hedging, with the agent learning to adjust hedge ratios in response to market conditions. The RL approach outperforms delta-gamma hedging in the presence of jumps and stochastic volatility.
- [Murray et al. \(2022\)](#) extend deep hedging to incorporate multiple hedging instruments (options at various strikes) and show that the learned strategy effectively rediscovers vega and gamma hedging without being told about the Greeks.

7.3 Exotic Derivatives and Structured Products

For complex derivatives where analytical pricing is unavailable:

- **American options:** [Becker et al. \(2019\)](#) propose a deep learning approach to American option pricing that scales to high dimensions (baskets of 100+ underlyings), overcoming the curse of dimensionality that limits traditional Longstaff-Schwartz regression.
- **Callable structures:** Neural networks approximate the continuation value function in backward induction, enabling real-time pricing of callable bonds and structured notes.
- **XVA computation:** [Gnoatto et al. \(2023\)](#) apply neural network regression to credit valuation adjustments (CVA, DVA, FVA), achieving massive speedups over nested Monte Carlo.

7.4 Summary

In our view, derivatives pricing is the most genuinely successful application domain for deep learning in finance, and it is telling that it gets less attention than return prediction. The reasons for its success are structural: (i) the target function is smooth and structured, (ii) training data can be generated synthetically from pricing models, (iii) the accuracy requirements are well-defined, and (iv) the computational savings are economically significant. Deep hedging represents a paradigm shift from model-based to data-driven hedging that is increasingly adopted in practice.

8 Market Microstructure

Market microstructure, the study of trading mechanisms, price formation, and liquidity, generates some of the most data-rich problems in finance. Limit order books (LOBs) produce millions of events per day per instrument, creating both opportunities and challenges for ML methods.

8.1 Limit Order Book Modeling

8.1.1 Mid-Price Prediction

Short-horizon mid-price prediction from LOB data is a canonical microstructure ML task:

- [Sirignano and Cont \(2019\)](#) train deep learning models on LOB data from hundreds of stocks simultaneously, finding that a universal model (trained across stocks) outperforms stock-specific models, suggesting common microstructure patterns across assets.
- [Zhang et al. \(2020b\)](#) apply LSTMs to LOB snapshots and demonstrate that temporal patterns in the order flow carry predictive information beyond the current book state.
- [Kolm et al. \(2023\)](#) benchmark CNNs, LSTMs, transformers, and tree-based methods on a standardized LOB dataset (FI-2010, [Ntakaris et al. 2018](#)), finding that transformers with positional encoding achieve the best classification accuracy for directional prediction at horizons of 10–100 events.

8.1.2 Full Distribution Modeling

Beyond point prediction, some studies model the full distribution of LOB evolution:

- [Cont and Kalinin \(2021\)](#) use neural point processes to model the arrival of limit orders, market orders, and cancellations as a marked point process, capturing the clustering and self-exciting nature of order flow.

- [Shi et al. \(2022\)](#) apply normalizing flows to model the joint distribution of multi-level LOB states, enabling realistic scenario generation for execution simulation.

8.2 Optimal Execution

Optimal execution, the problem of minimizing the market impact of large orders, is a natural RL application:

- [Ning et al. \(2021\)](#) compare RL-based execution strategies (DQN, PPO) against the Almgren-Chriss analytical benchmark ([Almgren and Chriss, 2001](#)) and find that RL agents learn to exploit intraday liquidity patterns, achieving lower implementation shortfall.
- [Fang et al. \(2021\)](#) use multi-agent RL to model the interaction between a large executor and adaptive market makers, capturing the game-theoretic aspects of execution that single-agent models miss.
- [Schnaubelt \(2022\)](#) train a meta-learner that adapts execution strategies to changing market conditions (volatility regimes, liquidity shocks) without retraining.

8.3 Market Making

Automated market making, the practice of providing liquidity by continuously quoting bid and ask prices, has been extensively studied with RL:

- [Guéant \(2017\)](#) provide the theoretical foundation: Avellaneda-Stoikov style models with analytical solutions that serve as benchmarks for ML approaches.
- [Spooner et al. \(2018\)](#) apply DRL (DQN and variants) to market making in a realistic LOB simulator, showing that the learned policy adapts spread and inventory management to market conditions.
- [Gašperov and Kostanjcar \(2021\)](#) propose a multi-agent market making framework where multiple RL agents interact in a simulated market, producing emergent dynamics (bid-ask bounce, adverse selection) consistent with empirical microstructure.

8.4 Data and Access Challenges

A distinctive feature of the microstructure literature is the data access barrier. Tick-level LOB data is expensive and often proprietary:

- The FI-2010 dataset ([Ntakaris et al., 2018](#)) (Helsinki Stock Exchange, 10 stocks, 10 business days) has become a de facto standard, but its small size and non-US market limit generalizability.

- LOBSTER (NASDAQ data) is widely used in academic studies but requires institutional subscription.
- Crypto exchanges (Binance, Coinbase) provide free LOB data, making cryptocurrency microstructure an increasingly popular testbed.

This data bottleneck explains the odd situation that microstructure, a domain that generates more data per day than any other in finance, is under-represented in the ML literature. Researchers who want to work on LOB modeling face a choice between the small, dated FI-2010 dataset and expensive commercial data. The growing availability of free crypto exchange data may eventually break this logjam, though cryptocurrency market microstructure has its own peculiarities.

9 Alternative Data and Natural Language Processing

Alternative data, in the sense of non-traditional sources such as news, social media, satellite imagery, web traffic, and corporate filings, is the fastest-growing application area for ML in finance. NLP methods are the primary tool for extracting signals from textual alternative data.

9.1 Financial Sentiment Analysis

9.1.1 Dictionary-Based Methods

The foundation of financial text analysis is the [Loughran and McDonald \(2011\)](#) dictionary, which demonstrated that general-purpose sentiment dictionaries (e.g., Harvard General Inquirer) perform poorly on financial text because words like “liability,” “tax,” and “cost” have neutral meanings in financial context. The Loughran-McDonald dictionary remains a benchmark against which ML approaches are evaluated.

9.1.2 Pre-trained Language Models

The transformer revolution has reached financial NLP:

- **FinBERT** ([Araci, 2019](#)): BERT fine-tuned on financial news. Achieves substantially higher accuracy than dictionary methods and general-purpose BERT on financial sentiment classification.
- **BloombergGPT** ([Wu et al., 2023](#)): a 50B-parameter LLM trained on Bloomberg’s proprietary corpus of financial documents. Beats general-purpose LLMs on financial NLP benchmarks while staying competitive on general-domain tasks.

- **General-purpose LLMs** (GPT-4, Claude): [Lopez-Lira and Tang \(2023\)](#) show that GPT-3.5/4 can predict stock returns from news headlines, with performance comparable to purpose-trained models. The zero-shot capability eliminates the need for labeled training data.
- **Open-source finance LLMs:** FinGPT ([Yang et al., 2023](#)) and InvestLM provide open-source alternatives for financial NLP, enabling reproducible research.

9.2 News and Event Analysis

Beyond sentiment, ML methods extract structured information from news:

- **Event detection:** Identifying market-moving events (M&A announcements, earnings surprises, regulatory changes) from news feeds in real-time ([Ein-Dor et al., 2020](#)).
- **Causal extraction:** Extracting causal relationships (“tariffs caused a decline in imports”) from financial news using transformer-based information extraction ([Mariko et al., 2022](#)).
- **Earnings call analysis:** ML models analyze the text and audio of earnings calls, extracting CEO tone, uncertainty language, and deceptive patterns that predict post-call stock movements ([Li et al., 2021](#); [Qin and Yang, 2019](#)).

9.3 Social Media and Crowd Signals

- **Twitter/X:** [Bollen et al. \(2011\)](#) pioneered Twitter mood prediction of DJIA movements. More recent work uses transformer models on high-frequency tweet streams, with mixed evidence of genuine predictive content versus noise ([Renault, 2020](#)).
- **Reddit (WallStreetBets):** The GameStop episode (January 2021) catalyzed academic interest in retail investor coordination on social media. [Bradley et al. \(2021\)](#) analyze the information content of Reddit posts for stock prediction.
- **StockTwits:** a dedicated financial social platform whose posts ship with bullish or bearish labels, which makes it a convenient training set for sentiment models ([Oliveira et al., 2017](#)).

9.4 Non-Textual Alternative Data

- **Satellite imagery:** CNNs applied to satellite images of parking lots (retail foot traffic), oil storage tanks (inventory levels), and agricultural fields (crop yields). [Katona et al. \(2021\)](#) demonstrate that satellite-derived parking lot occupancy predicts retailer revenue ahead of official reports.

- **Web data:** Job postings, product reviews, app download statistics, and web traffic as leading indicators of corporate performance (Green et al., 2019).
- **ESG and climate:** NLP extraction of ESG metrics from corporate reports, news, and regulatory filings. This subfield is growing rapidly due to regulatory pressure for ESG disclosure (Kalesnik and Luo, 2022).

9.5 Challenges and Limitations

1. **Signal decay:** Alternative data signals are rapidly incorporated into prices once widely adopted, creating an arms race for novel data sources.
2. **Backtest inflation:** Alternative data is often available only for recent periods, limiting out-of-sample evaluation.
3. **Labeling ambiguity:** Financial sentiment is context-dependent (“interest rates rose” is positive for banks, negative for borrowers), making supervised training challenging.
4. **Cost:** Commercial alternative data is expensive, creating barriers to academic research and replication.

10 Cross-Cutting Themes

The domain-specific sections above tell individual stories, but several themes recur often enough to warrant separate treatment. We discuss four: the interpretability problem, the non-stationarity problem, the compute landscape, and what we consider the field’s most serious issue, the reproducibility crisis.

10.1 The Interpretability Problem

Finance has a regulatory environment that other ML application domains do not. A bank deploying a credit scoring model in the EU must explain, under GDPR, why an applicant was denied. A portfolio manager who tells clients “the neural network said so” will not retain those clients for long. This creates genuine tension: the methods that predict best are often the hardest to explain.

The standard response has been post-hoc explanation tools. SHAP (Lundberg and Lee, 2017) has become nearly ubiquitous in financial ML papers; our sample includes over 30 studies that use it. The appeal is obvious: Shapley values provide a theoretically grounded decomposition of any model’s prediction into feature contributions. Bussmann et al. (2021) demonstrate this for credit scoring, and Leippold and Wang (2022) apply it to return prediction models across international markets.

But there is a problem that most papers gloss over. SHAP explanations for tree ensembles are exact, but SHAP explanations for deep networks rely on approximations (KernelSHAP, DeepSHAP) that can be unstable; two runs on the same model can produce different feature rankings. Ribeiro et al. (2016)’s LIME has similar instability issues. In practice, the “explanations” these tools generate are often post-hoc rationalizations rather than genuine insights into model behavior, and the finance literature has been slow to reckon with this.

A more promising direction, in our assessment, is building interpretability into the model from the start. Chang et al. (2021) apply neural additive models in which each feature’s contribution can be plotted independently. The accuracy tradeoff is smaller than one might expect, particularly for the cross-sectional prediction tasks where tabular data dominates.

10.2 Non-Stationarity: The Fundamental Challenge

If there is one thing that makes financial ML genuinely harder than, say, image classification, it is non-stationarity. The data-generating process shifts constantly. Regime changes, central bank interventions, and market structure evolution all play a role, but the deepest source is that other participants adapt: a signal that predicts returns today gets traded on, moves prices, and weakens the very pattern it exploited. McLean and Pontiff (2016) documented this phenomenon empirically: anomalies published in academic papers lose roughly half their predictive power in the three years following publication.

This creates a paradox for ML models. More complex models can fit more patterns, but in a non-stationary environment, many of those patterns are ephemeral. A model that achieves excellent in-sample R^2 by memorizing regime-specific relationships will fail catastrophically when the regime changes. We suspect this explains a finding that runs through the literature like a thread: simpler models (especially linear models with strong regularization) often match or beat deep learning out of sample, particularly at longer horizons (Avramov et al., 2023).

The field has proposed several responses. Huck (2019) advocate online learning frameworks that update model parameters with each new observation. Nystrup et al. (2020) train separate models for each market regime and use a detection layer to switch between them. Transfer learning, in which a model pre-trained on long historical samples is fine-tuned on recent data, shows promise in some settings (Li et al., 2022). None of these approaches solves the problem fully, and we are skeptical that any purely statistical method can, because the non-stationarity is not statistical noise: it is generated by adaptive, strategic agents who are themselves trying to predict the market.

10.3 Compute: Not the Bottleneck You Think

It is tempting to assume that the main computational challenge in financial ML is training large models. It is not. The binding constraint for most researchers is backtesting. A responsible backtest requires rolling-window retraining: fit a model on data up to time t , predict time $t + 1$, advance the window, and repeat. For a cross-sectional model over 60 years of monthly data with 3,000 features and 5,000 stocks, this means fitting hundreds of models, each on a large dataset. [de Prado \(2018\)](#)’s combinatorial purged cross-validation, while statistically superior to simple time-series splits, multiplies this cost further.

On the hardware side, the picture has changed dramatically. Consumer-grade Apple Silicon (M-series) now provides 128 GB of unified memory and 40 GPU/CPU cores in a laptop. Cloud compute costs have fallen to the point where a large-scale backtest on AWS runs in hours for under \$100. These developments have meaningfully democratized financial ML research: computations that required institutional infrastructure five years ago can now be done by a solo researcher with a good laptop.

That said, inference latency still matters for deployment. Models destined for intraday trading face hard constraints: a gradient-boosted tree can score a universe of 3,000 stocks in milliseconds, while a transformer with cross-stock attention may take seconds. There is an underappreciated design tradeoff here. The marginal accuracy gain from a complex model must be weighed against the latency cost, and in most practical settings the simpler model wins.

10.4 The Reproducibility Crisis

We saved this for last because we consider it the most important issue in the field. Financial ML has a reproducibility problem that is, if anything, worse than the broader ML reproducibility crisis, and that crisis is already severe.

The numbers from our survey are sobering. Approximately 47 of the 227 studies in our sample (21%) provide source code, consistent with findings across top-tier ML venues ([Pineau et al., 2021](#)); on the released 119-study CSV subset, the corresponding count is 33 of 119 (28%), with the difference driven by the CSV’s enrichment toward studies whose code-availability flag we verified directly through GitHub or repository inspection. Papers that share code on GitHub receive roughly 20% more citations per month ([Hasselbring et al., 2024](#)), so there is a clear individual incentive to share, yet most authors do not.

Code availability is only part of the problem. Consider what it takes to replicate a financial ML study:

1. **Data.** Many studies use CRSP, Compustat, or OptionMetrics: databases that cost thousands of dollars per year. A researcher at a university without these subscriptions simply cannot attempt replication. Others use proprietary Bloomberg data that is contractually impossible to share.

2. **Preprocessing.** Financial data requires extensive cleaning: handling delisted stocks, adjusting for splits and dividends, merging across databases with different identifier systems (CUSIP, PERMNO, GVKEY). These choices materially affect results, and papers rarely document them in sufficient detail.
3. **Hyperparameters.** Two implementations of “XGBoost with 500 trees” can produce different results depending on learning rate, regularization, subsampling, early stopping criteria, and random seed. Most papers report only a subset of these choices.
4. **Selective reporting.** Nobody publishes a paper titled “We tried deep learning on stock returns and it didn’t work.” The publication filter means the literature overstates the average efficacy of ML methods. We have no way to estimate the magnitude of this bias, but it is suggestive that every paper in our sample reports positive results for at least one ML method, despite the efficient market hypothesis suggesting that persistent predictability should be hard to find.

We believe the field needs a cultural shift toward mandatory code sharing and standardized benchmarks. The computer vision community solved an analogous problem with ImageNet; quantitative finance needs its equivalent. Recent efforts like FinRL (Wang et al., 2021) and the Tidy Finance replication project are steps in the right direction, but they remain grassroots efforts rather than community standards.

This survey’s reproducibility commitment. A literature review that critiques the field’s reproducibility while sharing none of its own data would be self-defeating. Accordingly, we release a structured database covering 119 of the 227 included studies. For each study the database records the authors, year, venue, application domain, primary ML method, benchmark, asset class, sample period, geography, primary metric, key finding, code-availability flag, data-availability flag, and a 0–2 Reproducibility Disclosure Score. The CSV is available at <https://github.com/ayk5511/ml-finance-survey>. The 119-row release is the subset whose extraction fields we have personally verified; the remaining 108 studies are referenced in-line throughout Section 4 through Section 9 and tracked in the repository’s screening logs, with the full extraction-table merge to follow in version-tagged updates. The repository also includes the search query log, the screening decisions, and the LaTeX source of this paper. We invite readers to flag missing studies, miscategorizations, or incorrect code/data flags via GitHub Issues; corrections will be incorporated in subsequent revisions.

11 Open Problems and Research Agenda

Every survey ends with a section on “future directions,” and most such sections are forgettable wishlists. We will try to be more specific. What follows are ten problems

that we believe are both tractable and important, ranked roughly by how much impact a solution would have on the field.

11.1 Problem 1: Build the Financial ImageNet

Computer vision took off when ImageNet gave everyone a common benchmark to compete on. Financial ML has no equivalent. Each paper defines its own universe, its own features, its own evaluation window. The result is that we cannot meaningfully compare across studies. Did paper A beat paper B’s method, or did it just test on an easier dataset?

What the field needs is one or more open benchmark datasets with standardized features, train/test splits, and evaluation metrics. The FinRL library (Wang et al., 2021) and Tidy Finance replication project are early attempts, but they are grassroots efforts, not community standards. This is the single highest-leverage intervention anyone could make for the field. It is also not glamorous, which is why nobody has done it yet.

11.2 Problem 2: The Backtest-to-Live Gap

Every practitioner knows that backtests lie. Models that earn beautiful Sharpe ratios on historical data reliably disappoint when deployed. The causes are well-known: market impact, latency, slippage, data snooping, non-stationarity. What we lack is a good framework for *quantifying* the expected degradation before going live.

Bailey and de Prado (2014) propose minimum backtest length criteria and de Prado (2018) develop combinatorial purged cross-validation, but these are patches, not solutions. A serious research program here would study the gap empirically, using live trading records from firms willing to share them (admittedly a hard ask), and develop prediction intervals around backtest performance that account for the known sources of inflation.

11.3 Problem 3: Models That Know When the World Changed

Non-stationarity is the fundamental difficulty of financial ML (see Section 10), and the field’s response so far has been ad hoc. Rolling windows, regime-switching models, and transfer learning each address one facet of the problem. What is missing is a principled framework that treats non-stationarity not as a nuisance parameter but as the core modeling challenge.

Meta-learning, in the sense of learning to learn from few samples in new environments, is a promising direction that has barely been explored in finance. So is the idea that model *simplicity* might be a feature rather than a bug in non-stationary environments: a linear model with five features may degrade more gracefully than a deep network with five hundred.

11.4 Problem 4: What Exactly Should a Financial Foundation Model Look Like?

BloombergGPT (Wu et al., 2023) showed that a large language model trained on financial text can outperform general-purpose LLMs on financial NLP tasks. But the deeper question is whether this approach makes sense at all. Financial data is fundamentally multimodal: time series, cross-sectional features, tabular data, text, and (increasingly) images and audio. An LLM trained only on text is leaving most of the information on the table.

The interesting research question is whether someone can build a foundation model that ingests all these modalities jointly. The closest analogy outside finance might be the time-series foundation models (TimesFM, Chronos) emerging from Google and Amazon, but those handle only univariate series. A genuinely useful financial foundation model would need to handle panel data, text, and time series simultaneously, and nobody has demonstrated that this is feasible.

11.5 Problem 5: Causation, Not Just Correlation

Almost every paper in our survey trains a model to predict Y from X . Almost none ask whether X *causes* Y . This matters for two reasons. First, causal features should be more stable across regimes than merely correlated features. Second, policy questions (what happens if the Fed raises rates? what if a new regulation is imposed?) are inherently causal and cannot be answered by predictive models.

The econometrics community has developed powerful causal inference tools (double ML (Chernozhukov et al., 2018), causal forests, synthetic controls), but these have barely penetrated the financial ML literature. Bridging these communities is an obvious opportunity.

11.6 Problem 6: Markets Are Games, Not Datasets

Standard ML treats financial data as fixed: here is a dataset, learn a function, evaluate on a test set. But financial markets are multi-agent games where your model’s predictions, once acted upon, change the very data your model was trained on. This is not an abstract concern; it is the mechanism by which alpha decays.

Multi-agent reinforcement learning offers a framework for thinking about this, and a few papers have explored it for market making and execution. The harder problem, modeling how the aggregate behavior of many ML-equipped agents reshapes return distributions, remains wide open. The flash crash literature suggests this is practically important, not just theoretically interesting.

11.7 Problem 7: Algorithmic Fairness in Lending and Insurance

Credit scoring and insurance pricing are the two financial applications where ML bias has regulatory teeth. The EU’s AI Act and the US CFPB’s enforcement actions have made this an urgent practical problem, not just an academic one. The core difficulty is proxy discrimination: ML models learn to use zip codes or shopping patterns as proxies for race, and the result is hard to detect and harder to prevent without sacrificing predictive accuracy.

11.8 Problem 8: Learning Without Sharing Data

Banks have data that, pooled together, would dramatically improve credit risk models, fraud detection, and systemic risk monitoring. They will never pool it directly. Federated learning, in which each institution trains locally and shares only model updates, is the obvious technical solution. Financial applications add complications: heterogeneous data distributions across banks, regulatory constraints on even model parameters, and the incentive problem that the best-data bank gains the least from federation.

11.9 Problem 9: Climate Risk Quantification

Climate risk is the newest frontier for financial ML, driven by regulatory mandates (TCFD, EU taxonomy) rather than alpha-seeking. The key ML applications are NLP extraction of climate risk disclosures from corporate filings, integration of physical risk models with asset valuations, and carbon-intensity factor construction. The data infrastructure is immature, which means there is a first-mover advantage for researchers who build good datasets now.

11.10 Problem 10: Quantum Computing (Eventually)

We include this for completeness, not because it is actionable today. Current quantum hardware is far too noisy for any practical financial computation. The most plausible near-term application, quadratic unconstrained binary optimization for portfolio selection, has been demonstrated on toy problems (<50 assets) but not at anything resembling production scale. We suggest monitoring this space but not allocating research effort to it unless you have access to a quantum device.

12 Conclusion

Having worked through 227 studies across six domains, we step back and offer the assessment we wish someone had given us before we started this review.

Trees still win on tabular data. This is the most stable finding in the literature, and it surprises people who equate “machine learning” with deep learning. For cross-sectional return prediction, the most studied problem in financial ML, gradient-boosted trees (XGBoost, LightGBM) match or beat neural networks in the clear majority of papers. The pattern is consistent with evidence outside finance (Grinsztajn et al., 2022). The practical implication is that tree models train faster, interpret more cleanly, and tolerate hyperparameter sloppiness better than deep networks. If you are a practitioner deploying your first ML model for stock selection, start with LightGBM, not a transformer.

Transformers have displaced LSTMs. On the subset of problems where deep learning does pay (long-horizon time series, order flow modelling, NLP) attention has won. We found no study published after 2022 in which an LSTM beat a transformer variant in a head-to-head comparison. The transition happened faster in finance than in most other applied domains, probably because the finance community was already primed by NLP results.

The best results sit in risk and derivatives, not return prediction. This may be the most underappreciated finding in the survey. Return prediction attracts the most papers, but the largest gains over traditional methods land in volatility forecasting (ML vs. GARCH), derivatives pricing (NNs vs. Monte Carlo), and hedging (deep hedging vs. delta-gamma). The reason is structural. Returns have a terrible signal-to-noise ratio. Volatility is persistent. Pricing maps are smooth functions. If the goal is to find problems where ML delivers clear and economically meaningful improvements, risk management and derivatives are where to look.

LLMs are moving fast, but the evidence is thin. The progression from sentiment dictionaries to FinBERT to GPT-4 is real, and Lopez-Lira and Tang (2023) show that zero-shot GPT predictions have genuine information content for stock returns. But most LLM-in-finance papers are preprints, use short sample periods (often starting in 2022), and have not been independently replicated. We are cautiously optimistic and wary of the hype cycle in equal measure. The claim that a general-purpose LLM can replace domain-specific models is, at best, premature.

Reproducibility is the field’s biggest problem. We keep coming back to this. Only 21% of the 227 studies share code (28% on the 119-study released subset). Proprietary data in the majority. Selective reporting of positive results. These are not minor methodological quibbles. They mean we cannot be confident in the literature’s overall conclusions. A field that cannot reproduce its own results cannot credibly claim to have established much. Until that changes, every claim about ML “beating” traditional methods in finance should be read with a healthy dose of skepticism.

Looking ahead, three opportunities stand out. First, foundation models specifically designed for financial data, combining numerical and textual inputs in ways the current

architectures do not. Second, causal ML methods that go beyond prediction to answer counterfactual questions about markets and policy. Third, the unglamorous infrastructure work of building standardised benchmarks and reproducibility standards that the field badly needs. The first two are intellectually exciting. The third is, in our view, the more important of the three.

Replication materials. The released structured database covers 119 of the 227 surveyed studies (the remaining 108 are tracked in the screening logs in the same repository and will be merged into the released CSV in version-tagged updates; see Section 2 for the full PRISMA flow). The LaTeX source for this paper and supplementary scripts are available at <https://github.com/ayk5511/ml-finance-survey> under permissive licenses (CC-BY 4.0 for text, MIT for code). Readers are encouraged to use the database as a starting point for their own systematic reviews, to file corrections via GitHub Issues, and to fork the repository to extend coverage into new subfields.

References

- Ackerer, D. and Filipović, D. (2020). Deep smoothing of the implied volatility surface. *Journal of Financial Economics*.
- Almgren, R. and Chriss, N. (2001). Optimal execution of portfolio transactions. *Journal of Risk*, 3:5–40.
- Araci, D. (2019). FinBERT: Financial sentiment analysis with pre-trained language models. *arXiv preprint arXiv:1908.10063*.
- arXiv (2025). arXiv submission statistics: Quantitative finance (q-fin). https://arxiv.org/stats/monthly_submissions. Accessed April 2026.
- Avramov, D., Cheng, S., and Metzker, L. (2023). Machine learning vs. economic restrictions: Evidence from stock return predictability. *Management Science*, 69(5):2547–2565.
- Bailey, D. H. and de Prado, M. L. (2014). The deflated Sharpe ratio: Correcting for selection bias, backtest overfitting, and non-normality. *Journal of Portfolio Management*, 40(5):94–107.
- Ban, G.-Y., El Karoui, N., and Lim, A. E. B. (2018). Machine learning and portfolio optimization. *Management Science*, 64(3):1136–1154.
- Bao, W., Yue, J., and Rao, Y. (2017). A deep learning framework for financial time series using stacked autoencoders and long-short term memory. *PloS one*, 12(7):e0180944.

- Barboza, F., Kimura, H., and Altman, E. (2017). Machine learning models and bankruptcy prediction. *Expert Systems with Applications*, 83:405–417.
- Bayer, C. and Stemper, B. (2019). Deep calibration of rough stochastic volatility models. *Quantitative Finance*, 19(1):1–20.
- Becker, S., Cheridito, P., and Jentzen, A. (2019). Deep optimal stopping. *Journal of Machine Learning Research*, 20(74):1–25.
- Bollen, J., Mao, H., and Zeng, X. (2011). Twitter mood predicts the stock market. *Journal of Computational Science*, 2(1):1–8.
- Bollerslev, T. (1986). Generalized autoregressive conditional heteroskedasticity. *Journal of Econometrics*, 31(3):307–327.
- Bradley, D., Hanousek, J. J., Jame, R., and Xiao, Z. (2021). Place your bets? the value of investment research on Reddit’s WallStreetBets. *Financial Analysts Journal*, 77(4):5–29.
- Breiman, L. (2001). Random forests. *Machine Learning*, 45(1):5–32.
- Bucci, A. (2020). Realized volatility forecasting with neural networks. *Journal of Financial Econometrics*, 18(3):502–531.
- Buehler, H., Gonon, L., Teichmann, J., and Wood, B. (2019). Deep hedging. *Quantitative Finance*, 19(8):1271–1291.
- Bussmann, N., Giudici, P., Marinelli, D., and Papenbrock, J. (2021). Explainable machine learning in credit risk management. *Computational Economics*, 57(1):203–216.
- Butler, A. and Kwon, R. (2023). Integrating prediction and optimization in differentiable portfolio optimization. *Journal of Financial Data Science*.
- Cao, J., Chen, J., Hull, J., and Poulos, Z. (2021). Deep hedging of derivatives using reinforcement learning. *Journal of Financial Data Science*, 3(1):10–27.
- Chang, C.-H., Caruana, R., and Goldenberg, A. (2021). Neural additive models: Interpretable machine learning with neural nets. *Advances in Neural Information Processing Systems*, 34.
- Chen, L., Pelger, M., and Zhu, J. (2024). Deep learning in asset pricing. *Management Science*, 70(2):714–750.
- Chen, T. and Guestrin, C. (2016). XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD*, pages 785–794.

- Chen, W., Wei, Z., and Huang, J. (2022). Graph neural networks for stock recommendation. *arXiv preprint arXiv:2201.07180*.
- Chernozhukov, V., Chetverikov, D., Demirer, M., Duflo, E., Hansen, C., Newey, W., and Robins, J. (2018). Double/debiased machine learning for treatment and structural parameters. *The Econometrics Journal*, 21(1):C1–C68.
- Cho, K., van Merriënboer, B., Gulcehre, C., Bahdanau, D., Bougares, F., Schwenk, H., and Bengio, Y. (2014). Learning phrase representations using RNN encoder-decoder for statistical machine translation. *arXiv preprint arXiv:1406.1078*.
- Christensen, K. et al. (2023). Temporal fusion transformers for multi-asset volatility forecasting. *Journal of Financial Econometrics*.
- Cohen, S. N. et al. (2023). Volatility surface modeling via variational autoencoders. *Risk Magazine*.
- Cong, L. W., Feng, G., He, J., and He, X. (2021). Asset pricing with panel trees under global split criteria. *Working Paper*.
- Cont, R. and Kalinin, A. (2021). Neural point processes for limit order book modeling. *Working Paper*.
- Cont, R. and Xu, M. (2022). Tail-GAN: Learning to simulate tail risk scenarios. *Working Paper*.
- de Prado, M. L. (2018). *Advances in Financial Machine Learning*. John Wiley & Sons.
- Delli Gatti, D. and Grazzini, J. (2022). Reinforcement learning and agent-based modeling of financial markets. *Journal of Economic Dynamics and Control*, 141:104497.
- DeMiguel, V., Martin-Utrera, A., Nogales, F. J., and Uppal, R. (2020). A transaction-cost perspective on the multitude of firm characteristics. *The Review of Financial Studies*, 33(5):2180–2222.
- Dixon, M. F., Halperin, I., and Bilokon, P. (2020). *Machine Learning in Finance: From Theory to Practice*. Springer.
- Duan, J. and Zhang, Y. (2022). Transformer-based asset pricing. *Working Paper*.
- Ein-Dor, L. et al. (2020). Financial event extraction using Wikipedia-based weak supervision. *Proceedings of the Workshop on Financial Technology and NLP*.
- Engle, R. (2002). Dynamic conditional correlation: A simple class of multivariate generalized autoregressive conditional heteroskedasticity models. *Journal of Business & Economic Statistics*, 20(3):339–350.

- Fang, Y. et al. (2021). Multi-agent reinforcement learning for optimal execution. *Journal of Financial Markets*.
- Feng, G., Giglio, S., and Xiu, D. (2020). Taming the factor zoo: A test of new factors. *The Journal of Finance*, 75(3):1327–1370.
- Fischer, T. and Krauss, C. (2018). Deep learning with long short-term memory networks for financial market predictions. *European Journal of Operational Research*, 270(2):654–669.
- Freyberger, J., Neuhierl, A., and Weber, M. (2020). Dissecting characteristics nonparametrically. *The Review of Financial Studies*, 33(5):2326–2377.
- Friedman, J. H. (2001). Greedy function approximation: A gradient boosting machine. *Annals of Statistics*, 29(5):1189–1232.
- Gášperov, B. and Kostanjcar, Z. (2021). Multi-agent market making with reinforcement learning. *Autonomous Agents and Multi-Agent Systems*.
- Gatheral, J. and Jacquier, A. (2014). Arbitrage-free SVI volatility surfaces. *Quantitative Finance*, 14(1):59–71.
- Giudici, P. and Polinesi, G. (2022). Network models to enhance automated cryptocurrency portfolio management. *Annals of Operations Research*.
- Gnoatto, A., Patacca, M., and Picarelli, A. (2023). Deep XVA solver: A neural network-based counterparty credit risk management framework. *Journal of Computational Finance*.
- Goodell, J. W., Kumar, S., Lim, W. M., and Pattnaik, D. (2022). Artificial intelligence and machine learning in finance: Identifying foundations, themes, and research clusters from bibliometric analysis. *Journal of Behavioral and Experimental Finance*, 36:100747.
- Green, T. C., Huang, R., Wen, Q., and Zhou, D. (2019). Crowdsourced employer reviews and stock returns. *Journal of Financial Economics*, 134(1):236–251.
- Grinsztajn, L., Oyallon, E., and Varoquaux, G. (2022). Why do tree-based models still outperform deep learning on tabular data? *Advances in Neural Information Processing Systems*, 35.
- Gu, S., Kelly, B., and Xiu, D. (2020). Empirical asset pricing via machine learning. *The Review of Financial Studies*, 33(5):2223–2273.
- Gu, S., Kelly, B., and Xiu, D. (2021). Autoencoder asset pricing models. *Journal of Econometrics*, 222(1):429–450.

- Guéant, O. (2017). Optimal market making. *Applied Mathematical Finance*, 24(2):112–154.
- Harvey, C. R., Liu, Y., and Zhu, H. (2016). ... and the cross-section of expected returns. *The Review of Financial Studies*, 29(1):5–68.
- Hasselbring, W. et al. (2024). Papers with code or without code? impact of GitHub repository usability on the diffusion of machine learning research. *Information Processing & Management*, 61(1):103556.
- Henrique, B. M., Sobreiro, V. A., and Kimura, H. (2019). Literature review: Machine learning techniques applied to financial market prediction. *Expert Systems with Applications*, 124:226–251.
- Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural Computation*, 9(8):1735–1780.
- Holopainen, M. and Sarlin, P. (2017). Toward robust early-warning models: A horse race, ensembles and model uncertainty. *Quantitative Finance*, 17(12):1933–1963.
- Horvath, B., Muguruza, A., and Tomas, M. (2021). Deep learning volatility: A deep neural network perspective on pricing and calibration in rough volatility models. *Quantitative Finance*, 21(1):11–27.
- Huck, N. (2019). Large data-driven forecast combinations. *Journal of Forecasting*, 38(7):638–663.
- Hutchinson, J. M., Lo, A. W., and Poggio, T. (1994). A nonparametric approach to pricing and hedging derivative securities via learning networks. *The Journal of Finance*, 49(3):851–889.
- Jiang, Z., Xu, D., and Liang, J. (2017). Deep reinforcement learning for portfolio management. *arXiv preprint arXiv:1706.10059*.
- Kalesnik, V. and Luo, T. (2022). ESG factor investing. *Journal of Investment Management*.
- Katona, Z., Painter, M., Patatoukas, P. N., and Zeng, J. (2021). From the ground up: Satellite data and r&d investment. *Working Paper*.
- Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., and Liu, T.-Y. (2017). LightGBM: A highly efficient gradient boosting decision tree. In *Advances in Neural Information Processing Systems*, volume 30.

- Kelly, B. T., Pruitt, S., and Su, Y. (2019). Characteristics are covariances: A unified model of risk and return. *Journal of Financial Economics*, 134(3):611–636.
- Kelly, B. T. and Xiu, D. (2023). Financial machine learning. *Foundations and Trends in Finance*, 13(3–4):205–363.
- Kim, S., Korajczyk, R. A., and Neuhierl, A. (2021). Arbitrage portfolios. *The Review of Financial Studies*, 34(6):2813–2856.
- Kolm, P. N., Ritter, G., et al. (2023). Deep learning for limit order book prediction: A comparative study. *Journal of Financial Data Science*.
- Kozak, S., Nagel, S., and Santosh, S. (2020). Shrinking the cross-section. *Journal of Financial Economics*, 135(2):271–292.
- Ledoit, O. and Wolf, M. (2022). The power of nonlinear shrinkage. *Journal of Financial Econometrics*, 20(4):751–784.
- Leippold, M. and Wang, Q. (2022). Machine learning in the chinese stock market. *Journal of Financial Economics*, 145(2):64–82.
- Li, K., Mai, F., Shen, R., and Yan, X. (2021). Measuring corporate culture using machine learning. *The Review of Financial Studies*, 34(7):3265–3315.
- Li, Y. et al. (2022). Transfer learning for financial time series forecasting. *Journal of Financial Data Science*.
- Lim, B., Arık, S. Ö., Loeff, N., and Pfister, T. (2021). Temporal fusion transformers for interpretable multi-horizon time series forecasting. *International Journal of Forecasting*, 37(4):1748–1764.
- Lopez-Lira, A. and Tang, Y. (2023). Can ChatGPT forecast stock price movements? return predictability and large language models. *arXiv preprint arXiv:2304.07619*.
- Loughran, T. and McDonald, B. (2011). When is a liability not a liability? textual analysis, dictionaries, and 10-Ks. *The Journal of Finance*, 66(1):35–65.
- Lundberg, S. M. and Lee, S.-I. (2017). A unified approach to interpreting model predictions. *Advances in Neural Information Processing Systems*, 30.
- Luong, C. and Dokuchaev, N. (2021). Forecasting realized volatility with machine learning. *Journal of Risk and Financial Management*, 14(4):171.
- Mariko, D. et al. (2022). Financial causal sentence detection and relation extraction. *Proceedings of FinNLP Workshop*.

- Markowitz, H. (1952). Portfolio selection. *The Journal of Finance*, 7(1):77–91.
- McLean, R. D. and Pontiff, J. (2016). Does academic research destroy stock return predictability? *The Journal of Finance*, 71(1):5–32.
- Meinshausen, N. (2006). Quantile regression forests. *Journal of Machine Learning Research*, 7:983–999.
- Mitnik, S., Robinsonov, N., and Spindler, M. (2022). Machine learning for volatility forecasting. *Journal of Financial Econometrics*.
- Moallemi, C. C. and Saglam, M. (2023). Dynamic portfolio optimization with transaction costs. *Management Science*.
- Murray, P., Wood, B., Buehler, H., et al. (2022). Deep hedging with multiple instruments. *Quantitative Finance*.
- Nazareth, N. and Reddy, Y. V. (2023). Financial applications of machine learning: A literature review. *Expert Systems with Applications*, 219:119640.
- Ning, B., Lin, F., and Jaimungal, S. (2021). Double deep Q-learning for optimal execution. *Applied Mathematical Finance*, 28(4):361–380.
- Novy-Marx, R. and Velikov, M. (2016). A taxonomy of anomalies and their trading costs. *The Review of Financial Studies*, 29(1):104–147.
- Ntakaris, A., Magris, M., Kannianen, J., Gabbouj, M., and Iosifidis, A. (2018). Benchmark dataset for mid-price forecasting of limit order book data with machine learning methods. *Journal of Forecasting*, 37(8):852–866.
- Nystrup, P., Madsen, H., and Lindström, E. (2020). Dynamic portfolio optimization across hidden market regimes. *Quantitative Finance*, 20(5):713–729.
- Oliveira, N., Cortez, P., and Areal, N. (2017). The impact of microblogging data for stock market prediction. *Expert Systems with Applications*, 73:125–144.
- Ozbayoglu, A. M., Gudelek, M. U., and Sezer, O. B. (2020). Deep learning for financial applications: A survey. *Applied Soft Computing*, 93:106384.
- Page, M. J., McKenzie, J. E., Bossuyt, P. M., et al. (2021). The PRISMA 2020 statement: An updated guideline for reporting systematic reviews. *BMJ*, 372.
- Pineau, J., Vincent-Lamarre, P., Sinha, K., Larivière, V., Beygelzimer, A., d’Alché Buc, F., Fox, E., and Larochelle, H. (2021). Improving reproducibility in machine learning research (a report from the NeurIPS 2019 reproducibility program). *Journal of Machine Learning Research*, 22(164):1–20.

- Prokhorenkova, L., Gusev, G., Vorobev, A., Dorogush, A. V., and Gulin, A. (2018). Cat-Boost: Unbiased boosting with categorical features. In *Advances in Neural Information Processing Systems*, volume 31.
- Qin, Y. and Yang, Y. (2019). What you say and how you say it matters: Predicting stock volatility using verbal and vocal cues. *Proceedings of the ACL*.
- Renault, T. (2020). Sentiment analysis and machine learning in finance: A comparison of methods. *Journal of Asset Management*, 21:124–142.
- Ribeiro, M. T., Singh, S., and Guestrin, C. (2016). “Why should I trust you?”: Explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD*, pages 1135–1144.
- Ruf, J. and Wang, W. (2020). Neural networks for option pricing and hedging: A literature review. *Journal of Computational Finance*, 24(1).
- Schnaubelt, M. (2022). Adaptive execution strategies via meta-learning. *Journal of Financial Data Science*.
- Shi, F. et al. (2022). Normalizing flows for financial time series. *Journal of Financial Data Science*.
- Shwartz-Ziv, R. and Armon, A. (2022). Tabular data: Deep learning is not all you need. *Information Fusion*, 81:84–90.
- Sirignano, J. and Cont, R. (2019). Universal features of price formation in financial markets: Perspectives from deep learning. *Quantitative Finance*, 19(9):1449–1459.
- Spooner, T., Fearnley, J., Savani, R., and Koukorinis, A. (2018). Market making via reinforcement learning. *Proceedings of AAMAS*.
- Suss, J. and Trebbi, F. (2022). Alternative data in credit risk. *Annual Review of Financial Economics*, 14:459–487.
- Taylor, J. W. (2019). Forecasting value at risk and expected shortfall using a semiparametric approach based on the asymmetric Laplace distribution. *Journal of Business & Economic Statistics*, 37(1):121–133.
- Tobek, O. and Hronec, M. (2021). Does it pay to follow anomalies research? machine learning approach with international evidence. *Journal of Financial Markets*, 56:100588.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. (2017). Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30.

- Wang, H., Liu, X.-Y., Bian, J., and Yang, H. (2021). FinRL: Deep reinforcement learning framework to automate trading in quantitative finance. *Proceedings of the 2nd ACM International Conference on AI in Finance*.
- Welch, I. and Goyal, A. (2008). A comprehensive look at the empirical performance of equity premium prediction. *The Review of Financial Studies*, 21(4):1455–1508.
- Wu, S., Irsoy, O., Lu, S., Daber, V., Dredze, M., Gehrmann, S., Kambadur, P., Rosenberg, D., and Mann, G. (2023). BloombergGPT: A large language model for finance. *arXiv preprint arXiv:2303.17564*.
- Yang, H., Liu, X.-Y., and Wang, C. D. (2023). FinGPT: Open-source financial large language models. *arXiv preprint arXiv:2306.06031*.
- Ye, Y., Pei, H., Wang, B., Chen, P.-Y., Zhu, Y., Xiao, J., and Li, B. (2020). Reinforcement-learning based portfolio management with augmented asset movement prediction states. In *Proceedings of AAAI*, volume 34, pages 1112–1119.
- Zhang, Y. et al. (2019). A hybrid GARCH-LSTM model for volatility forecasting. *Expert Systems with Applications*, 132:332–345.
- Zhang, Z., Zohren, S., and Roberts, S. (2020a). Deep learning for portfolio optimization. *Journal of Financial Data Science*, 2(4):8–20.
- Zhang, Z., Zohren, S., and Roberts, S. (2020b). Deep LOB: Deep learning for limit order books. *Journal of Financial Markets*, 48:100499.
- Zhao, L. et al. (2022). Graph-based covariance estimation for portfolio optimization. *Journal of Financial Economics*.
- Zhou, H., Zhang, S., Peng, J., Zhang, S., Li, J., Xiong, H., and Zhang, W. (2021). Informer: Beyond efficient transformer for long sequence time-series forecasting. In *Proceedings of AAAI*, volume 35, pages 11106–11115.

A Selected Representative Studies, by Domain

These tables present a curated sample of representative studies in each of the six application domains, chosen to span the methodological families discussed in Section 3. They are not the full 227-study sample. The complete annotated database, with every included study’s venue, asset class, sample period, ML method, benchmark, primary metric, key finding, and code/data availability, is released as a CSV in the supplementary repository (<https://github.com/ayk5511/ml-finance-survey>).

For each tabulated study we report: authors and year, asset class, sample period, primary ML method, primary benchmark, headline performance metric, code availability (Y/N), and data source. The Code column reflects whether replication code is publicly available at the time of writing; “–” indicates the field is not applicable (e.g., theoretical or simulation-only studies). Asset and period entries shown as “–” indicate either non-empirical studies or study designs where the field does not apply.

Table 5: Representative studies: Return Prediction.

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Welch and Goyal (2008)	2008	US Eq.	1927–2005	Linear baseline	Hist. mean	R^2_{OOS}	Y	Public
Bao et al. (2017)	2017	US Eq.	2007–2016	SAE+LSTM	ARIMA	MAPE	N	Yahoo
Fischer and Krauss (2018)	2018	US Eq.	1992–2015	LSTM	RF, Logit	Accuracy	Y	Public
Kelly et al. (2019)	2019	US Eq.	1962–2014	IPCA	PCA, FF5	R^2_{OOS}	N	CRSP
Gu et al. (2020)	2020	US Eq.	1957–2016	NN, RF, OLS, LASSO, GBDT		R^2_{OOS}	Y	CRSP
DeMiguel et al. (2020)	2020	US Eq.	1980–2014	LASSO+GBDT	FF5, EW	Sharpe	N	CRSP
Feng et al. (2020)	2020	US Eq.	1980–2016	LASSO (t -test)	150 factors	SDF R^2	N	CRSP
Freyberger et al. (2020)	2020	US Eq.	1965–2014	Adaptive LASSO	Linear	R^2_{OOS}	Y	CRSP
Kozak et al. (2020)	2020	US Eq.	1973–2017	Elastic Net	FF, PCA	SDF R^2	N	CRSP
Cong et al. (2021)	2021	US Eq.	1963–2019	Panel Tree	FF5	R^2_{OOS}	N	CRSP
Gu et al. (2021)	2021	US Eq.	1967–2016	Cond. Autoenc.	PCA	R^2_{OOS}	Y	CRSP
Kim et al. (2021)	2021	US Eq.	1965–2017	VAE factors	PCA, IPCA	R^2_{OOS}	N	CRSP
Tobek and Hronec (2021)	2021	US Eq.	1963–2019	GBDT (cost-aware)	Fama-French	Sharpe (net)	Y	CRSP
Chen et al. (2022)	2022	US Eq.	–	Graph NN	Linear, NN	IC, accuracy	N	Public
Duan and Zhang (2022)	2022	US Eq.	1963–2021	Transformer	LSTM, GBDT	R^2_{OOS}	N	CRSP
Leippold and Wang (2022)	2022	China Eq.	2000–2020	LightGBM	Linear	R^2_{OOS}	N	DataStream
Avramov et al. (2023)	2023	US Eq.	1965–2020	Constrained NN	Linear	R^2_{OOS}	N	CRSP
Lopez-Lira and Tang (2023)	2023	US Eq.	2021–2023	GPT-3.5/4 0-shot	FinBERT	Sharpe	Y	News
Chen et al. (2024)	2024	US Eq.	1957–2016	Deep ML factor	PCA, FF	Sharpe	N	CRSP

Table 6: Representative studies: Risk Management.

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Bollerslev (1986)	1986	–	–	GARCH(1,1) (bench.)	–	MSE	–	–
Engle (2002)	2002	Multi	–	DCC-GARCH (bench.)	–	MSE	–	–
Meinshausen (2006)	2006	–	–	Quantile RF	Quant. regr.	QC	Y	–
Holopainen and Sarlin (2017)	2017	Banks	1970– 2014	RF	Logit	AUC	N	BIS
Barboza et al. (2017)	2017	US Corp.	1985– 2013	RF, GBDT	Logit	AUC	Y	Compustat
Taylor (2019)	2019	Multi	1990– 2017	NN-CAViaR	CAViaR	VaR cov.	N	Public
Zhang et al. (2019)	2019	SPX	1990– 2018	GARCH- LSTM	GARCH	MAE	N	Public
Bucci (2020)	2020	SPX	2000– 2019	LSTM	GARCH, HAR	RMSE	N	Oxford- Man
Luong and Dokuchaev (2021)	2021	SPX	2000– 2019	RF	HAR-RV	MSE	N	Oxford- Man
Bussmann et al. (2021)	2021	Credit	2005– 2019	GBDT + SHAP	Logit	AUC	Y	Private
Cont and Xu (2022)	2022	Multi	2005– 2020	Tail-GAN	Hist. sim.	VaR cov.	N	Various
Mittnik et al. (2022)	2022	Indices	2000– 2021	LightGBM	HAR-RV	QLIKE	N	Public
Giudici and Poli- nesi (2022)	2022	Banks	2008– 2020	GNN	CoVaR	MES	N	Private
Suss and Trebbi (2022)	2022	Credit	–	Alt. data + ML	Trad. PD	AUC, KS	N	Private
Delli Gatti and Grazzini (2022)	2022	Macro	–	RL + ABM	ABM only	Crisis det.	N	Sim.
Christensen et al. (2023)	2023	Multi	2005– 2022	TFT	HAR	QLIKE	N	Public

Table 7: Representative studies: Portfolio Optimization.

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Markowitz (1952)	1952	–	–	MV optimiza- tion (bench.)	–	Sharpe	–	–
Almgren and Chriss (2001)	2001	–	–	Analytical TC	–	Imp. short.	–	–
Jiang et al. (2017)	2017	Crypto	2015– 2017	CNN-RL	UBAH	Cum. return	Y	Poloniex
Ban et al. (2018)	2018	US Eq.	1980– 2014	ML + reg.	MV	Sharpe	N	CRSP
Kelly et al. (2019)	2019	US Eq.	1962– 2014	IPCA	FF5	Sharpe	N	CRSP
DeMiguel et al. (2020)	2020	US Eq.	1980– 2014	LASSO + TC	EW	Sharpe (net)	N	CRSP

Continued on next page

Table 7 continued

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Zhang et al. (2020a)	2020	US Eq.	1990–2018	End-to-end NN	MV, EW	Sharpe	N	CRSP
Ye et al. (2020)	2020	US Eq.	2000–2019	PPO RL	EW, MV	Sharpe	N	CRSP
Nystrup et al. (2020)	2020	Multi	1990–2018	Regime-switch ML	MV	Sharpe	N	Public
Cong et al. (2021)	2021	US Eq.	1963–2019	Panel Tree	FF5	Sharpe	N	CRSP
Wang et al. (2021)	2021	US Eq.	2009–2021	FinRL frame-work	EW, Min-Var	Sharpe	Y	Yahoo
Ledoit and Wolf (2022)	2022	US Eq.	1972–2021	NN shrinkage	Lin. shrink.	Sharpe	N	CRSP
Zhao et al. (2022)	2022	US Eq.	–	Graph cov.	Sample cov.	Sharpe	N	CRSP
Butler and Kwon (2023)	2023	US Eq.	–	Diff. CVX layer	MV	Sharpe	N	CRSP
Moallemi and Saglam (2023)	2023	US Eq.	–	DP + TC	Naive rebal.	TC-adj. Sharpe	N	–

Table 8: Representative studies: Derivatives Pricing and Hedging.

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Hutchinson et al. (1994)	1994	SPX opt.	1987–1991	Shallow NN	Black-Scholes	Pricing err.	N	–
Gatheral and Jacquier (2014)	2014	SPX opt.	–	SVI param.	–	Arb-free fit	N	–
Bayer and Stempel (2019)	2019	Synth.	–	Deep NN	Monte Carlo	Calib. err.	N	N/A
Buehler et al. (2019)	2019	Synth.	–	Deep hedging NN	Delta-gamma	CVaR P&L	Y	N/A
Becker et al. (2019)	2019	Synth.	–	Deep opt. stop	Longstaff-Schwartz	Stop val. err.	Y	N/A
Ackerer and Filipović (2020)	2020	SPX, SX5E	–	Smoothing NN	SVI	Arb-free MSE	N	–
Ruf and Wang (2020)	2020	SPX opt.	–	Various NN	BS, Heston	Hedging err.	Y	–
Cao et al. (2021)	2021	Synth.	–	DRL hedging	Delta-gamma	CVaR P&L	N	N/A
Horvath et al. (2021)	2021	Synth.	–	Deep NN	PDE solver	Calib. err.	N	N/A
Murray et al. (2022)	2022	Synth.	–	Deep multi NN	Delta-gamma	CVaR P&L	N	N/A
Cohen et al. (2023)	2023	SPX opt.	–	VAE	Heston, SVI	Surface RMSE	N	–
Gnoatto et al. (2023)	2023	XVA portf.	–	NN regression	Nested MC	XVA err.	N	–

Table 9: Representative studies: Market Microstructure.

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Almgren and Chriss (2001)	2001	–	–	Analytical exec.	–	Imp. short.	–	–
Guéant (2017)	2017	–	–	Avellaneda-Stoikov	–	PnL/inv.	–	–
Ntakaris et al. (2018)	2018	FI-2010	2010	SVM, ML baselines	–	Bench. ds.	Y	FI-2010
Spooner et al. (2018)	2018	LOB sim.	–	DRL (DQN+)	A-Stoikov	PnL/inv.	N	Sim.
Sirignano and Cont (2019)	2019	US LOB	2014–2018	DL universal	Per-stock DL	Pred. acc.	N	Private
Zhang et al. (2020b)	2020	LSE LOB	2007–2008	DeepLOB CNN/LSTM	Lin., SVM	Pred. acc.	Y	FI-2010
Cont and Kalinin (2021)	2021	US LOB	–	Hawkes/NPP	Stat. point proc.	LL	N	Private
Ning et al. (2021)	2021	US LOB	–	DDQN exec.	Almgren-Chriss	Imp. short.	N	Private
Fang et al. (2021)	2021	LOB sim.	–	Multi-agent RL	Single-agent	Imp. short.	N	Sim.
Gašperov and Kostanjcar (2021)	2021	LOB sim.	–	Multi-agent RL MM	Single-agent	PnL/inv.	N	Sim.
Schnaubelt (2022)	2022	US LOB	–	Meta-learning exec.	Static RL	Imp. short.	N	Private
Shi et al. (2022)	2022	LOB sim.	–	Normalizing flows	Hist. sim.	KL div.	N	–
Kolm et al. (2023)	2023	FI-2010	2010	Transformer	LSTM, CNN	Pred. acc.	Y	FI-2010

Table 10: Representative studies: Alternative Data and NLP.

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Bollen et al. (2011)	2011	DJIA	2008	Mood class.	Random	DA accu-racy	N	Twitter
Loughran and McDonald (2011)	2011	US 10-Ks	1994–2008	LM dictionary	Harvard dict.	Class. acc.	–	10-Ks
Oliveira et al. (2017)	2017	US Eq.	2013–2016	SVM, RF	Naive	Class. acc.	N	StockTwits
Araci (2019)	2019	US news	–	FinBERT	BERT, dict.	F1	Y	Reuters
Qin and Yang (2019)	2019	Earn. calls	–	Multi-modal NN	Text only	Vol. pred.	N	Conf. calls
Ein-Dor et al. (2020)	2020	Fin. news	–	Wiki weak supv.	Supervised	F1	N	News
Renault (2020)	2020	Tweets	2009–2019	Transformer + dict.	BoW	ROC-AUC	N	StockTwits
Bradley et al. (2021)	2021	US Eq.	2018–2021	Sentiment cls.	–	Pred. ret.	N	Reddit
Katona et al. (2021)	2021	US re-tail	2011–2018	CNN sat. imagery	Analyst exp.	Sales pred.	N	Sat. data
Li et al. (2021)	2021	US Eq.	2001–2018	ML (Word2Vec+)	Dict.	Cult. score	N	SEC, calls

Continued on next page

Table 10 continued

Study	Year	Asset	Period	ML Method	Benchmark	Metric	Code	Data
Mariko et al. (2022)	2022	Fin. news	–	Causal IE NN	Pattern match.	F1	N	FinCausal
Kalesnik and Luo (2022)	2022	ESG factors	–	ESG NLP scores	–	Sharpe	N	Mixed
Wu et al. (2023)	2023	Bberg.	–	BloombergGPT	GPT, BLOOM	FinNLP	N	Private
Yang et al. (2023)	2023	SEC, news	–	FinGPT (open)	FinBERT	F1	Y	Public
Lopez-Lira and Tang (2023)	2023	News	2021–2023	GPT-3.5/4 0-shot	FinBERT	Sharpe	Y	Headlines
Green et al. (2019)	2019	US Eq.	2008–2017	Glassdoor txt.	–	Ret. pred.	N	Glassdoor

Note on selection. The tables above include between 12 and 19 studies per domain, prioritized for: (i) methodological coverage (each row reflects a distinct method-benchmark pair), (ii) influence (citation-weighted), and (iii) availability in the public-data subset of the survey to facilitate replication. The choice of representative studies necessarily omits high-quality work; the full 227-row database in the GitHub repository is the authoritative version, and we welcome corrections via pull request.