

DIGITAL DEPTH GAUGES WITH ROUND DEPTH BAR



MEASURE DEPTH OF
SMALL HOLES (>Ø4mm)

DATA
OUTPUT

MEASURE WIDTH AND DEPTH
OF GROOVES INSIDE BORE

- Non waterproof
- Resolution: 0.01mm/0.0005"
- Supplied with three interchangeable points (flat, spherical, disk)
- Buttons: on/off, set, mm/inch, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel
- Optional accessory: extension base
(code 6141, for 1148-120, 1148-120WL,
1148-200, 1148-200WL, 1148-300 and 1148-300WL)





1148-100S



1148-120



1148-200



With data interface (optional wireless transmitter code 7315-1148, receiver is needed page 7)

Code	Range *	Accuracy **	L	d	Remark
1148-100S	0-100mm/0-4"	±0.02mm	200mm	45mm	
1148-100	0-100mm/0-4"	±0.02mm	200mm	85mm	
1148-120	0-120mm/0-4.7"	±0.03mm	300mm	101mm	one-hand use, with mounting holes for extension base
1148-200	0-200mm/0-8"	±0.03mm	300mm	101mm	with mounting holes for extension base
1148-300	0-300mm/0-12"	±0.03mm	400mm	101mm	with mounting holes for extension base

one-hand use of 1148-120
and 1148-120WL



extension base for 1148-120,
1148-120WL, 1148-200, 1148-200WL,
1148-300 and 1148-300WL (optional)



Built-in wireless (receiver code 7315-2/3/6/7/8/9 is needed)


Code	Range *	Accuracy **	L	d	Remark
1148-100SWL	0-100mm/0-4"	±0.02mm	200mm	45mm	
1148-100WL	0-100mm/0-4"	±0.02mm	200mm	85mm	
1148-120WL	0-120mm/0-4.7"	±0.03mm	300mm	101mm	one-hand use, with mounting holes for extension base
1148-200WL	0-200mm/0-8"	±0.03mm	300mm	101mm	with mounting holes for extension base
1148-300WL	0-300mm/0-12"	±0.03mm	400mm	101mm	with mounting holes for extension base

* When disk points are used, the range is reduced by 10mm

** When disk points are used, the accuracy increases by 0.01mm

OPTIONAL DISK POINTS

Code	Description	H	Remark
1148-P101	0.5mm disk point	0.5±0.005mm	for narrow grooves
1148-P102	0.7mm disk point	0.7±0.005mm	for narrow grooves
1148-P103	1mm disk point	1±0.005mm	for grooves inside blind hole
1148-P104	0.5mm disk point	0.5±0.005mm	for grooves inside blind hole



1148-P101
(optional)

1148-P101
and 1148-P102

1148-P103
and 1148-P104