

- NLP - Paper Review - Sequence to Sequence Learning with Neural Networks

Ayoub Youssoufi, Yassin El Hajj Chéhade

February 10th, 2023

Table of Contents

1. Introduction

2. Model description

3. Experimental results

4. Model analysis

5. Conclusion

Introduction



Deep Neural Network (DNN) are extremely powerful models. However, they have some limitations:

- can only map vectors to vectors with fixed dimensionality
- cannot map sequences to sequences
- learning to map sequences to sequences is important
 - Machine Translation
 - Speech Recognition
 - Image caption generation
 - Many other interesting tasks

The goal of this paper : Solve the sequence to sequence problems

Can we use RNN ?

- Have a one-to-one correspondence between the input and the outputs
- have trouble learning "long-term dependencies"
 - Vanishing gradient problem: use of LSTM
 - Exploding gradient problem : Gradient clipping



Long-Short-Term-Memory (LSTM) is a certain RNN architecture that has no vanishing gradient $\Pr(Y_1, \dots, Y_T \mid X_1, \dots, X_q) = \prod_{q=1} \Pr(Y_q \mid v, Y_1, \dots, Y_{q-1})$

Table of Contents

1. Introduction

2. Model description

3. Experimental results

4. Model analysis

5. Conclusion

Main idea:

- Have an LSTM first read the input sequence
- Produce the output sequence




Figure: model reads an input sentence “ABC” and produces “WXYZ” as the output sentence.

Big Dataset:

The architecture :

- WMT'14 English to French
- 340M french words
- 303M English words
- 160K input words and 80K output words
- 4 layers of LSTMs

The learning parameters :

- batch_size = 128
- initialized LSTM: uniform distribution between -0.08 and 0.08
- learning rate is halved every 0.5 epoch /5epochs
- using Parallelization with 8 GPUs ...

Objective function

An experiments involved training a large deep LSTM. Trained by maximizing the objective function :

$$\frac{1}{|\mathcal{S}|} \sum_{(T,S) \in \mathcal{S}} \log p(T|S)$$

$$\hat{T} = \arg \max_T p(T|S)$$

- T: Target sentence
- S: Input sentence

Reverse the input of the input sentence when mapping to the output. (abc mapped to XYZ will be bca to XYZ)

Table of Contents

1. Introduction

2. Model description

3. Experimental results

4. Model analysis

5. Conclusion

Experimental results:

Method	test BLEU score (ntst14)
Bahdanau et al. [2]	28.45
Baseline System [29]	33.30
Single forward LSTM, beam size 12	26.17
Single reversed LSTM, beam size 12	30.59
Ensemble of 5 reversed LSTMs, beam size 1	33.00
Ensemble of 2 reversed LSTMs, beam size 12	33.27
Ensemble of 5 reversed LSTMs, beam size 2	34.50
Ensemble of 5 reversed LSTMs, beam size 12	34.81

Figure: The performance of the LSTM on WMT'14 English to French test set (ntst14). Note that an ensemble of 5 LSTMs with a beam of size 2 is cheaper than of a single LSTM with a beam of size 12.

Table of Contents

1. Introduction

2. Model description

3. Experimental results

4. Model analysis

5. Conclusion

Model analysis 1





Figure: The figure shows a 2-dimensional PCA projection of the LSTM hidden states that are obtained after processing the phrases in the figures. The phrases are clustered by meaning, which in these examples is primarily a function of word order, which would be difficult to capture with a bag-of-words model. Notice that both clusters have similar internal structure

Model analysis 2





Figure: The left plot shows the performance of our system as a function of sentence length. The right plot shows the LSTM's performance on sentences with progressively more rare words.

Table of Contents

1. Introduction

2. Model description

3. Experimental results

4. Model analysis

5. Conclusion

Conclusion

- Seq2Seq based on LSTM outperforms standard SMT.
- Reversing the order of words in the source sentence improves the performance.
- LSTM performs well in very long sentences.

Critic

Pros

- Well structured, clear

Limits

- reliance to left-to-right beam search decoder which may not be optimal for all the languages.
- Focus only in the single language pair (English-French) and not cross-lingual translation.
- The lack of exploration of other NLP tasks to validate the robustness of the model.

Questions

Thank you for your attention!