
MOHAMMED V UNIVERSITY IN RABAT
Faculty of Sciences





Computer Science Department

Master of Science in Intelligent Processing Systems

PROJECT REPORT

COMPUTER VISION

Title :

Real-Time Smart Food Scanner for Type 1 Diabetes Management

Presented by:

AYOUB ALRHOULI

FATIMA ZAHRA KABBAB

Pr. Fatima Ezzahra ZIANI Faculty of Sciences – Rabat *Supervisor*

Academic Year 2025–2026

Abstract

This project presents CarboScan Vision, a real-time smart food scanner designed to assist individuals with Type 1 Diabetes in managing carbohydrate intake. The system uses computer vision techniques to detect and decode food barcodes through a live camera feed.

After detecting a barcode, the application retrieves nutritional information from the OpenFoodFacts database using a web API. The carbohydrate content is analyzed and classified into three categories: low, medium, and high. Based on a user-defined carbohydrate target per meal, the system calculates the recommended maximum portion size.

The application is implemented in Python, using OpenCV for image processing, Pyzbar for barcode detection, Tkinter for the graphical user interface, and JSON storage for data persistence.

Experimental results show that the system achieves reliable detection performance under different lighting conditions while maintaining real-time responsiveness.

This project demonstrates how computer vision can support diabetes self-management by providing fast and practical nutritional information.

Keywords: Computer Vision, Barcode Detection, Diabetes Management, OpenFoodFacts, Python

Résumé

Ce projet présente CarboScan Vision, un système intelligent de reconnaissance alimentaire en temps réel destiné à aider les personnes atteintes de diabète de type 1 à gérer leur consommation de glucides.

Le système utilise des techniques de vision par ordinateur pour détecter et décoder les codes-barres alimentaires à partir d'un flux vidéo en temps réel.

Après la détection du code-barres, l'application récupère les informations nutritionnelles depuis la base de données OpenFoodFacts à l'aide d'une interface API. La teneur en glucides est ensuite analysée et classée en trois catégories : faible, moyenne et élevée. En fonction d'un objectif de glucides défini par l'utilisateur, le système calcule la portion maximale recommandée.

L'application est développée en Python en utilisant OpenCV pour le traitement d'image, Pyzbar pour la détection des codes-barres, Tkinter pour l'interface graphique et un fichier JSON pour le stockage des données.

Les résultats expérimentaux montrent que le système offre de bonnes performances de détection tout en conservant un fonctionnement en temps réel.

Mots clés : Vision par ordinateur, Code-barres, Diabète, OpenFoodFacts, Python

Contents

Abstract i

Résumé ii

List of Acronyms v

Introduction vi

1 Problem Statement Objectives 1
- 1.1 Problem Statement . . . 1
- 1.2 Challenges . . . 1
- 1.3 Aim of the Project . . . 1

2 System Architecture 2
- 2.1 Overall Architecture . . . 2
- 2.2 Module Description . . . 3
  - 2.2.1 Image Acquisition Module . . . 3
  - 2.2.2 Preprocessing Module . . . 3
  - 2.2.3 Barcode Detection Module . . . 4
  - 2.2.4 Product Information Retrieval Module . . . 4
  - 2.2.5 Nutritional Classification Module . . . 4
  - 2.2.6 Recommendation and Graphical User Interface Module . . . 4
  - 2.2.7 Data Persistence Module . . . 5

3 Methodology 6
- 3.1 Data Source . . . 6
- 3.2 Preprocessing . . . 6
- 3.3 Detection & Decoding . . . 7
- 3.4 API Integration . . . 7
- 3.5 User Interface . . . 8

4 Implementation 9
- 4.1 Programming Environment . . . 9
- 4.2 Key Code Components . . . 9
  - 4.2.1 CarboScanApp Class . . . 9
  - 4.2.2 Threading Architecture . . . 10
  - 4.2.3 Data Persistence . . . 10

5 Experiments & Results **11**
5.1 Test Conditions 11
5.1.1 Hardware Configuration 11
5.1.2 Test Scenarios 11
5.2 Evaluation Metrics 11
5.3 Results and Observations 12
5.3.1 Detection Performance 12
5.3.2 Key Findings 12
5.3.3 Challenges and Limitations 12
5.3.4 Future Improvements 13

Conclusion **14**

Bibliography **15**

List of Acronyms

Acronym	Meaning
API	Application Programming Interface
ROI	Region of Interest
GUI	Graphical User Interface
JSON	JavaScript Object Notation
FPS	Frames Per Second
HTTP	Hypertext Transfer Protocol
RGB	Red, Green, Blue Color Model
BGR	Blue, Green, Red Image Format
CV	Computer Vision
T1D	Type 1 Diabetes
CC	Carbohydrate Counting
UI	User Interface

Introduction

Type 1 diabetes (T1D) is a long-term disease in which the pancreas does not produce enough insulin. Insulin is a hormone that helps glucose, the main source of energy from food, enter the body's cells. In T1D, the immune system attacks and destroys the insulin-producing cells in the pancreas. As a result, glucose stays in the blood instead of going into the cells, causing high blood sugar levels and serious health problems. The exact cause of this immune attack is not fully known, but it may be linked to genetics or environmental factors, such as certain viruses or diet. T1D is not caused by eating too much sugar [1].

The first signs of T1D usually appear quickly. Common symptoms include frequent urination and intense thirst because high blood sugar causes the kidneys to produce more urine. Children may start wetting the bed again. Sudden weight loss can also occur, even when appetite is normal. Other early symptoms include tiredness, weakness, confusion, nausea, and vomiting. Some of these problems can happen due to dehydration or a condition called ketoacidosis. Ketoacidosis occurs when the body cannot use glucose for energy and starts producing ketones, a type of acid. If untreated, this can become life-threatening and even lead to a coma [1].

Even after diagnosis, T1D can affect many parts of the body if blood sugar is not well controlled. Long-term complications include eye damage, nerve damage, foot problems, kidney disease, heart and blood vessel problems, and episodes of low blood sugar (hypoglycemia). Hypoglycemia can cause dizziness, shaking, sweating, confusion, headache, irritability, or blurred vision. Severe cases may lead to seizures or coma. These risks show how important it is to manage blood sugar carefully [1].

Carbohydrate counting (CC) is a key tool for managing T1D. It helps patients track the amount of carbohydrates in meals and adjust insulin doses correctly. Studies show that CC improves blood sugar control and allows for more flexible eating. For children and teenagers with T1D, CC helps manage glucose without affecting weight or increasing insulin needs. Using CC with tools like automated insulin calculators can lower glycated hemoglobin (HbA1c), which is a measure of long-term blood sugar control. CC also helps people with type 2 diabetes when combined with low-glycemic diets, improving blood sugar and HbA1c [2].

In conclusion, tracking carbohydrates is essential to prevent high or low blood sugar, avoid complications, and improve the quality of life. Tools that provide real-time information on carbohydrates, like smart food scanners, can make it easier for patients to make safe and healthy choices every day [2].

Motivation for a Smart Food Scanner: For people with type 1 diabetes, accurately tracking carbohydrate intake is essential to maintaining stable blood glucose levels. Manual estimation of carbohydrates can be time-consuming, error-prone, and stressful, especially for children or busy adults. A real-time smart food scanner can automate this process by detecting and decoding food barcodes or identifying foods visually, then providing immediate information about their nutritional content. Such a system reduces human error, saves time, and helps users make better decisions about insulin doses and portion sizes, ultimately improving blood sugar management and reducing the risk of diabetes-related complications.

Project Goal: The goal of this project is to design and implement a real-time smart food scanner for type 1 diabetes management. Using computer vision techniques, the system captures images from a camera, detects and decodes food barcodes, and retrieves carbohydrate and nutritional information from public databases. By providing instant, accurate data, the system supports individuals in managing their meals more effectively, helping to maintain stable blood glucose levels and improve overall quality of life.

Chapter 1

Problem Statement Objectives

1.1 Problem Statement

People with type 1 diabetes must carefully monitor their carbohydrate intake to maintain stable blood glucose levels. Estimating carbohydrates manually from food labels or memory is often time-consuming and prone to errors. Mistakes in carbohydrate estimation can lead to dangerous blood sugar fluctuations, such as hypoglycemia or hyperglycemia, and increase the risk of long-term complications, including nerve, kidney, and eye damage.

1.2 Challenges

Managing carbohydrate intake for packaged foods presents several challenges:

- **Time-consuming calculations:** Reading labels and calculating carbohydrate content for each product can be slow and inconvenient.
- **Human error:** Misreading barcodes or incorrectly estimating serving sizes may result in inaccurate carbohydrate tracking.
- **Need for real-time support:** Current methods do not provide instant feedback, which is essential for fast decision-making and safe insulin dosing.

1.3 Aim of the Project

This project aims to address these challenges by developing a real-time smart food scanner that assists individuals with type 1 diabetes in estimating carbohydrate content quickly and accurately, thereby supporting better blood glucose management in daily life.

Chapter 2

System Architecture

2.1 Overall Architecture

CarboScan is an integrated system that combines real-time computer vision and nutritional analysis to help patients with Type 1 Diabetes make informed dietary choices. It analyzes packaged food products using barcode detection and carbohydrate evaluation and follows a modular pipeline that includes image acquisition and preprocessing, barcode detection, product information retrieval, nutritional analysis and classification, recommendation generation, as well as a graphical user interface and data storage for user interaction and saving results.

The global workflow can be summarized as follows:




Figure 2.1.1: Intelligent Nutritional Analysis and Carb Classification Pipeline

First, the system captures live video frames from the device camera using the OpenCV library. When the user activates scanning mode, a predefined Region of Interest (ROI) is

displayed on the screen to guide barcode placement. The captured frame is preprocessed to enhance barcode detection. The system then applies barcode decoding to extract the product's unique identifier.

Once a valid barcode is detected, the system sends an HTTP request to the OpenFoodFacts public database to retrieve nutritional information associated with the product. The carbohydrate content (grams per 100 g) is then analyzed and classified into predefined risk levels (Low, Medium, High). Based on a configurable carbohydrate target per meal, the system computes the recommended maximum portion size.

Finally, results are displayed in real time through a graphical user interface, and the scan is stored locally in a JSON-based persistence system for tracking daily consumption history. This architecture ensures real-time responsiveness, modular scalability, and user-centered interaction.

2.2 Module Description

The system is composed of several functional modules, each responsible for a specific task within the architecture.

2.2.1 Image Acquisition Module

The Image Acquisition module is responsible for capturing real-time video streams from the camera using the OpenCV library.

The camera is initialized using `cv2.VideoCapture`, and the frame resolution is configured to ensure sufficient clarity for accurate barcode detection. Video frames are continuously captured and refreshed through a timed callback mechanism, allowing the system to maintain real-time performance and smooth visual rendering.

This module guaranties stable and continuous visual input, forming the foundation for subsequent preprocessing and barcode detection operations.

2.2.2 Preprocessing Module

Before barcode detection, the selected Region of Interest (ROI) undergoes an image preprocessing stage to improve decoding accuracy and robustness. The preprocessing pipeline consists of several sequential operations:

- Conversion from BGR to grayscale simplifies the image and reduces computational complexity.
- Gaussian blurring reduces noise and smooths the image.
- Adaptive thresholding enhances contrast between barcode patterns and the background.

These preprocessing steps significantly improve detection robustness under varying lighting conditions and increase the reliability and success rate of barcode decoding.

2.2.3 Barcode Detection Module

Barcode detection is performed using the `pyzbar` library, which decodes 1D barcodes from the preprocessed image.

To maintain GUI responsiveness, barcode scanning is executed in a separate thread. This prevents blocking the main interface thread during detection.

Once a barcode is successfully decoded, its numeric identifier is extracted and passed to the next module for product information retrieval.

2.2.4 Product Information Retrieval Module

Once a barcode has been successfully decoded, the system retrieves detailed product information from the OpenFoodFacts API using an HTTP GET request implemented via the `requests` library. If the product exists in the database, the module extracts essential nutritional information, including the product name, brand, carbohydrates per 100 grams, and sugar content.

In the event that the product is not found, the system immediately notifies the user through the graphical interface. The retrieved data, originally provided in JSON format, is parsed and structured within the system for further processing. This integration of external nutritional data allows the system to translate the raw barcode information into meaningful dietary guidance for the user.

2.2.5 Nutritional Classification Module

This module evaluates carbohydrate content relative to diabetes dietary guidelines. The classification logic is based on carbohydrate content per 100 g:

$$\textbf{Low: } \leq 10g$$

$$\textbf{Medium: } 10g\text{–}20g$$

$$\textbf{High: } > 20g$$

In addition to classification, the system calculates the maximum allowable portion size based on a configurable carbohydrate target per meal:

$$\text{Max Portion (g)} = \left(\frac{\text{Carb Target}}{\text{Carbs per 100g}} \right) \times 100$$

This provides personalized dietary guidance for users with Type 1 Diabetes.

2.2.6 Recommendation and Graphical User Interface Module

The graphical user interface (GUI) is implemented using the `Tkinter` framework. It provides a live camera feed for real-time barcode scanning, controls to start and stop scanning, a daily carbohydrate tracker, a panel displaying detailed information about the last scanned product, and a table showing the history of scanned products.

Upon successful barcode detection, the system presents the product's name, brand, and nutritional information, classifies its carbohydrate content according to dietary guidelines, and calculates the recommended maximum portion size based on the user-defined carbohydrate target. Visual and auditory feedback are provided to confirm a successful detection.

2.2.7 Data Persistence Module

User data and scan history are stored locally in a JSON file. The stored data includes:

- Carb target
- Camera index
- Daily carbohydrate total
- Scan history

This ensures continuity between sessions and enables daily consumption tracking.

Chapter 3

Methodology

3.1 Data Source

The application utilizes the OpenFoodFacts API as the primary data source for nutritional information. OpenFoodFacts is a collaborative, free, and open database of food products from around the world, containing comprehensive nutritional data, including carbohydrate content, sugars, proteins, and other macronutrients.

The API returns data in JSON format containing the following information: product identification (name, brand, and barcode), nutritional values per 100 grams (carbohydrates, sugars, fats, proteins), product images and metadata, and allergen information along with the ingredients list.

3.2 Preprocessing

Image preprocessing is crucial for reliable barcode detection, especially when scanning from mobile phone screens or in challenging lighting conditions. The preprocessing pipeline consists of the following steps:

Grayscale Conversion: The captured RGB frame is converted to grayscale using OpenCV's `cvtColor()` function with the `COLOR_BGR2GRAY` flag. This step reduces computational complexity and improves barcode pattern recognition by removing color information that is irrelevant for barcode detection.

Gaussian Blur: A Gaussian blur with a 3×3 kernel is applied to reduce image noise and smooth out minor variations. This step helps improve the subsequent thresholding operation by reducing false edges and artifacts from camera sensor noise.

Adaptive Thresholding: Adaptive thresholding is employed to handle varying illumination conditions. Unlike global thresholding, which applies a single threshold to the entire image, adaptive thresholding computes a local threshold for small image regions. This makes it particularly effective for barcode detection on reflective surfaces or under uneven lighting conditions.

In this implementation, Gaussian adaptive thresholding is applied using the `ADAPTIVE_THRESH_GAUSSIAN_C` option. The threshold is calculated for each pixel from a weighted average of the intensity values in its local neighborhood. A window size of 11 pixels is used to define this neighborhood, and a constant value of 2 is subtracted from the computed mean to adjust the binarization level. These settings improve edge visibility and help preserve barcode features.

3.3 Detection & Decoding

Barcode detection and decoding are performed using the pyzbar library, a Python wrapper for the ZBar barcode reading library. The detection process operates on the preprocessed grayscale image within a defined Region of Interest (ROI).

Region of Interest (ROI): To improve detection performance and reduce false positives, a central Region of Interest (ROI) is defined within the camera frame. The ROI covers approximately 50% of the frame's width and height and is positioned at the center of the image.

By restricting barcode detection to this area, the system minimizes background interference and irrelevant patterns that may resemble barcode structures. This approach also guides the user to place the product within an optimal detection zone, thereby increasing decoding accuracy and reducing computational overhead. The ROI boundaries are dynamically calculated based on the frame dimensions to ensure adaptability across different camera resolutions.

Barcode Detection: Barcode detection is performed using the pyzbar.decode() function, which analyzes the preprocessed Region of Interest (ROI) and returns a list of detected barcode objects. Each detected object contains the decoded data, barcode type (e.g., EAN-13, UPC-A, QR Code), and the corresponding bounding box coordinates.

The system relies on the decoding capabilities provided by the Pyzbar library, which supports multiple common barcode formats such as EAN-13, UPC-A, QR Code, Code-128, and Code-39. Once a barcode is successfully detected, its numerical data is extracted and passed to the product information retrieval module.

3.4 API Integration

Once a barcode is successfully decoded, the extracted numeric identifier is sent to the OpenFoodFacts API through an HTTP GET request. The API response is returned in JSON format, from which relevant product and nutritional information is extracted for further processing.

To ensure system robustness and prevent interface blocking, several error-handling mechanisms are implemented. A timeout of 5 seconds is defined for the HTTP request to avoid indefinite waiting in case of network issues. The system verifies that a successful HTTP response (status code 200) is received before processing the returned data. Addi-

tionally, the API's internal *status* field is checked to confirm that the product exists in the database (status = 1). Network-related exceptions are handled to prevent application crashes and maintain system stability.

After retrieving the carbohydrate information from the API (see Section 2.2.5), the product is classified into Low, Medium, or High carbohydrate categories, and the maximum recommended portion size per meal is computed. The resulting information is then presented through the graphical interface.

3.5 User Interface

The graphical user interface (GUI) is developed using Python's Tkinter library, providing a cross-platform desktop application environment. The interface is organized into two main panels to separate visual acquisition from informational feedback.

Left Panel – Camera Feed: The left panel displays the live camera feed using a Tkinter canvas with a resolution of 800×600 pixels. During scanning mode, a green rectangular Region of Interest (ROI) is overlaid on the video stream to guide barcode placement.

This panel also includes interactive controls, namely:

- A Start/Stop Scanning button that toggles barcode detection mode.
- A Settings button that opens a configuration window where the carbohydrate target per meal and camera index can be adjusted.

Right Panel – Information Display: The right panel presents nutritional and tracking information. It includes:

- A Daily Carbohydrate Counter with reset functionality.
- A Last Scanned Product section displaying product name, brand, carbohydrate and sugar values, classification level, and recommended maximum portion size.
- A Scan History table implemented using a Treeview widget, showing timestamp, product name, carbohydrate content per 100 g, and classification level for scans performed during the current day.

All application data, including user settings, daily counter values, and scan history, are stored locally in a JSON file (carboscan_data.json) to ensure persistence across sessions.

Chapter 4

Implementation

4.1 Programming Environment

The application is implemented in Python 3.9+ with the following technology stack:

Library	Purpose
OpenCV	Image processing and camera feed handling
pyzbar	Barcode detection and decoding
Pillow	Image conversion and display for GUI
Requests	HTTP API communication with OpenFoodFacts
Tkinter	Graphical User Interface framework

Table 4.1: Key libraries used in the CarboScan application

4.2 Key Code Components

4.2.1 CarboScanApp Class

The main application is organized as a single class, `CarboScanApp`, which encapsulates all core functionality:

__init__(): Initializes the GUI, loads saved data, and starts the camera.

create_widgets(): Builds the Tkinter interface layout, including camera feed, controls, and information panels.

update_camera_feed(): Implements a continuous video display loop at approximately 30 FPS.

scan_barcode(): Performs barcode detection in a separate thread to maintain GUI responsiveness.

process_barcode(): Handles API calls and nutritional data processing.

save_data() / load_data(): Manages JSON-based persistence of application state and scan history.

4.2.2 Threading Architecture

To prevent the graphical interface from freezing during barcode scanning and API requests, the application uses Python's `threading` module. Barcode detection runs in a separate daemon thread, while the main thread is dedicated to updating the user interface. Thread-safe communication is achieved using the `root.after()` method for scheduling callbacks in the main thread.

4.2.3 Data Persistence

Application state is maintained in `carboscan_data.json`, which stores:

- User preferences (e.g., carbohydrate target per meal, camera index)
- Daily carbohydrate counter
- Scan history including timestamps

The JSON file is automatically loaded when the application starts and is updated after each scan or when user settings change, ensuring continuity across sessions.

Chapter 5

Experiments & Results

5.1 Test Conditions

The application was evaluated under various real-world scenarios to assess its performance and usability.

5.1.1 Hardware Configuration

- **Test System:** Windows 11 laptop
- **Camera:** Built-in 1080p webcam
- **Resolution:** 1920×1080 pixels
- **Frame rate:** 30 FPS

5.1.2 Test Scenarios

Scenario	Description
Physical Products	Scanning barcodes directly from product packaging
Phone Screens	Scanning barcodes displayed on mobile phone screens
Poor Lighting	Testing in dim or ambient lighting conditions
Bright Lighting	Testing under direct sunlight or bright artificial light
Damaged Codes	Partially obscured or worn barcodes

Table 5.1: Different test scenarios used to evaluate the system.

5.2 Evaluation Metrics

The following metrics were used to assess system performance:

- **Detection Success Rate:** Percentage of successful barcode detections.
- **Detection Time:** Average time from scan initiation to data display.

- **API Response Time:** Time taken for OpenFoodFacts API calls.
- **Product Coverage:** Percentage of scanned products found in the database.
- **User Interface Responsiveness:** Frame rate stability during scanning.

5.3 Results and Observations

5.3.1 Detection Performance

Condition	Success Rate	Avg. Time (s)
Physical products (good lighting)	95%	0.8
Phone screens	85%	1.2
Poor lighting	70%	1.5
Damaged/worn barcodes	60%	2.0

Table 5.2: Detection performance under different real-world conditions.

5.3.2 Key Findings

The evaluation of the system under various test conditions revealed several important observations:

- Adaptive thresholding significantly improved detection rates on phone screens, increasing success from 65% with global thresholding to 85%.
- The ROI-based approach effectively reduced false positives by approximately 80%.
- API response time from OpenFoodFacts averaged 1.2 seconds, with a product coverage of 92%.
- The graphical interface maintained a consistent 30 FPS even during barcode processing, thanks to the use of threading.
- User testing indicated a 95% satisfaction rate regarding interface clarity and overall ease of use.

5.3.3 Challenges and Limitations

During the evaluation, several challenges and limitations of the system were observed:

- Screen glare on phone displays can interfere with barcode detection, which can be mitigated by adjusting the viewing angle.
- Some regional products are not present in the OpenFoodFacts database.
- The application requires an active internet connection for API access
- Detection accuracy can be influenced by camera quality; while our tests used a 1080p webcam, lower-resolution cameras may yield reduced performance.

5.3.4 Future Improvements

Based on the evaluation results and observed limitations, several potential enhancements have been identified to further improve the system:

- Implement an offline mode using a cached product database to allow scanning without an internet connection.
- Provide a manual product entry for items that are not present in the database.
- Integrate insulin dose calculators to support more personalized diabetes management.
- Add multi-language support to improve accessibility for a broader range of users.
- Enable cloud synchronization to allow seamless data access and backup across multiple devices.
- Explore machine learning-based food recognition using images to extend detection capabilities beyond traditional barcode scanning.

Conclusion

This project presented the design and implementation of CarboScan Vision, a real-time smart food scanner for Type 1 Diabetes management.

The system successfully combines computer vision techniques and nutritional data retrieval to provide real-time carbohydrate information for packaged food products. By integrating barcode detection, nutritional classification, and a graphical user interface, the application allows users to obtain useful dietary information quickly and easily.

Experimental results demonstrated that the system performs reliably under different conditions and maintains real-time responsiveness. The modular architecture makes the system easy to extend and improve.

This project shows the potential of computer vision technologies in healthcare applications, particularly in assisting individuals with diabetes to manage their diet more effectively.

Future improvements may include offline databases, machine learning-based food recognition, and mobile application development.

In conclusion, CarboScan Vision provides a practical and efficient tool for supporting carbohydrate monitoring and improving diabetes self-management.

Bibliography

[1] Robert H. Shmerling. *Type 1 diabetes mellitus*. Jun 25, 2025. https://www.health.harvard.edu/diseases-and-conditions/type-1-diabetes-mellitus-a-to-z. [Accessed Feb 02, 2026].

[2] H. Ibrahim, Sara M and Shahat, Elham A and Amer, Lamar A and Aljohani, Abdullah K. *The Impact of Using Carbohydrate Counting on Managing Diabetic Patients: A Review*. Nov 18, 2023. https://pmc.ncbi.nlm.nih.gov/articles/PMC10726644/. [Accessed Feb 02, 2026].