

杂题混练

人员

蔡云翔、石宇赫、李佳声、窦浩轩、胡赫轩、崔嘉睿、穆鹏宇、程晟泰、梁钰涵、王梓同、刘浩、纪昀琨、张彧韶 到课

作业检查

上周作业链接: <https://vjudge.net/contest/652462>

密码: code@123

云晨轩、穆鹏宇、胡赫轩 完成 3 道题

孙乐涵、梁钰涵 完成 2 道题

程晟泰、杨洋、李佳声、崔嘉睿 完成 1 道题

其他同学未做

作业

<https://vjudge.net/contest/652462>, 上周 5 道作业题要求大家补完

<https://www.luogu.com.cn/contest/197227>, 课上 1 道题要求大家补完

<https://vjudge.net/contest/653870>, 课后作业 5 道题要求大家课后进行思考尝试

课堂表现

课上整体纪律比较好, 同学们课下要积极进行补题。

课堂内容

CF1119D Frets On Fire

二分查找

```
#include <bits/stdc++.h>

using namespace std;

typedef long long LL;
const int maxn = 1e5 + 5;
LL w[maxn], a[maxn], pSum[maxn];

int main()
{
    int n; cin >> n;
```

```

for (int i = 1; i <= n; ++i) cin >> w[i];
sort(w+1, w+n+1);

--n;
for (int i = 1; i <= n; ++i) a[i] = w[i+1] - w[i];
sort(a+1, a+n+1);
for (int i = 1; i <= n; ++i) pSum[i] = pSum[i-1] + a[i];

int m; cin >> m;
while (m -- ) {
    LL l, r; cin >> l >> r;
    LL d = r - l + 1;
    int pos = lower_bound(a+1, a+n+1, d) - a;
    cout << pSum[pos-1] + ((LL)n-pos+2) * d << " ";
}
return 0;
}

```

CF1551E Fixed Points

dp

$f[i][j]$: 处理到第 i 个数时, 保留 j 个数, 最多有几个地方满足 $b_i=i$ 的性质

$f[i][j] = \max(f[i-1][j-1] + (w[i]==j) \rightarrow \text{保留第 } i \text{ 个数 } f[i-1][j] \rightarrow \text{删除第 } i \text{ 个数})$

```

#include <bits/stdc++.h>

using namespace std;

const int maxn = 2000 + 5;
int w[maxn], f[maxn][maxn];

void solve() {
    int n, k; cin >> n >> k;
    for (int i = 0; i <= n+2; ++i) {
        for (int j = 0; j <= n+2; ++j) f[i][j] = 0;
    }

    for (int i = 1; i <= n; ++i) cin >> w[i];
    for (int i = 1; i <= n; ++i) {
        for (int j = 1; j <= i; ++j) f[i][j] = max(f[i-1][j-1] + (w[i]==j), f[i-1][j]);
    }

    for (int i = n; i >= 1; --i) {
        if (f[n][i] >= k) {
            cout << n-i << endl;
            return;
        }
    }
    cout << -1 << endl;
}

```

```

}

int main()
{
    int T; cin >> T;
    while (T -- ) solve();
    return 0;
}

```

CF1901D Yet Another Monster Fight

维护前后缀最大值

```

#include <bits/stdc++.h>

using namespace std;

const int maxn = 3e5 + 5;
int w[maxn], a[maxn], b[maxn];
int pMax[maxn], sMax[maxn];

int main()
{
    int n; cin >> n;
    for (int i = 1; i <= n; ++i) cin >> w[i];
    for (int i = 1; i <= n; ++i) {
        a[i] = w[i] + n - i, b[i] = w[i] + i - 1;
        pMax[i] = max(pMax[i - 1], a[i]);
    }
    for (int i = n; i >= 1; --i) sMax[i] = max(sMax[i + 1], b[i]);

    int res = 2e9;
    for (int i = 1; i <= n; ++i) {
        res = min(res, max({pMax[i - 1], w[i], sMax[i + 1]}));
    }
    cout << res << endl;
    return 0;
}

```

AT_arc100_b Equal Cut

双指针 或 二分

```

#include <bits/stdc++.h>

using namespace std;

typedef long long LL;
const int maxn = 2e5 + 5;

```

```

int w[maxn];
LL pSum[maxn];

LL get_sum(int l, int r) { return pSum[r] - pSum[l-1]; }

LL diff_value(int l, int mid, int r) {
    return abs(get_sum(l, mid) - get_sum(mid+1, r));
}

bool is_better(int l, int mid, int r) {
    return diff_value(l, mid+1, r) <= diff_value(l, mid, r);
}

int main()
{
    int n; cin >> n;
    for (int i = 1; i <= n; ++i) {
        cin >> w[i]; pSum[i] = pSum[i-1] + w[i];
    }

    LL res = 1e18;
    for (int i=1,j=2,k=3; j<=n-2; ++j) {
        while (i+1<j && is_better(1,i,j)) ++i;
        while (k+1<n && is_better(j+1,k,n)) ++k;
        LL a = get_sum(1, i), b = get_sum(i+1, j), c = get_sum(j+1, k), d =
get_sum(k+1, n);
        res = min(res, max({a,b,c,d}) - min({a,b,c,d}));
    }
    cout << res << endl;
    return 0;
}

```

CF30C Shooting Gallery

根据时间排序，抽象成一张图，递推

```

#include <bits/stdc++.h>

using namespace std;

typedef long long LL;
const int maxn = 1000 + 5;
struct node {
    int x, y, t; double p;
} w[maxn];
vector<int> vec[maxn];
bool cmp(node a, node b) { return a.t < b.t; }

LL dis_2(int x1, int y1, int x2, int y2) {
    int dx = x1-x2, dy = y1-y2;
    return (LL)dx*dx + (LL)dy*dy;
}

```

```

}
double f[maxn];

int main()
{
    int n; cin >> n;
    for (int i = 1; i <= n; ++i) cin >> w[i].x >> w[i].y >> w[i].t >> w[i].p;
    sort(w+1, w+n+1, cmp);

    for (int i = 1; i <= n; ++i) {
        for (int j = i+1; j <= n; ++j) {
            int d2 = dis_2(w[i].x, w[i].y, w[j].x, w[j].y);
            int t = w[j].t-w[i].t;
            if (d2 <= (LL)t*t) vec[j].push_back(i);
        }
    }

    double res = 0;
    for (int i = 1; i <= n; ++i) {
        for (int j : vec[i]) f[i] = max(f[i], f[j]);
        f[i] += w[i].p;
        res = max(res, f[i]);
    }
    printf("%.8f\n", res);
    return 0;
}

```

T494829 box

$f[i][j]$: 至少有 i 个章鱼小丸子、 j 个大饼时, 最少需要多少饭盒

```

#include <bits/stdc++.h>

using namespace std;

const int maxn = 300 + 5;
const int inf = 0x3f3f3f3f;
int f[maxn][maxn];

int main()
{
    int n; cin >> n;
    int x, y; cin >> x >> y;

    memset(f, 0x3f, sizeof(f));
    f[0][0] = 0;

    while (n -- ) {
        int a, b; cin >> a >> b;
        for (int i = x; i >= 0; --i) {
            for (int j = y; j >= 0; --j) f[i][j] = min(f[i][j], f[max(0,i-a)][max(0,j-

```

```
b)]+1);  
    }  
}  
cout << (f[x][y]==inf?-1:f[x][y]) << endl;  
return 0;  
}
```