

字符串练习2

人员

臧晨云 隋湫琛 于昊华 刘子彬 何佩瑜 刘克阳 初星熠 刘奕男 张高 陈之恒 霍佳铭 到课

上周作业检查

上周作业链接: <https://cppoj.kids123code.com/contest/4302>

王向东老师周六一点半C++字符串练习1

刷新

#	用户名	姓名	编程分	时间	A	B	C	D	E	F	G
1	liuzichen123	刘子彬	700	64	100	100	100	100	100	100	100
2	chuxingyi	初星熠	700	66	100	100	100	100	100	100	100
3	hepeiyu	何佩瑜	700	66	100	100	100	100	100	100	100
4	zangchenyun	臧晨云	700	67	100	100	100	100	100	100	100
5	zhanggao	张高	700	67	100	100	100	100	100	100	100
6	suihaochen	隋湫琛	700	67	100	100	100	100	100	100	100
7	liuyinan	刘奕男	600	55	100	100	100	100	100	100	0
8	lijingxuan	李景翾	600	56	100	100	100	100	100	100	0
9	huojiaming	霍佳铭	500	20	100	100		100	100	100	
10	liukeyang	刘克阳	500	53	100	100	100	100	100		
11	yuhao Hua	于昊华	400	36	100	100	100	100	0		

作业

<https://cppoj.kids123code.com/contest/4521> (课上讲了 A ~ E 题, 作业是 A ~ F题必做)

课堂表现

隋湫琛有点不细心，话比较多；臧晨云做得很快，而且很认真；其他同学上课都挺认真的，做题情况也不错。

课堂内容

统计数字字符个数

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;
```

```
int cnt = 0;
for (int i = 1; i <= n; i++) {
    if (s[i] >= '0' && s[i] <= '9') {
        cnt++;
    }
}
cout << cnt << endl;
return 0;
}
```

字符串中的空格移位

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;

    for (int i = 1; i <= n; i++) {
        if (s[i] == ' ') {
            cout << s[i];
        }
    }
    for (int i = 1; i <= n; i++) {
        if (s[i] != ' ') {
            cout << s[i];
        }
    }
    return 0;
}
```

手机

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;
```

```

int sum = 0;
for (int i = 1; i <= n; i++) {
    if
(s[i]=='a' || s[i]=='d' || s[i]=='g' || s[i]=='j' || s[i]=='m' || s[i]=='p' || s[i]=='t' || s[i]
=='w' || s[i]==' ') {
        sum++;
    }
    else if
(s[i]=='b' || s[i]=='e' || s[i]=='h' || s[i]=='k' || s[i]=='n' || s[i]=='q' || s[i]=='u' || s[i]
=='x') {
        sum+=2;
    }
    else if
(s[i]=='c' || s[i]=='f' || s[i]=='i' || s[i]=='l' || s[i]=='o' || s[i]=='r' || s[i]=='v' || s[i]
=='y') {
        sum+=3;
    }
    else {
        sum+=4;
    }
}
cout << sum << endl;
return 0;
}

```

简单加密

```

#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;

    for (int i = 1; i <= n; i++) {
        if (s[i]>='A' && s[i]<='Z') {
            s[i] -= 5;
            if (s[i] < 'A') {
                s[i] += 26;
            }
            cout << s[i];
        }
        else {
            cout << s[i];
        }
    }
}

```

```
    return 0;
}
```

调换位置

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    cin >> s;
    int n = s.size();
    s = " " + s;

    int p;
    for (int i = 1; i <= n; i++) {
        if (s[i] == ',') {
            p = i;
            break;
        }
    }

    for (int i = p+1; i <= n; i++) {
        cout << s[i];
    }
    cout << ",";
    for (int i = 1; i <= p-1; i++) {
        cout << s[i];
    }
    return 0;
}
```

删除字符串中间的*

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    cin >> s;
    int n = s.size();
    s = " " + s;

    int l,r;
```

```
for (int i = 1; i <= n; i++) {
    if (s[i] != '*') {
        l = i;
        break;
    }
}
for (int i = n; i >= 1; i--) {
    if (s[i] != '*') {
        r = i;
        break;
    }
}

for (int i = 1; i <= n; i++) {
    if (s[i] != '*') {
        cout << s[i];
    }
    else {
        if (i<=l || i>=r) {
            cout << s[i];
        }
    }
}
return 0;
}
```