

字符串练习2

人员

王纯硕 彭俊文 张嘉芮 解钧添 赵庭澍 屈钰轩 到课

上周作业检查

上周作业链接: <https://cppoj.kids123code.com/contest/4303>

王向东老师周六三点半C++字符串练习1											
🔄 刷新											
#	用户名	姓名	编程分	时间	A	B	C	D	E	F	G
1	cuixiaoze	崔孝泽	700	66	100	100	100	100	100	100	100
2	pengjunwen	彭俊文	700	67	100	100	100	100	100	100	100
3	chenzhiheng	陈之恒	700	67	100	100	100	100	100	100	100
4	quyuxuan	屈钰轩	700	67	100	100	100	100	100	100	100
5	xiejuntian	解钧添	700	68	100	100	100	100	100	100	100
6	wangchunshuo	王纯硕	600	56	100	100	100	100	100	100	
7	zhangjiarui	张嘉芮	500	55	100	100	100	100	100	0	

作业

<https://cppoj.kids123code.com/contest/4522> (课上讲了 A ~ E 题, 作业是 A ~ F题必做)

课堂表现

屈钰轩做得比较认真也比较快, 彭俊文做得有点不够细心, 其他同学课堂表现都不错, 做题认真, 思路也比较清晰, 但都不是很细心。

课堂内容

统计数字字符个数

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;

    int cnt = 0;
    for (int i = 1; i <= n; i++) {
        if (s[i]>='0' && s[i]<='9') {
```

```
        cnt++;
    }
}
cout << cnt << endl;
return 0;
}
```

字符串中的空格移位

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;

    for (int i = 1; i <= n; i++) {
        if (s[i] == ' ') {
            cout << s[i];
        }
    }
    for (int i = 1; i <= n; i++) {
        if (s[i] != ' ') {
            cout << s[i];
        }
    }
    return 0;
}
```

手机

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;

    int sum = 0;
    for (int i = 1; i <= n; i++) {
```

```

    if
    (s[i]=='a' || s[i]=='d' || s[i]=='g' || s[i]=='j' || s[i]=='m' || s[i]=='p' || s[i]=='t' || s[i]
    == 'w' || s[i]==' ') {
        sum++;
    }
    else if
    (s[i]=='b' || s[i]=='e' || s[i]=='h' || s[i]=='k' || s[i]=='n' || s[i]=='q' || s[i]=='u' || s[i]
    == 'x') {
        sum+=2;
    }
    else if
    (s[i]=='c' || s[i]=='f' || s[i]=='i' || s[i]=='l' || s[i]=='o' || s[i]=='r' || s[i]=='v' || s[i]
    == 'y') {
        sum+=3;
    }
    else {
        sum+=4;
    }
}
cout << sum << endl;
return 0;
}

```

简单加密

```

#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    getline(cin, s);
    int n = s.size();
    s = " " + s;

    for (int i = 1; i <= n; i++) {
        if (s[i]>='A' && s[i]<='Z') {
            s[i] -= 5;
            if (s[i] < 'A') {
                s[i] += 26;
            }
            cout << s[i];
        }
        else {
            cout << s[i];
        }
    }
    return 0;
}

```

调换位置

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    cin >> s;
    int n = s.size();
    s = " " + s;

    int p;
    for (int i = 1; i <= n; i++) {
        if (s[i] == ',') {
            p = i;
            break;
        }
    }

    for (int i = p+1; i <= n; i++) {
        cout << s[i];
    }
    cout << ",";
    for (int i = 1; i <= p-1; i++) {
        cout << s[i];
    }
    return 0;
}
```

删除字符串中间的*

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    cin >> s;
    int n = s.size();
    s = " " + s;

    int l,r;
    for (int i = 1; i <= n; i++) {
        if (s[i] != '*') {
            l = i;
            break;
        }
    }
```

```
}  
for (int i = n; i >= 1; i--) {  
    if (s[i] != '*') {  
        r = i;  
        break;  
    }  
}  
  
for (int i = 1; i <= n; i++) {  
    if (s[i] != '*') {  
        cout << s[i];  
    }  
    else {  
        if (i<=1 || i>=r) {  
            cout << s[i];  
        }  
    }  
}  
return 0;  
}
```