

字符串练习3

人员

王纯硕 彭俊文 张嘉芮 解钧添 赵庭澍 屈钰轩 陈奕圻 崔孝泽 到课

上周作业检查

上周作业链接: <https://cppoj.kids123code.com/contest/4522>

刷新

#	用户名	姓名	编程分	时间	A	B	C	D	E	F
1	xiejuntian	解钧添	600	75	100	100	100	100	100	100
2	wangchunshuo	王纯硕	600	76	100	100	100	100	100	100
3	cuixiaoze	崔孝泽	600	79	100	100	100	100	100	100
4	quyuxuan	屈钰轩	500	74	100	100	100	100	100	0
5	pengjunwen	彭俊文	500	75	100	100	100	100	100	
6	zhaotingshu	赵庭澍	500	77	100	100	100	100	100	0
7	chenyiqi	陈奕圻	500	77	100	100	100	100	100	
8	zhangjiarui	张嘉芮	500	78	100	100	100	100	100	

作业

<https://cppoj.kids123code.com/contest/4674> (课上讲了 A ~ F 题, 作业是 A ~ F 题必做, G 题选做)

课堂表现

今天重点给同学们讲解了字符串的 substr 和 find 两个方法, 第四题是一道非常综合的练习题, 建议同学们课下多写几遍第四题。

课堂内容

忽略大小写的字符串比较

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string a, b;
    getline(cin, a);
    getline(cin, b);
    int n = a.size();
    for (int i = 0; i < n; i++) {
        if (a[i]>='a' && a[i]<='z') {
            a[i] = a[i]-'a'+'A';
        }
    }
}
```

```
    if (b[i]>='a' && b[i]<='z') {  
        b[i] = b[i]-'a'+'A';  
    }  
}  
  
if (a < b) cout << "<";  
else if (a > b) cout << ">";  
else cout << "=";  
return 0;  
}
```

调换位置

```
#include <bits/stdc++.h>  
  
using namespace std;  
  
int main()  
{  
    string s;  
    cin >> s;  
    int n = s.size(), p;  
    for (int i = 0; i < n; ++i) {  
        if (s[i] == ',') {  
            p = i;  
            break;  
        }  
    }  
  
    cout << s.substr(p+1) << "," << s.substr(0, p);  
    return 0;  
}
```

验证子串

```
#include <bits/stdc++.h>  
  
using namespace std;  
  
int main()  
{  
    string a, b;  
    cin >> a >> b;  
    if (a.find(b) != -1) {  
        cout << b << " is substring of " << a << endl;  
    }  
    else if (b.find(a) != -1) {  
        cout << a << " is substring of " << b << endl;  
    }  
}
```

```
    }  
    else {  
        cout << "No substring" << endl;  
    }  
    return 0;  
}
```

【深基6.例6】文字处理软件

```
#include <bits/stdc++.h>  
  
using namespace std;  
  
int main()  
{  
    int n;  
    cin >> n;  
    string s;  
    cin >> s;  
    for (int i = 1; i <= n; ++i) {  
        int op;  
        cin >> op;  
        if (op == 1) {  
            string t;  
            cin >> t;  
            s += t;  
            cout << s << endl;  
        }  
        else if (op == 2) {  
            int a, b;  
            cin >> a >> b;  
            s = s.substr(a,b);  
            cout << s << endl;  
        }  
        else if (op == 3) {  
            int a;  
            string t;  
            cin >> a >> t;  
            s = s.substr(0,a) + t + s.substr(a);  
            cout << s << endl;  
        }  
        else {  
            string t;  
            cin >> t;  
            int p = s.find(t);  
            cout << p << endl;  
        }  
    }  
    return 0;  
}
```

atoz

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    cin >> s;
    int n = s.size();
    s = " " + s;

    int l, r;
    for (int i = 1; i <= n; ++i) {
        if (s[i] == 'A') {
            l = i;
            break;
        }
    }
    for (int i = n; i >= 1; i--) {
        if (s[i] == 'Z') {
            r = i;
            break;
        }
    }

    cout << r-l+1 << endl;
    return 0;
}
```

删除单词后缀

```
#include <bits/stdc++.h>

using namespace std;

int main()
{
    string s;
    cin >> s;
    int n = s.size();
    if (n>=2 && s.substr(n-2)=="er") {
        cout << s.substr(0, n-2) << endl;
    }
    else if (n>=2 && s.substr(n-2)=="ly") {
        cout << s.substr(0, n-2) << endl;
    }
    else if (n>=3 && s.substr(n-3)=="ing") {
        cout << s.substr(0, n-3) << endl;
    }
}
```

```
    }  
    else {  
        cout << s << endl;  
    }  
    return 0;  
}
```