

结构体排序

人员

王纯硕 彭俊文 张嘉芮 屈钰轩 陈奕圻 解钧添 李弘浩 赵庭澍 赵士锐 到课

上周作业检查

上周作业链接: <https://cppoj.kids123code.com/contest/4951>

刷新成功

王向东老师周六三点半C++自定义函数

刷新

#	用户名	姓名	编程分	时间	A	B	C	D	E	F	G	H
1	lihonghao	李弘浩	800	8605	100	100	100	100	100	100	100	100
2	zhaotingshu	赵庭澍	800	9136	100	100	100	100	100	100	100	100
3	wangchunshuo	王纯硕	800	9494	100	100	100	100	100	100	100	100
4	quyuxuan	屈钰轩	800	9498	100	100	100	100	100	100	100	100
5	chenyiqi	陈奕圻	800	9987	100	100	100	100	100	100	100	100
6	xiejuntian	解钧添	800	13316	100	100	100	100	100	100	100	100
7	zhangjiarui	张嘉芮	700	8904	100	100	100	100	100	100	100	
8	maxinyi	马欣怡	300	499	100	100	100					
9	pengjunwen	彭俊文	300	508	100	100	100					

作业

<https://cppoj.kids123code.com/contest/5143> (作业是 A ~ F 题必做)

课堂表现

今天课上讲了 结构体 和 结构体排序 的知识, 这部分知识不难, 同学们课上掌握不错, 但是还不熟, 需要课下再复习复习。

课堂内容

成绩排序

```
#include <bits/stdc++.h>

using namespace std;

struct node {
    string s;
    int c;
} a[25];

bool cmp(node p, node q) {
    if (p.c != q.c) return p.c > q.c;
    return p.s < q.s;
```

```
}

int main()
{
    int n;
    cin >> n;
    for (int i = 1; i <= n; i++) cin >> a[i].s >> a[i].c;
    sort(a+1, a+n+1, cmp);
    for (int i = 1; i <= n; ++i) {
        cout << a[i].s << " " << a[i].c << endl;
    }
    return 0;
}
```

坐标排序

```
#include <bits/stdc++.h>

using namespace std;

struct node {
    int x, y;
} a[10005];

bool cmp(node p, node q) {
    if (p.x != q.x) return p.x < q.x;
    return p.y < q.y;
}

int main()
{
    int n;
    cin >> n;
    for (int i = 1; i <= n; i++) cin >> a[i].x >> a[i].y;
    sort(a+1, a+n+1, cmp);
    for (int i = 1; i <= n; ++i) {
        cout << a[i].x << " " << a[i].y << endl;
    }
    return 0;
}
```

期末考试成绩排名

```
#include <bits/stdc++.h>

using namespace std;

struct node {
```

```

    int id;
    string s;
    int c;
} a[105];

bool cmp(node p, node q) {
    if (p.c != q.c) return p.c > q.c;
    return p.id < q.id;
}

int main()
{
    int n;
    cin >> n;
    for (int i = 1; i <= n; i++) cin >> a[i].id >> a[i].s >> a[i].c;
    sort(a+1, a+n+1, cmp);
    for (int i = 1; i <= n; ++i) {
        cout << a[i].id << " " << a[i].s << " " << a[i].c << endl;
    }
    return 0;
}

```

生日

```

#include <bits/stdc++.h>

using namespace std;

struct node {
    string s;
    int y, m, d;
    int id;
} a[105];

bool cmp(node p, node q) {
    if (p.y != q.y) return p.y < q.y;
    if (p.m != q.m) return p.m < q.m;
    if (p.d != q.d) return p.d < q.d;
    return p.id > q.id;
}

int main()
{
    int n;
    cin >> n;
    for (int i = 1; i <= n; i++) {
        cin >> a[i].s >> a[i].y >> a[i].m >> a[i].d;
        a[i].id = i;
    }
    sort(a+1, a+n+1, cmp);
    for (int i = 1; i <= n; ++i) {

```

```
    cout << a[i].s << endl;
}
return 0;
}
```

宇宙总统

```
#include <bits/stdc++.h>

using namespace std;

struct node {
    int id;
    string c;
} a[25];

bool cmp(node p, node q) {
    if (p.c.size() != q.c.size()) return p.c.size() > q.c.size();
    return p.c > q.c;
}

int main()
{
    int n;
    cin >> n;
    for (int i = 1; i <= n; i++) {
        cin >> a[i].c;
        a[i].id = i;
    }
    sort(a+1, a+n+1, cmp);
    cout << a[1].id << endl;
    cout << a[1].c << endl;
    return 0;
}
```

合影

```
#include <bits/stdc++.h>

using namespace std;

struct node {
    string s;
    int c;
} a[45];

bool cmp(node p, node q) {
    if (p.s=="male" && q.s=="male") {
```

```
        return p.c < q.c;
    } else if (p.s=="male" && q.s=="female") {
        return true;
    } else if (p.s=="female" && q.s=="male") {
        return false;
    } else {
        return p.c > q.c;
    }
}

int main()
{
    int n;
    cin >> n;
    for (int i = 1; i <= n; i++) {
        cin >> a[i].s >> a[i].c;
    }
    sort(a+1, a+n+1, cmp);
    for (int i = 1; i <= n; ++i) cout << a[i].c << " ";
    cout << endl;
    return 0;
}
```