Network Slicing and SDN Architecture in Hospital Networks

Next-Generation Network Architecture for Critical Healthcare:

A Software-Defined Network (SDN) Slicing Approach for Ultra-Reliable Low-Latency Communication (URLLC)

GROUP MEMBERS

212010020004- Ayşe Sümeyra Mert
212010020058- Fatma Zehra Bestil
212010020113- Betül Korkmaz

KONYA FOOD AND AGRICULTURE UNIVERSITY

KFAU - KGTÜ
15.04.2026

NGN PROJECT PROPOSAL
SMART HOSPITAL NETWORK

1. Project Title

Next-Generation Network Architecture for Critical Healthcare: A Software-Defined Network (SDN) Slicing Approach for Ultra-Reliable Low-Latency Communication (URLLC)

2. Introduction & Motivation

In recent years, healthcare systems have undergone a significant digital transformation driven by the rapid adoption of advanced technologies such as robotic-assisted surgery, wearable health monitoring devices, and high-resolution medical imaging systems. These innovations generate massive volumes of time-sensitive data that must be transmitted reliably and with minimal delay across hospital networks.

However, conventional hospital network infrastructures still rely on the traditional "best-effort" communication model, where all data traffic—regardless of its priority or criticality—is treated equally. In such environments, life-critical data streams, such as real-time patient monitoring signals or surgical robot commands, share the same network resources with non-critical traffic, including administrative data transfers, video streaming, or guest Wi-Fi usage. This lack of traffic differentiation can result in network congestion, increased latency, and unpredictable delays.

In critical healthcare scenarios, even millisecond-level delays can lead to severe consequences, including incorrect medical decisions, delayed interventions, or system failures in life-supporting devices. Therefore, ensuring ultra-reliable and low-latency communication has become a fundamental requirement for next-generation hospital networks.

To address these challenges, this project proposes a novel network architecture based on Software-Defined Networking (SDN) and Network Slicing technologies. SDN introduces a centralized control mechanism that enables dynamic and programmable network management, while Network Slicing allows the physical network infrastructure to be partitioned into multiple isolated virtual networks, each optimized for specific application requirements.

By leveraging these technologies, the proposed system aims to create dedicated network slices for different types of traffic, ensuring that mission-critical healthcare data is prioritized and isolated from less important traffic. This approach not only minimizes latency and improves reliability but also enhances network efficiency, scalability, and security.

Ultimately, the motivation of this project is to transform conventional hospital networks into intelligent, adaptive, and mission-critical infrastructures capable of supporting the stringent requirements of modern healthcare applications and future 5G/6G-enabled medical services.

3. Problem Statement

Modern hospital network infrastructures are increasingly struggling to meet the demands of growing data traffic and the diversity of connected medical and non-medical devices. The limitations of traditional network architectures, particularly their static configurations and reliance on the “best-effort” communication model, lead to significant performance and reliability issues in critical healthcare environments. In this context, the major challenges observed in existing hospital networks are detailed as follows:

Network Congestion

In hospital environments, critical data generated by medical devices shares the same network resources with high-bandwidth-consuming traffic produced by staff and guest users, such as video streaming, social media usage, and large file downloads. This coexistence results in network congestion, where packets are forced to wait in the same transmission queues regardless of their priority level. Consequently, even life-critical data packets may experience delays, leading to a degradation in overall network performance.

Latency

In critical healthcare applications, data transmission delays must be minimized to the level of milliseconds. However, in conventional network infrastructures, packets are transmitted without effective prioritization, which can result in delays even for urgent medical signals. For instance, a real-time cardiac alarm signal may be delayed due to simultaneous high-volume data transfers, such as MRI image backups. Such latency can negatively impact timely medical interventions and pose serious risks to patient safety.

Lack of Traffic Prioritization

Traditional networking devices, such as routers and switches, generally lack the capability to dynamically classify and prioritize data packets based on their content or criticality. As a result, there is no effective distinction between mission-critical healthcare data and non-essential user traffic. This limitation becomes particularly problematic under heavy network load conditions, where the performance of critical data flows is compromised, ultimately reducing the overall reliability of the system.

The presence of these challenges clearly indicates that existing hospital networks are insufficient to meet the stringent requirements of modern healthcare applications, particularly in terms of low latency, high reliability, and efficient traffic prioritization. Therefore, the need for more flexible, dynamic, and intelligent network management solutions has become inevitable.

4. Proposed Methodology (The Solution)

To address the limitations of traditional hospital network infrastructures, this project proposes a next-generation network architecture based on Software-Defined Networking (SDN) and Network Slicing technologies. The core idea is to transform the conventional “best-effort” network into a programmable, flexible, and priority-aware system capable of meeting the stringent requirements of critical healthcare applications.

In the proposed approach, the physical network infrastructure is logically partitioned into multiple isolated virtual network segments, known as slices. Each slice is specifically designed and optimized to serve a particular category of traffic with distinct performance requirements. This logical separation ensures that different types of data traffic do not interfere with each other, thereby improving overall network efficiency, reliability, and security.

SDN-Based Centralized Control

The architecture leverages an SDN controller to provide centralized and dynamic network management. The controller continuously monitors network conditions, classifies incoming traffic, and enforces routing and prioritization policies in real time. By decoupling the control plane from the data plane, SDN enables flexible traffic engineering and rapid adaptation to changing network conditions.

Network Slicing Strategy

Within this architecture, the network is divided into three primary slices:

URLLC Slice (Critical)

The Ultra-Reliable Low-Latency Communication (URLLC) slice is dedicated to mission-critical healthcare applications, such as surgical robots, intensive care unit (ICU) monitoring systems, and real-time patient data streams. This slice is configured with the highest priority level and is allocated guaranteed network resources, including reserved bandwidth and minimal queuing delay. The primary objective is to ensure ultra-low latency (below 5 ms) and near-perfect reliability for life-critical operations.

mIoT Slice (Sensor)

The Massive Internet of Things (mIoT) slice is designed for a large number of low-power and low-data-rate devices, such as temperature sensors, humidity sensors, and wearable health monitoring devices. Although these devices generate relatively small amounts of data, they require scalable connectivity and efficient resource utilization. This slice is optimized for handling high device density while maintaining moderate latency and reliability requirements.

eMBB Slice (General)

The Enhanced Mobile Broadband (eMBB) slice serves non-critical applications, including hospital staff communications, administrative systems, and guest internet access. This slice provides high bandwidth capacity but operates with lower priority compared to the URLLC

slice. During periods of network congestion, this slice may experience reduced performance to ensure that critical healthcare traffic remains unaffected.

By implementing this multi-slice architecture, the proposed system achieves strict traffic isolation, efficient resource allocation, and dynamic prioritization. As a result, critical healthcare data is delivered with minimal delay and maximum reliability, while non-essential traffic is managed without compromising overall network performance. This methodology provides a scalable and future-proof foundation for next-generation smart hospital networks.

5. System Components & Architecture

The proposed smart hospital network architecture is built upon a Software-Defined Networking (SDN) and Network Slicing-based multi-layer framework. The system is designed to ensure high performance, scalability, and ultra-low latency communication by integrating three main layers: the control plane, the data plane, and the edge computing layer.

5.1 Control Plane

The control plane represents the centralized intelligence of the network and is responsible for global network management and decision-making. In this architecture, SDN controllers such as ONOS or RYU are utilized to manage the entire network behavior.

The controller continuously monitors the network state, analyzes traffic flows, and determines the appropriate network slice assignment for each incoming data packet. Based on predefined policies and real-time network conditions, it dynamically generates routing rules and enforces them on the underlying infrastructure via the OpenFlow protocol.

By decoupling the control logic from the physical devices, the control plane enables a programmable and flexible network architecture capable of adapting to dynamic healthcare requirements.

5.2 Data Plane

The data plane is responsible for the actual transmission of data across the network. This layer consists of SDN-enabled intelligent switches that support the OpenFlow protocol. Unlike traditional routers, these switches do not make independent forwarding decisions; instead, they execute instructions received from the SDN controller.

Packets are processed based on flow table rules defined by the control plane and are forwarded to the appropriate output ports accordingly. This centralized forwarding mechanism allows fine-grained traffic management, prioritization, and efficient handling of mission-critical healthcare data.

As a result, the data plane ensures predictable and deterministic packet delivery, which is essential for time-sensitive medical applications.

5.3 Edge Nodes and Edge Computing Layer

The edge computing layer is responsible for processing data closer to its source, without relying on centralized cloud infrastructure. Edge nodes are deployed within the hospital environment as local computing units or servers.

This architecture significantly reduces latency by enabling real-time data processing at the network edge. For example, critical signals generated by patient monitoring systems can be analyzed directly at the edge node, triggering immediate alerts without waiting for cloud-based processing.

The integration of edge computing reduces network congestion, improves response time, and plays a crucial role in meeting the strict latency requirements of Ultra-Reliable Low-Latency Communication (URLLC) applications.

This three-layer architecture combines centralized control, intelligent packet forwarding, and distributed edge processing to deliver a highly efficient, scalable, and reliable next-generation hospital network infrastructure.

6. Technical Challenges & Risk Management

The implementation of SDN-based network slicing in critical healthcare environments introduces several technical challenges that must be carefully addressed to ensure system reliability, performance, and security. The main risks and their corresponding mitigation strategies are outlined below.

Risk 1: Violation of Slice Isolation

One of the primary challenges in a network slicing architecture is the potential violation of isolation between different network slices. In scenarios where resource contention occurs, traffic from lower-priority slices may interfere with high-priority critical healthcare traffic, leading to performance degradation in mission-critical applications.

Mitigation Strategy:
To address this issue, a Strict Resource Reservation mechanism is implemented. In this approach, a predefined percentage of network resources, including bandwidth and processing capacity (CPU resources), is permanently allocated and logically isolated for the critical slice (Slice A - URLLC). These resources are hardware-enforced and cannot be dynamically reallocated to other slices, ensuring guaranteed performance for life-critical healthcare services even under heavy network load conditions.

Risk 2: Single Point of Failure in SDN Controller

The SDN controller represents the central intelligence of the entire network architecture. However, this centralized design introduces a potential Single Point of Failure (SPoF), where a controller malfunction or outage could disrupt the entire network operation.

Mitigation Strategy:
To mitigate this risk, a redundant SDN controller architecture is implemented. Multiple controllers are deployed in a distributed manner to ensure high availability and fault tolerance. In the event of a controller failure, a fail-over mechanism automatically transfers control to a backup controller without interrupting network operations. This redundancy ensures continuous network management and maintains system reliability in critical healthcare environments.

Through these risk mitigation strategies, the proposed system enhances fault tolerance, guarantees resource isolation, and ensures uninterrupted operation of mission-critical hospital network services.

7. Simulation & Implementation Tools

To validate the proposed SDN-based network slicing architecture in a controlled and reproducible environment, several simulation and analysis tools will be utilized. These tools are selected to evaluate network performance, verify slicing behavior, and analyze traffic prioritization mechanisms under realistic conditions.

Mininet

Mininet is used as the primary network emulation platform for designing and simulating the proposed hospital network topology. It enables the creation of virtual hosts, switches, and links, allowing researchers to replicate complex SDN environments on a single machine. Through Mininet, different network slices (URLLC, mIoT, and eMBB) can be modeled and tested under varying traffic loads and congestion scenarios.

Wireshark

Wireshark is employed for detailed packet-level analysis of network traffic. It allows the measurement of key performance metrics such as latency, jitter, and packet loss. Additionally, Wireshark is used to verify whether traffic prioritization and slicing policies are correctly enforced by inspecting packet flows, headers, and transmission behavior across different slices.

OpenFlow Protocol

The OpenFlow protocol serves as the fundamental communication interface between the SDN controller and the network switches. It enables the centralized controller to dynamically install flow rules, manage routing decisions, and enforce slicing policies on the data plane. Through OpenFlow, real-time control and programmability of the network infrastructure are achieved, which is essential for implementing the proposed architecture.

Together, these tools provide a comprehensive simulation and validation environment, enabling accurate evaluation of the proposed smart hospital network in terms of performance, reliability, and scalability.

8. Key Performance Indicators (KPIs)

The performance of the proposed SDN-based network slicing architecture for smart hospital environments is evaluated using a set of well-defined Key Performance Indicators (KPIs). These metrics are essential to assess whether the system meets the stringent requirements of ultra-reliable and low-latency healthcare communications.

Latency (End-to-End Delay)

Latency is defined as the total time required for a data packet to travel from the source device to the destination. In critical healthcare applications, minimizing latency is essential for real-time decision-making and emergency response systems.

The target latency for the URLLC (Ultra-Reliable Low-Latency Communication) slice is set to **less than 5 milliseconds (< 5 ms).** This strict threshold ensures that time-sensitive medical data, such as patient vital signals or surgical robot commands, is transmitted without perceptible delay.

Reliability

Reliability refers to the successful and error-free delivery of data packets across the network. In healthcare environments, high reliability is crucial to prevent data loss that could compromise patient safety.

The proposed system aims to achieve a reliability level of **99.999% (five-nines availability)**, ensuring near-continuous operation with minimal downtime and extremely low packet loss rates.

Jitter (Delay Variation)

Jitter represents the variation in packet arrival time and is a critical metric for applications requiring consistent and predictable data transmission. High jitter can lead to synchronization issues, particularly in real-time medical monitoring systems.

The system is designed to maintain **minimal jitter within the critical slice**, ensuring stable and deterministic communication for healthcare applications where timing accuracy is essential.

These KPIs collectively define the performance expectations of the proposed architecture and serve as measurable benchmarks for evaluating the effectiveness of SDN and Network Slicing in smart hospital networks.

9. Conclusion

This study proposes a next-generation smart hospital network architecture based on Software-Defined Networking (SDN) and Network Slicing technologies, designed to meet the strict requirements of modern critical healthcare systems. The primary objective of the proposed framework is to transform traditional hospital networks, which are typically static and best-effort in nature, into intelligent, adaptive, and policy-driven infrastructures capable of supporting ultra-reliable and low-latency communication (URLLC).


The integration of SDN introduces centralized and programmable network control, enabling dynamic traffic management, real-time decision-making, and fine-grained resource allocation. In parallel, Network Slicing allows the physical network infrastructure to be logically partitioned into multiple isolated virtual networks, each optimized for specific service requirements such as critical medical applications, sensor-based monitoring systems, and general-purpose user traffic. This separation ensures strict traffic isolation, predictable performance, and efficient utilization of network resources.


Through this architecture, mission-critical healthcare services such as surgical robotics control, intensive care monitoring, and emergency response systems are prioritized over non-critical traffic, significantly reducing latency and minimizing the risk of network congestion. Furthermore, the incorporation of edge computing further enhances system responsiveness by enabling local data processing close to the source, thereby reducing dependency on centralized cloud infrastructure.

The proposed system also demonstrates strong scalability and adaptability, making it suitable for future expansion in large-scale healthcare environments. Its modular design allows seamless integration with emerging technologies such as 5G/6G networks, artificial intelligence-based traffic optimization, and distributed cloud computing systems. In particular, the envisioned integration with cloud-based consensus mechanisms (e.g., Paxos and State Machine Replication) ensures end-to-end data consistency, reliability, and fault tolerance across both network and computation layers.


In conclusion, this architecture not only improves the performance and reliability of hospital communication systems but also redefines the role of networking infrastructure in healthcare environments. By evolving from a passive data transport system into an intelligent, life-critical decision-support infrastructure, the proposed model lays a strong foundation for future 6G-enabled smart hospitals and next-generation digital healthcare ecosystems.

Diagrams and Graphs





Smart Hospital SDN Architecture



Proposed Mininet Network Topology

