

TaskFlow — Phase 1 Routing & Component Communication Reference

Last updated: covers Auth, Layout, Dashboard, Projects, Tasks, Kanban, Team, Settings, NotFound, and Shared.

1. Routing (app.routes.ts)

```
export const routes: Routes = [
  { path: '', redirectTo: 'login', pathMatch: 'full' },

  // Full screen – no Sidebar/Header
  { path: 'login', component: Login },
  { path: 'signup', component: Signup },

  // Everything below renders inside MainLayout (Sidebar + Header +
content)
  {
    path: '',
    component: MainLayout,
    children: [
      { path: 'dashboard', component: Dashboard },
      { path: 'projects', component: Projects },
      { path: 'projects/:id', component: ProjectDetails },
      { path: 'kanban', component: KanbanBoard },
      { path: 'team', component: Team },
      { path: 'settings', component: Settings },
      // Task Details route – not yet added, pending decision:
      // full page (/tasks/:id) vs. modal/panel like
      CreateTaskDialog
    ],
  },

  // Must stay LAST – catches unmatched URLs
  { path: '**', component: NotFound },
];
```

URL	Component	Layout?
/	—	redirects to /login
/login	Login	no
/signup	Signup	no
/dashboard	Dashboard	yes
/projects	Projects	yes
/projects/:id	ProjectDetails	yes
/kanban	KanbanBoard	yes
/team	Team	yes
/settings	Settings	yes
anything else	NotFound	no

Navigation directive used throughout: routerLink in templates only — no component ever injects the Router service (Phase 1 rule). The one exception worth knowing: reading :id from the URL

(ActivatedRoute) hasn't been wired up anywhere yet — ProjectDetails currently takes its data via @Input() with a mock fallback instead of pulling the real route param.

2. Auth

Component	Selector	Inputs	Outputs	Notes
Login	app-login	—	—	Imports RouterLink for the “Sign up” link
Signup	app-signup	—	—	Imports RouterLink for the “Log in” link

No parent/child relationship between the two — they're siblings, linked only via routerLink.

3. Layout shell

```
MainLayout
├─ Sidebar
├─ Header
│   └─ UserMenu
└─ <router-outlet> (page content)
```

Component	Selector	Inputs	Outputs	Notes
MainLayout	app-main-layout	—	—	Composes Sidebar + Header + router-outlet
Sidebar	app-sidebar	—	—	Static navItems[], uses routerLink + routerLinkActive
Header	app-header	—	—	Owns mock user + isUserMenuOpen state
UserMenu	app-user-menu	user, isOpen	logoutClicked	Child of Header — classic parent-owns-state, child-emits-event pattern

4. Dashboard

```
Dashboard
├─ StatCard (×4, looped)
├─ TaskSummary
├─ RecentProjects
└─ ActivityList
```

Component	Selector	Inputs	Outputs	Notes
Dashboard	app-dashboard	—	—	Owns stats[], feeds StatCard via *ngFor
StatCard	app-stat-card	label, value, icon, trend, trendPositive	—	Fully generic, driven entirely by @Input()
TaskSummary	app-task-summary	—	—	Holds its own mock statusGroups[] internally
RecentProjects	app-recent-projects	—	—	Holds its own mock projects[] internally
ActivityList	app-activity-list	—	—	Holds its own mock activities[] internally

Flagged for later: TaskSummary, RecentProjects, ActivityList don't take data via @Input() yet — once a real API/service exists, Dashboard would likely own the data and pass it down like it does for StatCard.

5. Projects

Projects

- └─ ProjectCard (×N, looped)
- └─ CreateProjectDialog

ProjectDetails

- └─ ProjectMembers

Component	Selector	Inputs	Outputs	Notes
Projects	app-projects	—	—	Owns projects[] + dialog open/close state
ProjectCard	app-project-card	project	cardClicked	Exports the shared Project interface
ProjectDetails	app-project-details	project (mock fallback)	—	Composes ProjectMember
ProjectMembers	app-project-members	members	—	Child of ProjectDetail
CreateProjectDialog	app-create-project-dialog	isOpen	closed, created	No FormGroup — inputs are unbound, “Create” just emits the event

6. Tasks

Tasks

- └─ TaskFilters
- └─ TaskCard (×N, looped)
 - └─ TaskStatusBadge
- └─ CreateTaskDialog

TaskDetails

- └─ TaskStatusBadge

Component	Selector	Inputs	Outputs	Notes
Tasks	app-tasks	—	—	Owns tasks[] & dialog state
TaskCard	app-task-card	task	cardClicked	Exports shared Task interface
TaskStatusBadge	app-task-status-badge	status	—	Shared across Tasks AND Kanban
TaskFilters	app-task-filters	—	statusChanged	Local activeSt state for chip styling; emits 1 but Tasks does actually filter 1
TaskDetails	app-task-details	task (mock fallback)	—	Not routed yet see open ques below
CreateTaskDialog	app-create-task-dialog	isOpen	closed, created	Same no-FormGroup pa as CreateProjectD

7. Kanban

KanbanBoard

- └─ KanbanColumn (×3: To Do / In Progress / Done)
 - └─ KanbanTask (×N, looped)

Component	Selector	Inputs	Outputs	Notes
KanbanBoard	app-kanban-board	—	—	Owns full tasks[], splits into 3 groups via getters (todoTasks, inProgressTasks, doneTasks)
KanbanColumn	app-kanban-column	title, tasks, accentColor	taskClicked	Bubbles clicks up from KanbanTask
KanbanTask	app-kanban-task	task	cardClicked	Compact variant of TaskCard, reuses the same Task interface

Known duplication (flagged on purpose): Tasks and KanbanBoard each hold their own copy of mock task data. This is exactly where a shared TaskService belongs once real data exists — both would inject it instead of duplicating the array.

8. Team

Team

└─ MemberCard (×N, looped)

MemberDetails (standalone, mock fallback)

Component	Selector	Inputs	Outputs	Notes
Team	app-team	—	—	Owns members[]
MemberCard	app-member-card	member	cardClicked	Exports shared MemberCard interface
MemberDetails	app-member-details	member (mock fallback)	—	Not routed yet, same pattern as ProjectDetails/TaskDetails

9. Settings & NotFound

Component	Selector	Inputs	Outputs	Notes
Settings	app-settings	—	—	Local activeTab state (Profile/Notifications/Settings) all visual-only
NotFound	app-not-found	—	—	Uses routerLink back to /dashboard

10. Shared (built, not yet wired into other components)

Component	Selector	Inputs	Outputs	
Button	app-button	variant, size, disabled, fullWidth, type	clicked	Content via <Content>
Modal	app-modal	isOpen, title, maxWidth	closed	Content via <Content> replace the overlay in CreateProjectModal
Avatar	app-avatar	initial, size, status	—	Could replace circle markup TaskCard, MemberCard
Badge	app-badge	text, variant	—	Could replace the status pill ProjectCard/MemberCard
EmptyState	app-empty-state	icon, title, description, actionLabel	actionClicked	Not used anywhere currently handle case

Loading	app-loading	size, fullPage, label	—	Not used anywhere once real async
Pagination	app-pagination	currentPage, totalPages	pageChanged	Not used anywhere lists (Probably have real data)
Search	app-search	placeholder	searchChanged	Could replace inputs in Header

Summary — communication pattern used everywhere

- **Parent → Child:** @Input() for data (project, task, member, user, etc.)
- **Child → Parent:** @Output() + EventEmitter for events (cardClicked, closed, created, logoutClicked, statusChanged)
- **Services:** none yet — every feature currently owns and duplicates its own mock data. First real candidate for a shared service is Task data between Tasks and Kanban.
- **Router:** routerLink / routerLinkActive only, no component injects Router or ActivatedRoute — consistent with the Phase 1 rule.

Open items

1. TaskDetails and MemberDetails exist but have no route yet — need a decision (full page vs. panel/modal) before wiring /tasks/:id and /team/:id.
2. Shared components (Button, Modal, Avatar, Badge, Search) are built but not yet swapped into the features that duplicate their functionality.
3. No service layer yet — expected, since Phase 1 is UI-only with mock data everywhere.