

CENG 280

Formal Languages and Abstract Machines

Spring 2022-2023

Homework I - Sample Solutions

Question 1

a) False. Strings are by definition are of fixed length, hence a countable set, whereas real numbers are uncountably infinite.

Note that answers arguing about the lack of the symbols ‘-’ or ‘.’ did not get any grades. Similarly, stating that irrational numbers have infinite digits, hence, cannot be represented got no grades. For example, the set $\{-1, -0.5, \pi, \sqrt{2}\}$ includes all the ‘violating’ cases, but can be represented with strings over the given alphabet: we can say 00 represents -1 , 01 represents -0.5 , 10 represents π and 11 represents $\sqrt{2}$. Main root of confusion seems to be that representations are confused with exact constructions.

b) False. The set of all finite representations is a countable set, whereas the set of languages over an alphabet is uncountably infinite.

Similar to **Q1a**), arguments that do not focus on the countability of the two sets did not get any points.

c) True. Zero repetition of a , followed by two repetition of b , followed by one repetition of a and lastly zero repetition of b .

d) False. Although the regular expression contains all strings that has ab as prefix, it also contains other strings such as aab .

Question 2

a) (20 points) Give each of K , Σ , δ , s , F .

$K : \{q_0, q_1, q_2, q_3\}$

$\Sigma : \{a, b\}$

$s : \{q_0\}$

$F : \{q_0, q_1, q_2\}$

$\delta :$

$$\begin{aligned}
\delta(q_0, a) &= q_1 \\
\delta(q_0, b) &= q_0 \\
\delta(q_1, a) &= q_1 \\
\delta(q_1, b) &= q_2 \\
\delta(q_2, a) &= q_3 \\
\delta(q_2, b) &= q_0 \\
\delta(q_3, a) &= q_3 \\
\delta(q_3, b) &= q_3
\end{aligned}$$

b) (20 points) Input is *abbaabab*. States are as following;

$q_0, q_1, q_2, q_0, q_1, q_1, q_2, q_3, q_3$.

Since it ends at q_3 which is not an accept state, the input is rejected by the DFA.

Question 3

This question aims to aid you in understanding the proof of **Theorem 2.2.1** by reusing its notation and walking through the conversion process step by step.

a)

$$\begin{aligned}
E(q_0) &= \{q_0, q_2\} \\
E(q_1) &= \{q_1\} \\
E(q_2) &= \{q_2\} \\
E(q_3) &= \{q_3, q_0, q_2\} \\
E(q_4) &= \{q_4, q_2, q_3, q_0\}
\end{aligned}$$

b) The erroneous steps are 4 and 5.

Step 4: The given instruction defines F' as $F' = \{Q \subseteq K \mid Q \subseteq F\}$. This is wrong, since we need to include states $Q \in K'$ that include *any of the* states $q \in F$ into the newly formed set F' . In terms of the textbook: $F' = \{Q \subseteq K \mid Q \cap F \neq \emptyset\}$.

Step 5: The new transitions should return the unions of the *empty closures* of the states reachable from the other states. In terms of the textbook:

$$\delta(Q, a) = \bigcup \{E(p) \mid p \in K \text{ and } (q, a, p) \in \Delta \text{ for some } q \in Q\}$$

Step 1: Just a restatement of the textbook's $K' = 2^K$.

Step 2: The two automata use the same alphabet. Note here that e is a special symbol and is not included in the alphabet of the NFA.

Step 3: This would be wrong if we hadn't restricted the set of considered NFAs to those which did not have empty-transition from the starting state. However, with this restriction, $E(s) = \{s\}$ which is the new starting state defined by the instructions.