


CS188: Exam Practice Session 3

Q1. Game Tree Variant

Pacman is going to play against a careless ghost, which makes a move that is optimal for Pacman $\frac{1}{3}$ of the time, and makes a move that minimizes Pacman's utility the other $\frac{2}{3}$ of the time.


(a) Fill in the correct utility values in the game tree below where Pacman is the maximizer:



(b) Draw a complete game tree for the game above that contains only max nodes, min nodes, and chance nodes.

Q2. Alpha-Beta Pruning


The number of nodes pruned using alpha-beta pruning depends on the order in which the nodes are expanded. For example, consider the following minimax tree.



In this tree, if the children of each node are expanded from left to right for each of the three nodes then no pruning is possible. However, if the expansion ordering were to be first Right then Left for node A, first Right then Left for node C, and first Left then Right for node B, then the leaf containing the value 4 can be pruned. (Similarly for first Right then Left for node A, first Left then Right for node C, and first Left then Right for node B.)


For the following tree, give an ordering of expansion for each of the nodes that will *maximize the number of leaf nodes* that are never visited due the search (thanks to pruning). **For each node, draw an arrow indicating which child will be visited first. Cross out every leaf node that never gets visited.**

Hint: Your solution should have three leaf nodes crossed out and indicate a child ordering for six of the seven internal nodes.



Q3. Utilities

Pacman is in a dilemma. He is trying to maximize his overall utility in a game, which is modeled as the following game tree.



The left subtree contains a utility of 12. The right subtree contains an unknown utility value. An oracle has told you that the value of the right subtree is one of -3 , -9 , or 21 . You know that each value is equally likely, but without exploring the subtree you do not know which one it is.

Now Pacman has 3 options:

1. Choose left;
2. Choose right;
3. Pay a cost of $c = 1$ to explore the right subtree, determine the exact utility it contains, and then make a decision.

(a) What is the expected utility for option 3?

(b) For what values of c (for example, $c > 5$ or $-2 < c < 2$) should Pacman choose option 3? If option 3 is never optimal regardless of the value for c , write None.