LEFT-01 Widgets report every thirty seconds when they have a clear link to the hub.

LEFT-02 A hub supports up to fifty widgets on a single radio channel.

LEFT-03 Place the hub at a central height, away from metal cabinets and microwave ovens.

LEFT-04 The status light shows whether the hub is connected to the cloud.

LEFT-05 Pairing requires holding the widget button for three seconds.

LEFT-06 Battery life is about two years at the default reporting interval.

LEFT-07 Lowering the reporting interval shortens battery life accordingly.

LEFT-08 Firmware updates install overnight when the hub is idle.

LEFT-09 Each widget keeps its own calibration offset after a restart.

LEFT-10 Remove a widget from the device list before reusing its serial number.

LEFT-11 The export endpoint returns CSV files for offline analysis.

LEFT-12 Support can read the diagnostic log from the device page on request.

RIGHT-01 Alerts can be scoped to one widget, a group of widgets, or a whole site.

RIGHT-02 Every rule chooses how long a condition must hold before it fires.

RIGHT-03 Snoozing silences notifications but keeps the event in the feed.

RIGHT-04 Channels include email, chat webhooks and text messages.

RIGHT-05 Dashboards refresh every fifteen seconds while the page is open.

RIGHT-06 Charts can show up to ninety days of history at full resolution.

RIGHT-07 Exported charts include the calibration offset that was applied.

RIGHT-08 Teams can share saved views with read-only access.

RIGHT-09 Administrators control which members can create alert rules.

RIGHT-10 Audit events record who changed a rule and when.

RIGHT-11 The mobile app shows the same feed as the web dashboard.

RIGHT-12 Offline mode queues acknowledgements until the connection returns.

Continuation notes. This page carries general reminders about storage and labelling. Keep spare widgets in a dry drawer at room temperature, and label each one with the site name before it leaves the office. Batteries should be replaced only by trained staff.

Continuation notes. This page carries general reminders about storage and labelling. Keep spare widgets in a dry drawer at room temperature, and label each one with the site name before it leaves the office. Batteries should be replaced only by trained staff.

Continuation notes. This page carries general reminders about storage and labelling. Keep spare widgets in a dry drawer at room temperature, and label each one with the site name before it leaves the office. Batteries should be replaced only by trained staff.

Continuation notes. This page carries general reminders about storage and labelling. Keep spare widgets in a dry drawer at room temperature, and label each one with the site name before it leaves the office. Batteries should be replaced only by trained staff.