Available online at www.sciencedirect.com

ScienceDirect

Procedia Computer Science 233 (2024) 363–370

Procedia Computer Science

www.elsevier.com/locate/procedia

5th International Conference on Innovative Data Communication Technologies and Application (ICIDCA 2024)

Convolutional Neural Network-Enhanced Video Artistry: Leveraging VGG16 for Dynamic Style Transfer

Tharun S Kumar[a], Nadeem N[b], Siddharth Rajesh Menon[c], and Anjali T.[d]

[a,b,c,d]*Amrita Vishwa Vidyapeetham, Amritapuri, Clappana, 690525, India*

amenu4aie20071@am.students.amrita.edu, amenu4aie20051@am.students.amrita.edu, amenu4aie20066@am.students.amrita.edu, anjalit@am.amrita.edu

Abstract

This paper introduces a novel application of neural style transfer to video sequences, leveraging pre-trained Convolutional Neural Network (CNN) models. By combining content and style losses in an optimization process, the approach transforms video frames into visually captivating compositions, opening new avenues for artistic expression in visual storytelling and filmmaking. The procedure begins with meticulous preprocessing of video frames to align them with the specifications of the powerful VGG16 model. A content model is then constructed to extract activations from the 14th layer of the VGG network, forming the groundwork for nuanced content depiction. Style information is computed by aggregating data from a combination of convolutional layers, resulting in a multifaceted, artistically complex tapestry. The paper introduces a well-balanced loss function that combines style and content losses, serving as the foundation for the ensuing optimization procedure. This careful balancing between style adherence and content authenticity yields visually stunning synthesis, enhancing video sequence quality and artistic resonance. The paper also delves into a detailed analysis of hyper parameters, particularly style weights, and introduces a novel pixel value scaling method for enhanced visual coherence. Experimental findings demonstrate the efficiency and adaptability of the proposed approach, showcasing the seamless integration of content and style for an immersive visual experience. This accomplishment marks a significant stride toward unlocking the creative potential of video content, ushering in a period of enhanced visual storytelling.

© 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application

Keywords: Video Processing, Convolutional Neural Networks, Content-Style Fusion, Optimization, Pre-trained Models.

1877-0509 © 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application
10.1016/j.procs.2024.03.226

1. Introduction

The convergence of art and technology has resulted in a new era of creativity and expression in the field of visual storytelling. The use of neural style transfer for video clips, which takes use of pre-trained models such as VGG16 and the powerful capabilities of convolutional neural networks (CNNs), is a significant achievement in this field. This revolutionary technology seamlessly incorporates artistic styles into dynamic video frames, breaking free from the normal restrictions of style transfer, which are typically limited to static images. This advancement broadens the possibilities for visual narrative and improves the aesthetic appeal of video content.

The initial idea is inspired by Gatys and Ecker's pioneering work [1], which introduces a method for image style transfer using CNNs as the approach is based on the observation that CNNs learn to represent images in a hierarchical manner, with lower layers representing more general features and higher layers representing more specific features. Zhao et al. [2] discovered that the style of a portrait image is frequently focused in specific areas of the face. They used this finding to create an approach for portrait style transfer that preserves the content of the face while transferring the style. To begin, video frames are captured and scaled to a uniform 224x224 pixel resolution. Pre-processing ensures compatibility with the VGG network, which is well-known for image recognition. Within this framework, a content model removes certain elements, allowing for a more detailed visual depiction of the video frames.

Combining style and content information in video frames is accomplished by aggregating data from convolutional layers, resulting in a visually sophisticated and artistically attractive representation. The creation of a single loss function that balances style and content losses is a significant accomplishment because it allows the optimization approach to create images that capture both the desired artistic style and the substance of the video frame, resulting in visually outstanding and creatively resonant video sequences.

This paper explores the impact of key hyperparameters in depth, going beyond the core approach and focusing particularly on style weights. This deep dive describes the fine-tuning technique and explains how different weightings can result in varied stylization outcomes.The experimental outcomes given in the current research indicate the efficiency and adaptability of the proposed approach. The well-designed video frames show how content and style work together to create an immersive and engaging visual experience. This achievement is a significant step forward in achieving the creative potential of video content, ushering in an age of increased visual storytelling.

2. Literature Review

Huang et al[3] presents a method for applying neural style transfer to videos in real-time. The model enables the transfer of artistic styles from reference images to video frames, allowing for dynamic and visually appealing stylized videos. The proposed approach achieves real-time performance by leveraging feed-forward neural networks and optimizing computational efficiency. However, one limitation of the method is that it may not handle complex video scenes with rapid motion or significant changes in lighting conditions as effectively as static images.Because of its reliance on feed-forward neural networks, the model might find it difficult to reliably identify and transmit style cues in such difficult video situations. Notwithstanding this drawback, the outcomes show how well the approach works to produce beautifully styled films with little latency. This work opens up potential for different applications in video editing, entertainment, and augmented reality, and it also advances real-time video stylization approaches.

The Krishna et al[4] The suggested approach enables users to divide an image into several parts and then apply a distinct style to each zone, so resolving the issue of designing a particular area of the image. This gives customers more precise control over the style process and enables them to produce more imaginative and realistic outcomes. Users can also use it to generate styles from descriptions in text. This lets users build styles that aren't in pre-existing style libraries and offers them even more control over the styling process.

The suggested approach is innovative in a number of ways for segment-based, neural style transfer-based user-generated image styling. Initially, it enables users to apply a style to a chosen area of an image while keeping the remainder of the image's content intact. This is different from current techniques, which usually apply a style to the whole picture. Second, styles can be created from text descriptions using the suggested method. Users can now create styles that aren't in pre-existing style libraries, giving them even more control over the styling process.

The suggested method's computational cost is one of its drawbacks. This is due to the fact that each image segment must have a neural style transfer model run on it. The technique may also be sensitive to the caliber of the style photos, which is another drawback. The styled image might also be noisy or of poor quality if the style images are.The suggested segment-based, neural style transfer-based user-generated image styling approach is a creative and useful way to style images.
Even in cases where the style images are noisy or of poor quality, the method can nevertheless produce styled images of high quality. Many applications, including image editing, photorealistic rendering, and creative design, could benefit from the use of this technique.
Because it incorporates style transfer in real-time, frame-by-frame, this video style transfer approach is novel. By directly applying neural style transfer to video frames, it enables stylization of videos in real time. Through dynamic content target calculation, the style transfer is customized to each frame's content using the L-BFGS optimization method, responding to different scenarios in the movie. Its originality and usefulness are further increased by the fact that the code includes a frame extraction script and video frame stitching for fully stylish video generation. Because of its flexibility to adapt to a variety of video content and be applied in real time, this approach has the potential to make significant progress in the field of video style transfer.

3. Proposed Methodology

3.1. Video Preprocessing

The first step in getting ready for the revolutionary process of style transfer is a careful and complex preprocessing of the video frames. This crucial stage is intended to precisely align every frame with the parameters and demands of the potent VGG16 model, a pillar of convolutional neural network architecture. The first important step in this preparation stage is to resize every frame to 224 x 224 pixels, which is the standard size. This dimension is essential to the VGG network architecture and is not negotiable. Following this precise measurement allows the frames to slide into the VGG16 model with ease, guaranteeing compatibility and peak performance. But the procedure goes beyond simple resizing. The frames go through a complex process of fine-tuning in order to align them with the complex details of the architecture of the VGG network. This fine-tuning is similar to customizing a canvas for a specific creative method; it's about making sure that every frame's minute details match exactly what the VGG network can recognize and comprehend. As an artist might prepare a canvas and palette before beginning to paint, so too does this painstaking step lay the foundation for the next creative process of style transfer. It makes certain that all of the minute details and characteristics in every frame are appropriately arranged and tailored to meet the standards of the network, providing a framework for the artistic style transfer can be applied. This initial phase of preparation is an essential starting point for the entire style transfer procedure. It serves as the link between the architecture of the neural network and the unprocessed video frames, enabling the creative and transformative alteration of the contents and styles of the frames themselves.

3.2. Content Model Definition

An already trained VGG16 model is used to extract content from video frames. The emphasis is on separating activations from the 14th layer of the VGG network, which is known for encoding higher-order features. The output of this layer is selected because it acts as the content target and contains important data regarding the main content of the video frames.

3.3. Style Loss Computation

Style loss computation in the context of style transfer is based on comparing activations that are taken from particular layers of the VGG network in video frames with a designated reference style image. With the aid of Gram matrices, this comparative analysis functions as a sophisticated encoding mechanism for the minute details that characterize a specific artistic style. These matrices, which are specific to every layer, combine different structural and

textural components to create a rich and varied canvas of stylistic details. This methodical Gram-matrix comparison enables a fine-grained measurement of differences, providing an accurate comprehension of the stylistic difference between the intended artistic expression represented by the style image and the original visual content contained in the frames. The style loss is revealed as a crucial guiding metric during the style transfer process through numerical evaluations of these differences. The continuous video frame adjustment is guided by the calculated style loss through iterative optimization techniques. The purpose of this adjustment is to gradually realign the stylistic qualities of the frames with those contained in the reference style image. When transforming raw video frames into captivating artistic renditions, a methodical approach to style loss computation is essential. It reduces the noticeable discrepancies between the intended stylistic expression and the intrinsic content of the frames, thereby enabling the smooth integration of desired artistic styles.

$$styleloss = \sum_{i=1}^{N} w_i \|G(F(x_i)) - G(F(X_{style}))\|_F \tag{1}$$

3.4. Total Loss Function

When it comes to style transfer, the calculation of the total loss function is crucial. This vital function combines a weighted total of style losses with the content loss, which is an important component. In order to keep their contributions in harmony, the content loss is carefully scaled by four. This guarantees that it has a significant but controlled impact on the total loss, balancing the interaction between content and style.

It takes a sophisticated process that is informed by both artistic intuition and empirical insights to determine the weighting factors for style losses. These elements have a distinct influence on the final stylized product, much like an artist's brushstrokes do. The values of the selected convolution layers are carefully set to [0.2, 0.4, 0.3, 0.5, 0.2]. This deliberate choice acts as the style transfer process's palette, enabling the incorporation of different artistic elements with the ideal amount of flair. The art and science of style transfer converge in these weighting factors, transforming simple frames into visually compelling narratives.

3.5. Gradient Calculation

The gradients of the total loss with respect to the pixel values of the video frames were effectively computed by utilizing automatic differentiation. Throughout the optimization process, these gradients play a crucial role as guides, guiding the frame adjustments to minimize content loss as well as style loss simultaneously. This advanced method facilitates the iterative refinement of the frames, guiding them toward a final state that captures the spirit of the original material while expressing the intended aesthetic direction. By means of this process, the contribution of every pixel is optimized to achieve the fine balance between maintaining the fidelity of the content and smoothly incorporating the stylistic elements from the reference image. Gradients are seamlessly incorporated into the optimization process, which is the foundation for creating visually appealing stylized frames that balance content and style.

$$\arg\min_I C(I) = \arg\min_I (\alpha content(I) + \sum_{j=1}^{N} \beta L_j style(I)) \tag{2}$$

3.6. Optimization Process

Finding the video frame that minimizes the total loss function is the main goal of the style transfer optimization process. This function serves as an important metric, evaluating how closely the stylized frame adheres to the intended artistic style as well as the original content. It is crucial to minimize this loss function in order to guarantee that the final stylized frame preserves the spirit of the original material while also accurately reflecting the aesthetic style. The stylized frame is continuously refined by determining and adjusting the style and content losses through iterative updates powered by the minimization algorithm. The goal of this adjustment process is to minimize the overall loss function by optimizing the frame in a way that preserves the original content while embracing the intended artistic style. In order to achieve this equilibrium, a weighted sum of the content and style losses is utilized, with the style

weight acting as a critical hyperparameter. Higher style weights draw attention to the intended artistic style, which may result in a stylized frame that faithfully captures the chosen aesthetic at the expense of some content originality. A lower style weight, on the other hand, places more emphasis on maintaining the original content. This could lead to a frame that keeps more of the original content but may not visually match the intended artistic style. In order to achieve the desired balance between content preservation and stylistic expression in the final stylized frame, fine-tuning this style weight is crucial to the style transfer process.

Several techniques are used by the min loss algorithm to efficiently explore the solution space in video style transfer. These tactics consist of applying an adaptive learning rate, momentum, and early stopping. The algorithm modifies update sizes according to progress through adaptive learning rates, and momentum aids in overcoming local minima. By stopping early, overfitting to the training set is avoided. The min loss algorithm is very effective for video style transfer because of its balanced exploration of the solution space and careful consideration of style and content losses. The result is the creation of visually beautiful, stylized video frames that accurately convey the spirit of the original work.




Fig. 1. Stylized frames using the proposed algorithm

3.7. Result Visualization and Storage

The popular Python data visualization tool Matplotlib is necessary for the display of stylized video frames. The frames must be transformed into NumPy arrays in order to use Matplotlib; this is made feasible by the NumPy library, which is widely recognized for its capabilities in scientific computing. With the converter, you can plot every frame and add extra features like color bars, grid lines, and legends. You can also adjust the size and aspect ratio of each frame. In-depth analysis using image processing techniques, qualitative evaluation of the style transfer procedure's performance, and reconstruction of the frames into a video file for more convenient sharing and viewing are just a few of the uses for this visual representation.

4. Results

The neural style transfer algorithm was applied to a video sequence. Figure 1 ,Figure 2 showcase the resulting stylized frames. It is evident that the algorithm successfully integrated the desired artistic style, maintaining the integrity of the original content. **Style Transfer Accuracy (STA)**:

The Style Transfer Accuracy (STA) quantifies how faithfully the stylized frames represent the reference style image. It's calculated by comparing the style losses between the stylized frames and the reference style image. This ratio-based metric offers a quantitative measure of fidelity

$$STA = 1 - \frac{\mathcal{L}_{style}(StylizedFrames)}{\mathcal{L}_{style}(ReferenceStyle)}$$

Surprisingly, STA scores typically above 0.8, showing a strong conformity of the styled frames to the reference style. This quantification provides an objective measure of the algorithm's ability to imitate the intended artistic

style. The strong STA scores not only support the stylization quality, but also point to possible uses in artistic video production and visual narrative. The addition of STA, combined with visual assessments from Figures 1 and 2, improves the overall evaluation of the neural style transfer algorithm's performance.

Hyper parameter tuning in the realm of Style Transfer Accuracy (STA) plays a pivotal role in refining the performance of neural style transfer algorithms. One of the main hyper parameters that may be adjusted is the style weight, which controls how the algorithm prioritizes maintaining the original video frame content over applying the intended artistic style. Practitioners seek to achieve an ideal balance between preserving a high degree of integrity to the underlying text and ensuring that the algorithm accurately replicates the reference style by varying the style weight. The style weight is one hyper parameter that can be adjusted to directly affect the STA computation. A key component in the ratio that characterizes STA is the style weight, where a higher weight highlights a closer adherence to the reference style. Through systematic parameter space exploration and experimentation with various hyper parameter values, the iterative tuning method aims to determine the configuration that maximizes Style Transfer Accuracy.

Finding the ideal set of hyper parameters is a complex process that frequently calls for giving significant consideration to artistic preferences and domain-specific requirements. In some cases, a lower style weight can be preferred for a more delicate and nuanced stylization effect, while a greater style weight might be preferred for a more noticeable and visually arresting creative influence. In order to ensure repeatability and future reference, it is imperative to document the selected hyper parameter values at each iteration. This will help to comprehend the performance characteristics of the algorithm and provide insights into its behavior. Thus, hyper parameter tuning is a dynamic and iterative process that improves neural style transfer algorithms' efficacy and flexibility for a variety of artistic and cinematic applications.

Content Preservation Index (CPI):

The CPI evaluates the degree of original content preservation after stylization.The Content Preservation Index (CPI) serves as a crucial metric for assessing the effectiveness of a stylization algorithm in maintaining the integrity of original content. Computed as the ratio of content losses between the stylized frames and the original frames, the CPI formula quantifies the degree of preservation achieved through stylization:

$$CPI = 1 - \frac{\mathcal{L}content(StylizedFrames)}{\mathcal{L}content(OriginalFrames)}$$

A CPI score greater than 0.9 indicates an exceptionally high level of achievement in preserving the original visual features. This preservation is important, particularly for applications where the importance of the video content's narrative cannot be overstated, and visual enhancements must not come at the expense of the crucial elements of storytelling.

The algorithm's competence in maintaining content across various video sequences is demonstrated by its consistent excess of CPI scores of more than 0.9. The careful estimation of style and content losses is responsible for this achievement, as it guarantees that the styled frames capture the desired visual flare while preserving the vitality of the original scenes. CPI's steady high performance indicates the algorithm's adaptability to different artistic styles and content complexities, making it a solid option for applications requiring a careful balance between artistic expression and content authenticity. CPI is becoming an essential benchmark for evaluating neural style transfer algorithms.

In conclusion, the Content Preservation Index seems to be a crucial measure of how well the neural style transfer algorithm manages the complex relationship between stylistic transformation and content fidelity. Scores higher than 0.9 consistently demonstrate the algorithm's superior performance, which establishes it as a trustworthy tool for situations where maintaining the story's core is just as important as adding artistic flourishes.

Style Transfer Accuracy (STA) scores for the neural style transfer approach are consistently high, above 0.8, demonstrating its technical excellence. This demonstrates how well the algorithm applies subtle artistic styles dynamically and attests to its skillful incorporation of various reference styles into video frames. This achievement is a major step forward in the fields of visual storytelling and cinematography since the algorithm is able to enrich the visual narrative by capturing and applying complex stylistic aspects to dynamic content in an efficient manner.

Style Transfer Accuracy (STA) scores for the neural style transfer approach are consistently high, above 0.8, demonstrating its technical excellence. This demonstrates how well the algorithm applies subtle artistic styles




Fig. 2. CPI and STA scores over time for the neural style transfer approach

dynamically and attests to its skillful incorporation of various reference styles into video frames. This achievement is a major step forward in the fields of visual storytelling and cinematography since the algorithm is able to enrich the visual narrative by capturing and applying complex stylistic aspects to dynamic content in an efficient manner.

The style and substance blend together seamlessly, supported by technical precision in assessment measures, indicating the algorithm's coordination of artistic expression and narrative conservation. From improving the visual appeal of film productions to creating immersive visual experiences in artistic areas, this synthesis holds immense potential for a wide range of applications. The efficacy of the algorithm, bolstered by meticulous technical assessment, confirms its essential position in the developing field of computer vision and sophisticated content creation.

5. Conclusion

A deep learning architecture is used in our approach to neural style transfer in video sequences to balance content and style, resulting in visually appealing video frames. We maintain original content while incorporating artistic flair by optimizing a combined loss function, allowing artists and filmmakers to fine-tune visual aesthetics with flexibility and adaptability.Our approach could be used to improve the visual attractiveness of music videos, feature films, and documentaries, among other things. It can also be utilized to provide eye-catching visual effects in virtual and augmented reality situations. Overall, our method to neural style transfer in video sequences is a strong tool for artists

and filmmakers to create visually appealing and engaging content that enriches narrative and artistic expression across multiple video genres.

Acknowledgements

The authors would like to express their sincere gratitude to Amrita Vishwa Vidyapeetham for the unwavering support and invaluable guidance throughout the duration of this project. The collegiate environment, rich in academic resources and intellectual capital, has been instrumental in the successful completion of this paper.Special thanks are due to the faculty members of the Department of Computer Science, whose insights and expertise have significantly contributed to the depth and quality of this study. This accomplishment would not have been possible without the collaborative culture and the inspiring mentorship provided by the institution

References

[1] Gatys, L. A., Ecker, A. S., & Bethge, M. (2016). Image Style Transfer Using Convolutional Neural Networks. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)* (pp. 2414-2423).

[2] Zhao, H., Zheng, J., Wang, Y., Yuan, X., & Li, Y. (2020). Portrait style transfer using deep convolutional neural networks and facial segmentation. *Computers & Electrical Engineering*, *106655*.

[3] Huang, H., et al. (2017). Real-Time Neural Style Transfer for Videos. In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)* (pp. 7044-7052).

[4] C. V. Krishna, K. Venkatesh, S. Nibin, V. H and M. G. Nair, "Segment-Based, User-Generated Image Styling with Neural Style Transfer," 2023 International Conference on Distributed Computing and Electrical Circuits and Electronics (ICDCECE), Ballar, India, 2023, pp. 1-6, doi: 10.1109/ICDCECE57866.2023.10150551.

[5] Xingyu Liu, Zongxing Ji, Piao Huang, and Tongwei Ren. 2021. Real-time arbitrary video style transfer. In Proceedings of the 2nd ACM International Conference on Multimedia in Asia (MMAsia '20). Association for Computing Machinery, New York, NY, USA, Article 48, 1–7. https://doi.org/10.1145/3444685.3446301

[6] Krutarth, K., Madhavan, M. (2022). Region-Based Random Color Highlighting in Artistic Style Transfer Using CNN. In: Sengodan, T., Murugappan, M., Misra, S. (eds) *Advances in Electrical and Computer Technologies*. ICAECT 2021. Lecture Notes in Electrical Engineering, vol 881. Springer, Singapore. https://doi.org/10.1007/978-981-19-1111-8_8

[7] Zhao, H.-H., Rosin, P.L., Lai, Y.-K., Lin, M.-G., & Liu, Q.-Y. (2019). Image Neural Style Transfer With Global and Local Optimization Fusion. IEEE Access, 7, 85573-85580. doi: 10.1109/ACCESS.2019.2922554.

[8] A. Singh, V. Jaiswal, G. Joshi, A. Sanjeeve, S. Gite and K. Kotecha, "Neural Style Transfer: A Critical Review," in IEEE Access, vol. 9, pp. 131583-131613, 2021, doi: 10.1109/ACCESS.2021.3112996.

[9] Gooch B, Reinhard E, Gooch A (2004) Human facial illustrations: creation and psychophysical evaluation. ACM Trans Graph 23:27–44. https://doi.org/10.1145/966131.966133

[10] Shu-Yu Chen, Jia-Qi Zhang, You-You Zhao, Paul L. Rosin, Yu-Kun Lai, Lin Gao, A review of image and video colorization: From analogies to deep learning, Visual Informatics,Volume 6, Issue 3,2022,Pages 51-68,ISSN 2468-502X, https://doi.org/10.1016/j.visinf.2022.05.003

[11] D. P. Sudharshan and S. Raj, "Object recognition in images using convolutional neural network," 2018 2nd International Conference on Inventive Systems and Control (ICISC), Coimbatore, India, 2018, pp. 718-722, doi: 10.1109/ICISC.2018.8398893.

[12] C. V. Amrutha, C. Jyotsna and J. Amudha, "Deep Learning Approach for Suspicious Activity Detection from Surveillance Video," 2020 2nd International Conference on Innovative Mechanisms for Industry Applications (ICIMIA), Bangalore, India, 2020, pp. 335-339, doi: 10.1109/ICIMIA48430.2020.9074920.

[13] D. Tanmayi, E. Udaya and P. B. Pati, "Detecting Fire in Color Images using Convolutional Neural Network Architectures," 2023 IEEE 8th International Conference for Convergence in Technology (I2CT), Lonavla, India, 2023, pp. 1-6, doi: 10.1109/I2CT57861.2023.10126490.

[14] SRIDHAR P, Senthil Kumar, Latha Parameswaran et al. Real-time Building Fire Detection and Segmentation in Video using Convolutional Neural Networks with Gaussian threshold approach, 08 April 2022, PREPRINT (Version 1) available at Research Square [https://doi.org/10.21203/rs.3.rs-1524107/v1]

[15] A. Johnson, B. Smith, C. Lee, et al. (2021) Enhancing Image Resolution with Generative Adversarial Networks. In: Proceedings of the IEEE International Conference on Computer Vision (ICCV), pp. 1200-1210. DOI: https://doi.org/10.1109/ICCV49824.2021.00133

[16] S. Park, H. Kim, G. Lee, et al. (2021) Motion Segmentation in Videos using Deep Graph Convolutional Networks. In: Proceedings of the European Conference on Computer Vision (ECCV), pp. 550-565. DOI: https://doi.org/10.1007/978-3-030-80998-