Available online at www.sciencedirect.com

ScienceDirect

Procedia Computer Science 233 (2024) 288–294

Procedia Computer Science

www.elsevier.com/locate/procedia

5th International Conference on Innovative Data Communication Technologies and Application (ICIDCA 2024)

Diagnosing Diabetes using Machine Learning-based Predictive Models

D Kaviyaadharshani[a], M Nivedhidha[a],R Jeyarohini[b], J Lece Elizabeth Rani[a] , M P Ramkumar[a] , G S R Emil Selvan[a]

[a]*Thiagarajar College of Engineering , Madurai , 625015, India*
[b]*PSNA College of Engineering and Technology, Dindigul 624622, India*

Abstract

Diabetes mellitus is becoming a major health concern causing kidney failure, retinopathy, and other neural diseases and thus becoming a major research area for advancement in machine learning. Analysis of diabetes data is very difficult due to inconsistency and poor data quality, Correlational Mmisodels, and the complex nature of most clinical data. Both diagnosis and treatment are unsuitable algorithms based on machine learning. This prompted us to review the various diabetes standards. Diagnosing diabetes at an early stage necessitates a methodological departure from past practices. The compiled information from all pertinent, independent qualitative investigations with the purpose of fixing the issue of diabetes prediction is discussed in the proposed work. This article discusses the research undertaken in detection of diabetes. The analysis of samples tested for diabetes from different state-of-the-art studies and recommending the best practice is conveyed in this work. Using risk stratification based on machine learning, diabetes-related individuals can be separated from non-diabetic patients.

© 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application

Keywords: Blood Sugar; Retinopathy; Diabetic symptoms; Correlational Model; Machine Learning; Type II Diabetes.

1. Introduction

According to the World Health Organization, this figure could reach 642 million by 2040, which would mean that one tenth of the people would have diabetes mellitus due to sedentary lifestyles and lack of physical exercise. Numerous writers have already undertaken thorough investigation on machine learning algorithms to predict diabetes. Hyperglycemia causes diabetes. Muscles and tissues need glucose. Poor nutrition and inactivity induce type 2 diabetes. Hyperglycemia causes diabetes. Meals may cause insulin failure. Unabsorbed sugar causes diabetes. Diabetes may damage nerves, blood vessels, eyes, kidneys, and other organs. Diabetes has three kinds. Juvenile diabetes damages pancreatic insulin-producing cells [1]. Many researchers have developed and shown machine learning-based diabetes prediction algorithms.

Machine learning-based diabetes prediction algorithms were compared. Research objectives:

- To learn more about the different methods of measuring diabetes.
- Assess and discuss the categorization accuracy of current models.
- Discuss the various characteristics needed to predict diabetes mellitus.
- To find areas in the body of existing literature where research is lacking.
- Provide a comparison of multiple models for diabetes prediction.
- Gradually collect more data on diagnosing diabetes early.

The goal of our examination of various diabetes models is to solve the problem of diagnosing diabetes by locating, analysing, and synthesizing the results of all applicable scientific studies. To achieve our goal of conducting this review, literature

1877-0509 © 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application
10.1016/j.procs.2024.03.218

search on diabetes is done for testing standards and selected relevant products for this review, such as:

- The paper must include several machine learning and prediction strategies for categorizing diabetic data.
- Various pre-processing methods to remove noise from the data must be included in the article.
- A number of performance criteria, such as true negative, sensitivity (Sn), true negative rate, specificity (Sp) and accuracy (ACC), were used to verify the authors' model.
- Comparisons were made between predictive models and numerous diabetes prediction models that already existed.

Given the ever-changing field of predictive analytics for diabetes, a sophisticated approach is necessary to effectively manage the disease's complexity. The International Diabetes Federation (IDF) estimates that 463 million persons worldwide, aged 20 to 79, had diabetes in 2019.According to IDF estimates, if current trends continue, there might be 700 million individuals with diabetes by 2045. In addition, it is crucial to give priority to ethical issues, privacy protections, and the need for clear and understandable models help ensure that predictive analytics is applied correctly in the healthcare industry. Predictive model optimisation is a continuous process that promises to improve patient outcomes by customising treatment plans in addition to improving early diagnosis.

The following is how the study is organized: The paper's Chapter 2 details the literature search we did for the review. Chapter 3 contains a discussion of different diabetes models by different authors, followed by a comparison of different methods based on multiple comparisons in Chapter 4. Then, Chapter 5 draws conclusions after discussing the current issues and challenges of different diabetes testing models.

2. Literature Review

Medical specialists assist patients return to regular life. Diabetes is serious. Decision-making requires classification. Diabetics and non-diabetics are identified and information is improved. Machine Learning Finds Diabetes Dataset Patterns. Machine learning improves healthcare. This research uses machine learning to detect diabetes kinds using medical and personal data. This section summarizes 10 years of research suggestions. Criticize diabetic treatment recommendations for different learning systems. Diabetes research continues. Sun and Zhang developed Neural Networks [1], Random Forest (RF), Decision Tree (DT), and Support Vector Machines (SVM)

Logistic regression (LR) diabetes classification, et al [2]. 128 patients were tested and 459 were trained. Logistic regression categorized 92% of them. It has not been verified against other diabetic models, which is its biggest drawback. Besides that training and testing were created Tafa et al., 2015. Predicting diabetes using SVM, and Naive Bayes (NB) algorithm. He tried three distinct data designs.80 type 2 diabetics and 402 eight-trait persons were in this sample. Naive Bayes and the SVM group had 97.6% accuracy without data, compared to 94.52% and 95.52% of the algorithms. The authors did not give data preparation tools to eliminate bad findings, Karan et al., 2012

ANN computation for diabetes diagnosis in end-to-end three-stage inevitable health system architecture Karan et al., 2012. Sensors and wearable gadgets measure basic parameters. PDAs and PCs connect layer 2's primary and final levels. The third level manages information and community health via strong servers. The neural network identifies the pathogen in subsequent stages. ANN computing powers client-server. PDAs and PCs handle layer 2 master-final system communication. The third level features sophisticated health and business database servers. Artificial neural networks analyse backdrop issues. ANN computing powers client-server. This viral process raises user and server computing and communication needs.

Sisodia et al., 2018 used NB, DT, and SVMs in the Pima Indians Diabetes 2 Journal of Healthcare Engineering dataset. Blood pressure is best predicted by NB. Prior to utilizing ten-fold cross validation, Sisodia divided the data into 10 test sets and 9 training sets. Estimating blood pressure with accuracy, precision, memory, and area under the curve. Neural networks, Naive Bayes, and random forests were all explored by Hussain et al., 2021. Evaluate machine learning approaches using Matthews's correlation coefficient. Kumar et al. [11] used LR, RF and NB study Pima dataset. 79% accuracy beat all three techniques. Olaniyi and Adnan [3] employ multi-layered, feed-forward neural networks or deep learning. The Pima dataset evaluated and analysed the approach. The dataset has 500 training and 268 test values. Normalizing data before preprocessing ensures numerical stability. Divide each attribute by its amplitude to normalize dataset values.

Author estimates 82% Gupta [4]. SVM/Naive Bayes diabetic data analysis. SVM beats Naive Bayes in K-fold cross validation. Kandhasamy et al., 2015 predicted diabetes using the SVM with J48, RF, k-NN, and UCI repository data. The writers utilized unprocessed components. The first phase eliminated data interference. Facts, facts, facts. After the first, the random forest has 100% accuracy and the decision tree 73.82%. et al. The main elements of the Pima diabetes dataset were investigated using PCA and discriminant analysis. The article compares selection. Radial root kernels, k-nearest neighbours, and AdaBoost classify. Perveen, etc. Canadian Primary Care Sentinel Surveillance Network data [5]. Gender, weight, lipids, fasting glucose, diastolic, and systolic blood pressure are recorded. Decision trees, bootstrapping, adaptive reinforcement classifiers.

Using ML methods, Gujral [6] discovered diabetic Retinopathy and neuropathy in early type 2 diabetes diagnosis. ML studies neural networks, principal components, DT, computational genetics, and fuzzy logic. Pima Indians Diabetes Dataset indexes most relevant data. Early diabetes identification decreases mortality. The diabetes hypothesis review concluded that self-diagnosis is unreliable for early detection. Neural networks benefit from SVMs, KPAs, and GAs.

Mamuda et al., 2017 control ML classifiers using scaled conjugate gradient, Levenberg-Marquardt, and Bayes rule. Splitting data into training and testing improves Levenberg-Marquardt.et al. Decision trees, Nearest neighbours, and random forests in local German hospital data. Neural networks diagnosed diabetes for Soltani and Jafarian [7]. The Pima Indians Diabetes dataset is 90% educational and 10% testing. 89 workshops.56% accurate vs 81.49% test. Tigga and Garg examined Pima diabetes data

[8]. Diabetes, BMI, and pregnancy are included. Estimate 75.32% RStudio accuracy. In the Pima Native American diabetes dataset, Yuvraj et al., 2017 employed NB, DT, and RF. Machine learning algorithms identified significant attributes from eight instead of thirteen.

Negi et al., 2016 generated 102,538 values and 49 elements. 64,419 persons had diabetes. Preprocessing recovers missing values and numericizes nominal data. Journal of Healthcare Engineering 3 selects papers using a packaging and rating system. Classifiers boost accuracy to 72%. Mercado et al., 2017 Bayesian Networks employed Hoeffding Trees, Random Forests, j48, JRip, Multilayer Perceptron, and Pima Indians Diabetes datasets. Consistently selecting the best first time improves performance. Four of eight characters are utilized. Age, BMI, diabetes, and diabetic family activities are influences. Hoeffding tree returns 76.2% and 75%. Actually 7%.

On a private dataset of 142,000 electrocardiograms, Swapner et al [9] used convolutional short-term memory networks and neural networks to achieve 90.9% accuracy. This document is unassigned. Increasing globally, it is a chronic disease to have type 2 diabetes mellitus (DM). India has 30 million diabetics and millions at danger. Early diabetes detection and prevention are important. As research has demonstrated, numerous ways have been utilized to evaluate the hypothesis of type 2 diabetes, which increases the illness detection window by analysing variables and regular behaviour, allowing type 2 diabetes prediction without medical testing. Medicine knows their symptoms, illnesses, and health impacts. Healthcare uses type 2 diabetes prediction systems. The model needs to be trained using the prepared data, an appropriate method needs to be selected, and the input variables need to be established. Lekha et al., 2018 collected respiratory data from 25 patients: 5 type 1, 11 healthy, and 9 type 2 diabetes mellitus. The 96% ROC curve skips cross-validation.

3. Prediction Methods of Diabetes

Kamrul Hasan's four-step technique predicts diabetes [16]. The first step removes outliers and adds missing values to the dataset. Outliers deviate from the norm. Because the result greatly affects certain missing numbers, the mean is used instead of the median. Outliers are anomalies. Classify machine learning since it doesn't grasp feature distribution and variety. Equation (1) calculates outcomes.

$$p(x) = \{x, if\ a1 - (\tfrac{3}{2}) * IQR\ \leq x\ \leq a3 + (\tfrac{3}{2}) * IQR, \quad reject\ otherwise \tag{1}$$

Where a1 – first range of features, a3 – third range of features, and IQR - interquartile range of features and P(x) - arithmetic mean of the outlier reading [3], the likelihood that x - the feature vector is in n-dimensional space. Estimated values, the authors identify all missing data values and supplement them with a summary of relevant factors.

$$q(x) = mean\ (x), if\ x = \frac{null}{missed}, x\ otherwise. \tag{2}$$

Where q(x) is the decision's numerical value and x is an equation (2) n-dimensional vector. Scaling normalizes distribution. Diabetes is predicted using four, six, and eight-character selection methods. The five-fold cross-validation method uses one testing data set and four identical training sets. Pima dataset was analyzed using K-NN, RF, AB, Multilayer Perceptron, DT, optimization, and Naive Bayes. Sensitivity, specificity, and ROC were measured. Each deployment benefits from functional and associated selection. Six features optimize classifiers. Diastolic blood pressure elimination and Blood Sugar pedigree are six variables. Optimize settings. K-Neighbors increases leaf size, neighbors, and spacing [7].

Authors pick Gini and consensus separator. Grid search reveals multilayer perceptron hidden layers. Hidden processing counts neurons. MLP loss. Cluster planning and machine learning optimized AUC (Area Under ROC Curve). Optimization assesses Ensemble Classifier. Soft-Weighted Gradient Voting Community. AUC weights samples without class distribution. AdaBoost preprocessing and gradient boosting with associated feature selection achieved 0.95 AUC. This method's developer prioritized AUC [3] above system correctness. To improve sensitivity and specificity, authors emphasized dataset preparation and feature selection. The authors tested numerous classifier combinations using preprocessed datasets with four, six, and eight features, which took time.

Maniruzzaman's method [13] used RF, AB [9], NB [4], and DT [5] on the NHANES dataset. The database includes 9858 people, 760 with diabetes and 9098 without. The writers cleaned up lacking data. 6561 individuals, 5904 non-diabetics, and 657 diabetics were left. Logistic regression, P-value, and variance are used to choose data features Alfian et al., 2018. LR calculates response probability using predictors. Estimate a logarithmic function using least squares technique. and assess the predictor-response association using a logistic regression model. The equation for the logit function is as follows:

$$log\ it\ (P_j) = log_e = \sum_{i=0}^{k} \beta_i X_i \tag{3}$$

Where P_j is the probability that the patient will have diabetes, P_j is the probability that he will not have diabetes, i = 0, 1, 2, k. There are 14 predictors or qualities altogether in this example, and "r" denotes the unknown regression coefficient. P values and odds ratios were calculated for each characteristic using Equation (3) and these regression coefficients. P value is produced through continuous t-testing and discontinuous chi-square testing Pham et al., 2017. Data are analyzed with Stata 14.10. P values under 0.005 are picked. Sets for training and validation were produced. Using a 10-fold cross-validation procedure, 2610 equally

sized chunks of the dataset are divided into training and testing dataset halves. Accuracy of categorisation is assessed through steps. Author estimates average categorization accuracy. After cross-validating relevant features, the authors utilized NB, RF, DT, and AB classifiers. Accuracy, predictive value, and f-measure were assessed. Multiple testing provided the K2, K5, and K10 models 92.54, 92.33, and 92.75 percent accuracy. Logistic regressions and random forest sampling were best.

Jakes method. Diabetes, cancer, and heart disease were studied. Data purification preceded a new machine learning strategy. Nullify missing data and evaluate feature correlations [8]. Zou et al., 2018 Correlation shows data set properties. Predicting using one dataset attribute and discarding the other. Separate training and evaluation data. 70% inspected, 30% evaluated. Compare filtered Naive Bayes and Random Forest classifier results. Diabetes in Pima Indians. Anaconda 4.1 parses. JME7 supplied true/false data. True=1, false=0. The correlation coefficient [16] measures two variables where null values replace missing values and avoid duplication. The authors built a correlogram matrix [5]. Blue is positive, red negative. Pigment density closely correlates. There is a difference between 1- and +1, where 1 - poor correlation and +1 - a perfect correlation. Puzzle matrices were built using correlation coefficients. Accuracy, accuracy, memory, and f1 score all point to diabetes. The accuracy of the training data is 76.72.46, the accuracy of the test data is 98.88, and the accuracy of the random forest is 74.03. An earlier technique eliminates data characteristics and replaces missing values with null values [13]. Results were pre-processed and calculated using Random Forest and Naive Bayes classification methods [4]. The method is evaluated using DBSCAN's comparison of noise inequality. The method outperforms K-word and DBSCAN. Due of the massive training and assessment data, Jackins prioritizes processing time and it improves diagnosis.

The fusion model for diabetes prediction (FMDP) involves two phases: training and assessment [10]. Prioritization, SVM/ANN classification, and algorithm training performance assessment are used to acquire data. UCI Machine Learning Repository references. Cleaning, normalizing, and splitting training and test data are first procedures. SVM and ANN were picked for their problem-solving abilities. Performance evaluation criteria vary. If the model fails the learning requirements, it is trained and the SVM and ANN outputs are integrated using a fuzzy model. Cloud-store a unified training model. Last, the medical records dataset and cloud-based preprocessing model are loaded. Comparing predicted and actual outcomes determines diabetes prediction accuracy.

The proposed methodology uses a set of ML algorithms to improve accuracy, including LR, NB, and RF classifiers. LR is a statistical technique used to predict binary outcomes using probabilities. NB is a probabilistic classifier that assumes feature independence. RF Classifier uses decision tree models to improve predictions. The proposed ensemble [11] uses a soft voting classifier that incorporates probabilistic predictions from multiple models. An ensemble of LR, NB, and RF models determines the final prediction by majority vote.

Machine learning is very effective in the clinical diagnosis of various diseases [35-38]. The proposed TIIDM disease classification system was developed using a collaborative ML approach. It describes how to use machine learning and assembly approaches to construct a practical framework. Process of creating a living system utilizing ML/EL techniques for the TIIDM cognitive framework. The algorithm [12] shows the entire process from entering data to achieving the desired results.

Insulin resistance and hyperglycemia indicate diabetes. Diabetes damages the eyes, heart, kidneys, blood vessels, killing. Machine learning predicts diabetes. Pricing signals development. Diabetes is predicted and diagnosed using machine learning [14]. Specific sampling and unrestricted analysis help diagnose and categories diabetes. Methods: This study supports diabetes diagnosis prediction models. Spearman and polynomial regression improve frame element selection and missing value imputation. RF, SVM, and 2GDNN classify. Grid search and k-fold hierarchical cross-validation modify model hyper parameters and assess prediction performance. Results: The 2GDNN model tests PIMA Indian and LMCH diabetic data with 97.25 and 97.33 accuracy. Conclusion: A robust diabetes prediction and diagnosis model is produced via classifier data preprocessing and hyper parameter optimization using a machine learning framework, outperforming state-of-the-art detection.

Diabetes elevates blood sugar, which is harmful. Lifesaving early detection. 13 binary data classification machine learning models were developed and evaluated using 768 counts and 2000 samples. Excellent 90:10. The validation dataset had 99.40% accuracy for k-means, LGBM, HGB, and decision trees, whereas the first dataset had 85% accuracy for random forest. A broad model [15] trains and validates algorithms that outperform the model on real data using one dataset and another.

4. Comparative Analysis

Predicting diabetes properly remains tough. Many characteristics predict diabetes, but it is hard to detect and utilize for early diagnosis. Thus, predicting traits and attributes is challenging. Despite years of inquiry, this topic remains unanswered. After reviewing the work of many colleagues and researchers, it was determined that it was impossible to forecast data features as the key role and that the optimal decision was 100% assured. Most studies employ NB, SVM, DT, RF, k-NN, multilayer perceptron, and for classification. Researchers are developing effective prediction techniques utilizing iterative neural networks or deep learning.

Kamrul Hasan et al, The authors work on 6 classification algorithms: Random Forest, k-NN, DT, MLP, AB [18] and Extreme GB [6]. Because the authors calculate the entropy of each step of the DT and RF, their technique is exceedingly time- and labour-intensive.

The main objective of the author is to combine AB and GB in order to raise the AUC to around 95%. Maniruzzaman et al. In 2019 [13] devised a method for selecting relevant data elements using logistic regression, likelihood values and likelihood ratio. The authors used the NHANES dataset [19]. This eliminates missing values by making use of notnull() and isnull() to check for missing data and reduces the total number of values from 9858 to 6561. Relating to the selection of sophisticated specific business processes.

In 2020, Jackins et al. [17] introduced a technique in which character correlation was evaluated after substituting zero values for missing data. One characteristic can be deleted and the other used for classification if the correlation between the two features is high. The authors constructed a matrix of correlograms after calculating the correlation between attributes. The method has a very long processing time.

This study predicts diabetes using a combination of ML approaches. Models from SVM and ANN make up the conceptual framework. To identify diabetes, these algorithms make use of a dataset. Based on the results of these models, the presence or absence of a diabetes diagnosis is determined through fuzzy logic. For final prediction, fuzzy rules are applied to the SVM and ANN findings' real output [10]. The integrated models are stored in the cloud.

Diabetic and nondiabetic patients were separated using the Pima dataset. Using accuracy, precision, recall, and F1 scores, are evaluated their method against other cutting-edge strategies. On the PIMA diabetic dataset, the ensemble approach [11] had the greatest values for all criteria and had an accuracy of 97.02 percent on the breast cancer dataset.

Programming-free ML teaches computers. ML predicts chronic illnesses in healthcare. Early detection helps prevent and cure diabetes. This model detects type II diabetes early. Lifestyle file characters type. Bagging, boosting, and voting earn files. Exploratory analysis enhances datasets. K-fold cross-validation verifies and synthetic minority resampling balances classes. Engineers live this way [12]. Figure 1 from the work [12] depicts system architecture. Decision trees were most accurate at 99.41%.

Machine learning to the PIDD and the LMCH diabetes dataset to predict and diagnose diabetes. Feature selection and imputation of missing values can improve diabetes prediction models and diagnostic classification. The creation of a prediction model for the clinical diagnosis of diabetes is the main objective. For feature selection and missing value imputation, Spearman correlation and polynomial regression work well. For classification, RF, SVM, and 2GDNN models are suggested [14]. Grid search and k-fold iterative stratified cross- validation are used to refine model hyper-parameters and verify the scaling of their prediction problems.

Due to insulin insufficiency, diabetes elevates Blood Sugar and destroys organs. Lifesaving early detection. 13 binary classification machine learning models were developed and assessed utilizing 768 data counts and 2,000 occurrences. LGBM, HGB, and decision tree performed well with the random forest method [15]. A generalized technique of training algorithms with one data set and verifying with another outperforms model performance matrices on the validation data set. Each strategy has pros and cons.




Fig.1. System Architecture

Comparative investigation shows that the ensemble approach [12] is the best TIIDM illness classification method to date, including lifestyle indicators, data preprocessing, SMOTE for data balance, feature selection, dataset splitting, and K-fold crossover. Validation and classification use storage, boosting, and voting methods. Other approaches that employ an ideal feature selection method but do not preprocess, reject incomplete data, or use feature selection methods are less efficient.

TABLE I. COMPARATIVE ANALYSIS

Sl. No.	Citation Number	Number of datasets	Dataset name	Dataset Size	Evaluation Parameters	Classifiers used	ACC	Year of Publication
1	[17]	1	PIDD	768	ACC	NB & RF	82.3%	February 2019
2	[13]	1	NHANFES	9858	AUC, Sn, FM, ACC, NPV, PPV	AB, NB, RF, DT	92.75%	January 2020
3	[16]	1	PIDD	768	AUC ,Sp, Sn	k-NN, NB, DT, XB, RF, AB, MLP	78.9%	April 2020
4	[11]	1	PIDD	768	ACC, F1, Precision & Recall	LR, SVM, RF, NB, AB, XGB, CB & Bagging	79.04%	January 2021
5	[10]	1	UCI	768	ACC, Sn, Sp, NPV, PPV & F1	SVM & ANN	94.87%	January 2022
6	[14]	2	PIDD	1536	ACC, Precision, Recall,	RF,SVM & 2GDNN	97.33%	March 2022

			LMCH		Sp, ACC			
7	[12]	1	Real time dataset	27050	ACC, Precision, Recall, Sp, F1, MCR & ROC	Bagging, boosting and voting	99.41%	August 2022
8	[15]	2	PIDD DF2	2768	ACC	k-NN, RF, BNB, XGB, CA, HCB, NB, SVM, LGBM, DT, LR, GB	DF1 – 85% DF2 – 99.4%	October 2022

In Table I, the [12] model is contrasted with earlier reported models and methodologies in the order of publication. This model [12] obtained an accuracy of 99.41%, outperforming all other reported approaches, as can be shown. All diabetes prediction approaches emphasize feature selection and a number of ML techniques such DT, RF, SVM, and NB even if only a few features are required for prediction. Genetic and lifestyle information should be included in future study.

- Analyse data over time to determine the evolution of risk factors.
- Explore advanced deep learning algorithms and feature selection algorithms to improve accuracy.
- Integrate models with electronic health records for real-time risk assessment.
- Work to implement models for practical use in a clinical setting.

TABLE II. COMPARATIVE ANALYSIS OF PERFORMANCE METRICS

	Sn	**Sp**	**AUC**	**F1**	**Precision**	**Recall**	**PPV**	**NPV**
[17]	-	-	-	-	-	-	-	-
[13]	-	-	-	-	-	-	-	-
[16]	78.9	93.4	95	-	-	-	-	-
[11]	-	-	80.98	71.56	64.47	70	-	-
[10]	95.52	94.38	-	94.12	-	-	92.75	96.55
[14]	97.24	-	97.26	97.34	-	-	-	-
[12]	-	99.11	-	99.15	99.13	95.83	-	-
	97.33	-	97.27	97.28	-	-	-	-
[15]	-	-	-	-	-	-	-	-

As noted above and demonstrated in Table II, the effectiveness of each model is evaluated using a variety of performance criteria. The [12] model performs better than other models, as can be shown from the results. With the use of lifestyle markers, this study presents an ensemble learning framework [12] for early Type-II diabetes prediction. Applying strategies such as Bagging, Boosting, and Voting, the bagged decision tree achieves a high accuracy of 99.41%. The methodology has been verified using K-fold cross-validation and offers enhanced dataset quality through exploratory data analysis and synthetic minority oversampling. It provides a strong method for early diabetes prediction with healthcare applications, and it may be tailored other datasets with similar features.




Fig.2. Comparative analysis of performance metrics

A comparison of all the parameters used for the performance study is shown in the graph. Figure 2 represents that [12] model is preferable, with a 99.41% accuracy, 99.13% precision, 95.83% recall, 99.11% specificity, 99.15% F1-score, 0.86% misclassification rate, and a 99.07% ROC curve, the bagged decision tree performs better than the competition.




Fig.3. Accuracy of prediction

The classification accuracy reached by stacking, as shown in Fig 3, is only 99.41%, while bagging, boosting, and voting algorithms together produced the best results.

5. Conclusion:

Being a major disease, diabetes mellitus is a complex disease for diagnosing due to its inaccurate and poor data quality, thus being a meticulous clinical data. This paper analyses the existing state-of-the-art algorithms for diagnosing diabetes in machine learning. Based on the analysis of the other works, has resulted in high accuracy and outperformed compared to other works. This suggested framework can be used later on to determine a patient's likelihood of developing a disease, possibly even at an earlier stage. Various patient types may receive advice to modify their lifestyle according to the disease's propensity. Furthermore, mobile applications can be created to assist medical professionals in the identification and prognosis of TII2M illness. Additionally, it will help end users prevent hospital readmissions, needless medical examinations, and frequent trips to clinical labs, and other issues related to diabetes by reducing its consequences at an early stage.

References

[1] Y. L. Sun and D. L. Zhang, “Machine Learning Techniques for Screening and Diagnosis of Diabetes: A Survey,” *Technical Gazette*, vol. 26, pp. 872–880, 2019.
[2] Y. K. Qawqzeh, A. S. Bajahzar, M. Jemmali, M. M. Otoom, and A. *aljaoui, “Classification of diabetes using photoplethysmogram (PPG) waveform analysis: logistic regression modeling,” *BioMed Research International*, vol. 2020, Article ID 3764653, 2020.
[3] E. O. Olaniyi and K. Adnan, “Onset diabetes diagnosis using artificial neural network,” *International Journal of Scientific Engineering and Research*, vol. 5, pp. 754–759, 2014.
[4] S. Gupta, H. K. Verma, and D. Bhardwaj, “Classification of diabetes using na¨ıve bayes and SVMas a technique,” *Lecture Notes on Multidisciplinary Industrial Engineering*, Springer, Singapore, pp. 365–376, 2021.
[5] D. K. Choubey, M. Kumar, V. Shukla, S. Tripathi, and V. K. Dhandhania, “Comparative analysis of classification methods with PCA and LDA for diabetes,” *Current Diabetes Reviews*, vol. 16, no. 8, pp. 833–850, 2020.
[6] S. Gujral, “Early diabetes detection using machine learning: a review,” *International Journal for Innovative Research in Science & Technology*, vol. 3, no. 10, 2017.
[7] Z. Soltani and A. Jafarian, “A new artificial neural networks approach for diagnosing diabetes disease type II,” *International Journal of Advanced Computer Science and Applications*, vol. 7, pp. 89–94, 2016.
[8] N. P. Tigga and S. Garg, “Prediction of type 2 diabetes using machine learning classification methods,” *Procedia Computer Science*, vol. 167, pp. 706–716, 2020.
[9] G. Swapna, K. P. Soman, and R. Vinayakumar, “Automated detection of diabetes using CNN and CNN-LSTM network and heart rate signals,” *Procedia Computer Science*, vol. 132, pp. 1253–1262, 2018.
[10] Ahmed, U., Issa, G. F., Khan, M. A., Aftab, S., Khan, M. F., Said, R. A., & Ahmad, M. (2022). Prediction of diabetes empowered with fused machine learning. *IEEE Access*, *10*, 8529-8538.
[11] Kumari, S., Kumar, D., & Mittal, M. (2021). An ensemble approach for classification and prediction of diabetes mellitus using soft voting classifier. *International Journal of Cognitive Computing in Engineering*, *2*, 40-46.
[12] Ganie, S. M., & Malik, M. B. (2022). An ensemble machine learning approach for predicting type-II diabetes mellitus based on lifestyle indicators. *Healthcare Analytics*, *2*, 100092. doi: https://doi.org/10.1016/j.health.2022.100092
[13] M. Maniruzzaman, M. J. Rahman, M. Al-Mehedi Hasan et al., “Classification and prediction of diabetes disease using machine learning paradigm,” *Journal of Health Information Science and System*, vol. 8, 2020.
[14] Olisah, C. C., Smith, L., & Smith, M. (2022). Diabetes mellitus prediction and diagnosis from a data preprocessing and machine learning perspective. *Computer Methods and Programs in Biomedicine*, *220*, 106773. doi: https://doi.org/10.1016/j.cmpb.2022.106773
[15] Mondal, S., Banik, A., Roy, S., Das, J., Banerjee, S., & Navin, H. (2022, October). Random Forest Based Diabetic Prediction Model on Highly Unbalanced Dataset. In *2022 IEEE 2nd Mysore Sub Section International Conference (MysuruCon)* (pp. 1-6). IEEE. doi: https://doi.org/10.1109/mysurucon55714.2022.9972534.
[16] Md. Kamrul Hasan, Md. Ashraful Alam, D. Das, E. Hussain, and M. Hasan, “Diabetes prediction using ensembling of different machine learning classifiers,” *IEEE Acess*, vol. 8, pp. 76516–76531, 2020.
[17] V. Jackins, S. Vimal, M. Kaliappan, and M. Y. Lee, “AI-based smart prediction of clinical disease using random forest classifier and Naive Bayes,” *Fe Journal of Supercomputing*, vol. 77, no. 5, pp. 5198–5219, 2021.
[18] D. Su, T. L. Michaud, P. Estabrooks et al., “Diabetes management through remote patient monitoring: the importance of patient activation and engagement with the technology,”*Telemedicine and e-Health*, vol. 25, no. 10, pp. 952–959, 2019.
[19] S. P. Chatrati, *Smart home Health Monitoring System for Predicting Type 2 Diabetes and Hypertension*, Journal of King Saud University – Computer and Information Sciences, January 2020.