Available online at www.sciencedirect.com

ScienceDirect

Procedia Computer Science 233 (2024) 97–107

Procedia Computer Science

www.elsevier.com/locate/procedia

5th International Conference on Innovative Data Communication Technologies and Application (ICIDCA 2024)

Enhancing Veracity: Empirical Evaluation of Fake News Detection Techniques

KS Sreekar Datta[1,*], G Narasimha Naidu[1], S Abhishek[b], Anjali T[1]

[a]*Department of Computer Science and Engineering, Amrita School of Computing, Amrita Vishwa Vidyapeetham, Amritapuri, India*

[b]*Rolls-Royce Inc, Bangalore, India*

1 amenu4aie20136@am.students.amrita.edu

Abstract

The relentless surge in the dissemination of fabricated news articles and misleading information poses a substantial threat to the veracity of information, trust in media sources, and the very foundations of democratic processes. In the contemporary landscape of information dissemination, the rampant propagation of false and misleading information has emerged as a paramount concern for both individuals and society at large. Consequently, the development of robust and efficient detection mechanisms has taken on a pivotal role in contemporary information ecosystems. The methodology employed encompasses three pivotal stages: initial data preprocessing, subsequent feature extraction involving the utilization of TF-IDF and Count Vectorization, and eventual classification that draws upon a diverse array of machine learning classifiers, in addition to deep learning models like Recurrent Neural Networks (RNN) and BERT networks. On a carefully selected dataset of instances of fake news, these models underwent rigorous testing and training.This research greatly aids in the continuous battle against disinformation by offering a methodical framework for identifying fake news. It also helps people and organisations make better decisions by shedding light on the relative merits of various deep learning and machine learning methods in this intricate and crucial context..

© 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application

Keywords:
Fake news; Data pre-processing;Feature extraction;Deep Learning;Machine Learning;TF-IDF Vectorizer;BERT.

1877-0509 © 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application
10.1016/j.procs.2024.03.199

1. Introduction

In an era characterized by the swift spread of information and the increasing challenge of distinguishing between verified facts and deceptive content, the phenomenon of fake news has become a significant threat to the reliability and trustworthiness of information. The repercussions of misinformation extend across societies, influencing public trust in media and shaking the very foundations of democratic systems. It is within this complex landscape that the pivotal role of fake news detection comes to the forefront.

The consequences of unbridled fake news dissemination are profound, affecting public perceptions, swaying decision-making processes, and, in some instances, even jeopardizing social and political stability. The urgency to counter this menace has never been more evident, and this research paper stands as a testament to the dedicated efforts aimed at upholding the sanctity of information [1]. The structured approach within this research methodology comprises five critical stages, each meticulously designed to tackle the multifaceted challenge of distinguishing truth from deception.

The integration of classical machine learning algorithms, coupled with cutting-edge deep learning architectures like BiLSTM and BERT, affords a comprehensive evaluation of information veracity. This amalgamation of techniques is designed to address the multifaceted challenge of fake news detection, presenting an innovative and robust framework that transcends the constraints of singular methodologies and promises to reshape the landscape of disinformation detection.

The proposed methodology serves not only as a means to an end but also as a testament to the unwavering commitment to safeguarding the authenticity of news sources. This research endeavor is far from a mere academic exercise; it represents a tangible journey toward developing practical solutions. At the intersection of innovation, machine learning, and deep learning technologies equip us to confront the ever-evolving facets of digital-age deception.

The strength of contextual knowledge and linguistic analysis is harnessed by a unique combination of traditional and cutting-edge methodologies, which ultimately improves the efficacy and accuracy of false news identification. This study's methodology stands out as a creative, all-encompassing strategy that has the potential to significantly advance the field of disinformation identification.

The study acknowledges the gravity of the research– to secure the pillars of trust, accuracy, and transparency in an era awash with information. The methodology used in this work is a new and advanced development in the field of fake news identification [2].

The pioneering approach to fake news detection distinguishes itself through its meticulous consideration of a wide array of textual features and a diverse selection of models. The incorporation of TF-IDF vectorization, which adeptly captures linguistic nuances while accommodating a rich spectrum of features, enhances the system's ability to adapt to the evolving landscape of disinformation.

2. Literature Review

The study [1] by N. F. Baarir and A. Djeffal et al. presents a novel machine learning strategy for detecting fake news, integrating multiple approaches and features to achieve high accuracy. Support Vector Machine (SVM) is used for categorization, incorporating confidence quantification to provide insights into news accuracy. However, limitations include potential issues with dataset representativeness and the absence of real-time detection capabilities.

The study[2] by Anjali Jain, Harsh Khatter et al. presents an innovative approach for identifying fake news in social media. The proposed model surpasses prior models with an accuracy of up to 93.6%. It consists of a news aggregator, authenticator, and recommendation system . Nevertheless, it does not examine the applicability of real-time technology, the dynamic nature of fake news, or potential multilingual or regionally specific issues.

The study [3] by N.R. Hatwar, Samrudhi Meshram et al. focused on classifying news as real or deceptive to address misinformation spread on social media platforms. However, it lacks insights into real-time applicability and the evolving nature of fake news. The evaluation primarily emphasizes accuracy, overlooking other essential metrics and challenges related to multilingual or region-specific content.

The study [4] by Ms. Ch. Uma devi, r. Priyanka et al. tackles the challenging task of fake news detection by employing Natural Language Processing (NLP) techniques to differentiate between genuine and deceptive news articles. Their work leveraged linguistic, syntactic, and semantic features, achieving accuracy levels comparable to human judgment. The limitations include its reliance on static datasets, which may not fully capture the evolving nature of fake news, and the omission of relevant metrics beyond accuracy in the evaluation.

The study [5] by Abdulaziz Albahr, Marwan Albahar et al. assess the performance of four machine learning techniques in fake news detection using the LIAR dataset . They highlight the superiority of the Naïve Bayes algorithm in fake news detection, attributing its success to its proficiency in text-based classification. However, the study has limitations, such as the lack of extensive feature engineering exploration and dataset-specific focus. It does not address real-time detection or consider evolving fake news tactics.

The study [6] by Imane Ennejjai, Hassan Badir et al conducts a comprehensive analysis of fake news detection methods using Naive Bayes with n-gram features, and are shown to be competitive with deep learning models, emphasizing the importance of feature engineering and dataset size. Limitations include a focus on small datasets and a lack of exploration into advanced techniques like transformer-based models.

The study [7] by Sheng How Kong, Li Mei Tan et al introduces a multidimensional approach to addressing fake news using NLP methods and deep learning models. They enhance fake news identification across various social media platforms by analyzing both news headlines and content, comparing N-gram and sequence vectors. Limitations of this research include its English-language focus and data sources, with potential future improvements involving the integration of multimedia data for a more comprehensive false news detection system.

This research offers a distinctive advantage by virtue of its holistic and versatile approach. While many previous studies tend to focus on either traditional machine learning models or more recent deep learning architectures in isolation, the proposed methodology successfully bridges this gap by integrating both. This synthesis allows us to harness the strengths of conventional linguistic analysis for feature extraction, while simultaneously benefiting from the contextual understanding provided by cutting-edge deep learning models.

The suggested research methodology showcases a comprehensive evaluation framework, which incorporates a wide range of performance metrics. This meticulous assessment, carried out on a separate data set, not only underscores the reliability of classifiers but also provides insights into their ability to effectively differentiate between genuine and deceptive news articles.

3. Proposed Methodology

The methodology used in this research is a novel and advanced development in the field of fake news identification. By combining a variety of feature extraction techniques, like the TF-IDF vectorizer, with a wide range of machine learning models as well as cutting-edge deep learning models, the research significantly broadens the scope of existing methodologies.

The suggested traditional and cutting-edge methods combine contextual understanding with linguistic analysis to increase the efficacy and accuracy of fake news detection. Consequently, the methodology presented in this study stands out as an innovative and holistic approach, poised to make substantial contributions to the field of misinformation detection.

3.1. Data Pre-Processing

Initial step is preprocessing the textual content, involving two key procedures. First, all text from the dataset is converted to lowercase to ensure uniformity. Subsequently, the removal of stopwords, which are common, ubiquitous terms such as ”the,” ”and,” and ”is,” is performed. These stopwords, while prevalent, typically carry limited semantic significance. Their elimination not only reduces data dimensionality but also diminishes potential noise in the dataset. Moreover, this approach allows the model to focus its attention on more meaningful and informative terms. This

data refinement process serves to enhance the model's efficiency and simultaneously mitigates the risk of overfitting, thereby establishing a solid foundation for subsequent analyses.

3.2. Feature extraction

The Bag-of-Words (BoW) model and the Term Frequency-Inverse Document Frequency (TF-IDF) transformation are used in the feature extraction process. This process is essential for transforming the unprocessed text data into a format that can be used for machine learning research. First, the Bag-of-Words model is implemented using the CountVectorizer function of the scikit-learn library. Tokenizing the text, creating a vocabulary, and converting the data into a sparse matrix—in which each row denotes a document and each column a distinct word from the vocabulary—are the steps involved in this process. The values in this matrix represent how frequently each word appears in a particular document.

The TfidfTransformer is used to apply the TF-IDF transformation after the Bag-of-Words representation. TF-IDF considers a word's uniqueness throughout the entire corpus (IDF) in addition to its frequency in a document (TF). The result is a TF-IDF matrix, in which each row represents a document and each column represents a different word. The values in each column denote the relative importance of each word within the corresponding document.

TF-IDF Vectorizer

A key component of text analysis and natural language processing, the TF-IDF vectorizer (Inverse Document Frequency & Term Frequency) is essential for converting textual data into numerical form. TF is a metric for a word's local importance that indicates how frequently it appears in a single document.

The TF-IDF technique is an invaluable asset for a multitude of text analysis tasks [7], ranging from information retrieval and text classification to sentiment analysis, enabling precise identification of key terms in a document while maintaining content integrity and authenticity.

Count Vectorizer

The Count vectorizer is a simple and effective method for numerically representing text data. By converting each document into a vector of word frequencies, it turns text into a "bag of words" representation. By counting the occurrences of each word in a document, you can use this method to create a feature vector. However, it disregards contextual information and word order

Count vectorization is widely used in various text analysis tasks, including document classification, text clustering, and information retrieval. It provides a solid foundation for machine learning algorithms to work with text data, making it a popular choice in text analysis pipelines due to its simplicity and speed.

3.3. Machine learning Classifiers

The machine learning classifiers used in this research are Naive Bayes, Logistic regression, Decision Tree, Random Forest and Support vector machine. The deep learning models used are RNN and BERT. Fig1 shows the basic methodology of the approach.

1. Logistic Regression : Logistic regression simulates the relationship between a dependent variable and a group of independent variables, by calculating the likelihood that a given data point will belong to a particular class. This approach is highly regarded because of its interpret ability, simplicity, and broad use in industries like finance and healthcare.

2. Naive Bayes : The Naive Bayes's computational efficiency and satisfactory accuracy make it especially useful for text classification tasks and spam filtering.Despite the naive assumption of feature independence, it is widely used in sentiment analysis, document categorization, and email classification.

3. Random Forest : The Random Forest provides strong performance across a variety of data types and applications, such as image recognition, financial forecasting, and ecological modelling, by combining the outcomes of individual decision trees there by reducing the over fitting and improve the accuracy.

4. Decision Tree : A decision tree is a structured visual representation used in data analysis and decision-making processes. It resembles a flowchart, breaking down complex problems into simpler, more manageable steps. Decision trees help individuals and organizations make informed choices by considering various factors and their outcomes. They are applied in diverse fields, from business strategy and medical diagnosis to risk assessment and recommendation systems.

5. Support Vector Machine (SVM) : Backing For applications involving regression and classification, Vector Machine is an effective algorithm. Even in high-dimensional spaces, it looks for the best hyperplane to optimize the margin between classes. SVMs are preferred because they can handle intricate data distributions and are used in bioinformatics, sentiment analysis, and picture categorization.

3.4. Deep Learning Classifiers

1. Recurrent Neural Networks : A specific class of neural networks designed for sequential data analysis is known as recurrent neural networks, or RNNs. Because of their special self-referencing connections, they are able to remember previous inputs. Because of their capacity to detect temporal patterns and dependencies, they have been widely used in natural language processing, audio recognition, time series forecasting, and even handwriting recognition. In response to these constraints, more sophisticated RNN variants—like LSTM and GRU networks—have surfaced. These variations include techniques that improve their ability to represent complex dependencies in sequential data, hence increasing their usefulness in a variety of deep learning areas.

2. Bidirectional LSTM :A well-liked recurrent neural network design for sequence modeling and natural language processing applications is called bidirectional long short-term memory, or BiLSTM. In contrast to conventional LSTMs, which perform unidirectional processing of input sequences, BiLSTMs improve their performance by taking into account data from both previous and subsequent time steps at the same time. Their ability to work in both directions allows them to better capture context and long-range relationships, which makes them ideal for tasks like named entity recognition, speech recognition, and sentiment analysis.. Fig 2 shows the Bi LSTM architecture used in our approach.

A BiLSTM processes the input sequence by having two LSTM layers, one that advances through time and the other that moves backward. Every time step, the outputs from both directions are merged to create a rich representation that includes data from the complete sequence. This bidirectional processing makes the model a useful tool in the field of deep learning for sequential data analysis by enhancing its comprehension of the context and relationships within the sequential data.




Fig. 1: Bidirectional LSTM

3.5. Architectures of Deep learning classifiers

BILSTM Architecture:

The first layer is an Embedding layer that converts words into continuous vectors, allowing the model to work with textual information. The subsequent Bidirectional LSTM layers are instrumental in capturing the intricate dependencies and context within the text. The bidirectional nature enables them to analyze information in both forward and backward directions, ensuring a comprehensive understanding of the sequential data. Following the LSTM layers, dense layers are introduced, which contribute to the model's ability to learn complex patterns. The final dense layer, with a single unit, is responsible for making the binary classification decision, where higher values indicate a higher likelihood of the text being classified as fake news. Additionally, a Dropout layer is included to mitigate overfitting by randomly deactivating 50% of the units during training. This model's architecture, coupled with the specified loss function, optimizer, and early stopping, forms a robust framework for fake news detection. During training, the model learns to distinguish between genuine and fake news articles, with the ultimate goal of contributing to the ongoing efforts to combat the dissemination of false information

BERT Architecture:

The initial input layers, namely 'input_ids' and 'input_mask', serve as the foundation of the model. 'input_ids' encode the tokenized text data, and 'input_mask' provides information about which tokens are to be attended to and which are to be ignored. This two-pronged input strategy is crucial for understanding the content within news articles.

The BERT layer, as the heart of the model, is responsible for extracting deep contextual information from the text. Given its pretrained nature on a vast corpus of text, it holds a profound understanding of language, enabling it to capture the intricate dependencies and meaning behind words and phrases. This results in a highly nuanced comprehension of the text, making it well-suited for distinguishing between genuine and fake news. To ensure model robustness and guard against overfitting, dropout layers are thoughtfully integrated into the architecture. A 50% dropout rate following the BERT layer, combined with an additional 20% dropout after the first dense layer, allows for generalization and adaptation to diverse textual data. The subsequent dense layers introduce non-linearity to the model's decision-making process.




Fig. 2: BERT

The initial dense layer employs the hyperbolic tangent (tanh) activation function, serving as a critical element for pattern recognition and feature extraction. Finally, the model converges with a dense layer using a sigmoid activation function, which is pivotal for binary classification. It calculates the probability that a given article is fake news, with values closer to 1 signifying a higher likelihood of falsehood. The model's training process is governed by the Adam optimizer, which fine-tunes the model's weights based on the provided dataset. Binary cross-entropy acts as the loss function, quantifying the difference between predicted and actual labels. Importantly, an Early Stopping callback is employed, ensuring that training ceases when the validation loss plateaus. This safeguard prevents overfitting, making the model adaptable to unseen data

BERT's groundbreaking approach lies in its bidirectional context modeling during pretraining, enabling it to grasp the relationships between words in a sentence by considering both preceding and subsequent words. Subsequently fine-tuned for specific NLP tasks, BERT produces contextualized word representations, capturing nuances and subtleties that previous models couldn't discern. Its versatility is evident in its remarkable performance across a spectrum of tasks, including machine reading comprehension, sentiment analysis, language translation, and text summarization.

BERT's influence extends to diverse domains, from healthcare to finance. Its ongoing impact is fueled by numerous variants and improvements, offering the promise of more efficient, scalable, and context-aware NLP models. Fig 3 shows the BERT architecture used in our approach

4. Experimental Results

The research demonstrates exceptional performance from both machine learning and deep learning classifiers, showcasing consistently high accuracy rates. This robust accuracy underscores the efficacy of the model across diverse techniques and highlights the reliability of the proposed approach in effectively discerning fake news from authentic content.

4.1. Naive Bayes

The Naive Bayes classifier achieved an accuracy of 95.33%, showcasing a respectable level of overall classification performance. It displayed a slightly higher precision for the "fake" class (97%) compared to the "real" class (93%), indicating that it has a tendency to be more certain when classifying instances as "fake" but may occasionally mis classify "real" instances. The recall for the "fake" class at 94% suggests that it misses a small proportion of "fake" instances. Consequently, the F1-score of 95% strikes a balance between precision and recall, highlighting its capacity to make accurate classifications while maintaining a reasonable margin for improvement.

4.2. Logistic Regression

The Logistic Regression model achieved an impressive accuracy of 98.83%, signifying its robust and reliable performance in this binary classification task. It performed very well for both "real" and "fake" classes, with outstanding accuracy, recall, and F1-score, all at 99%. As seen by the low frequency of false positives and false negatives, it can consistently provide very accurate forecasts. The model is a strong option for situations where accuracy and dependability are crucial due to its outstanding performance.

4.3. Random Forest

With a 99.2% accuracy rate, the Random Forest classifier proved to be dependable and strong. For both "real" and "fake" classes, it maintained a 99% accuracy rate, showing that it seldom ever guesses the wrong class. Furthermore, the model attained a 99% recall rate for both classes, indicating that it successfully recognises a significant percentage of relevant cases. Reliability for a wide range of applications is shown by the balanced F1-score of 99% for both classes, which highlights its strong trade-off between accuracy and recall.

4.4. Decision Tree

A notable performer, the Decision Tree model showed an outstanding accuracy of 99.55%. The data showed a perfect precision of 100% for the "real" class and 99% for the "fake" class. This indicates that "real" instances are classified with outstanding precision, whereas "fake" examples are only sometimes misclassified. With a recall of 99% for "real" and 100% for "fake," it successfully records the great majority of pertinent cases. The F1-scores of 100% for both classes highlight the exceptional overall performance of this model, which shows no mis classifications.

4.5. Support Vector Machine

The Support Vector Machine (SVM) model emerged as the top performer with a remarkable accuracy of 99.6%. It exhibited a precision of 99% for the "real" class and a perfect precision of 100% for the "fake" class, highlighting its ability to make highly accurate predictions with an exceptionally low rate of false positives. With a recall of 100% for both classes, it captures all instances effectively, further emphasizing its exceptional performance. The F1-scores of 100% for both classes underscore its overall excellence, making the SVM model a top choice for tasks where precision, recall, and accuracy are of paramount importance.




Fig. 3: Accuracy Graphs of Machine Learning Models




Fig. 4: Accuracy Curves of Bidirectional LSTM

4.6. Bidirectional LSTM

BiLSTM perfomed with accuracy 99.05% ,Fig 7 shows the training and validation accuracy using LSTM, Fig 8 shows the training and validation loss using LSTM. The model's performance is shown by the fact that training accuracy began at 90% initially and then became extremely near. Towards the conclusion of the loss graph, training loss and validation loss were not very close.

4.7. BERT

BERT performed with accuracy of 99.8%. Fig 5 shows the training and validation accuracy using BERT ,Fig 6 shows the training and validation loss using BERT.Training accuracy started from 90% in first epoch and ,and test accuracy in first epoch is close to 99% and from second epoch on wards which are very close after that indicates that model is




Fig. 5: Loss Curves of Bidirectional LSTM




Fig. 6: BERT Model Accuracy Curves

performing well and in loss graph training loss and test loss are not very close which indicates that model is performing very well performing good. Fig 4 shows the comparision of accuracies of various machine learning models used. Considering these observations, both models exhibit outstanding accuracy.

BERT, with its slightly higher accuracy and the consistent performance of training and test accuracy across epochs, appears to be performing exceptionally well in this particular task. The BERT model has a strong ability to generalize and classify instances accurately, making it the preferred choice in this context. The employed BERT (Bidirectional Encoder Representations from Transformers) model has demonstrated superior accuracy compared to the LSTM (Long Short-Term Memory) neural network. This notable performance discrepancy can be attributed to several key factors inherent to the BERT architecture and training methodology.

BERT, as a transformer-based model, excels at capturing contextualized word embeddings by considering the entire context of a word within a sentence. This ability enables BERT to discern nuanced meanings based on contextual relationships, surpassing the sequential processing limitations of the LSTM model. Moreover, BERT's proficiency in




Fig. 7: BERT Model Loss Curves

Table 1: Classification Results

Classifiers	Accuracy	Metrics			
		Classes	Precision	Recall	F1-score
Naive Bayes	95.33%	Real	93%	97%	95%
		Fake	97%	94%	96%
Logistic Regression	98.83%	Real	99%	99%	99%
		Fake	99%	99%	99%
Decision Tree	99.55%	Real	100%	99%	100%
		Fake	99%	100%	100%
Random Forest	99.2%	Real	99%	99%	99%
		Fake	99%	99%	99%
SVM	99.6%	Real	99%	100%	100%
		Fake	100%	100%	100%

transfer learning, leveraging pre-training on extensive corpora before fine-tuning on specific tasks, facilitates a more nuanced understanding of language patterns, particularly beneficial in scenarios with limited labeled data. The transformer architecture utilized by BERT is adept at capturing long-range dependencies in sequential data, outperforming traditional recurrent architectures like LSTM. Additionally, BERT's tokenization strategy, incorporating subword information, and advanced padding techniques contribute to more effective handling of vocabulary nuances and varying sequence lengths.

The inclusion of early stopping in the BERT model training process, monitoring validation loss to prevent overfitting, underscores the emphasis on generalization to unseen data. Furthermore, meticulous hyperparameter tuning, such as optimizing learning rates and dropout rates, likely contributes to the overall superior performance observed in the BERT-based fake news detection model. The success of the BERT model in outperforming the LSTM counterpart is rooted in its transformative architecture, contextualized embeddings, effective transfer learning, and meticulous attention to tokenization and hyperparameter optimization. These factors collectively empower BERT to discern subtle linguistic nuances, making it a potent tool for the nuanced task of fake news detection.

5. Conclusion

The proposed study has contributed a systematic and comprehensive methodology for the identification of fake news by integrating deep learning and machine learning techniques. Through rigorous testing and evaluation, our research demonstrates a robust capacity to distinguish between factual and fabricated information in the realm of news. The deployment of machine learning classifiers, notably with Support Vector Machines (SVM) emerging as a standout performer, alongside the integration of advanced deep learning models such as BERT, underscores the efficacy of our approach. This significant advancement provides an opportunity to fortify defenses against misinformation and uphold information integrity, particularly in an era where discerning truth from deception has become increasingly challenging.

The future scope of this research extends into several promising directions. Advanced neural network architectures, including attention mechanisms and transformer-based models beyond BERT, warrant exploration to ascertain their efficacy in fake news detection. Furthermore, the inclusion of linguistic and contextual cues, such as sentiment analysis and linguistic style, presents an exciting avenue for refining the granularity of fake news detection. Exploring techniques to identify the sources of misinformation, attribute content to creators, and discern the motivations behind the propagation of fake news could provide valuable insights into mitigating the impact of misinformation.

Acknowledgements

We would like to acknowledge that the research presented in this paper does not involve or utilize any data or resources from Rolls-Royce India Private Limited, Bangalore, India. The work presented here is based solely on independent research and publicly available data sources.

References

[1] N. F. Baarir and A. Djeffal, "Fake News detection Using Machine Learning," 2020 2nd International Workshop on Human-Centric Smart Environments for Health and Well-being (IHSH), Boumerdes, Algeria, 2021, pp. 125-130, doi: 10.1109/IHSH51661.2021.9378748.

[2] Jain, Anjali and Shakya, Avinash and Khatter, Harsh and Gupta, Amit. (2019). A smart System for Fake News Detection Using Machine Learning. 1-4. 10.1109/ICICT46931.2019.8977659.

[3] Hatwar, N.R., Meshram, S., Ghodeswar, S., Khond, P., Mendhule, S., andChaudhari, M. (Year of Publication). "FAKE NEWS DETECTION USING MACHINE LEARNING." International Research Journal of Modernization in Engineering Technology and Science

[4] Devi, C. U., Priyanka, R., Surendra, P. S., Priyanka, B. S., and Nikhila, C. N. D. L. (2019). "FAKE NEWS DETECTION USING MACHINE LEARNING." Journal of Emerging Technologies and Innovative search (JETIR)

[5] Abdulaziz Albahr and Marwan Albahar, "An Empirical Comparison of Fake News Detection using different Machine Learning Algorithms" International Journal of Advanced Computer Science and Applications(IJACSA), 11(9), 2020.

[6] Ennejjai, Imane and Ibn El Ahrache, Sara and Hassan, Badir. (2020). Fake news detection using deep learning

[7] S. H. Kong, L. M. Tan, K. H. Gan and N. H. Samsudin, "Fake News Detection using Deep Learning," 2020 IEEE 10th Symposium on Computer Applications and Industrial Electronics (ISCAIE), Malaysia, 2020, pp. 102-107

[8] W. Badr, "TowardsDataScience," 22 February 2019. [Online]. Available: https://towardsdatascience.com/having-animbalanced-dataset-here-is-how-you-can-solve-it1640568947eb.

[9] Vyas, Piyush, Jun Liu, and Omar El-Gayar. "Fake news detection on the web: An LSTM-based approach." (2021).

[10] Deepak, S., and Bhadrachalam Chitturi. "Deep neural approach to Fake-News identification." Procedia Computer Science 167 (2020): 2236-2243.

[11] Vinay, R., Premjith, B., Shukla, D., Soman, K.P. (2023). Feature Engineering and Selection for the Identification of Fake News in Social Media. In: Ray, K.P., Dixit, A., Adhikari, D., Mathew, R. (eds) Proceedings of the 2nd International Conference on Signal and Data Processing. CSDP 2022. Lecture Notes in Electrical Engineering, vol 1026. Springer, Singapore.

[12] Aravinda Reddy, D., Anand Kumar, M., Soman, K.P. (2019). LSTM Based Paraphrase Identification Using Combined Word Embedding Features. In: Wang, J., Reddy, G., Prasad, V., Reddy, V. (eds) Soft Computing and Signal Processing . Advances in Intelligent Systems and Computing, vol 898. Springer, Singapore

[13] P. Ganesh, L. Priya and R. Nandakumar, "Fake News Detection - A Comparative Study of Advanced Ensemble Approaches," 2021 5th International Conference on Trends in Electronics and Informatics (ICOEI), Tirunelveli, India, 2021, pp. 1003-1008, doi: 10.1109/ICOEI51242.2021.9453061.

[14] Anjali, B., R. Reshma, and V. Geetha Lekshmy. "Detection of counterfeit news using machine learning." 2019 2nd International Conference on Intelligent Computing, Instrumentation and Control Technologies (ICICICT). Vol. 1. IEEE, 2019.

[15] J. Nair, S. S. Akhil and V. Harisankar, "Fake News Detection Model for Regional Language," 2022 IEEE 7th International conference for Convergence in Technology (I2CT), Mumbai, India, 2022, pp. 1-7, doi: 10.1109/I2CT54291.2022.9824641.