Available online at www.sciencedirect.com

ScienceDirect

Procedia Computer Science 233 (2024) 432–443

Procedia Computer Science

www.elsevier.com/locate/procedia

5th International Conference on Innovative Data Communication Technologies and Application (ICIDCA 2024)

ShardedScale: Empowering Blockchain Transaction Scalability with Scalable Block Consensus

Praveen M Dhulavvagol[a], S G Totad[a], Atrey Mahadev Anagal[a], Swaroop Anegundi[a], Praveen Devadkar[a], Vinayak Sudhakar Kone[a,*]

[a]School of Computer Science and Engineering, KLE Technological Univerisity, Hubballi – 580032 (Karnataka), India
praveen.md@kletech.ac.in; vskonenpn@gmail.com

Abstract

Blockchain is a decentralized digital ledger technology that offers transparency, security, and immutability by recording and verifying transactions across multiple computers. However, it faces limitations such as scalability issues, high energy consumption, slow transaction validation, expanding storage requirements. Understanding these limitations is crucial for evaluating blockchain's suitability for specific use cases and finding solutions to overcome these challenges. Recognizing these limitations is imperative for assessing blockchain's applicability and devising solutions. This paper introduces a hybrid mechanism, ShardedScale, designed to enhance scalability, throughput, and system performance while mitigating time, gas, and ether consumption. The proposed ShardedScale approach combines various techniques including Proof of Work (PoW), Dynamic On-demand Proof of Stake (DPOS), Inter Planetary File System (IPFS), and sharding. ShardedScale achieved a remarkable 40% reduction in transaction confirmation times, a substantial 60% improvement in throughput, and demonstrated cost-effectiveness with a 30% reduction in gas price consumption and a 25% decrease in ethers consumption. These findings signify a significant step towards addressing challenges faced by traditional blockchain systems, providing valuable insights for future designs in blockchain technology.

© 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application

Keywords: Blockchain; PoS; DPoS; Consensus; Sharding; IPFS

1. Introduction

Blockchain technology is a decentralized and distributed ledger system that facilitates the secure and transparent recording and verification of digital transactions among multiple participants. It operates by organizing transactions

1877-0509 © 2024 The Authors. Published by Elsevier B.V.
This is an open access article under the CC BY-NC-ND license (https://creativecommons.org/licenses/by-nc-nd/4.0)
Peer-review under responsibility of the scientific committee of the 5th International Conference on Innovative Data Communication Technologies and Application
10.1016/j.procs.2024.03.233

into blocks and linking them through unique cryptographic hash values, forming a chain-like structure. The fundamental elements of a blockchain include cryptographic hashes, consensus mechanisms, and a network of nodes. Cryptographic hashes play a vital role in maintaining data integrity by generating distinct fixed-length identifiers for each block. Consensus mechanisms, such as Proof of Work or Proof of Stake, ensure agreement among nodes regarding transaction validity and order. Nodes, which can be either individuals or computers, maintain a complete copy of the entire blockchain and actively engage in validating transactions and creating new blocks.

1.1. Background

In 2008, Satoshi Nakamoto presented an original proposition regarding the establishment of a digital currency through a dispersed register and decentralized infrastructure [1]. By doing so, he aimed to create a method of carrying out financial transactions that were protected and transparent while circumventing the requirement for mediators such as banks or government entities. He accomplished this by employing encryption techniques along with a group of nodes that validated and recorded all trades onto a digital record called a blockchain. As a result of the achievement of Bitcoin, alternative currencies like Ethereum [2], Litecoin [3], and Ripple [4] began to arise, each providing distinctive characteristics and uses. Moreover, this technology has been utilized in several industries, voice based intelligent systems [5], encompassing logistics management, medicine, election processes, power distribution, social media [6] and others, thus fostering growth and experimentation.

1.2. Current Trend

Blockchain technology has numerous applications beyond cryptocurrencies. It can be utilized for supply chain management, voting systems, identity verification, smart contracts. By leveraging its trust and security benefits, blockchain has the potential to revolutionize various industries and enhance efficiency, accountability, and privacy in digital transactions. However, blockchain faces several challenges including limited scalability due to cost and high energy consumption; lack of a single comprehensive regulatory framework across jurisdictions; concerns related to environmental sustainability particularly in relation to energy usage during mining process; and potential vulnerability to quantum computing attacks which might disrupt encryption schemes used by public key infrastructure (PKI) systems [7]. Blockchain provides tamper-proof storage of different types of data in addition to transactions like ownership records and intellectual property rights. Key features of blockchain technology include decentralization, transparency, and data immutability achieved through consensus mechanisms like proof-of-work [8] , proof-of-stake, and delegate proof-of-stake [9] and many more. This enables reliable verification of transactions without relying on intermediaries, making it ideal for applications in finance, supply chains, voting systems, and other areas where trust and accountability are an essential part of the system. Efforts are underway to address these shortcomings by developing novel architectures, optimizing consensus protocols, deploying zero-knowledge proofs (ZKP) [10], introducing sidechains, implementing privacy enhancing techniques, and integrating cross-chain communication methods [11].

1.3. Sharding

Blockchain Sharding [12] is a technique that involves dividing the network's state into smaller sections or shards. This helps to address scalability and performance issues by distributing the computational load across multiple nodes, thereby increasing the network's capacity. However, sharding in blockchain technology comes with technical challenges that need to be tackled to maintain the system's decentralization. One of the significant challenges is achieving consensus on validated state updates across all participants without introducing centralization. Consensus across multiple shards requires designing cross-shard communication protocols that allow participants to agree on the current state without any single entity's control or influence. To overcome this challenge, researchers have explored several methods for enabling trustless cross-shard communication. One promising approach is to use cryptographic techniques such as secure multi-party computation (MPC) [13] and zero-knowledge proofs (ZKPs). Secure MPC allows multiple participants to jointly compute a function on their private inputs without revealing their inputs to each other. ZKPs enable participants to prove the validity of their inputs without disclosing any information about their

inputs themselves. These techniques help participants reach a shared agreement on the current state without requiring any single entity to control the network's state. Another approach is to use a sidechain [14] [15] architecture where a secondary blockchain, called a sidechain, is used to store data related to a specific application or use case. This data can be transferred between the main chain and the sidechain as required, allowing participants to agree on the current state without requiring any single entity's control or influence. Sidechain architectures are particularly useful for applications that require specialized functionality or involve high-volume, low-value transactions [16].

The contributions of the proposed ShardedScale are as follows:

- Configure a blockchain network and integrate sharding mechanism.
- Build a smart contract which integrate the functionalities of PoW, DPoS and sharding technique.
- Integrate IPFS with hybrid consensus to create a decentralized and resilient storage solution for the network data.
- Perform comparative study analysis of the proposed ShardedScale approach with existing consensus mechanisms.

The paper is structured in the following manner: Section 1 delves into blockchain technology and outlines the research paper's objectives. Section 2 explores relevant literature to provide an overview of blockchain consensus mechanisms and issues. Section 3 unveils the proposed ShardedScale architecture and the proposed system's workflow. Section 4 elaborates on the implemented modules. Section 5 presents the results and comparative study analysis of the proposed ShardedScale approach against existing systems. Section 6 concludes the paper, highlighting its implications and potential directions for future exploration.

2. Literature Review

The surveyed literature emphasizes various aspects of sharding-based blockchain protocols, shedding light on innovative solutions and challenges in the field. Kokoris-Kogias et al. introduced OmniLedger, a protocol employing sharding for enhanced blockchain performance. With distributed randomness generation, VRF-based leader election, and Byzantine fault-tolerant consensus, the protocol achieves secure sharding. Atomix, a two-step atomic commit protocol, is presented for cross-shard transactions, accompanied by a comprehensive security analysis that demonstrates resistance to diverse attacks, including censorship and double-spending attacks. The performance evaluation showcases the protocol's ability to achieve high throughput and low latency while upholding strong security guarantees [17].

In Abdelhafiz's work, the focus shifts to the distribution of databases through sharding, aimed at improving throughput and reducing reaction time. The author addresses challenges associated with distributed databases, such as monolithic architecture and custom requirements. The paper concludes by highlighting the benefits of Oracle sharding, which automates the entire life cycle of shards, from deployment to schema creation and data routing [18]. Wang introduces a sharding scheme, NRSS, designed to tackle performance issues arising from node differences in blockchain systems. NRSS evaluates node behavior, scoring them based on past performance to balance the proportion of honest and dishonest nodes in each committee. This, in turn, enhances transaction throughput and blockchain security. Experimental evaluations demonstrate the effectiveness of NRSS in improving both transaction throughput and security [19].

Zheng's paper introduces Aeolus, a novel approach to enhance the performance of permissioned blockchain systems. By extending a single blockchain peer into a cluster and utilizing distributed state update sharding, Aeolus achieves parallel and distributed transaction execution. Comparative analysis reveals that Aeolus outperforms existing platforms, reaching over 100,000 TPS across 32 shards [20]. Huang's work addresses the issue of imbalanced transaction assignments in sharding-based blockchain systems. The author utilizes the Lyapunov Optimization framework to allocate network resources to blockchain shards elastically, maintaining stable transaction processing even under bursty-TX injection attacks. The proposed algorithm, based on drift-plus-penalty, is supported by theoretical analyses and numerical simulations, demonstrating its effectiveness in maintaining system stability [21]. Amiri's model for a permissioned blockchain system, designed for networks with numerous nodes, introduces clusters of 3f+1 nodes for processing transactions in parallel. Sharding data across clusters, the model supports both intra- and cross-shard transactions, resulting in a directed acyclic graph for the blockchain ledger. The paper highlights the need

for workload-aware sharding and suggests future work on developing a consensus protocol for ordering intra- and cross-shard transactions [22].

The literature survey reveals common challenges in blockchain, including securing cross-shard transactions while maintaining high throughput and low latency. Additionally, optimizing the allocation of network resources to prevent imbalanced transaction assignments and implementing workload-aware sharding for efficient transaction processing emerge as crucial areas for future research. Finally, the necessity for a consensus protocol to order intra- and cross-shard transactions is underscored as an essential consideration for advancing sharding-based blockchain systems.

3. Proposed Methodology

To address the challenges of scalability and performance within the Blockchain network, the proposed ShardedScale a hybrid system design that seamlessly integrates sharding, IPFS, and DPOS. This innovative approach aims to optimize transaction processing by leveraging the strengths of each component. In the context of developing a hybrid blockchain solution that integrates Proof of Work (PoW), Delegated Proof of Stake (DPoS), Inter Planetary File System (IPFS), and sharding to overcome scalability, throughput, time, and gas price limitations, the role of smart transactions becomes pivotal. Smart transactions play a crucial role in enhancing the efficiency and functionality of the hybrid blockchain solution. These transactions are programmable and self-executing, allowing for the automation of specific actions based on predefined conditions. The proposed ShardedScale system design can be seen in Fig.1.




Fig. 1. Proposed ShardedScale System Design

3.1. Blockchain Configuration

Establishing a blockchain infrastructure using Geth (Go Ethereum) on a Linux environment necessitates a methodical deployment process to guarantee a resilient and secure decentralized network. The setup commences with installing Geth through the package manager or by acquiring the binary distribution. Upon installation, initialize a new blockchain or establish a connection to an existing one by configuring the genesis block and dedicating a data directory. Next, initiate the Geth node, specifying parameters such as the network ID, data directory, and port settings. Facilitate synchronization with the Ethereum network to ensure real-time replication of the latest state. Users can interact with the blockchain via the Geth console or through RPC for programmatic access. Security considerations should be paramount, encompassing the implementation of firewalls and the adoption of secure key management practices to safeguard the integrity of the blockchain network. Consistent updates and adherence to industry best practices in network administration are essential for establishing a robust and dependable blockchain infrastructure

utilizing Geth on the Linux platform, thereby laying a solid foundation for decentralized applications and smart contracts. The Fig. 2 shows the mining process in the configured blockchain network.




Fig. 2. Mining in the Configured Blockchain Network

3.2. Sharding for Improved Scalability

Scalability refers to the ability of a blockchain network to handle an increasing number of users and transactions without compromising performance. It is a crucial aspect for the widespread adoption of blockchain technology, as it directly impacts factors such as transaction speed, transaction fees, and network congestion. Two key metrics that define blockchain scalability are throughput and cost. Throughput measures the number of transactions a network can ~~process~~ transactions per second (TPS). A higher TPS indicates better scalability, as it allows the network to accommodate more users and transactions without experiencing delays or congestion. Cost, on the other hand, refers to the transaction fees incurred when using the network. Lower transaction fees incentivize users to adopt the network, further driving its scalability. Sharding, serves as a pivotal strategy to enhance the scalability of the Blockchain network. This innovative approach involves segmenting the network into smaller, manageable sections, known as shards, and holds the key to fostering independent transaction processing within each shard. By breaking down the network into discrete shards, each with its distinct set of responsibilities, the proposed approach enables parallel processing of transactions. This strategic division ensures that the entire network is not burdened with processing every transaction, thereby significantly enhancing scalability [23]. Furthermore, each shard is equipped with its unique consensus mechanism, tailored to optimize the processing of transactions.

3.3. Decentralized Storage with IPFS

The integration of the Inter Planetary File System (IPFS) serves a critical role in ensuring efficient and decentralized storage of data. This strategic incorporation enhances the overall reliability and resilience of the system by revolutionizing the way data is stored and retrieved. IPFS operates on a fundamental principle of decentralization, departing from traditional, centralized storage systems. By distributing file storage across the network, the IPFS reduces the risk of a single point of failure and enhance the system's robustness. Each node within the network becomes a potential source of data, contributing to a more resilient and fault-tolerant architecture. A pivotal aspect of proposed approach is the storage of file hashes on the blockchain [24]. This not only serves as a reference point for the authenticity and integrity of files but also aligns with the blockchain's immutable nature. The blockchain hash stored alongside these file hashes acts as a secure anchor, verifying the authenticity of the requested files and ensuring that the data retrieved is consistent with the stored records.

3.4. Democratic Decision-Making with DPOS

The integration of Delegated Proof-of-Stake (DPOS) emerges as a pivotal mechanism for establishing a democratic

and efficient decision-making process. This strategic inclusion of DPOS not only enhances the governance structure but also promotes inclusivity and streamlined decision-making within the Blockchain network. DPOS introduces a unique and democratic approach by relying on voting to select block producers. In this system, participants within the network exercise their voting rights to choose individuals or entities that will assume the responsibility of validating transactions and creating blocks. This democratic selection process fundamentally transforms the governance landscape, allowing network participants to actively shape the direction of the blockchain.

3.5. Transaction Processing

Transactions can be either intra-shard or cross-shard. Intra-shard transactions are processed within a single shard, while cross-shard transactions require communication and coordination between shards. A cross-shard communication protocol enables information exchange and state synchronization between shards, ensuring consistent views of the network. To maintain security and consistency, a shard reconfiguration protocol defines how shards are created, merged, split, or migrated. Techniques like random sampling, voting, and reputation may be employed for shard reconfiguration.




Fig. 3. System Flow for the proposed ShardedScale

Fig. 3 depicts the proposed system implementation flow. Sharding begins by creating smaller subsets or shards of the blockchain. Each shard is independently processed by a subset of nodes. Transactions within a shard are processed in parallel, enhancing scalability. Cross-shard communication mechanisms are implemented for transactions involving multiple shards. Shard-level consensus and coordination mechanisms ensure node collaboration and network security. Proof-of-Work (PoW) is utilized as a consensus mechanism, where mining nodes compete to solve mathematical problems for block creation. DPOS, on the other hand, relies on voting to select block producers who validate transactions and create blocks. IPFS is employed for decentralized file storage, with file hashes stored on the blockchain. Retrieving files involves requesting them using their IPFS hash and verifying authenticity with the stored blockchain hash. Sharding involves a systematic process, determining parameters, dividing the network into shards, and assigning unique address ranges to avoid conflicts. Inter-shard communication ensures collaborative validation of cross-shard transactions, while periodic state sharing synchronizes shard views. Shard merging and splitting address load imbalance issues, balancing network performance over time. The shard selection algorithm plays a crucial role in ensuring a balanced approach to reconfiguration.

4. Implementation

The proposed ShardedScale approach is divided among modules as follows, outlining a systematic and comprehensive strategy for its deployment and execution.

4.1. Sharding Module

The algorithm presented in the Algorithm 1 determines the sharding parameters and divides a network into shards. It takes the network size and desired shard size as inputs and outputs the shard assignments. The algorithm calculates the number of shards based on the network size and desired shard size. It then assigns nodes to each shard, balancing the load and ensuring connectivity. The shard assignments are recorded for each node, and the results are stored in a configuration file or database for future use.

Algorithm 1: Sharding Module – Determine the sharding Parameters and Divide the Network into Shards

```
Prerequisites:
        Input: network size, desired shard size
        Output: shard assignments
Step 1: Determine the number of shards needed based on network size and desired shard size.
        numShards ← [networkSize/desiredShardSize]
Step 2: Assign nodes to each shard in a way that balances load and maintains connectivity.
        for shard ← 1 to numShards do
        // Select nodes for this shard
                nodes ← selectNodesForShard(shardSize)
                // Record the shard assignments
                for node in nodes do
                    shardAssignments[node] ← shard
                end for
        end for
Step 3: Store shard assignments in a configuration file or database for later use
        storeShardAssignments(shardAssignments)
```

4.2. Sharding Communication Module

The Algorithm 2 assigns addresses and determines cross-shard transactions based on shard assignments and connectivity graphs for each shard. It takes the shard assignments and connectivity graph as inputs and outputs the protocol for cross-shard communication. The algorithm iterates over each node in a shard and checks its connectivity with nodes in other shards. If a connection exists, it adds a cross-shard communication protocol for the corresponding shards and nodes.

Algorithm 2: Sharding Communication Module - Assigning addresses and determining cross-shard transaction

```
Prerequisites:
        Input: shard assignments, connectivity graph for each shard
        Output: protocol for cross-shard communication

        for each node in nodesInShard do
                for each otherNode in otherShard do
                        if isNodeConnected(connectivityGraph[shard], node, connectivityGraph[otherShard],
                otherNode) then
                                addCrossShardCommunicationProtocol (shard, otherShard, node, otherNode)
                        end if
                end for
        end for
```

4.3. Transaction Addressing Module

The Algorithm 3 assigns addresses to transactions based on the given shards, shard size, transactions, and shard IDs. It takes these inputs and outputs the transaction addresses. The algorithm initializes a dictionary to store the address range for each shard. It then calculates the start and end address for each shard and stores them in the

dictionary. The "assign_address" function is used to assign an address to a transaction based on the specified shard. It verifies if the shard ID is valid and throws an error if not. It also checks if the transaction address falls within the shard's address range and throws an error if it does not. Finally, it returns the transaction address if it satisfies the shard's address range.

Algorithm 3: Transaction Addressing Module

```
Prerequisites:
        Input: shards, shard size, transactions, shard IDs
        Output: transaction addresses
Step 1: Initialize a dictionary to store address range for each shard
        shard_addresses ← {}
Step 2: Calculate the start and end address for each shard and store them in the dictionary
        for each shard in shards do
                start_address ← shard_size × shard_id
                end_address ← start_address + shard_size - 1
                shard_addresses[shard] ← (start_address, end_address)
        end for
Step 3: Define function to check the validity of the shards.
        function assign_address (transaction, shard)
                if shard not in shard_addresses then
                        throw error ("Invalid shard ID")
                end if
                (start_address, end_address) ← shard_addresses[shard]
                transaction_address ← calculate_transaction_address(transaction)
                if transaction_address < start_address or transaction_address > end_address then
                        throw error ("Transaction address out of shard range")
                end if

                return transaction_address
        end function
```

5. Results and Discussion

The examination of performance metrics, encompassing scalability, throughput, and resource consumption, sheds light on the tangible impact and efficiency of ShardedScale in comparison to alternative models. Through an in-depth analysis, the implications of the findings are explored.




Fig. 4. (a) Transaction Distribution before Sharding; (b) Transaction Distribution after Sharding

In Fig. 4(a), a pie chart visually represents the distribution of transactions processed by each node in the system. Notably, Node 4 stands out as it is responsible for the highest share of transactions, accounting for 31.2% of the total. Conversely, Node 8 processes the lowest proportion of transactions, amounting to 3.8%. This chart offers valuable

insights into the workload distribution among nodes within the system. Understanding such distribution is crucial for optimizing performance, as it allows for identifying potential bottlenecks and areas of imbalance. Fig. 4(b) presents another pie chart illustrating a different scenario. In this case, each node is shown to have an equal share of transactions, with each node processing 12.5% of the total. This balanced distribution signifies that transaction workloads have been effectively rebalanced across all nodes. Achieving such equilibrium is advantageous for system performance, as it prevents individual nodes from being overburdened, contributing to more efficient and stable operation.

5.1. Scalability

Based on the graph represented in Fig. 5, it can be observed that the proposed ShardedScale approach exhibits enhanced scalability in comparison to the existing mechanisms. This scalability advantage can contribute to the overall effectiveness and versatility of the proposed approach in various applications and scenarios.




Fig. 5. Graph depicting Scalability

5.2. Gas Price Consumption

The vertical bar graph in Fig. 6 provides a visual representation of the percentage reduction in gas prices achieved by various consensus mechanisms. ShardedScale stands out with the lowest gas price consumption, showing a 55% reduction, while the other mechanisms DPOS, and PoW + PoS exhibit reductions of 85%, and 78%, respectively. The PoW is the baseline considered for comparison with 100% Gas Usage.




Fig. 6. Gas Price Consumption of different systems

5.3. Throughput

The bar chart in Fig. 7 provides a comprehensive visualization of the throughput increase achieved by different consensus mechanisms in blockchain systems. The PoW is considered as baseline for comparison depicting 100%. ShardedScale stands out as the most impactful, demonstrating a substantial 196% increase in throughput, while DPOS, and PoW + PoS exhibit increases of 145%, and 168%, respectively.




Fig. 7. Throughput of different systems

5.4. Energy Consumption

The bar chart in Fig. 8 meticulously illustrates the energy consumption of different consensus mechanisms across varying transaction groups in the context of blockchain systems. Four consensus mechanisms—Proof-of-Work (PoW), Proof-of-Stake (PoS), Hybrid PoW + PoS, and ShardedScale are examined in terms of their energy consumption measured in kilowatt-hours (kWh). The x-axis represents different transaction groups, ranging from 10 transactions to 10,000 transactions, while the y-axis denotes the energy consumption in kWh. Notably, ShardedScale consistently demonstrates the lowest energy consumption across all transaction groups, showcasing its efficiency in minimizing energy requirements for transaction processing. In contrast, PoW exhibits the highest energy consumption, particularly evident with larger transaction groups.




Fig. 8. Energy Consumption of different Systems for different number of Transactions

The efficiency of block generation mechanisms directly impacts the throughput of the blockchain. ShardedScale's ability to generate blocks efficiently contributes to reduced transaction confirmation times and increased overall

network performance. The way in which data is distributed and stored across the network influences both transaction processing and the overall robustness of the blockchain. The overall efficiency of ShardedScale, considering resource utilization and network responsiveness, is a crucial factor. A well-balanced and responsive network contributes to improved user experience and increased confidence in the system.

5.5. Comparative Study Analysis

The comparative study analysis in Table 1 evaluates the proposed ShardedScale blockchain in contrast to other prominent approaches, including Ethereum, Ethereum 2.0, Binance, FileCoin, and Polkadot. ShardedScale employs a consensus mechanism that combines Proof of Work (PoW), Delegated Proof of Stake (DPoS), Sharding, and Inter Planetary File System (IPFS), resulting in very high throughput and scalability. In terms of gas consumption, ShardedScale demonstrates very low levels, distinguishing it from Ethereum with high gas consumption. Similarly, Ether consumption in ShardedScale is minimal compared to Ethereum. Transaction confirmation time is noted as very fast for ShardedScale, contrasting with the slower confirmation times associated with Ethereum. Overall, ShardedScale appears to offer a compelling combination of high throughput, scalability, and efficiency in gas and Ether consumption, positioning it favorably against other blockchain approaches.

Table 1. Comparative Study Analysis of proposed ShardedScale with other approaches.

Criteria	Proposed ShardedScale	Ethereum	Ethereum 2.0	Binance	FileCoin	Polkadot
Consensus Mechanism	PoW + DPoS + Sharding + IPFS	PoW	PoS	PoW + PoS	PoREP	NPoS
Throughput	Very High	Moderate	High	High	Moderate	High
Scalability	Very High	Limited	High	High	Limited	High
Gas Consumption	Very Low	High	Low	Moderate	Moderate	Moderate
Ether Consumption	Minimal	High	Minimal	Moderate	Moderate	Moderate
Transaction Confirmation Time	Very Fast	Slow	Fast	Fast	Slow	Fast

6. Conclusion and Future Scope

The proposed ShardedScale showed a remarkable 40% reduction in transaction confirmation times compared to alternative models. This achievement can be attributed to the synergies of streamlined DPoS consensus, the distributed IPFS file system, and sharding's parallel processing capabilities. Notably, throughput experienced a substantial 60% improvement, driven by efficient block generation, decentralized storage, and parallel transaction processing with the proposed ShardedScale approach. The proposed ShardedScale also demonstrated cost-effectiveness, as evidenced by a 30% reduction in gas price consumption and a 25% decrease in ethers consumption, attributed to optimized consensus and storage mechanisms. Furthermore, the scalability, a pivotal factor for blockchain viability, witnessed a significant 70% improvement over traditional PoW consensus mechanism. Potential enhancements in consensus mechanisms and optimization algorithms could further elevate DPoS efficiency. Advanced cryptography within IPFS may reinforce data security, and sharding could evolve to support dynamic strategies for optimal resource utilization. The introduction of cross-chain interoperability protocols may foster a more interconnected and collaborative decentralized ecosystem, overcoming prevailing challenges. Future research may pivot towards standardized frameworks and tools for broader accessibility.

References

[1] Nakamoto, S. (2008) "Bitcoin: A Peer-to-Peer Electronic Cash System." SSRN Electronic Journal.

[2] Vujičić, D., Jagodić, D., and Ranđić, S. (2018) "Blockchain technology, bitcoin, and Ethereum: A brief overview." In 2018 17th International Symposium INFOTEH-JAHORINA (INFOTEH), East Sarajevo, Bosnia and Herzegovina, pp. 1-6.

[3] Miglietti, C., Kubosova, Z., and Skulanova, N. (2019) "Bitcoin, Litecoin, and the Euro: an annualized volatility analysis." Studies in Economics and Finance, vol. ahead-of-print, no. ahead-of-print.
[4] Qiu, T., Zhang, R., and Gao, Y. (2019) "Ripple vs. SWIFT: Transforming Cross Border Remittance Using Blockchain Technology." Procedia Computer Science, vol. 147, pp. 428-434.
[5] Kone, Vinayak Sudhakar et al. (2023) "Voice-based Gender and Age Recognition System." In 2023 International Conference on Advancement in Computation & Computer Technologies (InCACCT), pages 74--80.
[6] Kone, Vinayak Sudhakar et al. (2023) "Emoji Prediction Using Bi-Directional LSTM." In ITM Web of Conferences, volume 53. EDP Sciences.
[7] Zheng, Z., Xie, S., Dai, H. N., Chen, X., and Wang, H. (2018) "Blockchain challenges and opportunities: a survey." International Journal of Web and Grid Services, vol. 14, no. 4, pp. 352-375.
[8] Gervais, A., Karame, G. O., Wüst, K., Glykantzis, V., Ritzdorf, H., and Capkun, S. (2016) "On the Security and Performance of Proof of Work Blockchains." In Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security - CCS'16.
[9] Saad, S. M. S., Radzi, R. Z. R. M., and Othman, S. H. (2021) "Comparative Analysis of the Blockchain Consensus Algorithm Between Proof of Stake and Delegated Proof of Stake." In 2021 International Conference on Data Science and Its Applications (ICoDSA).
[10] Sun, X., Yu, F. R., Zhang, P., Sun, Z., Xie, W., and Peng, X. (2021) "A Survey on Zero-Knowledge Proof in Blockchain." IEEE Network, vol. 35, no. 4, pp. 198-205.
[11] Pupyshev, Aleksei et al. (2020) "Gravity: a blockchain-agnostic cross-chain communication and data oracles protocol." arXiv (Cornell University).
[12] Lepikhin, Dmitry et al. (2020) "GShard: Scaling Giant Models with Conditional Computation and Automatic Sharding." arXiv (Cornell University).
[13] Du, Wenliang, and Atallah, Mikhail J. (2001) "Secure multi-party computation problems and their applications: a review and open problems." In Proceedings of the 2001 workshop on new security paradigms.
[14] Singh, Amritraj, et al. (2020) "Sidechain technologies in blockchain networks: An examination and state-of-the-art review." Journal of Network and Computer Applications, 149, 102471.
[15] Kim, Soohyeong, Kwon, Yongseok, and Cho, Sunghyun. (2018) "A survey of scalability solutions on blockchain." In 2018 International Conference on Information and Communication Technology Convergence (ICTC). IEEE.
[16] Fan, Daniel Kastensson. (2018) "A Blockchain-Based Solution to High-Volume Web Scraping With Smart Contracts on Ethereum."
[17] Kokoris-Kogias, E., Jovanovic, P., Gasser, L., Gailly, N., Syta, E., and Ford, B. (2018) "OmniLedger: A Secure, Scale-Out, Decentralized Ledger via Sharding." IEEE Xplore.
[18] Abdelhafiz, B. M. (2020) "Distributed Database Using Sharding Database Architecture." IEEE Xplore.
[19] Wang, J.-R., Zhou, Y., Li, X., Xu, T., and Qiu, T. (2019) "A Node Rating Based Sharding Scheme for Blockchain." In International Conference on Parallel and Distributed Systems.
[20] Zheng, P. et al. (2022) "Aeolus: Distributed Execution of Permissioned Blockchain Transactions via State Sharding." IEEE Transactions on Industrial Informatics, pp. 1-1.
[21] Huang, H. et al. (2022) "Elastic Resource Allocation Against Imbalanced Transaction Assignments in Sharding-Based Permissioned Blockchains." IEEE Transactions on Parallel and Distributed Systems, vol. 33, no. 10, pp. 2372-2385.
[22] Amiri, M. J., Agrawal, D., and El Abbadi, A. (2019) "On Sharding Permissioned Blockchains." IEEE Xplore.
[23] Dhulavvagol, P. M., Bhajantri, V. H., and Totad, S. G. (2020) "Performance Analysis of Distributed Processing System using Shard Selection Techniques on Elasticsearch." Procedia Computer Science, vol. 167, pp. 1626-1635.
[24] Dhulavvagol, P. M., and Totad, S. G. (2023) "Performance Enhancement of Distributed System Using HDFS Federation and Sharding." Procedia Computer Science, vol. 218, pp. 2830-2841.