

# Shipper Integration Guide for selloship.com

## 1. Overview

This guide provides comprehensive instructions and API references for shipping providers or logistics aggregators to integrate with **selloship.com**, an order management platform. This integration enables sellers to seamlessly fulfill orders, generate shipping labels, and track shipments.

---

## 2. Benefits of Integration

- Automated allocation of shipping provider based on pincode and priority
  - Real-time tracking and status updates
  - PDF shipping label generation
  - Centralized order management
- 

## 3. Integration Flow Summary

1. **Waybill Generation:** Generate waybill number and shipping label
  2. **Get Shipment Status:** Retrieve latest shipment tracking details
  3. **Waybill Cancellation:** Cancel generated AWB before dispatch (optional)
  4. **Generate Manifest:** Download manifest PDF (mandatory for aggregators)
-

## 4. API Specifications

### 4.1 SP Authentication

- **Endpoint:** `/authToken`
- **Method:** POST
- **Headers:**

- `Content-Type: application/json`

#### Request Payload:

```
JSON
{
  "username": "your_username",
  "password": "your_password"
}
```

#### Response:

```
JSON
{
  "status": "SUCCESS",
  "token": "your_api_token"
}
```

Base will use this token in `Authorization` header (`apikey`) in all subsequent requests.

---

### 4.2 Waybill Generation

- **Endpoint:** `/waybill`
- **Method:** POST

- **Headers:**

```
0 Content-Type: application/json

0 Authorization: <api_token>
```

### **Payload Highlights:**

- Complete order, item, address, and logistics details

### **Request Payload**

JSON

```
{
  "Shipment": {
    "orderCode": "String",
    "invoiceCode": "String",
    "weight": "53.4000",
    "length": "30",
    "height": "10",
    "breadth": "15",
    "items": [
      {
        "name": "String",
        "quantity": 2,
        "skuCode": "string",
        "itemPrice": 600.00,
```

```
        "category": "string",
    },
    {
        "name": "String",
        "quantity": 1,
        "skuCode": "string",
        "itemPrice": 600.00,
        "category": "string",
    }
]
},
"deliveryAddressDetails": {
    "name": "String",
    "email": "String",
    "phone": "8888888888",
    "address1": "String",
    "address2": "String",
    "pincode": "122016",
    "city": "Gurgaon",
    "state": "Haryana",
    "country": "India",
```

```
    "alternatePhone": "9090909090",  
  },  
  "pickupAddressId": "String",  
  "pickupAddressDetails": {  
    "name": "String",  
    "email": "String",  
    "phone": "9999999999",  
    "address1": "String",  
    "address2": "String",  
    "pincode": "400092",  
    "city": "Mumbai",  
    "state": "Maharashtra",  
    "country": "India",  
  },  
  "returnAddressId": "String",  
  "returnAddressDetails": {  
    "name": "String",  
    "email": "String",  
    "phone": "9999999999",  
    "address1": "String",  
    "address2": "String",
```

```
    "pincode": "400092",

    "city":      "Mumbai",

    "state": "Maharashtra",

    "country": "India",

  },

  "currencyCode": "INR",

  "paymentMode": "PREPAID",

  "totalAmount": "200.00",

  "collectableAmount": "0",

  "courierName": "String",

  "courierID": "String",

  "isLablePdf": "boolean",

]

}
```

## Response:

```
JSON

{
  "status": "SUCCESS",
  "waybill": "AWB123456789",
  "shippingLabel": "https://...label.pdf",
  "courierName": "FedEx",
  "routingCode": "Code123"
}
```

**Note:** Shipping label must be in **PDF** format via downloadable link.

---

### 4.3 Get Shipment Status

- **Endpoint:** `/waybillDetails`
- **Method:** GET
- **Headers:**
  - `Content-Type: application/json`
  - `Authorization: <api_token>`

#### Query Parameter:

- `waybills` (comma-separated AWB numbers in quotes):
  - Example: `"3113210963421,5213410156781"`

#### Response:

```
JSON
{
  "Status": "SUCCESS",
  "waybillDetails": [
    {
      "waybill": "AWB123456789",
      "currentStatus": "IN_TRANSIT",
      "statusDate": "25-Jun-2025 10:30:00",
      "current_location": "Mumbai Hub"
    }
  ]
}
```

---

## 4.4 Waybill Cancellation (Optional)

- **Endpoint:** `/cancel`

- **Method:** POST

- **Headers:**

- `Content-Type: application/json`

- `Authorization: <api_token>`

### Request:

```
JSON
{
  "waybill": "AWB123456789"
}
```

### Response:

```
JSON
{
  "status": "SUCCESS",
  "waybill": "AWB123456789",
  "errorMessage": "Pickup is successfully cancelled"
}
```

---



## 4.5 Generate Manifest (Mandatory for Aggregators)

- **Endpoint:** `/manifest`
- **Method:** POST
- **Headers:**
  - `Content-Type: application/json`
  - `Authorization: <api_token>`

### Request:

```
JSON
{
  "awbNumbers": ["AWB123456789", "AWB987654321"]
}
```

### Response:

```
JSON
{
  "status": "SUCCESS",
  "manifestNumber": 987654,
  "manifestDownloadUrl": https://manifest.pdf
}
```

Must be a valid **PDF** file link.

---

## 5. Common Error Handling

Each API supports standard response codes:

- **SUCCESS**: Operation completed successfully
- **FAILED**: Includes `message` and `reason` fields for debugging

Example Error:

JSON

```
{
  "status": "FAILED",
  "message": "Delivery Pincode is not serviceable",
  "reason": "INVALID_PINCODE"
}
```

---

## 6. Requirements & Best Practices

- All responses must conform to specified schema
  - All labels and manifests **must be in PDF format**
  - Provide AWB lists in quotes, max 50 per status call
  - Ensure timestamps follow `dd-mmm-yyyy HH:mm:ss` format
  - Maintain secure token-based communication
-

## 7. Final Steps

Once your team reviews this documentation and is ready:

1. Reach out to selloship.com's **Solutioning Team**
2. Share test credentials and base URLs
3. Perform sandbox integration
4. Move to production environment

---

For questions or clarification, contact: [it.hemrajthakor@selloship.com](mailto:it.hemrajthakor@selloship.com)

---

**End of Document**