

**5.37 kWH Stackable**

**51.2 V 105 AH**



| Model Name                        | ESS51.2V105AH            |
|-----------------------------------|--------------------------|
| Specification                     | 51.2V 105Ah              |
| Capacity (kwh)                    | 5.37 KWH                 |
| BMS Type                          | Smart JBD/PALY           |
| communication                     | Rs485                    |
| Max charging current              | 100 AMP                  |
| cycle life                        | ≥4000 Cycles @ 80% DOD   |
| Depth of Discharge (DOD)          | 95%                      |
| Operating Temperature (Charge)    | 0°C to 45°C              |
| Operating Temperature (Discharge) | -20°C to 60°C            |
| Storage Temperature               | 0°C to 40°C              |
| Weight                            | Approx. 55 kg            |
| Installation                      | Rack Mounted / Stackable |
| Warranty                          | 5 Years (Standard)       |

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

**7.68 kWh Stackable**

**51.2 V 150 AH**



| Model Name                        | ESS51.2V150AH                             |
|-----------------------------------|-------------------------------------------|
| Specification                     | 51.2V 150AH                               |
| Capacity (kwh)                    | 7.68 KWH                                  |
| BMS Type                          | Smart JBD/PALY                            |
| communication                     | RS485/CAN                                 |
| Max charging current              | 120A(single) /180A (multiple in parallel) |
| cycle life                        | ≥4000 Cycles @ 80% DOD                    |
| Depth of Discharge (DOD)          | 95%                                       |
| Operating Temperature (Charge)    | -10~50°C                                  |
| Operating Temperature (Discharge) | -20°C to 60°C                             |
| Case Material                     | Metal                                     |
| Weight                            | Approx. 65 kg                             |
| Installation                      | Rack Mounted                              |
| Warranty                          | 5 Years (Standard)                        |

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

**51.2 V 230 AH**



**Parallel Expandable**



**Modular Design**



**Smart BMS**



**OEM & ODM Support**



**CAN & RS485 Communication**



| Model Name                   | ESS51.2V230AH           |
|------------------------------|-------------------------|
| Nominal Voltage              | 51.2 V                  |
| Nominal Capacity             | 230 Ah                  |
| Capacity (kWh)               | 11.78 kWh               |
| Battery Chemistry            | LiFePO <sub>4</sub>     |
| Communication                | CAN / RS485             |
| Max Charging Current         | 100 A                   |
| Cycle Life @ 80% DOD         | ≥4000 Cycles            |
| Depth of Discharge           | 95%                     |
| Continuous Discharge Current | 0.5 C (115 A)           |
| Discharge Current            | 1 C (230 A, 10 Seconds) |
| Charge Voltage               | 58.4 V                  |
| Storage Temperature          | 0°C to 40°C             |
| Parallel Expansion           | Up to 16 Units          |
| BMS                          | Intelligent Smart BMS   |
| Warranty                     | 5 Years                 |

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

**51.2 V 314 AH**

**Parallel Expandable**

**Modular Design**

**Smart BMS**

**OEM & ODM Support**

**CAN & RS485 Communication**


| Model Name                   | ESS51.2V314AH              |
|------------------------------|----------------------------|
| Nominal Voltage              | 51.2 V                     |
| Nominal Capacity             | 314 Ah                     |
| Capacity (kWh)               | 16.08 kWh                  |
| Battery Chemistry            | LiFePO <sub>4</sub>        |
| Communication                | CAN / RS485                |
| Max Charging Current         | 100 A                      |
| Cycle Life @ 80% DOD         | ≥4000 Cycles               |
| Depth of Discharge           | 95%                        |
| Continuous Discharge Current | 0.5 C (115 A)              |
| Discharge Current            | 1 C (314 A, 10 Seconds)    |
| Charge Voltage               | 58.4 V                     |
| Storage Temperature          | 0°C to 40°C                |
| Scalability                  | Up to 16 Units in Parallel |
| BMS                          | Intelligent Smart BMS      |
| Warranty                     | 5 Years                    |

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

**48 V 314AH**



**15 KWH**  
CAPACITY



**SMART BMS**  
Protection



**LifeP04**  
Technology



**4000+**  
Cycle Life



| Model Name               | ESS48V314AH                  |
|--------------------------|------------------------------|
| Specification            | 48V 314AH                    |
| Capacity (kwh)           | 15.07KWH                     |
| BMS Type                 | Smart JBD/DALY               |
| communication            | RS485                        |
| Max charging current     | 200AMP                       |
| cycle life               | ≥ 4000 Cycles @ 80% DoD      |
| Depth of Discharge (DOD) | 95%                          |
| Operating Voltage Range  | 43.2V – 58.4V                |
| Charging Temperature     | 0°C to 55°C                  |
| Discharging Temperature  | -20°C to 60°C                |
| Storage Temperature      | 0°C to 35°C                  |
| Scalability              | Parallel Expansion Supported |
| Installation             | Floor Standing               |
| Design Life              | 10+ Years                    |
| Warranty                 | Up to 7 Years                |

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.