

Technical Datasheet

12.8 V 100 AH



Parallel Expandable



Smart BMS



Eco Friendly



Model Name	ESS12.8V100AH
Specification	12.8V 100AH
Capacity (kwh)	1.28 kWh (1280 Wh)
Battery Type	Lithium Iron Phosphate (LiFePO ₄)
BMS Type	Smart JBD
communication	RS485
Max charging current	50AMP
cycle life	≥ 4000 Cycles @ 80% DoD
Depth of Discharge (DOD)	95%
Charging Temperature	0°C to 55°C
Discharging Temperature	-20°C to 60°C
Operating Voltage Range	10.0V – 14.6V
Discharge Cut-off Voltage	10.0V
Peak Discharge Current	200A (10 sec)
Storage Temperature	0°C to 35°C
Design Life	10+ Years
Warranty	Up to 5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

12.8 V 100 AH



**1.28 kWh
Capacity**



Smart BMS



Modular Design



Model Name	ESS12.8V100AH
Specification	12.8V 100AH
Capacity (kwh)	1.28 kWh (1280 Wh)
Battery Type	Lithium Iron Phosphate (LiFePO ₄)
BMS Type	Smart JBD
communication	RS485
Max charging current	50AMP
cycle life	≥ 4000 Cycles @ 80% DoD
Depth of Discharge (DOD)	95 %
Charging Temperature	0°C to 55°C
Discharging Temperature	-20°C to 60°C
Operating Voltage Range	10.0V – 14.6V
Discharge Cut-off Voltage	10.0V
Peak Discharge Current	200A (10 sec)
Storage Temperature	0°C to 35°C
Design Life	10+ Years
Warranty	Up to 5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

25.6 V 105 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



OEM & ODM Support



Model Name	ESS25.6V105AH
Specification	25.6V 105AH
Capacity (kwh)	2.69 kWh (2688 Wh)
Battery Type	Lithium Iron Phosphate (LiFePO ₄)
communication	BT
Max charging current	50 AMP
Cycle Life	≥ 4000 Cycles @ 80% DoD
Depth of Discharge (DOD)	95%
Operating Voltage Range	21.6V – 29.2V
Charge Voltage	28.8V
BMS	Intelligent Built-in BMS
Charging Temperature	0°C to 55°C
Installation	Wall Mount / Floor Standing
Warranty	Up to 5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

60.3 kWh Stackable

48 V 314 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



Model Name	ESS48V314AH
Specification	48 V 314 AH
Capacity (kwh)	15.07 KWH
Battery Chemistry	Lithium Iron Phosphate (LiFePO ₄)
BMS Type	Smart 16S 200AMP
communication	RS485
Max charging current	180AMP
Cycle Life	≥4000 Cycles @ 80% DoD
Depth of Discharge (DOD)	95%
Operating Voltage Range	43.2V – 58.4V
Installation	Floor Standing
Scalability	Parallel Expansion Supported
Design Life	10+ Years
Warranty	Up to 6 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

5.37 kWh Stackable

51.2 V 105 AH



Model Name	ESS51.2V105AH
Specification	51.2V 105Ah
Capacity (kwh)	5.37 KWH
BMS Type	Smart JBD/PALY
communication	Rs485
Max charging current	100 AMP
cycle life	≥4000 Cycles @ 80% DOD
Depth of Discharge (DOD)	95%
Operating Temperature (Charge)	0°C to 45°C
Operating Temperature (Discharge)	-20°C to 60°C
Storage Temperature	0°C to 40°C
Weight	Approx. 55 kg
Installation	Rack Mounted / Stackable
Warranty	5 Years (Standard)

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

7.68 kWh Stackable

51.2 V 150 AH



Model Name	ESS51.2V150AH
Specification	51.2V 150AH
Capacity (kwh)	7.68 KWH
BMS Type	Smart JBD/PALY
communication	RS485/CAN
Max charging current	120A(single) /180A (multiple in parallel)
cycle life	≥4000 Cycles @ 80% DOD
Depth of Discharge (DOD)	95%
Operating Temperature (Charge)	-10~50°C
Operating Temperature (Discharge)	-20°C to 60°C
Case Material	Metal
Weight	Approx. 65 kg
Installation	Rack Mounted
Warranty	5 Years (Standard)

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.