

19.2 kWH Stackable

96 V 50 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



Model name	ESS96V50AH
Specification	96V 50AH
Capacity (kwh)	4.8 KWH
Battery Chemistry	LiFePO ₄ (Lithium Iron Phosphate)
communication	CAN / RS485
Max charging current	50 A
cycle life	≥4000 Cycles @ 80% DOD
Depth of Discharge (DOD)	95%
Charge Voltage	109.5 V
Discharge Cut-off Voltage	75 V
Maximum Charging Current	50 A
Continuous Discharge Current	50 A
Storage Temperature	0°C to 40°C
Installation	Floor Standing / Rack Mounted
Warranty	5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

120 V Stackable UPS

50 , 100 , 150 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



Model Name	ESS120V50AH	ESS120V100AH	ESS120V150AH
Specification	120V 50Ah	120V 100Ah	120V 150Ah
Capacity (kWh)	6.0 kWh	12.0 kWh	18.0 kWh
Battery Chemistry	LiFePO ₄	LiFePO ₄	LiFePO ₄
Communication	CAN / RS485	CAN / RS485	CAN / RS485
Max Charging Current	50 A	100 A	150 A
Cycle Life @ 80% DOD	≥4000 Cycles	≥4000 Cycles	≥4000 Cycles
Depth of Discharge	95%	95%	95%
continue Dis-Current	0.5 C	0.5 C	0.5 C
Discharge Current	1C (10 Seconds)	1C (10 Seconds)	1C (10 Seconds)
Charge Voltage	136.8 V	136.8 V	136.8 V
Storage Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C
Warranty	5 Years	5 Years	5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

240 V Stackable UPS

50 , 100 , 150 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



Model Name	ESS240V50AH	ESS240V100AH	ESS240V150AH
Specification	240V 50Ah	240V 100Ah	240V 150Ah
Capacity (kWh)	12.0 kWh	24.0 kWh	36.0 kWh
Battery Chemistry	LiFePO ₄	LiFePO ₄	LiFePO ₄
Communication	CAN / RS485	CAN / RS485	CAN / RS485
Max Charging Current	50 A	100 A	150 A
Cycle Life @ 80% DOD	≥4000 Cycles	≥4000 Cycles	≥4000 Cycles
Depth of Discharge	95%	95%	95%
continue Dis-Current	0.5 C	0.5 C	0.5 C
Discharge Current	1C (10 Seconds)	1C (10 Seconds)	1C (10 Seconds)
Charge Voltage	273.6 V	273.6 V	273.6 V
Storage Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C
Warranty	5 Years	5 Years	5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

360 V Stackable UPS

50 , 100 , 150 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



Model Name	ESS360V50AH	ESS360V100AH	ESS360V150AH
Specification	360V 50Ah	360V 100Ah	360V 150Ah
Capacity (kWh)	18.0 kWh	36.0 kWh	54.0 kWh
Battery Chemistry	LiFePO ₄	LiFePO ₄	LiFePO ₄
Communication	CAN / RS485	CAN / RS485	CAN / RS485
Max Charging Current	50 A	100 A	150 A
Cycle Life @ 80% DOD	≥4000 Cycles	≥4000 Cycles	≥4000 Cycles
Depth of Discharge	95%	95%	95%
continue Dis-Current	0.5 C	0.5 C	0.5 C
Discharge Current	1C (10 Seconds)	1C (10 Seconds)	1C (10 Seconds)
Charge Voltage	410.4 V	410.4 V	410.4 V
Storage Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C
Warranty	5 Years	5 Years	5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.

480 V Stackable UPS

50 , 100 , 150 AH



Parallel Expandable



Modular Design



Smart BMS



CAN & RS485 Communication



Model Name	ESS480V50AH	ESS480V100AH	ESS480V150AH
Specification	480V 50Ah	480V 100Ah	480V 150Ah
Capacity (kWh)	24.0 kWh	48.0 kWh	72.0 kWh
Battery Chemistry	LiFePO ₄	LiFePO ₄	LiFePO ₄
Communication	CAN / RS485	CAN / RS485	CAN / RS485
Max Charging Current	50 A	100 A	150 A
Cycle Life @ 80% DOD	≥4000 Cycles	≥4000 Cycles	≥4000 Cycles
Depth of Discharge	95%	95%	95%
continue Dis-Current	0.5 C	0.5 C	0.5 C
Peak Discharge Current	1C (10 Seconds)	1C (10 Seconds)	1C (10 Seconds)
Charge Voltage	547.2 V	547.2 V	547.2 V
Storage Temperature	0°C to 55°C	0°C to 55°C	0°C to 55°C
Warranty	5 Years	5 Years	5 Years

Note: Battery life is either 4000 cycles or 5 years. which ever is coming early.