



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment 7

Student Name: Ayush Tiwari

UID: 23BCS11366

Branch: BE-CSE

Section: Group: KRG-3B

Semester: 5

Date of performance: 29-10-2025

Subject name: ADBMS

Subject code: 23CSP-333

MEDIUM LEVEL PROBLEM

Requirements: design a trigger which:

1. Whenever there is a insertion or deletion on student table then, the currently inserted or deleted row should be printed on the console.

CODE:

```
-- create student table for testing
```

```
CREATE TABLE IF NOT EXISTS student
```

```
( id SERIAL PRIMARY KEY, name
```

```
TEXT NOT NULL, age INTEGER, class
```

```
TEXT
```

```
);
```

```
-- function for student audit (prints inserted/deleted row using RAISE NOTICE)
```

```
CREATE OR REPLACE FUNCTION fn_student_audit()
```

```
RETURNS TRIGGER
```

```
LANGUAGE plpgsql
```

```
AS
```

```
$$ BE
```

```
GIN
```

```
IF TG_OP = 'INSERT' THEN
```

```
RAISE NOTICE 'Inserted Row -> ID: %, Name: %, Age: %, Class: %',
```

```
NEW.id, NEW.name, NEW.age, NEW.class;
```

```
RETURN NEW;  
  
ELSIF TG_OP = 'DELETE' THEN  
    RAISE NOTICE 'Deleted Row -> ID: %, Name: %, Age: %, Class: %',  
        OLD.id, OLD.name, OLD.age, OLD.class;  
  
    RETURN OLD;  
  
END IF;  
  
RETURN NULL;  
  
END;  
  
$$;
```

-- trigger for student table

```
DROP TRIGGER IF EXISTS trg_student_audit ON student;
```

```
CREATE TRIGGER trg_student_audit
```

```
AFTER INSERT OR DELETE ON student
```

```
FOR EACH ROW
```

```
EXECUTE FUNCTION fn_student_audit();
```

```
INSERT 0 1
```

```
INSERT 0 1
```

```
DELETE 1
```

sno	message
1	Employee name Jyoti has been added at 2025-10-30 07:17:39
2	Employee name Neha has been added at 2025-10-30 07:17:39
3	Employee name Jyoti has been deleted at 2025-10-30 07:17:39

(3 rows)

HARD LEVEL PROBLEM

Requirements: Design postgresql triggers that:

1. Whenever a new employee is inserted in tbl_employee, a record should be added to tbl_employee_audit:

"Employee name <emp_name> has been added at <current_time>"



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

2. Whenever an employee is deleted from tbl_employee, a record should be added to tbl_employee_audit:

"Employee name <emp_name> has been deleted at <current_time>"

CODE:

-- Create employee tables

CREATE TABLE IF NOT EXISTS tbl_employee

(emp_id SERIAL PRIMARY KEY, emp_name

VARCHAR(100) NOT NULL, emp_salary

NUMERIC

);

CREATE TABLE IF NOT EXISTS tbl_employee_audit

(sno SERIAL PRIMARY KEY, message

TEXT

);

-- function to insert audit messages into tbl_employee_audit

CREATE OR REPLACE FUNCTION audit_employee_changes()

RETURNS TRIGGER

LANGUAGE plpgsql

AS

\$\$ BE

GIN

IF TG_OP = 'INSERT' THEN

INSERT INTO tbl_employee_audit(message)

VALUES (

'Employee name ' || NEW.emp_name || ' has been added at ' || to_char(NOW(),

'YYYY-MM-DD HH24:MI:SS')



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

```
);  
  
RETURN NEW;  
  
ELSIF TG_OP = 'DELETE' THEN  
    INSERT INTO tbl_employee_audit(message)  
    VALUES (  
        'Employee name ' || OLD.emp_name || ' has been deleted at ' || to_char(NOW(),  
        'YYYY-MM-DD HH24:MI:SS')  
    );  
  
    RETURN OLD;  
  
END IF;  
  
  
RETURN NULL;  
  
END;  
  
$$;  
  
-- trigger for tbl_employee  
  
DROP TRIGGER IF EXISTS trg_employee_audit ON tbl_employee;  
  
CREATE TRIGGER trg_employee_audit  
AFTER INSERT OR DELETE ON tbl_employee  
FOR EACH ROW  
EXECUTE FUNCTION audit_employee_changes();
```

Discover. Learn. Empower.

----- TESTING THE TRIGGERS -----

```
-- clear tables for a clean test (optional)  
  
TRUNCATE TABLE tbl_employee_audit RESTART IDENTITY;  
TRUNCATE TABLE tbl_employee RESTART IDENTITY;  
TRUNCATE TABLE student RESTART IDENTITY;
```



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

-- Test student trigger (you should see RAISE NOTICE messages in the console)

```
INSERT INTO student(name, age, class) VALUES ('Aniket', 15, '10A');
```

```
INSERT INTO student(name, age, class) VALUES ('Tanmay', 16, '11B');
```

```
DELETE FROM student WHERE name = 'Aniket';
```

-- Test employee trigger

```
INSERT INTO tbl_employee(emp_name, emp_salary) VALUES ('Jyoti', 50000);
```

```
INSERT INTO tbl_employee(emp_name, emp_salary) VALUES ('Neha', 65000);
```

```
DELETE FROM tbl_employee WHERE emp_name = 'Jyoti';
```

-- Check audit logs

```
SELECT * FROM tbl_employee_audit ORDER BY sno;
```

```
psql:commands.sql:42: NOTICE: trigger "trg_student_audit" for relation "student" does not exist, skipping
psql:commands.sql:100: NOTICE: trigger "trg_employee_audit" for relation "tbl_employee" does not exist, skipping
psql:commands.sql:115: NOTICE: Inserted Row -> ID: 1, Name: Aniket, Age: 15, Class: 10A
psql:commands.sql:116: NOTICE: Inserted Row -> ID: 2, Name: Tanmay, Age: 16, Class: 11B
psql:commands.sql:117: NOTICE: Deleted Row -> ID: 1, Name: Aniket, Age: 15, Class: 10A
```