

EURSKEM AI · ENGINEERING DOCUMENTATION

VOLUME 4

API Reference

Every HTTP endpoint exposed by the FastAPI application, with methods, paths, and authorization level.

Platform: Agentic Workflow Platform

Version: 0.1.0 · Generated: 2026-08-22

Built by Ayush Khandelwal

Typed workflows compiled to LangGraph · zero-token preflight · strict evidence lifecycle

1. Overview

The application mounts **163 routes** across **26 routers**. Data routes live under `/api/*` and identity routes under `/auth/*`; both sit behind Redis rate limiting, request-size limits, trusted-host checks, and a strict CORS policy wired in `app/main.py` and `app/security/middleware.py`. Authorization is role-based (admin / consultant / viewer) through `app/security/dependencies.py`, and every run-scoped read is additionally filtered by the caller's session scope, so one user can never observe another user's runs.

2. Authorization Map

Method	Path	Required level
GET	<code>/openapi.json</code>	?
GET	<code>/docs</code>	?
GET	<code>/docs/oauth2-redirect</code>	?
GET	<code>/redoc</code>	?
GET	<code>/health</code>	Public
GET	<code>/ready</code>	Public
POST	<code>/auth/token</code>	Public
GET	<code>/auth/me</code>	Authenticated
POST	<code>/auth/logout</code>	Public
GET	<code>/api/cost/run/{run_id}</code>	Authenticated
GET	<code>/api/cost/session/{session_id}</code>	Authenticated
GET	<code>/api/cost-admin/pricing</code>	Authenticated
PUT	<code>/api/cost-admin/pricing/{model}</code>	Authenticated
DELETE	<code>/api/cost-admin/pricing/{model}</code>	Authenticated
GET	<code>/api/cost-admin/infra-allocations</code>	Authenticated
PUT	<code>/api/cost-admin/infra-allocations/{model}</code>	Authenticated
GET	<code>/api/cost-admin/cache-summary</code>	Authenticated
GET	<code>/api/cost-admin/budgets</code>	Authenticated
PUT	<code>/api/cost-admin/budgets/global</code>	Authenticated
PUT	<code>/api/cost-admin/budgets/session/{session_id}</code>	Authenticated

GET	/api/cost-admin/overview	Authenticated
GET	/api/	Public
GET	/api/node-types	Authenticated
GET	/api/node-types/{node_type}/models	Public
POST	/api/workflows/validate	Authenticated
POST	/api/workflows/autofix	Authenticated
GET	/api/workflows/preflight-stats	Authenticated
POST	/api/workflows/run	Authenticated
POST	/api/workflows/{run_id}/resume	Authenticated
POST	/api/workflows/subprocess-callback/{token}	Public
GET	/api/workflows	Public
GET	/api/workflows/by-name/{name}	Public
GET	/api/workflows/{name}/detail	Public
GET	/api/workflows/{name}/stats	Authenticated
POST	/api/workflows/save	Public
DELETE	/api/workflows/{name}	Authenticated
PUT	/api/workflows/{name}/draft	Public
GET	/api/workflows/{name}/draft	Public
DELETE	/api/workflows/{name}/draft	Public
GET	/api/workflows/{name}/versions	Public
GET	/api/workflows/{name}/versions/{version_id}	Public
POST	/api/workflows/{name}/versions/{version_id}/restore	Public
GET	/api/runs/{run_id}/events	Authenticated
GET	/api/files	Public
POST	/api/eval/score-output	Authenticated
GET	/api/eval/golden-set	Authenticated
POST	/api/eval/run	Authenticated
GET	/api/eval/history	Authenticated
GET	/api/eval/workflow-golden-set	Authenticated

POST	/api/eval/workflow-compare	Authenticated
GET	/api/inspect/chunks	Authenticated
POST	/api/inspect/retrieve	Authenticated
GET	/api/audit/session/{session_id}	Authenticated
GET	/api/runs/mine	Authenticated
GET	/api/runs/mine/{run_id}	Authenticated
GET	/api/runs/mine/{run_id}/pending-gate	Authenticated
GET	/api/runs/mine/{run_id}/business-projection	Authenticated
POST	/api/runs/mine/{run_id}/business-narration	Authenticated
GET	/api/runs/mine/{run_id}/business-explanation	Authenticated
GET	/api/runs/mine/{run_id}/business-technical/{activity_id}	Authenticated
POST	/api/runs/mine/{run_id}/business-action	Authenticated
POST	/api/runs/mine/{run_id}/fact-correction	Authenticated
POST	/api/runs/mine/{run_id}/assign	Authenticated
POST	/api/runs/mine/{source_run_id}/retry	Authenticated
POST	/api/runs/mine/{run_id}/pause	Authenticated
POST	/api/runs/mine/{run_id}/resume	Authenticated
POST	/api/runs/mine/{source_run_id}/restart	Authenticated
DELETE	/api/runs/mine/{run_id}	Authenticated
POST	/api/proposals/coverage	Authenticated
GET	/api/proposals/runs/{run_id}/review	Authenticated
POST	/api/proposals/{proposal_id}/sources/{source_id}/versions	Authenticated
GET	/api/proposals/{proposal_id}/sources/versions	Authenticated
POST	/api/proposals/{proposal_id}/verify-claims	Authenticated
POST	/api/proposals/{proposal_id}/concept-alternatives	Authenticated
POST	/api/proposals/{proposal_id}/approvals	Authenticated
POST	/api/proposals/{proposal_id}/approvals/{approval_id}/decision	Authenticated
GET	/api/proposals/{proposal_id}/approvals	Authenticated
POST	/api/proposals/{proposal_id}/horizon-evaluation	Authenticated

POST	/api/proposals/{proposal_id}/evidence/verify	Authenticated
POST	/api/proposals/{proposal_id}/render	Authenticated
POST	/api/proposals/{proposal_id}/render/docx	Authenticated
GET	/api/research/skills	Authenticated
GET	/api/workflow-input-files/capabilities	Authenticated
POST	/api/workflow-input-files	Authenticated
POST	/api/workflow-input-files/extract	Authenticated
GET	/api/workflow-input-files/content	Authenticated
GET	/api/llm/models	Authenticated
GET	/api/llm/models/openrouter	Authenticated
POST	/api/llm/models/{model}/probe	Authenticated
POST	/api/pipelines/validate	Public
POST	/api/pipelines/run	Authenticated
POST	/api/pipelines/{pipeline_run_id}/advance	Authenticated
GET	/api/pipelines/mine	Authenticated
GET	/api/pipelines/mine/{pipeline_run_id}	Authenticated
POST	/api/pipelines/{pipeline_run_id}/abandon	Authenticated
GET	/api/pipelines	Public
GET	/api/pipelines/by-name/{name}	Public
POST	/api/pipelines/save	Public
GET	/api/candidates/{run_id}	Authenticated
POST	/api/candidates/{run_id}/verify-claim	Authenticated
GET	/api/runs/mine/{run_id}/chat	Authenticated
POST	/api/runs/mine/{run_id}/chat	Authenticated
POST	/api/node-types/ask	Authenticated
POST	/api/node-types/draft-prompt	Authenticated
POST	/api/node-types/draft-instructions	Authenticated
POST	/api/node-types/draft-code	Authenticated
POST	/api/workflows/generate	Authenticated

GET	/api/entity-registry/entity-types	Public
GET	/api/entity-registry	Authenticated
POST	/api/entity-registry	Authenticated
DELETE	/api/entity-registry	Authenticated
GET	/api/builder/operators	Authenticated
POST	/api/builder/output-contract	Authenticated
POST	/api/builder/schema-preview	Authenticated
POST	/api/builder/node-test	Authenticated
POST	/api/builder/simulate	Authenticated
POST	/api/builder/assist/schema	Authenticated
POST	/api/builder/assist/rules	Authenticated
GET	/api/builder/mcp/servers	Authenticated
GET	/api/builder/mcp/servers/{server_id}/tools	Authenticated
GET	/api/builder/mcp/servers/{server_id}/health	Authenticated
POST	/api/builder/mcp/test-tool	Authenticated
GET	/api/builder/email/connections	Authenticated
GET	/api/builder/email/connect/{provider}	Authenticated
GET	/api/builder/email/oauth/callback/{provider}	Public
PATCH	/api/builder/email/connections/{connection_id}	Authenticated
DELETE	/api/builder/email/connections/{connection_id}	Authenticated
GET	/api/builder/integrations/connect/{provider}	Authenticated
GET	/api/builder/integrations/oauth/callback/{provider}	Public
GET	/api/builder/integrations/connections	Authenticated
DELETE	/api/builder/integrations/connections/{connection_id}	Authenticated
GET	/api/builder/integrations/connections/{connection_id}/files	Authenticated
GET	/api/builder/integrations/connections/{connection_id}/path/{file_id}	Authenticated
GET	/api/builder/integrations/connections/{connection_id}/download/{file_id}	Authenticated
POST	/api/knowledge/collections	Authenticated
GET	/api/knowledge/collections	Authenticated

GET	/api/knowledge/collections/{collection_id}	Authenticated
POST	/api/knowledge/profiles	Authenticated
GET	/api/knowledge/profiles	Authenticated
GET	/api/knowledge/profiles/{profile_id}	Authenticated
POST	/api/knowledge/profiles/defaults	Authenticated
GET	/api/knowledge/ingestion-presets	Authenticated
GET	/api/knowledge/doc-types	Authenticated
GET	/api/knowledge/embedding-models	Authenticated
POST	/api/knowledge/collections/{collection_id}/indexes	Authenticated
GET	/api/knowledge/collections/{collection_id}/indexes	Authenticated
POST	/api/knowledge/collections/{collection_id}/indexes/{index_id}/activate	Authenticated
POST	/api/knowledge/collections/{collection_id}/ingestions	Authenticated
GET	/api/knowledge/ingestions	Authenticated
GET	/api/knowledge/ingestions/{ingestion_job_id}	Authenticated
POST	/api/knowledge/ingestions/{ingestion_job_id}/cancel	Authenticated
GET	/api/knowledge/collections/{collection_id}/documents	Authenticated
GET	/api/knowledge/documents/{document_id}	Authenticated
GET	/api/knowledge/documents/{document_id}/source-url	Authenticated
GET	/api/retrieval/presets	Authenticated
POST	/api/retrieval/search	Authenticated
POST	/api/retrieval/compare	Authenticated
GET	/api/retrieval/traces	Authenticated
GET	/api/retrieval/traces/{retrieval_request_id}	Authenticated
POST	/api/rag-agents	Authenticated
GET	/api/rag-agents	Authenticated
GET	/api/rag-agents/{rag_agent_id}	Authenticated
POST	/api/rag-agents/{rag_agent_id}/query	Authenticated

3. Endpoints by Router

audit

Method	Path	Summary
GET	/api/audit/session/{session_id}	Return the session audit.

auth

Method	Path	Summary
POST	/auth/token	Compute the login.
GET	/auth/me	Rehydrate identity from the auth cookie after a page refresh.
POST	/auth/logout	Clear the auth cookie. Must match the path the cookie was set with.

builder

Method	Path	Summary
GET	/api/builder/operators	Which operators apply to which field type, and how to render each one.
POST	/api/builder/output-contract	What each step guarantees, as typed dotted paths (§40).
POST	/api/builder/schema-preview	Compile visual schema rows and show what the model will be held to.
POST	/api/builder/node-test	Run one node against sample data (§21).
POST	/api/builder/simulate	Run a workflow in memory and return a per-step trace (§23, §24, §47).
POST	/api/builder/assist/schema	Propose a structured-output schema from a description (§37).
POST	/api/builder/assist/rules	Turn a described business rule into deterministic configuration (§36).
GET	/api/builder/mcp/servers	Configured MCP servers for the Builder's connection panel.
GET	/api/builder/mcp/servers/{server_id}/tools	Discover what a server can do (§5).
GET		

	<code>/api/builder/mcp/servers/{server_id}/health</code>	Live connection check, for the panel's Test Connection button.
POST	<code>/api/builder/mcp/test-tool</code>	Run one MCP tool with literal arguments (§21).
GET	<code>/api/builder/email/connections</code>	Configured mailboxes for the Email node's connection picker.

candidates

Method	Path	Summary
GET	<code>/api/candidates/{run_id}</code>	Every acquired evidence PDF for a run, plus discovered candidates.
POST	<code>/api/candidates/{run_id}/verify-claim</code>	Run the gpt-5.6-sol secondary check for one internal-evidence record.

cost

Method	Path	Summary
GET	<code>/api/cost/run/{run_id}</code>	Run the cost.
GET	<code>/api/cost/session/{session_id}</code>	Compute the session cost.

cost-admin

Method	Path	Summary
GET	<code>/api/cost-admin/pricing</code>	Direct/local catalog pricing (editable overrides layered on MODEL_PRICING defaults)
PUT	<code>/api/cost-admin/pricing/{model}</code>	Set the pricing override.
DELETE	<code>/api/cost-admin/pricing/{model}</code>	Clear the pricing override.
GET	<code>/api/cost-admin/infra-allocations</code>	List the infra allocations.
PUT	<code>/api/cost-admin/infra-allocations/{model}</code>	Set the infra allocation.
GET	<code>/api/cost-admin/cache-summary</code>	Compute the cache summary.
GET	<code>/api/cost-admin/budgets</code>	Return the budgets.
PUT	<code>/api/cost-admin/budgets/global</code>	Set the global budget.
PUT	<code>/api/cost-admin/budgets/session/{session_id}</code>	Set the session budget.

GET	/api/cost-admin/overview	Compute the cost overview.
-----	--------------------------	----------------------------

email-oauth

Method	Path	Summary
GET	/api/builder/email/connect/{provider}	Starts the authorization-code flow: stash a one-time state (+ PKCE
GET	/api/builder/email/oauth/callback/{provider}	The provider redirects the user's browser back here after consent.
PATCH	/api/builder/email/connections/{connection_id}	The only lever to actually let a connection send — every connection
DELETE	/api/builder/email/connections/{connection_id}	Compute the disconnect.

entity-registry

Method	Path	Summary
GET	/api/entity-registry/entity-types	List the entity types.
GET	/api/entity-registry	List the entities.
POST	/api/entity-registry	Register the entity.
DELETE	/api/entity-registry	Delete the entity.

eval

Method	Path	Summary
POST	/api/eval/score-output	Score the output.
GET	/api/eval/golden-set	List the golden set.
POST	/api/eval/run	Run the result.
GET	/api/eval/history	Compute the history.
GET	/api/eval/workflow-golden-set	List the workflow golden set.
POST	/api/eval/workflow-compare	Run the same golden set of real customer messages through the flagship

general

Method	Path	Summary
GET	/openapi.json	
GET	/docs	
GET	/docs/oauth2-redirect	
GET	/redoc	

health

Method	Path	Summary
GET	/health	Return live dependency status without failing the liveness request.
GET	/ready	Return 503 until every required runtime dependency is reachable.

inspect

Method	Path	Summary
GET	/api/inspect/chunks	List ingested chunks grouped by source document.
POST	/api/inspect/retrieve	Run a query through hybrid search + rerank and show the ranked chunks.

integration-oauth

Method	Path	Summary
GET	/api/builder/integrations/connect/{provider}	Starts the authorization-code flow: stash a one-time state (+ PKCE
GET	/api/builder/integrations/oauth/callback/{provider}	The provider redirects the user's browser back here after consent.
GET	/api/builder/integrations/connections	List the connections.
DELETE	/api/builder/integrations/connections/{connection_id}	Compute the disconnect.
GET	/api/builder/integrations/connections/{connection_id}/files	Live folder/search browsing for the node config panel's file picker
GET	/api/builder/integrations/connections/{connection_id}/path/{file_id}	Breadcrumb chain for the file browser: walk `parent_id` up from
GET	/api/builder/integrations/connections/{connection_id}/download/{file_id}	Streams one file's real bytes straight to the browser — a plain

knowledge

Method	Path	Summary
POST	/api/knowledge/collections	Create the collection.
GET	/api/knowledge/collections	List the collections.
GET	/api/knowledge/collections/{collection_id}	Return the collection.
POST	/api/knowledge/profiles	Create the profile.
GET	/api/knowledge/profiles	List the profiles.
GET	/api/knowledge/profiles/{profile_id}	Return the profile.
POST	/api/knowledge/profiles/defaults	Create the default profiles.
GET	/api/knowledge/ingestion-presets	Compute the ingestion presets.
GET	/api/knowledge/doc-types	Document types a Collection may declare.
GET	/api/knowledge/embedding-models	Embedding models selectable when building an Index.
POST	/api/knowledge/collections/{collection_id}/indexes	Create the index.
GET	/api/knowledge/collections/{collection_id}/indexes	List the indexes.
POST	/api/knowledge/collections/{collection_id}/indexes/{index_id}/activate	Compute the activate index.
POST	/api/knowledge/collections/{collection_id}/ingestions	Start the ingestion.
GET	/api/knowledge/ingestions	List the ingestions.
GET	/api/knowledge/ingestions/{ingestion_job_id}	Return the ingestion.
POST	/api/knowledge/ingestions/{ingestion_job_id}/cancel	Cancel the ingestion.
GET	/api/knowledge/collections/{collection_id}/documents	List the documents.
GET	/api/knowledge/documents/{document_id}	Return the document.
GET	/api/knowledge/documents/{document_id}/source-url	Compute the document source url.

llm

Method	Path	Summary
GET	/api/llm/models	Return public capability metadata without URLs or credentials.
GET		

	<code>/api/llm/models/openrouter</code>	Live OpenRouter model catalog (via OpenRouter's own `GET /v1/models`), cached with a
POST	<code>/api/llm/models/{model}/probe</code>	Probe an enabled local endpoint; never return its private address.

node-types-chat

Method	Path	Summary
POST	<code>/api/node-types/ask</code>	Compute the ask about node types.
POST	<code>/api/node-types/draft-prompt</code>	Draft the prompt.
POST	<code>/api/node-types/draft-instructions</code>	Draft the instructions.
POST	<code>/api/node-types/draft-code</code>	Draft the code.

pipelines

Method	Path	Summary
POST	<code>/api/pipelines/validate</code>	Validate a pipeline without running a stage or spending tokens.
POST	<code>/api/pipelines/run</code>	Run the result.
POST	<code>/api/pipelines/{pipeline_run_id}/advance</code>	Compute the advance.
GET	<code>/api/pipelines/mine</code>	Compute the my pipeline runs.
GET	<code>/api/pipelines/mine/{pipeline_run_id}</code>	Compute the my pipeline run detail.
POST	<code>/api/pipelines/{pipeline_run_id}/abandon</code>	Manually move a stuck pipeline out of running/gated so any run that is
GET	<code>/api/pipelines</code>	Library view: saved pipeline files on disk, mirroring GET / workflows.
GET	<code>/api/pipelines/by-name/{name}</code>	Return the pipeline.
POST	<code>/api/pipelines/save</code>	Save the pipeline.

proposals

Method	Path	Summary
POST	<code>/api/proposals/coverage</code>	Compute the coverage.
GET	<code>/api/proposals/runs/{run_id}/review</code>	Compute the review run.

POST	/api/proposals/{proposal_id}/sources/{source_id}/versions	Register the source version.
GET	/api/proposals/{proposal_id}/sources/versions	List the source versions.
POST	/api/proposals/{proposal_id}/verify-claims	Verify the claims.
POST	/api/proposals/{proposal_id}/concept-alternatives	Compute the concept alternatives.
POST	/api/proposals/{proposal_id}/approvals	Compute the request approval.
POST	/api/proposals/{proposal_id}/approvals/{approval_id}/decision	Compute the decide approval.
GET	/api/proposals/{proposal_id}/approvals	List the approvals.
POST	/api/proposals/{proposal_id}/horizon-evaluation	Compute the horizon evaluation.
POST	/api/proposals/{proposal_id}/evidence/verify	Verify already-fetched full text and return a citable evidence package.
POST	/api/proposals/{proposal_id}/render	Render a proposal and persist both sanitised HTML and final PDF.
POST	/api/proposals/{proposal_id}/render/docx	Render a proposal as editable DOCX and persist its sanitised source.

rag-agents

Method	Path	Summary
POST	/api/rag-agents	Create the agent.
GET	/api/rag-agents	List the agents.
GET	/api/rag-agents/{rag_agent_id}	Return the agent.
POST	/api/rag-agents/{rag_agent_id}/query	Query the agent.

research

Method	Path	Summary
GET	/api/research/skills	List the scientific skills.

retrieval

Method	Path	Summary
--------	------	---------

GET	/api/retrieval/presets	Return editable starting configurations; saving creates a profile.
POST	/api/retrieval/search	Search the result.
POST	/api/retrieval/compare	Compare the result.
GET	/api/retrieval/traces	List the traces.
GET	/api/retrieval/traces/{retrieval_request_id}	Return the trace.

run-chat

Method	Path	Summary
GET	/api/runs/mine/{run_id}/chat	Return the run chat.
POST	/api/runs/mine/{run_id}/chat	Compute the ask about run.

runs

Method	Path	Summary
GET	/api/runs/mine	Compute the my runs.
GET	/api/runs/mine/{run_id}	Compute the my run detail.
GET	/api/runs/mine/{run_id}/pending-gate	The human-review gate a paused run is currently waiting on, if any.
GET	/api/runs/mine/{run_id}/business-projection	Business View's data source — this run reshaped into business language.
POST	/api/runs/mine/{run_id}/business-narration	Rephrase this work item's already-decided status in business language.
GET	/api/runs/mine/{run_id}/business-explanation	"Why?" — the facts and rules behind the handling decision (§20, §48).
GET	/api/runs/mine/{run_id}/business-technical/{activity_id}	The technical layer behind one business activity (§5, §47).
POST	/api/runs/mine/{run_id}/business-action	Perform one typed Business View action (§53, §54).
POST	/api/runs/mine/{run_id}/fact-correction	Overwrite one extracted fact on this run and mark what it fed as stale.
POST	/api/runs/mine/{run_id}/assign	Record who a work item is assigned to — a plain annotation on the
POST	/api/runs/mine/{source_run_id}/retry	Create a new attempt that reuses every completed node checkpoint.

POST	/api/runs/mine/{run_id}/pause	Ask a running workflow to pause at its next node boundary.
POST	/api/runs/mine/{run_id}/resume	Resume a run paused by the run-history "pause" action.
POST	/api/runs/mine/{source_run_id}/restart	Create a brand-new run of the same workflow and original inputs.
DELETE	/api/runs/mine/{run_id}	Delete the run endpoint.

workflow-generation

Method	Path	Summary
POST	/api/workflows/generate	Generate the workflow endpoint.

workflow-input-files

Method	Path	Summary
GET	/api/workflow-input-files/capabilities	Return the authoritative UI picker limits and accepted extensions.
POST	/api/workflow-input-files	Store files and return stable references suitable for workflow state.
POST	/api/workflow-input-files/extract	Convert one uploaded document into plain text for the HITL editor.
GET	/api/workflow-input-files/content	Download one uploaded input after enforcing the authenticated scope.

workflows

Method	Path	Summary
GET	/api/	List the workflows.
GET	/api/node-types	The Workflow Builder UI calls this to populate the palette and forms.
GET	/api/node-types/{node_type}/models	Returns the default allowed model list for a node type.
POST	/api/workflows/validate	Validate a workflow without running a node or consuming LLM tokens.
POST	/api/workflows/autofix	Best-effort repair of a workflow's preflight errors: deterministic
GET	/api/workflows/preflight-stats	Platform-wide preflight reliability rollup across every / validate,

POST	/api/workflows/run	Run the result.
POST	/api/workflows/{run_id}/resume	Resume doesn't need services for execution — the cached compiled graph in
POST	/api/workflows/subprocess-callback/{token}	Deliver a Subprocess child's terminal result to its waiting parent.
GET	/api/workflows	Library view in the UI calls this to render the workflow collection.
GET	/api/workflows/by-name/{name}	Builder calls this to load an existing workflow for editing.
GET	/api/workflows/{name}/detail	Workflow Library details panel calls this to refresh `library` and
GET	/api/workflows/{name}/stats	Library "Runs and performance" tab. Session-scoped like Run History
POST	/api/workflows/save	Builder calls this on Save. Validates the YAML parses to a WorkflowSpec
DELETE	/api/workflows/{name}	Permanently removes a workflow's YAML together with its autosave
PUT	/api/workflows/{name}/draft	Autosave a recoverable draft. Never compiled/preflighted — a draft may
GET	/api/workflows/{name}/draft	Builder calls this on load to offer 'Resume draft' for a newer autosave.
DELETE	/api/workflows/{name}/draft	Delete the workflow draft.
GET	/api/workflows/{name}/versions	List the workflow versions.
GET	/api/workflows/{name}/versions/{version_id}	Return the workflow version.
POST	/api/workflows/{name}/versions/{version_id}/restore	Restoring an old version is Save-equivalent: it must pass the same
GET	/api/runs/{run_id}/events	Authenticated Server-Sent Events stream for one workflow run.
GET	/api/files	Stream a file from object storage by key (used by the Output Viewer).