

## Library Indian Institute of Science Education and Research Mohali



## DSpace@IISERMohali (/jspui/)

- / Publications of IISER Mohali (/jspui/handle/123456789/4)
- / Research Articles (/jspui/handle/123456789/9)

Please use this identifier to cite or link to this item: http://hdl.handle.net/123456789/2090

Title: Precision and correctness in the evaluation of electrocatalytic water splitting: revisiting activity

parameters with a critical assessment

Authors: Karthik, P.E. (/jspui/browse?type=author&value=Karthik%2C+P.E.)

Keywords: Electrocatalytic

Water splitting

Oxygen evolution reaction (OER)

Electrochemically active surface area (ECSA)

Issue Date: 2018

Publisher: Royal Society of Chemistry

Citation: Energy and Environmental Science, 11(4), pp. 744-771

Abstract:

The number of research reports published in recent years on electrochemical water splitting for hydrogen generation is higher than for many other fields of energy research. In fact, electrochemical water splitting, which is conventionally known as water electrolysis, has the potential to meet primary energy requirements in the near future when coal and hydrocarbons are completely consumed. Due to the sudden and exponentially increasing attention on this field, many researchers across the world, including our group, have been exerting immense efforts to improve the electrocatalytic properties of the materials that catalyze the oxygen evolution reaction (OER) at the anode and the hydrogen evolution reaction (HER) at the cathode, aided by the recent revolutionary discovery of nanomaterials. However, the pressure on the researchers to publish their findings rapidly has caused them to make many unnoticed and unintentional errors, which is mainly due to lack of clear insight on the activity parameters. In this perspective, we have discussed the use and validity of ten important parameters, namely overpotential at a defined current density, iR-corrected overpotential at a defined current density, Tafel slope, exchange current density (j0), mass activity, specific activity, faradaic efficiency (FE), turnover frequency (TOF), electrochemically active surface area (ECSA) and measurement of double layer capacitance (CdI) for different electrocatalytic materials that are frequently employed in both OER and HER. Experimental results have also been provided in support of our discussions wherever required. Using our critical assessments of the activity parameters of water splitting electrocatalysis, researchers can ensure precision and correctness when presenting their data regarding the activity of an electrocatalyst.

Description: Only IISERM authors are available in the record.

URI: https://pubs.rsc.org/en/content/articlelanding/2018/ee/c7ee03457a#!divAbstract

(https://pubs.rsc.org/en/content/articlelanding/2018/ee/c7ee03457a#!divAbstract) http://hdl.handle.net/123456789/2090 (http://hdl.handle.net/123456789/2090)

Appears in Res

Research Articles (/jspui/handle/123456789/9)

Files in This Item

File Description Size Format

Need to add pdf.odt (/jspui/bitstream/123456789/2090/1/Need%20to%20add%20pdf.odt)

8.63 OpenDocument kB Text

View/Open (/jspui/bitstream/12345

Show full item record (/jspui/handle/123456789/2090?mode=full)

**. I** (/jspui/handle/123456789/2090/statistics)

Items in DSpace are protected by copyright, with all rights reserved, unless otherwise indicated.