



Library Indian Institute of Science Education and Research Mohali



DSpace@IISERMohali / Thesis & Dissertation / Master of Science / MS-17

Please use this identifier to cite or link to this item: http://hdl.handle.net/123456789/4252

Title: A Proposed rat-race coupler design with a ferromagnetic core

Authors: Shinde, Adesh Navanath

Keywords: Proposed

coupler design ferromagnetic core

Issue Apr-2022

Date:

Publisher: IISER Mohali

Abstract:

Microwave couplers are the most often used passive devices in microwave circuitry. The primary function is to divide (or combine) a radio frequency signal into (from) two distinct signals by a phase difference and specific ratio. A decrease in the size of a dis- tributed coupler would prove helpful with the demand for smaller electronic devices. A Rat-Race Coupler is a microwave coupler made from microstrips shaped like a ring/circle. In the case of a conventional four-port Rat-race coupler, each port is positioned one-quarter wavelength (λ) apart around the top half of the ring. The bottom half of the ring measures three-quarter wavelengths (λ). It has three branches that are 90 \circ phase-shifted from each other and one branch that provides a 270 \circ phase shift. The central idea of this work is concerned with effects after the addition of a ferro- magnetic material core inside the ring of Rat-race Coupler. After adding the ferromagnetic core, we see some phase shifting and non-reciprocal circuit effects. We propose two types of Rat-race couplers design in this work; the conventional one and also the reduced electri- cal length Rat-race coupler.

URI: http://hdl.handle.net/123456789/4252

Appears in Collections:

MS-17

Files in This Item:

File	Description	Size	Format	
Yet to obtain consent.pdf		144.56 kB	Adobe PDF	View/Open

Show full item record



Items in DSpace are protected by copyright, with all rights reserved, unless otherwise indicated.



Customized & Implemented by - Jivesna Tech