



## Library Indian Institute of Science Education and Research Mohali



**DSpace@IISERMohali (/jspui/)**  
**/ Thesis & Dissertation (/jspui/handle/123456789/1)**  
**/ Doctor of Philosophy (PhD) (/jspui/handle/123456789/268)**  
**/ PhD-2012 (/jspui/handle/123456789/955)**

Please use this identifier to cite or link to this item: <http://hdl.handle.net/123456789/1207>

---

Title: Activation of a ubiquitin fold containing pre-mRNA splicing regulator Sde2 by deubiquitinating enzymes Ubp5 and Ubp15 in *Schizosaccharomyces pombe*

---

Authors: Pandit, Prashant Arun (/jspui/browse?type=author&value=Pandit%2C+Prashant+Arun)

---

Keywords: Biology  
RNA Splicing  
Ubiquitin system  
Western blot (WB) assay  
DNA isolation

---

Issue 1-Oct-2019  
Date:

---

Publisher: IISERM

---

**Abstract:** The genetic information in eukaryotes flows into protein-coding messenger RNAs through transcription and pre-mRNA splicing. A multi-megadalton protein complex, spliceosome, removes non-coding introns and joins exons to generate translatable mRNAs. It is made of five small nuclear ribonucleoproteins (snRNPs) and more than 200 proteins. In addition, many protein/RNA interactions and post-translational modifications play key roles in regulating the machinery. Ubiquitin and ubiquitin-like proteins (UBLs) are post-translational modifiers functioning in protein degradation, cell cycle, transcription, immune defence, as well as in splicing regulation. Ubiquitin or UBLs share a  $\beta$ - grasp fold and are synthesized as precursor molecules which get processed and activated by deubiquitinating enzymes (DUBs) or UBL-specific proteases respectively. These enzymes are highly substrate specific and are essential for ubiquitin and UBL associated pathways. In my thesis work, we report the mechanism of activation of a novel ubiquitin-like protein Sde2 by deubiquitinating enzymes (DUB) Ubp5 and Ubp15. Sde2 is an intron-specific pre-mRNA splicing factor required for splicing of selective pre-mRNAs in *Schizosaccharomyces pombe*. The structure of Sde2 has an N-terminal ubiquitin-like fold (Sde2-UBL) followed by a conserved GG~KGG motif and a C-terminal helical domain (Sde2-C). The precursor gets processed at the GG~K site by Ubp5 and Ubp15. Processing of Sde2 precursor is required for its association with the spliceosome; thereby, processing defective mutants of Sde2 show  $\Delta$ sde2-like splicing defects. The Sde2-UBL is essential for generating the functional Sde2-C with a lysine at its N-terminus. Chromosomal mutations of this lysine resulted in reduced recruitment of another splicing factor Cay1 in the spliceosome and also showed splicing defects. Strikingly, *S. pombe* Ubp5 and Ubp15 cleave both Sde2-UBL and ubiquitin which are less than 20% identical to each other. However, a homolog of these DUBs in humans, USP7, processes ubiquitin but not Sde2. By swapping the domains of USP7 with Ubp15, we have narrowed down a region in Ubp15 that is responsible for its dual specificity towards Sde2-UBL and ubiquitin. Thus, we have demonstrated that two DUB paralogs activate distinct UBLs with roles in diverse processes related to the ubiquitin system and pre-mRNA splicing. Finally, I will also discuss how these two processes might be connected in the biological system.


**URI:** IISERM (IISERM)  
<http://hdl.handle.net/123456789/1207> (<http://hdl.handle.net/123456789/1207>)

**Appears in** PhD-2012 (</jspui/handle/123456789/955>)  
**Collections:**

Files in This Item:

File	Description	Size	Format	
PH12112.pdf ( <a href="/jspui/bitstream/123456789/1207/3/PH12112.pdf">/jspui/bitstream/123456789/1207/3/PH12112.pdf</a> )		8.24 MB	Adobe PDF	<a href="/jspui/bitstream/123456789/1207/3/">View/Open</a> ( <a href="/jspui/bitstream/123456789/1207/3/">/jspui/bitstream/123456789/1207/3/</a> )

[Show full item record \(/jspui/handle/123456789/1207?mode=full\)](/jspui/handle/123456789/1207?mode=full)

 </jspui/handle/123456789/1207/statistics>

Items in DSpace are protected by copyright, with all rights reserved, unless otherwise indicated.

Admin Tools

[Edit...](#)

[Export Item](#)

[Export \(migrate\) Item](#)

[Export metadata](#)

