



# Library Indian Institute of Science Education and Research Mohali



DSpace@IISERMohali / Thesis & Dissertation / Doctor of Philosophy (PhD) / PhD-2016

Please use this identifier to cite or link to this item: <http://hdl.handle.net/123456789/4151>

Title:	Investigation of nano-carbon/ non-carbon material interfaces for electronics and renewable energy conversion applications
Authors:	<a href="#">Riyajuddin, SK</a>
Keywords:	interfaces energy
Issue Date:	Sep-2021
Publisher:	IISER Mohali
Abstract:	Interface investigation of nano-carbon/non-carbon material is an interesting topic of research. Depending of the different interface properties leads to the different application. Here in this work, we have studied different interface of carbonaceous material (Graphene, CNT, NGQD) along with non-carbon material which could have potential application in the field of electronics and renewable energy conversion. The seamless interface between graphene-CNTs create a low resistive path via forming C-C covalent bonds which leads to higher field emission properties in terms of high current density (236 mA/cm <sup>2</sup> ) and field enhancement factor ( $\beta \sim 41315$ ) which is tailored by $\sim 4$ -fold as compared to bare CNT mat. Using the concept of seamless carbonaceous matrix for the facile root of electronic transition, further $\pi\pi$ - $\pi\pi$ stacking concept has been adopted for graphene-g-C <sub>3</sub> N <sub>4</sub> matrix which intern provide to developed highly liner piezoresistive strain sensor with a small gauge factor (1.89). Alternatively, similar interface via $\pi\pi$ - $\pi\pi$ co-ordination between carbon and metal phosphide interface i.e., 3D graphene with Cu <sub>3</sub> P-g-C <sub>3</sub> N <sub>4</sub> makes the suitable electrocatalyst for overall water splitting with the cell voltage of 1.54 V to achieve a current density of 10 mA/cm <sup>2</sup> can emerge a new domain for renewable energy management. In addition, $\pi\pi$ - $\pi\pi$ interaction between carbonaceous material along with Si and non-transition metal phosphide/oxide can potentially developed a new platform to designing novel PEC technology. The pours seamless graphene-CNTs matrix along with d-d coupled mixed transition bimetal metal phosphide/non-transition metal phosphide proved to be a suitable matrix for developing alternative PEC technology.
URI:	<a href="http://hdl.handle.net/123456789/4151">http://hdl.handle.net/123456789/4151</a>
Appears in Collections:	<a href="#">PhD-2016</a>

## Files in This Item:

File	Description	Size	Format	
<a href="#">It is under embargo period.pdf</a>		139.68 kB	Adobe PDF	<a href="#">View/Open</a>

Show full item record



Items in DSpace are protected by copyright, with all rights reserved, unless otherwise indicated.

## Admin Tools

Edit...

Export Item

Export (migrate) Item

Export metadata