



# Library Indian Institute of Science Education and Research Mohali



**DSpace@IISERMohali (/jspui/)**  
**/ Publications of IISER Mohali (/jspui/handle/123456789/4)**  
**/ Research Articles (/jspui/handle/123456789/9)**

Please use this identifier to cite or link to this item: <http://hdl.handle.net/123456789/2164>

Title:	A high-performance rotating graphite fiber brush air-cathode for microbial fuel cells
Authors:	Patil, Sunil A. (/jspui/browse?type=author&value=Patil%2C+Sunil+A.)
Keywords:	Bioenergy Microbial fuel cell Rotating air-cathode Co-doped carbon Oxygen reduction reaction Power output
Issue Date:	2018
Publisher:	Elsevier B.V.
Citation:	Applied Energy, 211, pp. 1089-1094
Abstract:	<p>Microbial fuel cells (MFC) represent an emerging technology to harvest electric energy from waste streams like wastewaters. To further increase MFC performance, the individual fuel cell processes, such as the cathodic oxygen reduction (ORR) need to be further improved. The commonly used, two-dimensional air-cathodes usually show limited performance due to a low three-phase ORR interface and a low oxygen mass transfer rate. To address these issues, a binder-free rotating three-dimensional air-cathode that provides a larger three-phase ORR interface and an enhanced oxygen mass transfer rate is reported in this paper. The cathode is prepared by coating a self-supporting N and P co-doped carbon ORR catalyst layer onto a graphite fiber brush current collector (GB/NPC). No binder and diffusion layer are used to avoid the limitations associated with these components. The electrochemical tests demonstrate enhanced ORR electrocatalysis under rotation conditions. In MFCs, a high performance was achieved by operating the GB/NPC air-cathode at a slow rotation speed. For example, at 20 rpm, it delivered three times higher cathodic current (<math>1.02 \pm 0.05 \text{ mA cm}^{-2}</math>) and two times higher power output (<math>879 \pm 16 \text{ mW m}^{-2}</math>, normalized to the projected surface area of air-cathode) than its counterpart non-rotating, static air-cathode (<math>0.35 \pm 0.03 \text{ mA cm}^{-2}</math> and <math>486 \pm 11 \text{ mW m}^{-2}</math>, respectively). The rotating conditions increased the availability of catalytic sites for the ORR, and improved oxygen diffusion and <math>\text{OH}^-</math> transport at or within the air-cathode. This study thus presents a promising approach for enhancing the performance of air-cathodes, which is often the major performance-limiting component of the MFCs.</p>
Description:	Only IISERM authors are available in the record.
URI:	<a href="https://www.sciencedirect.com/science/article/abs/pii/S0306261917317269#!">https://www.sciencedirect.com/science/article/abs/pii/S0306261917317269#!</a> ( <a href="https://www.sciencedirect.com/science/article/abs/pii/S0306261917317269#!">https://www.sciencedirect.com/science/article/abs/pii/S0306261917317269#!</a> ) <a href="http://hdl.handle.net/123456789/2164">http://hdl.handle.net/123456789/2164</a> ( <a href="http://hdl.handle.net/123456789/2164">http://hdl.handle.net/123456789/2164</a> )
Appears in Collections:	Research Articles (/jspui/handle/123456789/9)

Files in This Item:


File	Description	Size	Format
------	-------------	------	--------

Need to add pdf.odt  
(/jspui/bitstream/123456789/2164/1/Need%20to%20add%20pdf.odt)

8.63    OpenDocument  
kB       Text

[View/Open \(/jspui/bitstream/123456789/2164/1/Need%20to%20add%20pdf.odt\)](#)

[Show full item record \(/jspui/handle/123456789/2164?mode=full\)](#)

 [\(/jspui/handle/123456789/2164/statistics\)](#)

Items in DSpace are protected by copyright, with all rights reserved, unless otherwise indicated.