



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

Experiment No. 8
Implement Restoring algorithm using c-programming
Name: Ayush Gupta
Roll Number: 14
Date of Performance:
Date of Submission:

**Aim:** To implement Restoring division algorithm using c-programming.

**Objective -**

- To understand the working of Restoring division algorithm.
- To understand how to implement Restoring division algorithm using c-programming.

**Theory:**





# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

```
int left(int [], int []);
```

```
int add(int [], int []);
```

```
int main()
```

```
{
```

```
    int a, b, m[4]={0,0,0,0}, q[4]={0,0,0,0}, acc[4]={0,0,0,0}, m2[4], i, n=4;
```

```
    printf("Enter the Dividend: ");
```

```
    scanf("%d", &a);
```

```
    printf("Enter the Divisor: ");
```

```
    scanf("%d", &b);
```

```
    dec_bin(a, q);
```

```
    dec_bin(b, m);
```

```
    twos(m, m2);
```

```
    printf("\nA\tQ\tComments\n");
```

```
    for(i=3; i>=0; i--)
```

```
    {
```

```
        printf("%d", acc[i]);
```

```
    }
```

```
    printf("\t");
```

```
    for(i=3; i>=0; i--)
```

```
    {
```

```
        printf("%d", q[i]);
```

```
    }
```

```
    printf("\tStart\n");
```

```
    while(n>0)
```

```
    {
```

```
        left(acc, q);
```

```
        for(i=3; i>=0; i--)
```

```
        {
```

```
            printf("%d", acc[i]);
```

```
        }
```

```
        printf("\t");
```

```
        for(i=3; i>=1; i--)
```

```
        {
```

```
            printf("%d", q[i]);
```

```
        }
```

```
        printf("\tLeft Shift A,Q\n");
```

```
        add(acc, m2);
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

```
for(i=3; i>=0; i--)
{
    printf("%d", acc[i]);
}
printf("\t");
for(i=3; i>=1; i--)
{
    printf("%d", q[i]);
}
printf(" \tA=A-M\n");
if(acc[3]==0)
{
    q[0]=1;
    for(i=3; i>=0; i--)
    {
        printf("%d", acc[i]);
    }
    printf("\t");
    for(i=3; i>=0; i--)
    {
        printf("%d", q[i]);
    }
    printf("\tQo=1\n");
}
else
{
    q[0]=0;
    add(acc, m);
    for(i=3; i>=0; i--)
    {
        printf("%d", acc[i]);
    }
    printf("\t");
    for(i=3; i>=0; i--)
    {
        printf("%d", q[i]);
    }
    printf("\tQo=0; A=A+M\n");
}
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

```
}  
n--;  
}  
printf("\nQuotient = ");  
for(i=3; i>=0; i--)  
{  
    printf("%d", q[i]);  
}  
printf("\tRemainder = ");  
for(i=3; i>=0; i--)  
{  
    printf("%d", acc[i]);  
}  
printf("\n");  
return 0;  
}
```

```
int dec_bin(int d, int m[])  
{  
    int b=0, i=0;  
    for(i=0; i<4; i++)  
    {  
        m[i]=d%2;  
        d=d/2;  
    }  
    return 0;  
}
```

```
int twos(int m[], int m2[])  
{  
    int i, m1[4];  
    for(i=0; i<4; i++)  
    {  
        if(m[i]==0)  
        {  
            m1[i]=1;  
        }  
        else
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

```
{
    m1[i]=0;
}
}
for(i=0; i<4; i++)
{
    m2[i]=m1[i];
}
if(m2[0]==0)
{
    m2[0]=1;
}
else
{
    m2[0]=0;
    if(m2[1]==0)
    {
        m2[1]=1;
    }
    else
    {
        m2[1]=0;
        if(m2[2]==0)
        {
            m2[2]=1;
        }
        else
        {
            m2[2]=0;
            if(m2[3]==0)
            {
                m2[3]=1;
            }
            else
            {
                m2[3]=0;
            }
        }
    }
}
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

```
    }  
}  
return 0;  
}
```

```
int left(int acc[], int q[])  
{  
    int i;  
    for(i=3; i>0; i--)  
    {  
        acc[i]=acc[i-1];  
    }  
    acc[0]=q[3];  
    for(i=3; i>0; i--)  
    {  
        q[i]=q[i-1];  
    }  
}
```

```
int add(int acc[], int m[])  
{  
    int i, carry=0;  
    for(i=0; i<4; i++)  
    {  
        if(acc[i]+m[i]+carry==0)  
        {  
            acc[i]=0;  
            carry=0;  
        }  
        else if(acc[i]+m[i]+carry==1)  
        {  
            acc[i]=1;  
            carry=0;  
        }  
        else if(acc[i]+m[i]+carry==2)  
        {  
            acc[i]=0;  
            carry=1;  
        }  
    }  
}
```



# Vidyavardhini's College of Engineering and Technology

## Department of Artificial Intelligence & Data Science

```
}  
else if(acc[i]+m[i]+carry==3)  
{  
    acc[i]=1;  
    carry=1;  
}  
}  
return 0;  
}
```

### Output -

Enter the Dividend: 12

Enter the Divisor: 2

A	Q	Comments
0000	1100	Start
0001	100_	Left Shift A,Q
1111	100_	A=A-M
0001	1000	Q <sub>0</sub> =0; A=A+M
0011	000_	Left Shift A,Q
0001	000_	A=A-M
0001	0001	Q <sub>0</sub> =1
0010	001_	Left Shift A,Q
0000	001_	A=A-M
0000	0011	Q <sub>0</sub> =1
0000	011_	Left Shift A,Q
1110	011_	A=A-M
0000	0110	Q <sub>0</sub> =0; A=A+M

Quotient = 0110      Remainder = 0000

### Conclusion -

This experiment concerning the Restoring Division Algorithm has furnished an in-depth grasp of this essential approach to binary division. The algorithm's meticulous, sequential restoration process facilitates precise quotient computation, endowing it with substantial





# **Vidyavardhini's College of Engineering and Technology**

## **Department of Artificial Intelligence & Data Science**

utility in the realm of computer arithmetic. This experiment has not only underscored the significance of comprehending and putting into practice division algorithms but has also exemplified its pragmatic utilization across a spectrum of computer systems and data processing assignments.