

Experiment No. 3

Aim: Construct a responsive website using Bootstrap.

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <title>Responsive Website with Bootstrap</title>

  <!-- Bootstrap CSS CDN -->

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/bootstrap.min.css" rel="stylesheet"
  integrity="sha384-EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC"
  crossorigin="anonymous">

</head>

<body>

  <!-- Navigation Bar -->

  <nav class="navbar navbar-expand-lg navbar-dark bg-dark">

    <div class="container">

      <a class="navbar-brand" href="#">My Website</a>

      <button class="navbar-toggler" type="button" data-bs-toggle="collapse" data-bs-
      target="#navbarNav" aria-controls="navbarNav" aria-expanded="false" aria-label="Toggle navigation">

        <span class="navbar-toggler-icon"></span>

      </button>

      <div class="collapse navbar-collapse" id="navbarNav">

        <ul class="navbar-nav ms-auto">

          <li class="nav-item">

            <a class="nav-link active" href="#">Home</a>

          </li>

        </ul>

      </div>

    </div>

  </nav>


```

```
<li class="nav-item">
```

```
  <a class="nav-link" href="#">About</a>
```

```
</li>
```

```
<li class="nav-item">
```

```
  <a class="nav-link" href="#">Services</a>
```

```
</li>
```

```
<li class="nav-item">
```

```
  <a class="nav-link" href="#">Contact</a>
```

```
</li>
```

```
</ul>
```

```
</div>
```

```
</div>
```

```
</nav>
```

```
<!-- Hero Section -->
```

```
<section class="bg-light text-dark text-center p-5">
```

```
  <div class="container">
```

```
    <h1>Welcome to Our Responsive Website</h1>
```

```
    <p class="lead">This website is built using Bootstrap 5 and adapts to any screen size.</p>
```

```
    <a href="#" class="btn btn-primary">Get Started</a>
```

```
  </div>
```

```
</section>
```

```
<!-- Responsive Grid with Cards -->
```

```
<section class="py-5">
```

```
  <div class="container">
```

```
    <div class="row">
```

```
      <!-- Card 1 -->
```

```
<div class="col-md-4">
```

```
  <div class="card mb-4">
```

```
    
```

```
    <div class="card-body">
```

```
      <h5 class="card-title">Card Title 1</h5>
```

```
      <p class="card-text">This is a brief description of the content inside the card. It can be  
extended to multiple lines.</p>
```

```
      <a href="#" class="btn btn-primary">Learn More</a>
```

```
    </div>
```

```
  </div>
```

```
</div>
```

```
<!-- Card 2 -->
```

```
<div class="col-md-4">
```

```
  <div class="card mb-4">
```

```
    
```

```
    <div class="card-body">
```

```
      <h5 class="card-title">Card Title 2</h5>
```

```
      <p class="card-text">This is another brief description with more content inside the card.</p>
```

```
      <a href="#" class="btn btn-primary">Learn More</a>
```

```
    </div>
```

```
  </div>
```

```
</div>
```

```
<!-- Card 3 -->
```

```
<div class="col-md-4">
```

```
  <div class="card mb-4">
```

```
    
```

```
    <div class="card-body">
```

<h5 class="card-title">Card Title 3</h5>

<p class="card-text">This card contains more content and links to additional resources.</p>

Learn More

</div>

</div>

</div>

</div>

</div>

</section>

<!-- Footer -->

<footer class="bg-dark text-light text-center py-3">

<div class="container">

<p>© 2024 My Website | All Rights Reserved</p>

</div>

</footer>

<!-- Bootstrap JS CDN (with Popper) -->

<script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js" integrity="sha384-FgpCn4Bz4YJQd4V8xNcQ1jjj4Z1pJTAW4DlzJ7/cn9hfoHeZw5ZxkPpRXxMXQbZS" crossorigin="anonymous"></script>

</body>

</html>