COMPUTER NETWORKG

EXPERIMENT 8

Name: Ayush Jain SAP ID: 60004200132

Batch: B2

Computer Engineering

Aim: Implement and understand TCP-UDP scenario in NS2.

Theory:

A "UDP" agent that is attached to n0 is connected to a "null" agent attached to n3. A "null" agent frees the packets received. An "FTP" and a "CBR" traffic generator are respectively attached to "TCP" and "UDP" agents, and the "CBR" is configured to generate 1 Kbytes packets at the rate of 100 packets per second.

The default TCP packet size in ns-2 is 1000 bytes, so the bottleneck bandwidth is nominally 100 packets/sec or 0.1 packets/ms. The bandwidth \times RTT_{noLoad} product is 0.1 packets/ms \times 120 ms = 12 packets.

Code:

```
#Create a simulator object set ns [new Simulator]
#Define different colors for data flows (for NAM)
$ns color 1 Blue
$ns color 2 Red

#Open the NAM trace file
set nf [open out.nam w]
$ns namtrace-all $nf

#Define a 'finish' procedure
proc finish {} { global ns nf
$ns flush-trace #Close
the NAM trace file close
$nf
#Execute NAM on the trace file
exec nam out.nam &
exit 0
}
```

#Create four nodes set n0 [\$ns node] set n1 [\$ns node] set n2 [\$ns node] set n3 [\$ns node]

#Create links between the nodes \$ns duplex-link \$n0 \$n2 2Mb 10ms DropTail \$ns duplex-link \$n1 \$n2 2Mb 10ms DropTail \$ns duplex-link \$n2 \$n3 1.7Mb 20ms DropTail

#Set Queue Size of link (n2-n3) to 10 \$ns queue-limit \$n2 \$n3 10

#Give node position (for NAM) \$ns duplex-link-op \$n0 \$n2 orient right-down \$ns duplex-link-op \$n1 \$n2 orient right-up \$ns duplex-link-op \$n2 \$n3 orient right

#Monitor the queue for link (n2-n3). (for NAM) \$ns duplex-link-op \$n2 \$n3 queuePos 0.5

#Setup a TCP connection set tcp [new Agent/TCP] \$tcp set class_ 2 \$ns attachagent \$n0 \$tcp set sink [new Agent/TCPSink] \$ns attach-agent \$n3 \$sink \$ns connect \$tcp \$sink \$tcp set fid_ 1

#Setup a FTP over TCP connection set ftp [new Application/FTP] \$ftp attach-agent \$tcp \$ftp set type_ FTP

#Setup a UDP connection set udp [new Agent/UDP] \$ns attach-agent \$n1 \$udp set null [new Agent/Null] \$ns attach-agent \$n3 \$null \$ns connect \$udp \$null \$udp set fid_ 2

#Setup a CBR over UDP connection set cbr [new Application/Traffic/CBR] \$cbr attach-agent \$udp \$cbr set type_ CBR \$cbr set packet_size_ 1000 \$cbr set rate_1mb \$cbr set random_false

#Schedule events for the CBR and FTP agents

\$ns at 0.1 "\$cbr start"

\$ns at 1.0 "\$ftp start"

\$ns at 4.0 "\$ftp stop"

\$ns at 4.5 "\$cbr stop"

#Detach tcp and sink agents (not really necessary)

\$ns at 4.5 "\$ns detach-agent \$n0 \$tcp; \$ns detach-agent \$n3 \$sink"

#Call the finish procedure after 5 seconds of simulation time \$ns at 5.0 "finish"

#Print CBR packet size and interval puts "CBR
packet size = [\$cbr set packet_size_]" puts "CBR
interval = [\$cbr set interval_]"

#Run the simulation \$ns run

Output:

