

# Uptime Monitoring Platform

## PostgreSQL Database Schema (DDL)

Generated: 2026-06-16

Source: live database 'uptime\_db' @ localhost:55432

Engine: PostgreSQL 16.6 (dumped via pg\_dump)

Migration revision: 004 (latest)

Contents: 14 application tables + alembic\_version

15 primary keys | 16 foreign keys | 15 indexes | 14 sequences

## schema.sql - Complete DDL

```
-- =====
-- Uptime Monitoring Platform ? PostgreSQL Schema (DDL)
-- Generated from the LIVE database via pg_dump (authoritative, includes all
-- applied Alembic migrations up to revision 004).
-- Source DB: uptime_db @ localhost:55432 | PostgreSQL 16.6
-- =====

--
-- PostgreSQL database dump
--

--
-- Dumped from database version 16.6
-- Dumped by pg_dump version 16.6

SET statement_timeout = 0;
SET lock_timeout = 0;
SET idle_in_transaction_session_timeout = 0;
SET client_encoding = 'WIN1252';
SET standard_conforming_strings = on;
SELECT pg_catalog.set_config('search_path', '', false);
SET check_function_bodies = false;
SET xmloption = content;
SET client_min_messages = warning;
SET row_security = off;

SET default_tablespace = '';

SET default_table_access_method = heap;

--
-- Name: alembic_version; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.alembic_version (
    version_num character varying(32) NOT NULL
);

--
-- Name: alert_rules; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.alert_rules (
    id integer NOT NULL,
    user_id integer NOT NULL,
    monitor_id integer,
    name character varying(255) NOT NULL,
    consecutive_failures integer,
    recovery_confirmations integer,
    silence_minutes integer,
    escalation_after_minutes integer,
    is_active boolean,
    created_at timestamp with time zone DEFAULT now()
);

--
-- Name: alert_rules_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.alert_rules_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;
```

```
-- Name: alert_rules_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -  
--
```

```
ALTER SEQUENCE public.alert_rules_id_seq OWNED BY public.alert_rules.id;
```

```
--  
-- Name: api_keys; Type: TABLE; Schema: public; Owner: -  
--
```

```
CREATE TABLE public.api_keys (  
    id integer NOT NULL,  
    user_id integer NOT NULL,  
    name character varying(255) NOT NULL,  
    key_prefix character varying(12) NOT NULL,  
    key_hash character varying(255) NOT NULL,  
    permissions text,  
    last_used_at timestamp with time zone,  
    expires_at timestamp with time zone,  
    is_active boolean,  
    created_at timestamp with time zone DEFAULT now()  
);
```

```
--  
-- Name: api_keys_id_seq; Type: SEQUENCE; Schema: public; Owner: -  
--
```

```
CREATE SEQUENCE public.api_keys_id_seq  
    AS integer  
    START WITH 1  
    INCREMENT BY 1  
    NO MINVALUE  
    NO MAXVALUE  
    CACHE 1;
```

```
--  
-- Name: api_keys_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -  
--
```

```
ALTER SEQUENCE public.api_keys_id_seq OWNED BY public.api_keys.id;
```

```
--  
-- Name: audit_logs; Type: TABLE; Schema: public; Owner: -  
--
```

```
CREATE TABLE public.audit_logs (  
    id integer NOT NULL,  
    user_id integer,  
    action character varying(100) NOT NULL,  
    resource_type character varying(50),  
    resource_id integer,  
    details text,  
    ip_address character varying(50),  
    user_agent character varying(500),  
    created_at timestamp with time zone DEFAULT now()  
);
```

```
--  
-- Name: audit_logs_id_seq; Type: SEQUENCE; Schema: public; Owner: -  
--
```

```
CREATE SEQUENCE public.audit_logs_id_seq  
    AS integer  
    START WITH 1  
    INCREMENT BY 1  
    NO MINVALUE  
    NO MAXVALUE  
    CACHE 1;
```

```
--
-- Name: audit_logs_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.audit_logs_id_seq OWNED BY public.audit_logs.id;

--
-- Name: incidents; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.incidents (
    id integer NOT NULL,
    monitor_id integer NOT NULL,
    outage_start_time timestamp with time zone DEFAULT now(),
    recovery_time timestamp with time zone,
    error_message text,
    incident_status character varying(20) DEFAULT 'ongoing'::character varying
);

--
-- Name: incidents_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.incidents_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;

--
-- Name: incidents_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.incidents_id_seq OWNED BY public.incidents.id;

--
-- Name: maintenance_windows; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.maintenance_windows (
    id integer NOT NULL,
    user_id integer NOT NULL,
    name character varying(255) NOT NULL,
    description text,
    starts_at timestamp with time zone NOT NULL,
    ends_at timestamp with time zone NOT NULL,
    is_recurring boolean,
    recurrence_cron character varying(100),
    affected_monitors text,
    created_at timestamp with time zone DEFAULT now()
);

--
-- Name: maintenance_windows_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.maintenance_windows_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;
```

```
--
-- Name: maintenance_windows_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.maintenance_windows_id_seq OWNED BY public.maintenance_windows.id;

--
-- Name: monitor_logs; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.monitor_logs (
    id integer NOT NULL,
    monitor_id integer NOT NULL,
    response_time double precision,
    http_status integer,
    is_up boolean NOT NULL,
    error_message character varying(500),
    checked_at timestamp with time zone DEFAULT now()
);

--
-- Name: monitor_logs_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.monitor_logs_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;

--
-- Name: monitor_logs_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.monitor_logs_id_seq OWNED BY public.monitor_logs.id;

--
-- Name: monitors; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.monitors (
    id integer NOT NULL,
    user_id integer NOT NULL,
    monitor_name character varying(255) NOT NULL,
    target_url text NOT NULL,
    monitor_type character varying(50) DEFAULT 'http'::character varying,
    "interval" integer DEFAULT 300,
    timeout integer DEFAULT 10,
    http_method character varying(10) DEFAULT 'GET'::character varying,
    expected_status_code integer DEFAULT 200,
    custom_headers text,
    request_body text,
    current_status character varying(20) DEFAULT 'pending'::character varying,
    is_paused boolean DEFAULT false,
    uptime_percentage character varying(10) DEFAULT '100.00'::character varying,
    created_at timestamp with time zone DEFAULT now(),
    last_checked_at timestamp with time zone,
    keyword character varying(255),
    dns_record_type character varying(10) DEFAULT 'A'::character varying,
    failure_count integer DEFAULT 0,
    alert_threshold integer DEFAULT 1
);

--
-- Name: monitors_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--
```

```
CREATE SEQUENCE public.monitors_id_seq
  AS integer
  START WITH 1
  INCREMENT BY 1
  NO MINVALUE
  NO MAXVALUE
  CACHE 1;

--
-- Name: monitors_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.monitors_id_seq OWNED BY public.monitors.id;

--
-- Name: notifications; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.notifications (
  id integer NOT NULL,
  user_id integer NOT NULL,
  notification_type character varying(50) NOT NULL,
  destination character varying(500) NOT NULL,
  enabled boolean DEFAULT true,
  created_at timestamp with time zone DEFAULT now()
);

--
-- Name: notifications_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.notifications_id_seq
  AS integer
  START WITH 1
  INCREMENT BY 1
  NO MINVALUE
  NO MAXVALUE
  CACHE 1;

--
-- Name: notifications_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.notifications_id_seq OWNED BY public.notifications.id;

--
-- Name: organizations; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.organizations (
  id integer NOT NULL,
  name character varying(255) NOT NULL,
  slug character varying(100) NOT NULL,
  owner_id integer NOT NULL,
  logo_url character varying(500),
  plan character varying(50),
  created_at timestamp with time zone DEFAULT now()
);

--
-- Name: organizations_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.organizations_id_seq
  AS integer
  START WITH 1
```

```
INCREMENT BY 1
NO MINVALUE
NO MAXVALUE
CACHE 1;

--
-- Name: organizations_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.organizations_id_seq OWNED BY public.organizations.id;

--
-- Name: status_pages; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.status_pages (
    id integer NOT NULL,
    user_id integer NOT NULL,
    slug character varying(100) NOT NULL,
    company_name character varying(255) NOT NULL,
    logo_url character varying(500),
    custom_domain character varying(255),
    is_public boolean DEFAULT true,
    description text,
    created_at timestamp with time zone DEFAULT now()
);

--
-- Name: status_pages_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.status_pages_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;

--
-- Name: status_pages_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.status_pages_id_seq OWNED BY public.status_pages.id;

--
-- Name: team_members; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.team_members (
    id integer NOT NULL,
    org_id integer NOT NULL,
    user_id integer NOT NULL,
    role character varying(50),
    invited_by integer,
    joined_at timestamp with time zone DEFAULT now()
);

--
-- Name: team_members_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.team_members_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
```

```
NO MAXVALUE
CACHE 1;

--
-- Name: team_members_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.team_members_id_seq OWNED BY public.team_members.id;

--
-- Name: users; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.users (
    id integer NOT NULL,
    name character varying(255) NOT NULL,
    email character varying(255) NOT NULL,
    password_hash character varying(255) NOT NULL,
    role character varying(50) DEFAULT 'owner'::character varying,
    subscription_plan character varying(50) DEFAULT 'free'::character varying,
    is_verified boolean DEFAULT false,
    created_at timestamp with time zone DEFAULT now(),
    totp_secret character varying(64),
    totp_enabled boolean DEFAULT false,
    last_login_at timestamp with time zone,
    avatar_url character varying(500)
);

--
-- Name: users_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.users_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;

--
-- Name: users_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.users_id_seq OWNED BY public.users.id;

--
-- Name: webhook_deliveries; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.webhook_deliveries (
    id integer NOT NULL,
    endpoint_id integer NOT NULL,
    event character varying(50) NOT NULL,
    payload text,
    response_status integer,
    response_body text,
    success boolean,
    delivered_at timestamp with time zone DEFAULT now()
);

--
-- Name: webhook_deliveries_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.webhook_deliveries_id_seq
    AS integer
```



```

START WITH 1
INCREMENT BY 1
NO MINVALUE
NO MAXVALUE
CACHE 1;

--
-- Name: webhook_deliveries_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.webhook_deliveries_id_seq OWNED BY public.webhook_deliveries.id;

--
-- Name: webhook_endpoints; Type: TABLE; Schema: public; Owner: -
--

CREATE TABLE public.webhook_endpoints (
    id integer NOT NULL,
    user_id integer NOT NULL,
    name character varying(255) NOT NULL,
    url character varying(1000) NOT NULL,
    secret character varying(255),
    events text,
    is_active boolean,
    last_triggered_at timestamp with time zone,
    created_at timestamp with time zone DEFAULT now()
);

--
-- Name: webhook_endpoints_id_seq; Type: SEQUENCE; Schema: public; Owner: -
--

CREATE SEQUENCE public.webhook_endpoints_id_seq
    AS integer
    START WITH 1
    INCREMENT BY 1
    NO MINVALUE
    NO MAXVALUE
    CACHE 1;

--
-- Name: webhook_endpoints_id_seq; Type: SEQUENCE OWNED BY; Schema: public; Owner: -
--

ALTER SEQUENCE public.webhook_endpoints_id_seq OWNED BY public.webhook_endpoints.id;

--
-- Name: alert_rules id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.alert_rules ALTER COLUMN id SET DEFAULT nextval('public.alert_rules_id_seq'::regclass)
;

--
-- Name: api_keys id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.api_keys ALTER COLUMN id SET DEFAULT nextval('public.api_keys_id_seq'::regclass);

--
-- Name: audit_logs id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.audit_logs ALTER COLUMN id SET DEFAULT nextval('public.audit_logs_id_seq'::regclass);

```

```
--
-- Name: incidents id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.incidents ALTER COLUMN id SET DEFAULT nextval('public.incidents_id_seq'::regclass);

--
-- Name: maintenance_windows id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.maintenance_windows ALTER COLUMN id SET DEFAULT nextval('public.maintenance_windows_id
_seq'::regclass);

--
-- Name: monitor_logs id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.monitor_logs ALTER COLUMN id SET DEFAULT nextval('public.monitor_logs_id_seq'::regclas
s);

--
-- Name: monitors id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.monitors ALTER COLUMN id SET DEFAULT nextval('public.monitors_id_seq'::regclass);

--
-- Name: notifications id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.notifications ALTER COLUMN id SET DEFAULT nextval('public.notifications_id_seq'::regcl
ass);

--
-- Name: organizations id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.organizations ALTER COLUMN id SET DEFAULT nextval('public.organizations_id_seq'::regcl
ass);

--
-- Name: status_pages id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.status_pages ALTER COLUMN id SET DEFAULT nextval('public.status_pages_id_seq'::regclas
s);

--
-- Name: team_members id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.team_members ALTER COLUMN id SET DEFAULT nextval('public.team_members_id_seq'::regclas
s);

--
-- Name: users id; Type: DEFAULT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.users ALTER COLUMN id SET DEFAULT nextval('public.users_id_seq'::regclass);

--
-- Name: webhook_deliveries id; Type: DEFAULT; Schema: public; Owner: -
--
```

```
ALTER TABLE ONLY public.webhook_deliveries ALTER COLUMN id SET DEFAULT nextval('public.webhook_deliveries_id_seq'::regclass);
```

```
--  
-- Name: webhook_endpoints id; Type: DEFAULT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.webhook_endpoints ALTER COLUMN id SET DEFAULT nextval('public.webhook_endpoints_id_seq'::regclass);
```

```
--  
-- Name: alembic_version alembic_version_pkc; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.alembic_version  
ADD CONSTRAINT alembic_version_pkc PRIMARY KEY (version_num);
```

```
--  
-- Name: alert_rules alert_rules_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.alert_rules  
ADD CONSTRAINT alert_rules_pkey PRIMARY KEY (id);
```

```
--  
-- Name: api_keys api_keys_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.api_keys  
ADD CONSTRAINT api_keys_pkey PRIMARY KEY (id);
```

```
--  
-- Name: audit_logs audit_logs_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.audit_logs  
ADD CONSTRAINT audit_logs_pkey PRIMARY KEY (id);
```

```
--  
-- Name: incidents incidents_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.incidents  
ADD CONSTRAINT incidents_pkey PRIMARY KEY (id);
```

```
--  
-- Name: maintenance_windows maintenance_windows_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.maintenance_windows  
ADD CONSTRAINT maintenance_windows_pkey PRIMARY KEY (id);
```

```
--  
-- Name: monitor_logs monitor_logs_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.monitor_logs  
ADD CONSTRAINT monitor_logs_pkey PRIMARY KEY (id);
```

```
--  
-- Name: monitors monitors_pkey; Type: CONSTRAINT; Schema: public; Owner: -  
--
```

```
ALTER TABLE ONLY public.monitors
```

```
    ADD CONSTRAINT monitors_pkey PRIMARY KEY (id);

--
-- Name: notifications notifications_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.notifications
    ADD CONSTRAINT notifications_pkey PRIMARY KEY (id);

--
-- Name: organizations organizations_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.organizations
    ADD CONSTRAINT organizations_pkey PRIMARY KEY (id);

--
-- Name: status_pages status_pages_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.status_pages
    ADD CONSTRAINT status_pages_pkey PRIMARY KEY (id);

--
-- Name: status_pages status_pages_slug_key; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.status_pages
    ADD CONSTRAINT status_pages_slug_key UNIQUE (slug);

--
-- Name: team_members team_members_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.team_members
    ADD CONSTRAINT team_members_pkey PRIMARY KEY (id);

--
-- Name: users users_email_key; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.users
    ADD CONSTRAINT users_email_key UNIQUE (email);

--
-- Name: users users_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.users
    ADD CONSTRAINT users_pkey PRIMARY KEY (id);

--
-- Name: webhook_deliveries webhook_deliveries_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.webhook_deliveries
    ADD CONSTRAINT webhook_deliveries_pkey PRIMARY KEY (id);

--
-- Name: webhook_endpoints webhook_endpoints_pkey; Type: CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.webhook_endpoints
    ADD CONSTRAINT webhook_endpoints_pkey PRIMARY KEY (id);
```

```
--
-- Name: ix_alert_rules_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_alert_rules_id ON public.alert_rules USING btree (id);

--
-- Name: ix_api_keys_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_api_keys_id ON public.api_keys USING btree (id);

--
-- Name: ix_api_keys_key_prefix; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_api_keys_key_prefix ON public.api_keys USING btree (key_prefix);

--
-- Name: ix_audit_logs_created_at; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_audit_logs_created_at ON public.audit_logs USING btree (created_at);

--
-- Name: ix_audit_logs_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_audit_logs_id ON public.audit_logs USING btree (id);

--
-- Name: ix_audit_logs_user_created; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_audit_logs_user_created ON public.audit_logs USING btree (user_id, created_at);

--
-- Name: ix_incidents_monitor_start; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_incidents_monitor_start ON public.incidents USING btree (monitor_id, outage_start_time);

--
-- Name: ix_incidents_monitor_status; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_incidents_monitor_status ON public.incidents USING btree (monitor_id, incident_status);

--
-- Name: ix_maintenance_windows_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_maintenance_windows_id ON public.maintenance_windows USING btree (id);

--
-- Name: ix_monitor_logs_monitor_checked; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_monitor_logs_monitor_checked ON public.monitor_logs USING btree (monitor_id, checked_at);

--
```

```
-- Name: ix_organizations_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_organizations_id ON public.organizations USING btree (id);

--
-- Name: ix_organizations_slug; Type: INDEX; Schema: public; Owner: -
--

CREATE UNIQUE INDEX ix_organizations_slug ON public.organizations USING btree (slug);

--
-- Name: ix_team_members_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_team_members_id ON public.team_members USING btree (id);

--
-- Name: ix_webhook_deliveries_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_webhook_deliveries_id ON public.webhook_deliveries USING btree (id);

--
-- Name: ix_webhook_endpoints_id; Type: INDEX; Schema: public; Owner: -
--

CREATE INDEX ix_webhook_endpoints_id ON public.webhook_endpoints USING btree (id);

--
-- Name: alert_rules alert_rules_monitor_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.alert_rules
    ADD CONSTRAINT alert_rules_monitor_id_fkey FOREIGN KEY (monitor_id) REFERENCES public.monitors(id) ON DELETE CASCADE;

--
-- Name: alert_rules alert_rules_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.alert_rules
    ADD CONSTRAINT alert_rules_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: api_keys api_keys_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.api_keys
    ADD CONSTRAINT api_keys_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: audit_logs audit_logs_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.audit_logs
    ADD CONSTRAINT audit_logs_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE SET NULL;

--
-- Name: incidents incidents_monitor_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--
```

```
ALTER TABLE ONLY public.incidents
  ADD CONSTRAINT incidents_monitor_id_fkey FOREIGN KEY (monitor_id) REFERENCES public.monitors(id) ON DELETE
  CASCADE;

--
-- Name: maintenance_windows maintenance_windows_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.maintenance_windows
  ADD CONSTRAINT maintenance_windows_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE
  CASCADE;

--
-- Name: monitor_logs monitor_logs_monitor_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.monitor_logs
  ADD CONSTRAINT monitor_logs_monitor_id_fkey FOREIGN KEY (monitor_id) REFERENCES public.monitors(id) ON DELETE
  CASCADE;

--
-- Name: monitors monitors_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.monitors
  ADD CONSTRAINT monitors_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: notifications notifications_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.notifications
  ADD CONSTRAINT notifications_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: organizations organizations_owner_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.organizations
  ADD CONSTRAINT organizations_owner_id_fkey FOREIGN KEY (owner_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: status_pages status_pages_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.status_pages
  ADD CONSTRAINT status_pages_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: team_members team_members_invited_by_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.team_members
  ADD CONSTRAINT team_members_invited_by_fkey FOREIGN KEY (invited_by) REFERENCES public.users(id);

--
-- Name: team_members team_members_org_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.team_members
  ADD CONSTRAINT team_members_org_id_fkey FOREIGN KEY (org_id) REFERENCES public.organizations(id) ON DELETE
  CASCADE;
```

```
--
-- Name: team_members team_members_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.team_members
    ADD CONSTRAINT team_members_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- Name: webhook_deliveries webhook_deliveries_endpoint_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.webhook_deliveries
    ADD CONSTRAINT webhook_deliveries_endpoint_id_fkey FOREIGN KEY (endpoint_id) REFERENCES public.webhook_endpoints(id) ON DELETE CASCADE;

--
-- Name: webhook_endpoints webhook_endpoints_user_id_fkey; Type: FK CONSTRAINT; Schema: public; Owner: -
--

ALTER TABLE ONLY public.webhook_endpoints
    ADD CONSTRAINT webhook_endpoints_user_id_fkey FOREIGN KEY (user_id) REFERENCES public.users(id) ON DELETE CASCADE;

--
-- PostgreSQL database dump complete
--
```