Phase 2 Report

Project Title

SPAM EMAIL DETECTION SYSTEM

Problem Id: 22

Name: Akshat Dobhal

University Roll No: 2028631

Sec: Q(G1)

Name: Ayush Kandwal

University Roll No: 2028405

Sec: Q(G1)

Name:Ashmit Nautiyal

University Roll No: 2028670

Sec : Q(G1)

1. **Problem Description** 3
2. **Architecture** 4
3. **Models Used**..... 5
4. **Evaluation metrics used** 6
5. **Preliminary Results and Visualizations** 8
6. **References** 10

1.Problem Description

With the rapid growth of digital communication, email has become one of the most widely used platforms for information exchange. However, this has also led to a significant increase in unwanted and harmful messages, commonly known as spam emails. These spam messages not only clutter users' inboxes but may also contain malicious links, phishing attempts, and fraudulent content.

Manually identifying and filtering spam emails is inefficient, time-consuming, and prone to human error. Therefore, there is a need for an automated system that can accurately classify emails as spam or non-spam (ham).

The objective of this project is to develop a machine learning-based email classification system that can:

- Process and clean raw email text data
- Extract meaningful features from textual content
- Train classification models using techniques such as TF-IDF and algorithms like Logistic Regression, SVM, etc.
- Evaluate model performance using metrics like accuracy, confusion matrix, and precision

The system should be capable of improving email filtering efficiency and reducing the risk associated with spam messages by providing accurate and fast predictions.

Additionally, the model should be scalable so that it can handle large volumes of email data in real-time applications. It should also be adaptable to evolving spam patterns by retraining with new data. The project aims to enhance user security and privacy by minimizing exposure to harmful content. Furthermore, it can be integrated into existing email platforms to automate spam detection seamlessly. Continuous evaluation and optimization of the model will ensure better accuracy over time. Overall, this system contributes to creating a safer and more efficient digital communication environment.

.

2.Architecture



3.Models Used (Applied/ Planned) Give a brief introduction of the models used

1. Logistic Regression

Logistic Regression is a supervised machine learning algorithm used for binary classification tasks.
It predicts the probability of an input belonging to a particular class using a sigmoid function.
In this project, it is used to classify emails as spam or ham based on text features.
It performs well with high-dimensional data such as TF-IDF vectors.
The model is simple, fast, and easy to implement and interpret.
It provides good baseline performance for text classification problems.
However, it may struggle with complex non-linear relationships in data.

2. Support Vector Machine (SVM)

SVM is a powerful supervised learning algorithm used for classification tasks.
It works by finding the optimal hyperplane that separates different classes.
It is highly effective in high-dimensional feature spaces like text data.
SVM can handle both linear and non-linear classification using kernel functions.
It is known for its high accuracy in spam detection problems.
The model is robust against overfitting, especially in complex datasets.
However, it requires more computational resources and tun

3. Naive Bayes

Naive Bayes is a probabilistic classification algorithm based on Bayes' Theorem.
It assumes independence between features, which works well for text data.
It is widely used in spam filtering and email classification tasks.
The model is fast, efficient, and requires less training data.
It performs well with large datasets and high-dimensional inputs.
It is easy to implement and computationally inexpensive.
However, its assumption of feature independence may reduce accuracy in some cases.

4.Evaluation metrics used

To measure the performance of the spam email classification model, several evaluation metrics are used. These metrics help in understanding how well the model is predicting spam and non-spam emails.

1. Accuracy:
Accuracy measures the overall correctness of the model.
It is defined as the ratio of correctly predicted instances to the total instances.
It gives a general idea of model performance.
Higher accuracy indicates better performance of the model.
However, it may be misleading if the dataset is imbalanced.
It does not differentiate between types of errors.
Therefore, it is used along with other metrics.

2. Precision:
Precision measures how many predicted spam emails are actually spam.
It focuses on reducing false positives.
It is important when misclassifying normal emails as spam is costly.
High precision means fewer false alarms.
It ensures reliability of spam detection.
It is calculated using true positives and false positives.
Precision is crucial in email filtering systems.

3. Recall:
Recall measures how many actual spam emails are correctly identified.
It focuses on reducing false negatives.
High recall ensures most spam emails are detected.
It is important for security and avoiding harmful emails.
It balances the effectiveness of the model.
It is calculated using true positives and false negatives.
Recall is also known as sensitivity.

4. F1-Score:
F1-Score is the harmonic mean of precision and recall.
It provides a balance between precision and recall.
It is useful when both false positives and false negatives matter.
A high F1-score indicates a well-performing model.
It is especially useful for imbalanced datasets.
It combines both metrics into a single value.
It helps in comparing different models effectively.

5. Confusion Matrix:
Confusion Matrix is a table used to evaluate classification performance.

It shows actual vs predicted values.
It includes True Positive, True Negative, False Positive, and False Negative.
It provides detailed insight into model errors.
It helps in calculating other metrics like precision and recall.
It is often visualized using a heatmap.
It is very useful for understanding model performance clearly.

Preliminary Results and Visualizations



The initial implementation of the spam email classification model produced promising results. After preprocessing the dataset and applying feature extraction techniques like TF-IDF, the model was trained using algorithms such as Logistic Regression. The preliminary results indicate that the model is capable of effectively distinguishing between spam and non-spam emails.

The performance of the model was evaluated using metrics such as accuracy, precision, recall, and F1-score. The accuracy achieved was reasonably high, indicating that most emails were classified correctly. Precision and recall values showed a good balance, meaning the model was able to identify spam emails while minimizing false classifications.

To better understand the performance, a confusion matrix was generated. It provided a detailed view of correct and incorrect predictions, including true positives, true negatives, false positives, and false negatives. This helped in identifying areas where the model could be improved.

.



R2 Score: 0.9
Confusion Matrix:
[[961 5]
[8 141]]

5. References:

Books:

1. *Let Us Python* – Yashavant Kanetkar
2. *Hands-On Machine Learning with Scikit-Learn* – Aurélien Géron

Online Resources:

1. https://www.geeksforgeeks.org/
2. https://scikit-learn.org/